PROJECT REPORT

DIGITAL WALKIE-TALKIE

Design and Implementation of an ESP32-S3-Based Digital Walkie-Talkie Using Digital Signal Processing

Subject	Digital Signal Processing
Project Team	Sanket Pawar | Vishakha Kirange | Pranjal Sawant
Roll Numbers	24104A0030 | 25104A2001 | 25104A2002
Department	Electronics and Telecommunication Engineering – A

1. Aim

To design and develop a digital walkie-talkie using the ESP32-S3 microcontroller for digital audio processing and the nRF24L01+ RF transceiver for wireless voice communication.

2. Objective

- To capture voice using the INMP441 digital MEMS microphone.
- To process digital audio samples using the ESP32-S3 microcontroller.
- To transmit and receive audio data wirelessly using the nRF24L01+ transceiver.
- To reproduce the received audio using the MAX98357A digital audio amplifier and speaker.
- To understand the application of DSP in real-time wireless voice communication.
- To develop a portable communication system using a battery-powered circuit.

3. Tools Utilized

Hardware Components

- **ESP32-S3:** Main controller for digital audio processing and communication control.
- **nRF24L01+ RF Transceiver:** Transmits and receives digital data packets in the 2.4 GHz band.
- **INMP441 Microphone:** Captures voice and provides digital audio samples through I2S.
- **MAX98357A Amplifier:** Amplifies digital audio to drive the speaker.
- **Speaker:** Converts the electrical audio signal into audible sound.
- **Battery:** Provides portable power.
- **Antenna:** Transmits and receives radio-frequency signals.
- **Push Buttons:** Control push-to-talk operation.
- **PCB and Connecting Wires:** Connect the electronic components.

Software and Development Tools

- Arduino IDE or ESP-IDF
- Embedded C/C++
- I2S digital audio interface
- SPI communication interface
- Serial Monitor for debugging

4. Methodology

Step 1:Voice Input: The INMP441 microphone captures voice and provides digital audio samples to the ESP32-S3 through I2S.

Step 2: Digital Signal Processing: The ESP32-S3 handles the audio samples in software. Depending on the implemented program, operations such as buffering, digital filtering, and audio-level adjustment can be performed.

Step 3: Packet Formation: The audio samples are divided into smaller blocks and organized into data packets for wireless transmission.

Step 4: Wireless Transmission: The ESP32-S3 sends the packets to the nRF24L01+ through SPI. The transceiver transmits the data wirelessly.

Step 5: Wireless Reception: The receiving nRF24L01+ receives the transmitted packets and transfers the data to the receiving ESP32-S3.

Step 6: Audio Reconstruction: The ESP32-S3 reconstructs the received audio samples and sends them to the MAX98357A amplifier through I2S.

Step 7: Audio Output: The amplifier drives the speaker to reproduce the transmitted voice.

Step 8: Push-to-Talk Control: The push-to-talk button controls the transmission and reception modes according to the programmed logic.

5. Results

The project is designed to demonstrate wireless voice communication using digital audio processing and an RF transceiver.

The expected outcomes are:

- Capturing voice using the digital microphone.
- Handling digital audio samples using the ESP32-S3.
- Transmitting and receiving audio packets wirelessly.
- Reconstructing and playing the received voice.
- Controlling communication through a push-to-talk button.

The actual communication range, audio quality, latency, and packet loss should be recorded after testing the prototype.

6. Analysis

The project combines digital audio processing, embedded programming, and wireless communication.

The ESP32-S3 handles digital audio samples and system control. The INMP441 captures voice, while the MAX98357A drives the speaker. The nRF24L01+ provides the wireless data link between the devices.

The performance of the system depends on the audio sampling rate, packet size, wireless data rate, processing delay, and environmental interference.

Advantages:

1. Portable and compact design.
2. Wireless voice communication.
3. Practical demonstration of DSP concepts.
4. Programmable operation using a microcontroller.
5. Useful for learning digital audio interfaces and RF communication.

Limitations:

1. Wireless interference may affect audio quality.
2. Packet loss may cause interruptions in voice playback.
3. Processing and transmission may introduce latency.
4. Battery capacity limits operating time.
5. Continuous audio requires efficient packet handling and sufficient wireless throughput.

7. Conclusion

The digital walkie-talkie demonstrates the application of Digital Signal Processing in wireless voice communication. The ESP32-S3 handles digital audio samples, and the nRF24L01+ transmits and receives the audio data wirelessly. The MAX98357A amplifier and speaker reproduce the received voice.

This mini-project provides practical knowledge of digital audio handling, embedded programming, I2S and SPI interfaces, and wireless communication.

8. Future Scope

- Implement digital noise-reduction filters to improve voice clarity.
- Introduce audio compression to reduce transmission requirements.
- Improve packet handling to minimize audio interruptions.
- Add voice activity detection to identify speech and silence.
- Optimize power consumption to increase battery life.
- Measure and improve communication range and latency.
- Add status LEDs and battery-level indication.
- Evaluate audio quality under different environmental conditions.

9. Appendix: Photographs of Project Visualization



