

Maximum Subarray Sum Deletion

Absolutely. This is a **Dynamic Programming (DP)** problem, but the key is to build the idea from something very simple.

1. What is the problem asking?

We have an integer array.

We need to find a **contiguous subarray** whose sum is as large as possible.

But there is one special permission:

We may delete **at most one element** from that subarray.

So for every possible subarray, we can either:

- delete nothing, or
- delete exactly one element.

But after deletion, **at least one element must remain**.

Example

[1, -2, 0, 3]

Without deletion:

```
1 + (-2) + 0 + 3 = 2
```

But we can delete -2:

```
1 + 0 + 3 = 4
```

So answer = **4**.

2. The important word: contiguous

A subarray must contain consecutive elements.

For:

```
[1, -2, 0, 3]
```

Valid subarrays include:

```
[1]
[1, -2]
[1, -2, 0]
[1, -2, 0, 3]
[-2]
[-2, 0]
[-2, 0, 3]
[0]
[0, 3]
[3]
```

But:

```
[1, 0, 3]
```

is **not originally a subarray**, because -2 is between them.

However, we can get [1, 0, 3] by taking:

```
[1, -2, 0, 3]
```

and deleting -2.

That's exactly what makes this problem interesting.

3. First think about the brute-force solution

Before jumping to DP, let's think like a beginner.

We could try:

1. Generate every possible subarray.

2. For each subarray:

- calculate its sum without deletion.
- try deleting every element one by one.
- calculate the resulting sum.

3. Keep the maximum.

For an array of size n :

There are approximately:

```
n2
```

subarrays.

And for each subarray, we might try:

```
n
```

different deletions.

So this can become approximately:

```
O(n3)
```

which is far too slow for:

```
n <= 100000
```

We need something around **$O(n)$** .

4. Let's first understand normal Maximum Subarray

Forget deletion for a moment.

The normal problem is **Maximum Subarray Sum**, solved by **Kadane's Algorithm**.

Suppose:

```
arr = [1, -2, 0, 3]
```

We keep:

```
current = maximum subarray sum ending at current position
```

At every element:

```
current = max(arr[i], current + arr[i])
```

Why?

Suppose we're at 3.

We have two choices:

Start a new subarray

```
[3]
sum = 3
```

Extend previous subarray

```
previous + 3
```

Take whichever is larger.

5. Now introduce deletion

The difficulty is:

At any point, we may have already deleted one element.

So we actually need to remember **two different situations**.

State 1: No deletion

Let:

```
noDelete
```

mean:

Maximum sum of a subarray ending at the current position where we haven't deleted anything.

For example:

```
arr = [1, -2, 0, 3]
```

State 2: One deletion

Let:

```
oneDelete
```

mean:

Maximum sum of a valid subarray ending at the current position where exactly one element has been deleted.

Now we have two states:

```
noDelete
oneDelete
```

This is the key observation of the entire problem.

6. How do we update these states?

Suppose the current element is:

```
x = arr[i]
```

State 1: No deletion

We haven't deleted anything.

We have two choices.

Choice A: Start here

```
noDelete = x
```

Choice B: Extend previous subarray

```
noDelete = previousNoDelete + x
```

Therefore:

```
newNoDelete = max(x, noDelete + x)
```

This is just Kadane's algorithm.

7. Now the interesting part: one deletion

Suppose current element is:

```
x
```

and we want exactly one deletion.

There are **two possibilities**.

Possibility 1: Delete the current element

Suppose before current element we had:

```
[1, -2]
```

and current element is:

```
-2
```

We can delete -2.

Then the sum is simply the previous **noDelete**:

```
newOneDelete = previousNoDelete
```

Why?

Because we're saying:

```
"I'm using my one deletion right now."
```

Possibility 2: We already deleted something earlier

For example:

```
[1, -2, 0, 3]
```

Suppose we already deleted -2.

Then our current sum before 3 is:

```
1 + 0 = 1
```

Now add 3:

```
1 + 3 = 4
```

So:

```
newOneDelete = previousOneDelete + x
```


Therefore:

```
newOneDelete = max(
    previousNoDelete,
    previousOneDelete + x
)
```


This is the central recurrence.

8. The intuition in one picture

At every element x , think:



So:



```

    +-- keep current
    |
    v
newOneDelete

```

Therefore:

```

newNoDelete = max(x, noDelete + x)
newOneDelete = max(
    noDelete,
    oneDelete + x
)

```

9. Why does this work?

This is a classic **DP state** idea.

At every position, we don't care about the entire history.

We only need to know:

```

What is the best sum ending here
without deletion?

What is the best sum ending here
with one deletion?

```

Everything before that is already summarized in those two values.

That's why we can solve the problem in **O(n)** instead of checking all subarrays.

10. Important issue: the subarray must remain non-empty

This matters especially for:

```
[-1, -1, -1, -1]
```

Could we take:

```
[-1]
```

and delete -1?

No!

Because then the resulting subarray is empty.

The problem explicitly says:

At least one element must remain.

Therefore answer is:

```
-1
```

not 0.

This is why we should **not initialize our answer to 0**.

Instead, initialize using the first element.

11. C++ code

```

C++
class Solution {
public:
    int maximumSum(vector<int>& arr) {
        int noDelete = arr[0];
        int oneDelete = INT_MIN;

        int ans = arr[0];

        for (int i = 1; i < arr.size(); i++) {
            int x = arr[i];

            int newNoDelete = max(x, noDelete + x);
            int newOneDelete = max(noDelete, oneDelete + x);

            noDelete = newNoDelete;
            oneDelete = newOneDelete;

            ans = max(ans, max(noDelete, oneDelete));
        }
    }
}

```

```
    }  
    return ans;  
};
```

12. Explain every important line

Initialization

```
C++  
int noDelete = arr[0];
```

We start with the first element.

For example:

```
arr[0] = 1
```

So:

```
noDelete = 1
```

Why is oneDelete = INT_MIN?

```
C++  
int oneDelete = INT_MIN;
```

Initially, we haven't processed enough elements to delete one while keeping at least one element.

We don't want to accidentally treat an impossible state as a valid answer.

INT_MIN represents:

This state is currently impossible.

Answer

```
C++  
int ans = arr[0];
```

This is important because all numbers might be negative.

For:

```
[-1, -1, -1, -1]
```

we need the answer to be -1, not 0.

13. Update noDelete

```
C++  
int newNoDelete = max(x, noDelete + x);
```

Two choices:

Start fresh

```
x
```

Extend previous subarray

```
noDelete + x
```

Take maximum.

Exactly Kadane's algorithm.

14. Update oneDelete

```
C++  
int newOneDelete = max(noDelete, oneDelete + x);
```

Again, two possibilities.

Delete current element

```
previous noDelete
```

We don't add x because we're deleting it.

Already deleted something

```
previous oneDelete + x
```

We keep the current element.

Therefore:

```
newOneDelete = max(noDelete, oneDelete + x)
```

15. Why do we use temporary variables?

Notice:

```
C++
int newNoDelete = ...
int newOneDelete = ...
```

instead of immediately changing **noDelete**.

That's important because both new states depend on the **old** values.

If we did:

```
C++
noDelete = ...
oneDelete = ...
```

too early, then **oneDelete** might accidentally use the newly updated **noDelete**.

Using temporary variables makes the transition clear and correct.

16. Complete dry run — Example 1

Given:

```
arr = [1, -2, 0, 3]
```

We want:

```
4
```

Let's make a table.

i	x	noDelete	oneDelete	ans
0	1	1	impossible	1
1	-2	-1	1	1
2	0	0	1	1
3	3	3	4	4

Let's understand each row.

Step 1: x = 1

Initially:

```
noDelete = 1
oneDelete = -∞
ans = 1
```

We have:

```
[1]
```

Sum:

```
1
```

Step 2: $x = -2$

Current:

```
noDelete = 1
oneDelete = -∞
x = -2
```

Calculate newNoDelete

```
max(-2, 1 + (-2))
= max(-2, -1)
= -1
```

So:

```
newNoDelete = -1
```

Calculate newOneDelete

We have:

```
max(noDelete, oneDelete + x)
```

So:

```
max(1, -∞ + (-2))
= 1
```

Why 1?

Because we can delete -2:

```
[1, -2]
  ↑
delete
```

Remaining:

```
[1]
```

Sum:

```
1
```

So:

```
oneDelete = 1
```

Answer remains:

```
1
```

17. Step 3: $x = 0$

Current:

```
noDelete = -1
oneDelete = 1
```

New noDelete

```
max(0, -1 + 0)
= max(0, -1)
= 0
```

So:

```
noDelete = 0
```

New oneDelete

```
max(-1, 1 + 0)
= max(-1, 1)
= 1
```

This corresponds to:

```
[1, -2, 0]
```

with -2 deleted:

```
[1, 0]
```

Sum:

```
1
```

So:

```
oneDelete = 1
```

Answer:

```
1
```

18. Step 4: x = 3

Current:

```
noDelete = 0
oneDelete = 1
```

New noDelete

```
max(3, 0 + 3)
= 3
```

So:

```
noDelete = 3
```

This is:

```
[3]
```

New oneDelete

```
max(0, 1 + 3)
= max(0, 4)
= 4
```

Where did 4 come from?

Our previous one-deletion state was:

```
[1, 0]
```

which came from:

```
[1, -2, 0]
```

after deleting -2.

Now add 3:

```
[1, 0, 3]
```

Sum:

```
1 + 0 + 3 = 4
```

Therefore:

```
answer = 4
```

19. Visualizing the winning solution

Original:

```
[ 1, -2, 0, 3 ]
      ↑
    delete
```

After deletion:

```
[ 1, 0, 3 ]
```

Sum:

```
1 + 0 + 3 = 4
```

Therefore:

```
Output = 4
```

20. Dry run of Example 2

```
arr = [1, -2, -2, 3]
```

The optimal answer is simply:

```
[3]
```

Let's see what DP does.

x	noDelete	oneDelete	ans
1	1	$-\infty$	1
-2	-1	1	1
-2	-2	1	1
3	3	4	4

Wait — this appears to give **4**, which seems wrong according to the example!

This is an important point: let's carefully examine the recurrence.

For:

```
[1, -2, -2, 3]
```

we can delete **only one** -2.

That gives:

```
[1, -2, 3]
```

sum:

```
2
```

So **4** cannot be correct.

The issue is that the compact recurrence above has a subtle state-definition problem if **oneDelete** is allowed to represent an invalid "deleted element but no remaining element" transition in the wrong way.

A safer and very clear formulation is to use:

```
dp0 = best sum ending here with no deletion
dp1 = best sum ending here with one deletion
```

with:

```
newDp0 = max(x, dp0 + x)
newDp1 = max(dp1 + x, dp0)
```

But let's inspect the calculation:

At **x = -2**:

```
dp0 = -1
dp1 = 1
```

At the next -2:

```
newDp1 = max(1 + (-2), -1)
        = max(-1, -1)
        = -1
```

Then at 3:

```
newDp1 = max(-1 + 3, -2)
        = 2
```

So the correct table is:

	x	dp0	dp1	ans
	1	1	$-\infty$	1
	-2	-1	1	1
	-2	-2	-1	1
	3	3	2	3

And the answer is:

```
3
```

This also demonstrates why **careful state updating matters**.

21. Example 3 — all negative

```
arr = [-1, -1, -1, -1]
```

We cannot delete the only element of a subarray.

The best possible non-empty subarray is:

```
[-1]
```

Therefore:

```
answer = -1
```

Our initialization:

```
C++
ans = arr[0];
```

ensures that we don't incorrectly return 0.

22. Final intuition to remember

If you see:

Maximum subarray + at most one deletion

immediately think:

```
Two states
```

State 1

```
dp0
```

Maximum sum ending at current position with **no deletion**.

State 2

```
dp1
```

Maximum sum ending at current position with **one deletion**.

Transitions:

```
newDp0 = max(x, dp0 + x)
```

For one deletion:

```
newDp1 = max(
    dp1 + x, // already deleted something earlier
    dp0     // delete current element
)
```

And answer:

```
max(dp0, dp1)
```

over all positions.

23. Correct C++ solution

```
C++
class Solution {
public:
    int maximumSum(vector<int>& arr) {
        int dp0 = arr[0]; // no deletion
        int dp1 = INT_MIN; // one deletion

        int ans = arr[0];

        for (int i = 1; i < arr.size(); i++) {
            int x = arr[i];

            int newDp0 = max(x, dp0 + x);
            int newDp1 = max(dp1 + x, dp0);

            dp0 = newDp0;
            dp1 = newDp1;

            ans = max(ans, max(dp0, dp1));
        }

        return ans;
    }
};
```

Why dp0 is enough when deleting x?

Suppose:

```
dp0 = 5
x = -10
```

If we delete -10, the resulting sum is:

```
5
```

So:

```
C++
newDp1 = dp0;
```

That's exactly what the transition represents.

24. Complexity

The array is traversed exactly once.

Time

```
O(n)
```

where n is the array length.

Since:

```
n <= 100000
```

this is easily fast enough.

Space

We only store:

```
dp0
dp1
ans
```

So:

```
O(1)
```

extra space.

The one-line memory trick

Remember this:

dp0 = best subarray ending here without deleting.
dp1 = best subarray ending here after deleting one element.

Then ask:

```
dp0:
  Start new OR extend
dp1:
  Delete current OR extend an already-deleted subarray
```

which gives:

```
dp0 = max(x, dp0 + x)
dp1 = max(oldDp0, dp1 + x)
```

That is the entire DP idea behind **Maximum Subarray Sum with One Deletion**.

Yes. If you want to write this in a **proper DP-table form**, rather than the optimized **O(1)** space version, it becomes much easier to visualize.

The idea is that for every index **i**, we store **two DP values**.

1. DP states

Let:

```
C++
dp[i][0]
```

mean:

Maximum sum of a subarray ending at index **i** with **no deletion**.

And:

```
C++
dp[i][1]
```

mean:

Maximum sum of a subarray ending at index **i** with **exactly one deletion**.

So our DP table looks like:

Index i	dp[i][0]	dp[i][1]
0	no deletion	one deletion
1	no deletion	one deletion
2	no deletion	one deletion
...	...	...

2. The recurrence

Suppose:

```
C++
x = arr[i]
```

Case 1: No deletion

We have two choices:

Start a new subarray

```
x
```

Continue the previous subarray

```
dp[i-1][0] + x
```

Therefore:

```
C++
dp[i][0] = max(arr[i], dp[i-1][0] + arr[i]);
```

This is basically **Kadane's algorithm**.

3. Case 2: Exactly one deletion

Again, two possibilities.

Option 1: Delete the current element

Suppose:

```
arr = [1, -2, 0]
```

At -2, we can delete it.

The previous subarray was:

```
[1]
```

So:

```
C++
dp[i][1] = dp[i-1][0];
```

We don't add `arr[i]` because we deleted it.

Option 2: We already deleted something earlier

For example:

```
[1, -2, 0]
```

We already deleted -2.

Now when we encounter 0, we keep it:

```
[1, 0]
```

Therefore:

```
C++
dp[i-1][1] + arr[i]
```

So:

```
C++
dp[i][1] = max(
    dp[i-1][0],
    dp[i-1][1] + arr[i]
);
```

4. Full DP code

Here is the version I would recommend writing if your goal is to **understand the DP form**:

```
C++
class Solution {
public:
    int maximumSum(vector<int>& arr) {
        int n = arr.size();

        // dp[i][0] = maximum sum ending at i
        //             without deleting any element
        // dp[i][1] = maximum sum ending at i
        //             after deleting exactly one element

        vector<vector<int>> dp(n, vector<int>(2));

        // Base case
        dp[0][0] = arr[0];
        dp[0][1] = INT_MIN;

        int ans = arr[0];

        for (int i = 1; i < n; i++) {
            // Case 1: No deletion
            dp[i][0] = max(
                arr[i],
                dp[i - 1][0] + arr[i]
            );

            // Case 2: One deletion
            dp[i][1] = max(
                dp[i - 1][0],           // delete arr[i]
                dp[i - 1][1] + arr[i]   // already deleted earlier
            );

            // Update answer
            ans = max(
                ans,
                max(dp[i][0], dp[i][1])
            );
        }

        return ans;
    }
};
```

5. Let's understand the code line by line

Step 1: Get array size

```
C++
int n = arr.size();
```

For:

```
[1, -2, 0, 3]
```

we have:

```
n = 4
```

Step 2: Create DP table

```
C++
vector<vector<int>> dp(n, vector<int>(2));
```

This creates:

```
n rows
2 columns
```

For example, if **n = 4**:

	0 no delete	1 one delete
i=0	dp[0][0]	dp[0][1]
i=1	dp[1][0]	dp[1][1]
i=2	dp[2][0]	dp[2][1]
i=3	dp[3][0]	dp[3][1]

This is the actual DP table.

6. Base case

```
C++
dp[0][0] = arr[0];
```

Suppose:

```
arr[0] = 1
```

Then:

```
dp[0][0] = 1
```

Because the best subarray ending at index 0 without deletion is:

```
[1]
```

Now:

```
C++
dp[0][1] = INT_MIN;
```

Why?

Because with only one element:

```
[1]
```

we **cannot delete it**.

If we delete it, we'd have:

```
[]
```

which is forbidden.

So:

```
dp[0][1] = impossible
```

We represent impossible with:

```
C++
INT_MIN
```

7. Start the answer

```
C++
int ans = arr[0];
```

Why not:

```
C++
int ans = 0;
```

Because the answer can be negative.

For example:

```
[-1, -1, -1, -1]
```

The answer is:

```
-1
```

not 0.

8. Start the loop

```
C++
for (int i = 1; i < n; i++)
```

We start from $i = 1$ because we already handled index 0 as our base case.

9. Calculate $dp[i][0]$

```
C++
dp[i][0] = max(
    arr[i],
    dp[i - 1][0] + arr[i]
);
```

There are two choices.

Choice 1: Start new

```
C++
arr[i]
```

Choice 2: Extend previous

```
C++
dp[i - 1][0] + arr[i]
```

Take the maximum.

10. Calculate $dp[i][1]$

This is the most important line:

```
C++
dp[i][1] = max(
    dp[i - 1][0],
    dp[i - 1][1] + arr[i]
);
```

Let's separate it.

First possibility

```
C++
dp[i - 1][0]
```

This means:

Delete the current element.

For example:

```
[1, -2]
  ↑
delete
```

The sum becomes:

```
1
```

So we use the previous $dp[i-1][0]$.

Second possibility

```
C++
dp[i - 1][1] + arr[i]
```

This means:

We already deleted an element earlier, so keep the current element.

Example:

```
[1, -2, 0]
  ↑
deleted
```

Now when we reach 0:

```
1 + 0 = 1
```

So we extend `dp[i-1][1]`.

11. Dry run with the DP table

Let's use:

```
arr = [1, -2, 0, 3]
```

Initially:

```
dp[0][0] = 1
dp[0][1] = INT_MIN
```

Table:

i	arr[i]	dp[i][0]	dp[i][1]
0	1	1	-∞
1	-2	?	?
2	0	?	?
3	3	?	?

i = 1

```
arr[1] = -2
```

Calculate `dp[1][0]`

```
dp[1][0]
= max(arr[1], dp[0][0] + arr[1])
= max(-2, 1 + (-2))
= max(-2, -1)
= -1
```

So:

```
dp[1][0] = -1
```

Calculate `dp[1][1]`

```
dp[1][1]
= max(dp[0][0], dp[0][1] + arr[1])
```

The first option:

```
dp[0][0] = 1
```

means:

Delete -2.

So:

```
[1, -2]
X
```

becomes:

```
[1]
```

sum = 1.

Therefore:

```
dp[1][1] = 1
```

Table:

i	arr[i]	dp[i][0]	dp[i][1]
0	1	1	$-\infty$
1	-2	-1	1
2	0	?	?
3	3	?	?

12. i = 2

```
arr[2] = 0
```

dp[2][0]

```
max(
    0,
    dp[1][0] + 0
)
```

```
= max(0, -1)
= 0
```

Therefore:

```
dp[2][0] = 0
```

dp[2][1]

```
max(
    dp[1][0],
    dp[1][1] + 0
)
```

```
= max(-1, 1 + 0)
= max(-1, 1)
= 1
```

So:

```
dp[2][1] = 1
```

This represents:

```
[1, -2, 0]
  X
```

After deleting -2:

```
[1, 0]
```

sum:

```
1
```

Table:

i	arr[i]	dp[i][0]	dp[i][1]
0	1	1	$-\infty$
1	-2	-1	1
2	0	0	1
3	3	?	?

13. i = 3

```
arr[3] = 3
```

dp[3][0]

```
max(
    3,
    dp[2][0] + 3
)
```

```
)

= max(3, 0 + 3)
= 3
```

So:

```
dp[3][0] = 3
```

dp[3][1]

```
max(
    dp[2][0],
    dp[2][1] + 3
)

= max(0, 1 + 3)
= 4
```

So:

```
dp[3][1] = 4
```

This represents:

```
[1, -2, 0, 3]
  X
```

After deletion:

```
[1, 0, 3]
```

Sum:

```
1 + 0 + 3 = 4
```

Final table:

i	arr[i]	dp[i][0]	dp[i][1]
0	1	1	-∞
1	-2	-1	1
2	0	0	1
3	3	3	4

Therefore:

```
answer = 4
```

14. Why do we take $\max(dp[i][0], dp[i][1])$?

Because the problem says:

at most one deletion

"At most one" means:

```
0 deletions
OR
1 deletion
```

So at every position, either state can give the answer.

That's why:

```
C++
ans = max(ans, max(dp[i][0], dp[i][1]));
```

15. DP form vs optimized form

The DP-table version uses:

```
dp[n][2]
```

so its space complexity is:

```
0(n)
```

The optimized version notices that:

```
dp[i]
```

only depends on:

```
dp[i-1]
```

So we don't actually need the entire table.

We can just keep:

```
C++
dp0
dp1
```

giving:

```
Space = 0(1)
```

Full DP table

```
dp[0]
↓
dp[1]
↓
dp[2]
↓
dp[3]
↓
...
```

Optimized

```
previous dp
↓
dp0, dp1
↓
new dp0, dp1
```

The most important thing to remember for an exam

If asked to "solve using DP", write these four things:

State

```
dp[i][0] = maximum subarray sum ending at i
           without deletion
dp[i][1] = maximum subarray sum ending at i
           with exactly one deletion
```

Base case

```
C++
dp[0][0] = arr[0];
dp[0][1] = INT_MIN;
```

Transition

```
C++
dp[i][0] = max(arr[i], dp[i-1][0] + arr[i]);
dp[i][1] = max(dp[i-1][0],
               dp[i-1][1] + arr[i]);
```

Answer

```
C++
ans = max(dp[i][0], dp[i][1]);
```

That is the **proper 2-state DP formulation** of this problem.

Yes — your **DP idea is basically correct**. The main error is in this line:

```
C++
int curr_totalsum = max(totalsum, totalsum + x);
```

You forgot the possibility of **starting a new subarray from x**.

It should be:

```
C++
int curr_totalsum = max(x, totalsum + x);
```

There is also an initialization problem with:

```
C++
int ans = 0;
```

because the answer can be negative.

Let's go through it carefully.

1. Your first error: curr_totalsum

You wrote:

```
C++
int curr_totalsum = max(totalsum, totalsum + x);
```

But **totalsum** means:

Best sum of a subarray ending at the **previous index**.

For normal Kadane's algorithm, when we see **x**, we have **two choices**:

Choice 1: Start a new subarray

```
C++
x
```

Choice 2: Extend the previous subarray

```
C++
totalsum + x
```

Therefore:

```
C++
int curr_totalsum = max(x, totalsum + x);
```

Why isn't totalsum itself a choice?

Because we're defining **totalsum** as:

maximum sum **ending at the current position**.

If we simply take:

```
C++
totalsum
```

then we're saying:

"Don't include x."

But then the subarray doesn't end at the current index anymore.

2. Simple example showing the problem

Consider:

```
arr = [1, -2, 3]
```

Initially:

```
C++
totalsum = 1;
```

At $x = -2$:

Your code:

```
C++
curr_totalsum = max(1, 1 + (-2));
                = max(1, -1)
                = 1;
```

But that's wrong according to our state definition.

The best subarray **ending at index 1** is:

```
[1, -2]
```

with sum:

```
-1
```

So it should be:

```
C++
curr_totalsum = max(-2, 1 + (-2));
                = max(-2, -1);
                = -1;
```

That's why the first argument must be x .

3. Your second transition is actually correct

You wrote:

```
C++
int curr_delete_sum = max(totalsum, delete_sum + x);
```

This is correct.

Remember:

```
delete_sum =
maximum sum ending at previous position
with exactly one deletion
```

There are two possibilities.

Possibility 1: Delete current x

```
C++
totalsum
```

We don't add x .

For example:

```
[1, -2]
  x
```

Delete -2.

Remaining:

```
[1]
```

sum = 1.

So:

```
C++
totalsum
```

is correct.

Possibility 2: Already deleted something

```
C++
delete_sum + x
```

For example:

```
[1, -2, 0]
  x
```

We already deleted -2.

Now we keep 0:

```
1 + 0 = 1
```

So:

```
C++
delete_sum + x
```

is correct.

Therefore:

```
C++
int curr_delete_sum = max(totalsum, delete_sum + x);
```

is good.

4. Your second error: ans = 0

You wrote:

```
C++
int ans = 0;
```

This is dangerous because the answer can be negative.

Look at:

```
arr = [-1, -1, -1, -1]
```

The answer is:

```
-1
```

because we cannot delete the only element of the chosen subarray.

But if:

```
C++
ans = 0;
```

then:

```
C++
ans = max(0, -1);
```

will always remain:

```
0
```

So your program would incorrectly return 0.

Instead:

```
C++
int ans = arr[0];
```

5. There is one more subtle point

You have:

```
C++
```

```
int delete_sum = INT_MIN;
```

That's good.

But then this:

```
C++
delete_sum + x
```

can technically cause **integer overflow** if `delete_sum` is `INT_MIN`.

For example:

```
INT_MIN + (-10000)
```

goes outside the range of `int`.

In practice, for this problem you should use a safe check, or use `long long`.

Since the constraints are small enough that normal sums fit in `int`, an easy approach is:

```
C++
int curr_delete_sum = totalsum;

if (delete_sum != INT_MIN) {
    curr_delete_sum = max(curr_delete_sum, delete_sum + x);
}
```

Or use `long long`.

6. Your corrected code

Keeping your exact style and variable names:

```
C++
class Solution {
public:
    int maximumSum(vector<int>& arr) {
        int totalsum = arr[0];

        // Maximum sum ending at previous position
        // with exactly one deletion
        int delete_sum = INT_MIN;

        int n = arr.size();

        // Answer can be negative
        int ans = arr[0];

        for (int i = 1; i < n; i++) {
            int x = arr[i];

            // Possibility 1:
            // Don't delete anything.
            //
            // Either:
            // 1. Start a new subarray from x
            // 2. Extend the previous subarray
            int curr_totalsum = max(x, totalsum + x);

            // Possibility 2:
            // Exactly one deletion.
            //
            // Either:
            // 1. Delete the current element x
            //    -> use totalsum
            //
            // 2. We already deleted an element previously
            //    -> extend delete_sum by x
            int curr_delete_sum = totalsum;

            if (delete_sum != INT_MIN) {
                curr_delete_sum =
                    max(curr_delete_sum, delete_sum + x);
            }

            // Update states for next iteration
            totalsum = curr_totalsum;
            delete_sum = curr_delete_sum;

            // Best answer so far
            ans = max(ans, max(totalsum, delete_sum));
        }

        return ans;
    }
};
```

7. Let's see the important correction

Your code:


```
C++
int curr_totalsum = max(totalsum, totalsum + x);
```

✗ Wrong.

Correct:

```
C++
int curr_totalsum = max(x, totalsum + x);
```

Because:



8. Your DP states are actually good

Your variable names correspond nicely to the DP states:

```
C++
totalsum
```

means:

```
dp[i][0]
```

Maximum sum ending at *i* with no deletion.

And:

```
C++
delete_sum
```

means:

```
dp[i][1]
```

Maximum sum ending at *i* with one deletion.

So your optimized DP is:

```
dp0 = totalsum
dp1 = delete_sum
```

And your transitions are:

```
C++
new_dp0 = max(x, dp0 + x);
new_dp1 = max(dp0, dp1 + x);
```

That's the core of the problem.

9. One more thing about your comment

You wrote:

"no delete the current element ... either increase the current sum or extend the previous sum"

I'd phrase it more precisely:

```
C++
// No deletion:
// Either start a new subarray with x,
// or extend the previous subarray by adding x.
```

And:

```
C++
// One deletion:
// Either delete the current x,
// or an element was already deleted previously,
// so extend that subarray by adding x.
```

This wording matches exactly what the DP is doing.

Final corrected transition to memorize

For this problem, remember just these two equations:

```
C++
new_dp0 = max(x, dp0 + x);
```

and

```
C++
new_dp1 = max(dp0, dp1 + x);
```

where:

```
dp0 = no deletion
dp1 = one deletion
```

Your overall approach was **very close** — the main conceptual mistake was forgetting the "**start a new subarray with x**" option in `curr_totalsum`, plus initializing `ans` to `0`.

ChatGPT can make mistakes. Check important info.