HELLO, MY NAME IS VISHAL PRAJAPATI, IN THIS PROJECT I HAVE UTILIZE SQL QUERY TO SOLVE SOME QUESTIONS RELATED TO PIZZA SALES

Retrieve the total number of orders placed.

```sql
SELECT
    *
FROM
    orders;
SELECT
    COUNT(order_id) AS total_orders
FROM
    orders;
```

Result Grid

	total_orders
▶	24872

Calculate the total revenue generated from pizza sales.

```
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
            2) AS total_sales
FROM
    order_details
        JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

Result Grid

	total_sales
▶	817860.05

List the top 5 most ordered pizza types along with their quantities.

```sql
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

Result Grid | Filter Rows:

name	quantity
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

Join the necessary tables to find the total quantity of each pizza category ordered.

```sql
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

Result Grid | Filter Rows:

category	quantity
Classic	14888
Supreme	11987
Veggie	11649
Chicken	11050

Group the orders by date and calculate the average number of pizzas ordered per day.

```sql
SELECT
    ROUND(AVG(quantity), 0) as avg_pizza_ordered_per_day
FROM
    (SELECT
        orders.order_date, SUM(order_details.quantity) AS quantity
    FROM
        orders
    JOIN order_details ON orders.order_id = order_details.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

Result Grid | Filter Rows:

avg_pizza_ordered_per_day
150

Determine the top 3 most ordered pizza types based on revenue

```sql
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
        JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

Calculate the percentage contribution of each pizza type to total revenue.

```sql
select pizza_types.category,
round(sum(order_details.quantity * pizzas.price) / (SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
            2) AS total_sales
FROM
    order_details
        JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id )*100,2) as revenue

from pizza_types join pizzas
on pizzas.pizza_type_id = pizza_types.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category order by revenue desc ;
```

Result Grid | Filter Rows:

category	revenue
Classic	26.91
Supreme	25.46
Chicken	23.96
Veggie	23.68

Analyze the cumulative revenue generated over time

```sql
select order_date,
sum(revenue) over(order by order_date) as cum_revenue
from
(select orders.order_date,
sum(order_details.quantity * pizzas.price) as revenue
from order_details join pizzas
on order_details.pizza_id = pizzas.pizza_id
join orders
on orders.order_id = order_details.order_id
group by orders.order_date) as sales ;
```

Result Grid | Filter Rows:

order_date	cum_revenue
1/1/2015	2713.850000000004
1/10/2015	5177.8
1/11/2015	7050.1
1/12/2015	8969.150000000001
1/13/2015	11018.750000000002
1/14/2015	13546.150000000001
1/15/2015	15530.95
1/16/2015	18125.100000000002
1/17/2015	20189.200000000004
1/18/2015	22166.050000000003
1/19/2015	24553.200000000004
1/2/2015	27285.100000000006

Result 2

Determine the top 3 most ordered pizza types based on revenue for each pizza category

```
select name, revenue from
(select category, name, revenue,
rank() over(partition by category order by revenue desc) as rn
from
(select pizza_types.category, pizza_types.name,
sum((order_details.quantity) * pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) as b
where rn <=3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5
The Classic Deluxe Pizza	38180.5
The Hawaiian Pizza	32273.25
The Pepperoni Pizza	30161.75
The Spicy Italian Pizza	34831.25
The Italian Supreme Pizza	33476.75
The Sicilian Pizza	30940.5
The Four Cheese Pizza	32265.70000000065
The Mexicana Pizza	26780.75
The Five Cheese Pizza	26066.5