

theHarvester

TheHarvester is a powerful and widely used OSINT (Open Source Intelligence) tool that helps Ethical Hackers, Penetration Testers, and cybersecurity professionals collect information related to target domains and organizations from various search engines, databases, and other publicly available services. The primary function of theHarvester is to gather critical information about a target domain, such as:

- **Subdomains:** Alternative domain addresses linked to the target.
- **Emails:** Employee or organizational email addresses. One of the most valuable pieces of information you can collect during a reconnaissance phase is a list of email addresses. These emails can later be used for social engineering attacks or identifying potential weak points in security configurations.
- **IP Addresses:** TheHarvester can map domain names to associated IP addresses. These addresses can be used for further network scanning and vulnerability analysis.
- **Hostnames:** Additional domain names or services linked to the target.

Installing on Other Linux Distributions

- `git clone https://github.com/laramies/theHarvester.git`
- `cd theHarvester`
- `sudo pip3 install -r requirements.txt`

Basic Command :

```
theHarvester -d -b
```

Common options:

Here's a breakdown of the most commonly used options in TheHarvester:

- **-d <domain>:** Specifies the domain to search.

- **-b <source>:** Defines the data source (e.g., yahoo, bing, shodan). You can specify multiple sources separated by commas.
 - **-l <limit>:** Limit the number of results fetched from the data sources.
 - **-f <filename>:** Save the output into a file (in HTML format).
 - **-n:** Perform DNS enumeration using search results.
 - **-t:** Perform DNS TLD expansion.
 - **-s <start>:** Start with a specific result number (useful when you want to skip initial results).
 - **-v:** Enable verbose mode for more detailed output.
-
- **Basic Usage Example:** To search for a subdomain (e.g., infosectrain.com) using Yahoo as the search engine:

- **Command**

```
theHarvester -d infosectrain.com -b yahoo
```

```
theHarvester -d infosectrain.com -b yahoo,bing -l 100 -v
```

```
theharvester -d example.com -b yahoo,bing -f results
```