



Java

Q1	Print Table
Code	<pre>import java.util.Scanner; class table { table(int a1) { for(int i=1; i<= 10; i++) { System.out.println(a1 +" * "+ i +" = "+ a1*i); } } } class newTable { public static void main(String args[]) { Scanner sc = new Scanner(System.in); System.out.print("Enter Number: "); int a = sc.nextInt(); table s1 = new table(a); } }</pre>



Output	<pre>D:\WorkSpaces\Java\HD>javac table.java D:\WorkSpaces\Java\HD>java newTable Enter Number: 9 9 * 1 = 9 9 * 2 = 18 9 * 3 = 27 9 * 4 = 36 9 * 5 = 45 9 * 6 = 54 9 * 7 = 63 9 * 8 = 72 9 * 9 = 81 9 * 10 = 90</pre>
Q2	Print Factorial
Code	<pre>import java.util.Scanner; class factorial { int factorial = 1; factorial(int a1) { for(int i=1; i<= a1; i++) { factorial =factorial * i; } System.out.println("Print: "+ factorial); } } class newFactorial { public static void main(String args[]) { Scanner sc = new Scanner(System.in);</pre>



	<pre>System.out.print("Enter Number: "); int a = sc.nextInt(); factorial s1 = new factorial(a); } }</pre>
Output	<pre>D:\WorkSpaces\Java\HD>java newFactorial Enter Number: 5 Print: 120 D:\WorkSpaces\Java\HD>java newFactorial Enter Number: 10 Print: 3628800</pre>
Q3	Vowel or constant
Code	<pre>import java.util.Scanner; class vowel { vowel(char ch) { if(ch == 'a' ch == 'e' ch == 'i' ch == 'o' ch == 'u' ch == 'A' ch == 'E' ch == 'I' ch == 'O' ch == 'U') { System.out.println("Vowel"); } else { System.out.println("Consonant"); } } } class newVowel { public static void main(String args[]) { Scanner sc = new Scanner(System.in); System.out.print("Enter Character: ");</pre>



	<pre>char a = sc.next().charAt(0); vowel v 1 = new vowel(a); } }</pre>
Output	<pre>D:\WorkSpaces\Java\HD>java newVowel Enter Character: f Consonant D:\WorkSpaces\Java\HD>java newVowel Enter Character: o Vowel</pre>
Q4	Enter number and return name of month
Code	<pre>import java.util.Scanner; class Month { Month(int a) { switch(a) { case 1: System.out.println("January"); break; case 2: System.out.println("February"); break; case 3: System.out.println("March"); break; case 4: System.out.println("April"); break; case 5:</pre>



	<pre>System.out.println("May"); break; case 6: System.out.println("June"); break; case 7: System.out.println("July"); break; case 8: System.out.println("August"); break; case 9: System.out.println("September"); break; case 10: System.out.println("October"); break; case 11: System.out.println("November"); break; case 12: System.out.println("December"); break; default: System.out.println("Invalid Month Number"); } } } class NewMonth { public static void main(String args[]) { Scanner sc = new Scanner(System.in);</pre>
--	---



	<pre>System.out.print("Enter Month Number: "); int a = sc.nextInt(); Month m1 = new Month(a); } }</pre>
Output	<pre>D:\WorkSpaces\Java\HD>java NewMonth Enter Month Number: 5 May D:\WorkSpaces\Java\HD>java NewMonth Enter Month Number: 13 Invalid Month Number</pre>
Q5	Print Square
Code	<pre>import java.util.Scanner; class square { square() { System.out.println("Program of square"); } square(int a1) { System.out.println("Square:"+ a1*a1); } } class t1 { public static void main(String args[]) { Scanner sc = new Scanner(System.in); System.out.print("Enter Number: "); int a = sc.nextInt(); square s1 = new square(a); } }</pre>



Output	<pre>D:\WorkSpaces\Java\HD>javac t1.java D:\WorkSpaces\Java\HD>java t1 Enter Number: 5 Square:25</pre>