

REC-CIS

Flag question

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d",&a);
6     scanf("%d",&b);
7     scanf("%d",&c);
8     if ((a*a + b*b == c*c) || (b*b + c*c == a*a) || (a*a + c*c == b*b))
9     {
10         printf("yes");
11     }
12     else {
13         printf("no");
14     }
15     return 0;
16 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

REC-CIS

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d", &n);
6     if(n%2!=0)
7     {
8         printf("Weird");
9     }
10    else if(n%2==0)
11    {
12        if(2<=n && 2<=5){
13            printf("Not Weird");
14        }
15        else if (n>=20)
16        {
17            printf("Not Weird");
18        }
19        else if (6<=n && n<=20)
20        {
21            printf("Weird");
22        }
23    }
24    } return 0;
25 }

```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

REC-CIS

Flag question

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     scanf("%d",&a);
6     scanf("%d",&b);
7     int c,d;
8     c = a%10;
9     d = b%10;
10    if(c==d)
11    {
12        printf("true");
13    }
14    else
15    {
16        printf("false");
17    }
18    return 0;
19 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓