

REC-CIS

Answer: (pending registration)

```
1 #include<stdio.h>
2 int main(){
3     long long int n,t,i,nut=0;
4     scanf("%lld %lld",&n,&t);
5     for(i=1;i<=n;i++){
6         nut=nut+i;
7         if(nut==t){
8             nut=nut-1;
9         }
10    }
11    printf("%lld",nut%1000000007);
12 }
```

	Input	Expected	Got	
✓	2 2	3	3	✓
✓	2 1	2	2	✓
✓	3 3	5	5	✓

REC-CIS

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main(){
3     int n,x,y=1;
4     scanf("%d",&n);
5     while(n!=0 && y==1){
6         x=n%10;n=n/10;
7         if(x==2||x==3||x==4||x==7){
8             y++;
9         }
10    }
11    if(y==1){
12        printf("true");
13    }
14    else{
15        printf("false");
16    }
17 }

```

	Input	Expected	Got	
✓	6	true	true	✓
✓	89	true	true	✓
✓	25	false	false	✓

Passed all tests! ✓

REC-CIS

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int n,x=0;
5     while(scanf("%d",&n)==1){
6         if(n%2!=0){
7             x++;
8         }
9     }
10    printf("%d",x);
11    return 0;
12 }
    
```

	Input	Expected	Got	
✓	5 10 15 20 25 30 35 40 45 50	5	5	✓

Passed all tests! ✓

Question 2

Given a number N, return true if and only if it is a *confusing number* which satisfies the following condition: