

REC-CIS

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int n,k;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr[i]);
10    }
11    scanf("%d",&k);
12    for(int a=0;a<=n-k;a++)
13    {
14        int max=arr[a];
15        for(int b=a;b<a+k;b++)
16        {
17            if(arr[b]>max)
18            {
19                max=arr[b];
20            }
21        }
22        printf("%d ",max);
23    }
24 }
```

	Input	Expected	Got	
✓	8 1 3 5 2 1 8 6 9 3	5 5 5 8 8 9	5 5 5 8 8 9	✓
✓	10 7 7 5 9 9 8 5	7 7 5 9 9 8 5	7 7 5 9 9 8 5	✓

REC-CIS

```
11 scanf("%d",&k);
12 for(int a=0;a<=n-k;a++)
13 {
14     int max=arr[a];
15     for(int b=a;b<a+k;b++)
16     {
17         if(arr[b]>max)
18         {
19             max=arr[b];
20         }
21     }
22     printf("%d ",max);
23 }
24 }
```

	Input	Expected	Got	
✓	8 1 3 5 2 1 8 6 9 3	5 5 5 8 8 9	5 5 5 8 8 9	✓
✓	10 3 7 5 1 2 9 8 5 3 2 3	7 7 5 9 9 9 8 5	7 7 5 9 9 9 8 5	✓

Passed all tests! ✓

Question 2
Correct
Marked out of 1.00

Given an array and a threshold value find the output.
Input: {5,8,10,13,6,2}
Threshold = 3

REC-CIS

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,t,count=0;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8     {
9         scanf("%d",&arr[i]);
10    }
11    scanf("%d",&t);
12    for(int j=0;j<n;j++)
13    {
14        while(arr[j]>0){
15            arr[j]-=t;
16            count++;
17        }
18    }
19    printf("%d",count);
20 }
```

	Input	Expected	Got	
✓	6 5 8 10 13 6 2 3	17	17	✓
✓	7 20 35 57 30 56 87 30 10	33	33	✓

Passed all tests! ✓

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     scanf("%d",&a);
6     int arr1[a];
7     for(int i=0;i<a;i++)
8     scanf("%d",&arr1[i]);
9     scanf("%d",&b);
10    int arr2[b];
11    for(int i=0;i<b;i++)
12    scanf("%d",&arr2[i]);
13    int p=0,q=0;
14    while((p<a)&&(q<b))
15    {
16        if(arr1[p]<arr2[q])
17        {
18            printf("%d ",arr1[p]);
19            p++;
20        }
21        else if(arr1[p]>arr2[q])
22        {
23            printf("%d ",arr2[q]);
24            q++;
25        }
26        else
27        {
28            printf("%d ",arr1[p]);
29            p++;
30            q++;
31        }
32    }
33    for(int j=p;j<a;j++)
34    {
35        printf("%d ",arr1[j]);
36    }
37    for(int j=q;j<b;j++)
38    {
```

REC-CIS

```
25 }
26 else
27 {
28     printf("%d ",arr1[p]);
29     p++;
30     q++;
31 }
32 }
33 for(int j=p;j<a;j++)
34 {
35     printf("%d ",arr1[j]);
36 }
37 for(int j=q;j<b;j++)
38 {
39     printf("%d ",arr2[j]);
40 }
41 }
```

	Input	Expected	Got	
✓	5 1 2 3 6 9 4 2 4 5 10	1 2 3 4 5 6 9 10	1 2 3 4 5 6 9 10	✓

Passed all tests! ✓

Finish review