

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int t;
4     scanf("%d",&t);
5     while(t-->0)
6     {
7         int n,m,d,min,temp;
8         scanf("%d %d",&n,&m);
9         d=n-m;
10        int arr[n];
11        for(int i=0;i<n;i++)
12            scanf("%d",&arr[i]);
13        for(int j=0;j<n;j++)
14        {
15            min=j;
16            for(int k=j;k<n;k++)
17            {
18                if(arr[k]<arr[min])
19                    min=k;
20            }
21            temp=arr[min];
22            arr[min]=arr[j];
23            arr[j]=temp;
24        }
25        int maxsum=0,minsum=0;
26        for(int a=0;a<d;a++)
27            minsum+=arr[a];
28        for(int b=n-1;b>m-1;b--)
29            maxsum+=arr[b];
30        printf("%d\n",maxsum-minsum);
31    }
32 }
```

REC-CIS

```
22     arr[min]=arr[j];
23     arr[j]=temp;
24 }
25 int maxsum=0,minsum=0;
26 for(int a=0;a<d;a++)
27     minsum+=arr[a];
28 for(int b=n-1;b>m-1;b--)
29     maxsum+=arr[b];
30 printf("%d\n",maxsum-minsum);
31 }
32 }
```

	Input	Expected	Got	
✓	1 5 1 1 2 3 4 5	4	4	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 1.00

Flag question

A new deadly virus has infected large population of a planet. A brilliant scientist has discovered a new strain of virus which can cure this disease. Vaccine produced from this virus has various strength depending on midichlorians count. A person is cured only if midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

Input Format

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n,min1,min2,temp,flag=1;
4     scanf("%d",&n);
5     int vac[n],pat[n];
6     for(int i=0;i<n;i++)
7         scanf("%d",&vac[i]);
8     for(int i=0;i<n;i++)
9         scanf("%d",&pat[i]);
10    for(int j=0;j<n-1;j++){
11        min1=j,min2=j;
12        for(int k=j;k<n;k++){
13            {
14                if(vac[k]<vac[min1])
15                    min1=k;
16                if(pat[k]<pat[min2])
17                    min2=k;
18            }
19            temp=vac[min1];
20            vac[min1]=vac[j];
21            vac[j]=temp;
22
23            temp=pat[min2];
24            pat[min2]=pat[j];
25            pat[j]=temp;
26        }
27    for(int i=0;i<n;i++)
28    {
29        if(vac[i]<=pat[i])
30        {
31            flag=0;
32            break;
33        }
34    }
35    if(flag==1)
36        printf("Yes");
37    else
```

REC-CIS

```
31         flag=0;
32         break;
33     }
34 }
35 if(flag==1)
36     printf("Yes");
37 else
38     printf("No");
39 }
```

	Input	Expected	Got	
✓	5 123 146 454 542 456 100 328 248 689 200	No	No	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 1.00

[Flag question](#)

You are given an array of n integer numbers $a_1, a_2, \dots, a_n$. Calculate the number of pair of indices (i, j) such that $1 \leq i < j \leq n$ and $a_i \text{ xor } a_j = 0$.

Input format

- First line: n denoting the number of array elements
- Second line: n space separated integers $a_1, a_2, \dots, a_n$.

REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n,count=0;
4     scanf("%d",&n);
5     int arr[n];
6     for(int i=0;i<n;i++)
7         scanf("%d",&arr[i]);
8     for(int i=0;i<n-1;i++){
9         for(int j=i+1;j<n;j++){
10             if((arr[i]^arr[j])==0)
11                 count++;
12         }
13     }
14     printf("%d",count);
15 }
```

	Input	Expected	Got	
✓	5 1 3 1 4 3	2	2	✓

Passed all tests! ✓

REC-CIS

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8         scanf("%d",&arr[i]);
9     int max=arr[0];
10    for(int i=1;i<n;i++)
11    {
12        if(arr[i]>max)
13            max=arr[i];
14    }
15    max++;
16    int min=0;
17    for(int a=0;a<n;a++)
18    {
19        for(int b=0;b<n;b++){
20            if(arr[b]<arr[min])
21                min=b;
22        }
23        printf("%d ",min);
24        arr[min]=max;
25    }
26 }
```

	Input	Expected	Got	
✓	5 4 5 3 7 1	4 2 0 1 3	4 2 0 1 3	✓

Passed all tests! ✓