Caption-Image Retrieval

Searching photos by typing a sentence

Vishanth (PES1UG24AM323) · **Kshitij Gupta** (PES1UG24AM915)

UE24CS352A Machine Learning — Mini-Project · October 2026

1. The idea — search photos with words

top results from 5,000 photos the model never saw in training

"a man riding a wave on a surfboard"

search



#1 #2 #3 #4 #5

- We all have thousands of photos — scrolling to find one is painful
- Our system: **type a sentence → get the matching photos**
- These are **real results** from our model, on photos it never saw while training

2. The task, and how we score it

- **Input:** a collection of photos + a sentence describing one of them
- **Output:** the photos ranked from best match to worst

Test caption: "a bear walking down the grass in the open" → all 5,000 test images ranked



rank 1 | rank 2 | **rank 3** | rank 4 | rank 5 | • • •

correct image is at rank 3

R@1: ✗ miss


R@5: ✓ hit

R@10: ✓ hit

Recall@K = % of all queries that are a hit. Mean rank = average position of the correct image.

- **Recall@K (R@K)** = how often the right photo is in the **top K**. Higher is better.
- **Mean rank** = where the right photo lands on average. Lower is better.

3. The data — Microsoft COCO 2017




1 image → 5 captions written by 5 different people

1. a big burly grizzly bear is show with grass in the background
2. the large brown bear has a black nose
3. closeup of a brown bear sitting in a grassy area
4. a large bear that is sitting on grass
5. a close up picture of a brown bear s face

	Training (to learn)	Validation (to pick best model)	Test (final score)
Photos	**113,287**	5,000	5,000 — never seen in training
Captions	566,435	25,000	25,000

4. Preparing the captions




- The vocabulary (**26,351 words**) is built from the training captions only
- Each word starts with a **GloVe** vector — 300 numbers that already capture its meaning, learned from Wikipedia-scale text
- 20 slots is enough: only **0.6%** of captions get cut short

5. Preparing the photos




photo (centre crop)



VGG-19 (already trained, we don't change it)


4,096 numbers
= what is in the photo

scale to length 1 (L2-normalise)




- **VGG-19** is a famous network already trained to recognise objects — we use it as-is
- Each photo becomes **4,096 numbers** describing what is in it
- **Scaling every vector to length 1 was essential** — without it the model just memorised (chart, right)
- The 19.3 GB image zip was **streamed**, never stored — we kept only 1.9 GB of numbers

6. Our approach — one shared space for photos and sentences




- Two **encoders** turn a photo and a sentence into **1,024 numbers** each — a point in the same space
- Training places matching pairs **close together**; searching = find the **nearest** photos

7. Baseline — average the words, fit one matrix




- Caption = **average of its word vectors** (300 numbers)
- One matrix `W` maps it to the photo's 4,096 VGG numbers — **least squares**, solved with one formula in seconds
- **Weakness:** averaging forgets word order and **dilutes** the important words

8. Main model — a GRU reads the caption word by word



- **Caption encoder:** GloVe vectors → **GRU** (a recurrent neural network with a 1,024-number memory) → the caption's point
- **Image encoder:** one learned layer, 4,096 VGG numbers → 1,024
- **17.2 M** learnable numbers in total (7.9 M of them are the word vectors, which are fine-tuned)


9. How it learns — the margin ranking loss



- In each batch of **128** pairs, every photo has 1 right caption and **127 wrong ones** (the other photos' captions) — free negatives
- Penalty whenever a wrong caption is not farther away than the right one by the **margin 0.1**


Optimizer	Batch	Margin	Max words	Epochs	Time per epoch
Adam, learning rate 0.001	128	0.1	20	20	~1.4 min (laptop GPU)


10. Implementation — the pipeline



- **PyTorch** on an Apple **M3 Pro** laptop GPU (VGG-19 + GRU); **NumPy** for the baseline
- Feature extraction downloads only byte ranges of the 19.3 GB zip — never the whole file
- The demo encodes the 5,000 test photos **once**, so each query is answered instantly
- The best-validation model is scored on the test set **once**, at the end

11. Results — test set (5,000 unseen photos)






- The GRU beats the baseline on **every** measure: R@10 **17.5% → 43.8%** (2.5×)
- Average position of the right photo: **157th → 48th** out of 5,000 (top 1%)


5K: search all 5,000 test photos. 1K: the standard protocol from published papers — five groups of 1,000, averaged. Full table (R@1, R@5, mean rank) in the write-up.

12. More data helped most

- An earlier run trained on only **5,000** photos: R@10 **28.3%**
- Full COCO, **23× more data**, same model: **43.8%** (+15.5 points)
- Reference paper (Stanford CS229): **86.8%** on 1K vs our **77.9%**
- Why we are ~9 points behind:
  - **20 epochs** vs up to 50 — ours was still improving
  - **1 crop** per photo vs their average of 10 crops
  - slightly different test photos




13. Demo — query: "a cycle"




- **10 of 10** results are **bicycles or motorcycles** — all photos the model never saw
- "cycle" appears only **219 times** in training captions (vs 6,940 for "motorcycle")

14. Training progress



- After **one** pass over the data the GRU already beats the baseline (23.2% vs 17.5%)
- Still climbing at epoch 20 → **training longer should help**

15. Where it fails — "two dogs playing in the snow"



- It finds **snow** and **dogs** — but only **one** photo has *two* dogs in snow
- **Why:** each photo is **one summary vector**, so the model cannot count or check that things appear together

16. Conclusions & future work

What we showed

- A GRU sentence encoder **beats averaging words by 2.5×** (R@10 43.8% vs 17.5%)
- **More data mattered most**: 5,000 → 113,287 photos, +15.5 points
- **Scaling image vectors to length 1** was essential (2% → 49% in a pilot)
- Close to the published result (77.9% vs 86.8%), trained on a laptop

Next steps

- Train **longer**, with **10-crop** image features
- Focus the loss on the **hardest** wrong answer (VSE++)
- Let the model look at **image regions** (attention) to handle counting and combinations

Thank you

Questions?

`github.com/Vishanth21/neural_caption-image_retrieval`