

Positive-Class Weighting Induces Systematic Probability Distortion in Deep Learning Models for Chest Radiography under Deidentified-Data Cohort Shift

Vishesh Panghal*

^aDepartment of Artificial Intelligence and Data Science, Poornima Institute of Engineering and Technology (PIET), Jaipur, 302022, Rajasthan, India

Article Information

- **Article Type:** Original Research Article
- **Target Journal:** *Computer Methods and Programs in Biomedicine* (Elsevier)
- **Corresponding Author:** Vishesh Panghal (pvt.panghal@gmail.com)
- **Text Word Count:** Approximately 3,650 words (excluding abstract, references, tables, and figures)
- **Structured Abstract Word Count:** 313 words
- **Number of Figures:** 5
- **Number of Tables:** 5 (plus 5 supplementary tables)
- **Number of References:** 23

Highlights

- Positive loss weighting induces an additive population logit offset of $\log w$.

*Corresponding author.

Email address: pvt.panghal@gmail.com (Vishesh Panghal)

- Finite neural network logits empirically cluster tightly around theoretical $\log w$.
- Temperature scaling cannot correct this intercept-type calibration bias.
- Analytic offset ($z - \log w$) cuts 73.7% of Brier error without retraining.
- Selective triage exposes trade-offs between calibrated risk and screening referral.