

Name: Vishesh Singh Bhadauria
Email ID: Vishesh.Bhadauria@Coforge.com
Emp ID: 85011029

1. When does Exceptions in Java arises in code sequence?

- a) Run Time
- b) Compilation Time
- c) Can Occur Any Time
- d) None of the mentioned

2. Which of these keywords is not a part of exception handling?

- a) try
- b) finally
- c) thrown
- d) catch

3. Which of these keywords must be used to monitor for exceptions?

- a) try
- b) finally
- c) throw
- d) catch

4. Which of these keywords must be used to handle the exception thrown by try block in some rational manner?

- a) try
- b) finally
- c) throw
- d) catch

5. Which of these keywords is used to manually throw an exception?

- a) try
- b) finally
- c) throw

6. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("Hello" + " " + 1 / 0);
        }
        catch(ArithmeticException e)
        {
            System.out.print("World");
        }
    }
}
```

- ```
}
```
- a) Hello
  - b) World**
  - c) HelloWorld
  - d) Hello World

7. What will be the output of the following Java program?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a, b;
 b = 0;
 a = 5 / b;
 System.out.print("A");
 }
 catch(ArithmeticException e)
 {
 System.out.print("B");
 }
 }
}
```

- a) A
- b) B**
- c) Compilation Error
- d) Runtime Error

8. What will be the output of the following Java program?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a, b;
 b = 0;
 a = 5 / b;
 System.out.print("A");
 }
 catch(ArithmeticException e)
 {
 System.out.print("B");
 }
 finally
 {

```

```

 System.out.print("C");
 }
}

```

- a) A
- b) B
- c) AC
- d) BC

9. What will be the output of the following Java program?

```

class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int i, sum;
 sum = 10;
 for (i = -1; i < 3 ;++i)
 sum = (sum / i);
 }
 catch(ArithmeticException e)
 {
 System.out.print("0");
 }
 System.out.print(sum);
 }
}

```

- a) 0
- b) 05
- c) Compilation Error
- d) Runtime Error

### Exceptional handling:

10. Which of the following keywords is used for throwing exception manually?

- a) finally
- b) try
- c) throw
- d) catch

11. Which of the following classes can catch all exceptions which cannot be caught?

- a) RuntimeException
- b) Error
- c) Exception
- d) ParentException

12. Which of the following is a super class of all exception type classes?

- a) Catchable
- b) RuntimeExceptions

- c) String
- d) Throwable

13. Which of the following operators is used to generate instance of an exception which can be thrown using throw?

- a) thrown
- b) alloc
- c) malloc
- d) new

14. Which of the following keyword is used by calling function to handle exception thrown by called function?

- a) throws
- b) throw
- c) try
- d) catch

15. Which of the following handles the exception when a catch is not used?

- a) finally
- b) throw handler
- c) default handler
- d) java run time system

16. Which part of code gets executed whether exception is caught or not?

- a) finally
- b) try
- c) catch
- d) throw

17. Which of the following should be true of the object thrown by a throw statement?

- a) Should be assignable to String type
- b) Should be assignable to Exception type
- c) Should be assignable to Throwable type
- d) Should be assignable to Error type

18. At runtime, error is recoverable.

- a) True
- b) False

19. Which of these is a super class of all exceptional type classes?

- a) String
- b) RuntimeExceptions
- c) Throwable
- d) Cacheable

20. Which of these class is related to all the exceptions that can be caught by using catch?

- a) Error
- b) Exception
- c) RuntimeException
- d) All of the mentioned

21. Which of these class is related to all the exceptions that cannot be caught?

- a) Error
- b) Exception
- c) RuntimeException
- d) All of the mentioned

22. Which of these handles the exception when no catch is used?

- a) Default handler
- b) finally
- c) throw handler
- d) Java run time system

23. What exception thrown by parseInt() method?

- a) ArithmeticException
- b) ClassNotFoundException
- c) NullPointerException
- d) NumberFormatException

24. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 System.out.print("Hello" + " " + 1 / 0);
 }
 finally
 {
 System.out.print("World");
 }
 }
}
```

- a) Hello
- b) World
- c) Compilation Error
- d) First Exception then World

25. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int i, sum;
 sum = 10;
 for (i = -1; i < 3 ;++i)
 {
 sum = (sum / i);
 }
 }
 }
}
```

```

 System.out.print(i);
 }
}
catch(ArithmeticException e)
{
 System.out.print("0");
}
}
}

```

- a) -1
- b) 0
- c) -10
- d) -101

26. Which of these keywords is used to generate an exception explicitly?

- a) try
- b) finally
- c) throw
- d) catch

27. Which of these class is related to all the exceptions that are explicitly thrown?

- a) Error
- b) Exception
- c) Throwable
- d) Throw

28. Which of these operator is used to generate an instance of an exception than can be thrown by using throw?

- a) new
- b) malloc
- c) alloc
- d) thrown

29. Which of these keywords is used to by the calling function to guard against the exception that is thrown by called function?

- a) try
- b) throw
- c) throws
- d) catch

30. What will be the output of the following Java code?

```

class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a = args.length;
 int b = 10 / a;
 System.out.print(a);
 }
 try
 {

```

```

 if (a == 1)
 a = a / a - a;
 if (a == 2)
 {
 int []c = {1};
 c[8] = 9;
 }
 }
 catch (ArrayIndexOutOfBoundsException e)
 {
 System.out.println("TypeA");
 }
 catch (ArithmeticException e)
 {
 System.out.println("TypeB");
 }
}
}
}

```

- a) TypeA
- b) TypeB
- c) Compile Time Error**
- d) 0TypeB

31. What will be the output of the following Java code?

```

class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 System.out.print("A");
 throw new NullPointerException ("Hello");
 }
 catch(ArithmeticException e)
 {
 System.out.print("B");
 }
 }
}

```

- a) A
- b) B
- c) Hello
- d) Runtime Exception**

32. What will be the output of the following Java code?

```

public class San
{
 public static void main(String[] args)
 {
 try

```

```

 {
 return;
 }
 finally
 {
 System.out.println("Finally");
 }
 }
}

```

- a) Finally
- b) Compilation fails
- c) The code runs with no output
- d) An exception is thrown at runtime

33. What will be the output of the following Java code?

```

public class San
{
 public static void main(String args[])
 {
 try
 {
 System.out.print("Hello world ");
 }
 finally
 {
 System.out.println("Finally executing ");
 }
 }
}

```

- a) The program will not compile because no exceptions are specified
- b) The program will not compile because no catch clauses are specified
- c) Hello world
- d) Hello world Finally executing

34. Which of these clause will be executed even if no exceptions are found?

- a) throws
- b) finally
- c) throw
- d) catch

35. A single try block must be followed by which of these?

- a) finally
- b) catch
- c) finally & catch
- d) none of the mentioned

36. Which of these exceptions handles the divide by zero error?

- a) ArithmeticException
- b) MathException
- c) IllegalAccessException



d) `IllegalException`

37. Which of these exceptions will occur if we try to access the index of an array beyond its length?

- a) `ArithmeticException`
- b) `ArrayException`
- c) `ArrayIndexException`
- d) `ArrayIndexOutOfBoundsException`

38. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a = args.length;
 int b = 10 / a;
 System.out.print(a);
 }
 catch (ArithmeticException e)
 {
 System.out.println("1");
 }
 }
}
```

Note : Execution command line : `$ java exception_handling`

- a) 0
- b) 1
- c) Compilation Error
- d) Runtime Error

39. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 throw new NullPointerException ("Hello");
 }
 catch(ArithmeticException e)
 {
 System.out.print("B");
 }
 }
}
```

- a) A

- b) B
- c) Compilation Error
- d) Runtime Error

40. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a = 1;
 int b = 10 / a;
 try
 {
 if (a == 1)
 a = a / a - a;
 if (a == 2)
 {
 int c[] = {1};
 c[8] = 9;
 }
 }
 finally
 {
 System.out.print("A");
 }
 }
 catch (Exception e)
 {
 System.out.println("B");
 }
 }
}
```

- a) A
- b) B
- c) AB
- d) BA

41. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 int a = args.length;
```

```

int b = 10 / a;
System.out.print(a);
try
{
 if (a == 1)
 a = a / a - a;
 if (a == 2)
 {
 int []c = {1};
 c[8] = 9;
 }
}
catch (ArrayIndexOutOfBoundsException e)
{
 System.out.println("TypeA");
}
catch (ArithmeticException e)
{
 System.out.println("TypeB");
}
}

```

Note: Execution command line: \$ java exception\_handling one two

- a) TypeA
- b) TypeB
- c) Compilation Error**
- d) Runtime Error

42. What is the use of try & catch?

- a) It allows us to manually handle the exception
- b) It allows to fix errors
- c) It prevents automatic terminating of the program in cases when an exception occurs**
- d) All of the mentioned

43. Which of these keywords are used for the block to be examined for exceptions?

- a) try**
- b) catch
- c) throw
- d) check

44. Which of these keywords are used for the block to handle the exceptions generated by try block?

- a) try
- b) catch**
- c) throw
- d) check

45. Which of these keywords are used for generating an exception manually?

- a) try
- b) catch

- c) throw
- d) check

46. Which of these statements is incorrect?

- a) try block need not to be followed by catch block
- b) try block can be followed by finally block instead of catch block
- c) try can be followed by both catch and finally block
- d) try need not to be followed by anything

47. What will be the output of the following Java code?

```
class Output
{
 public static void main(String args[])
 {
 try
 {
 int a = 0;
 int b = 5;
 int c = b / a;
 System.out.print("Hello");
 }
 catch(Exception e)
 {
 System.out.print("World");
 }
 }
}
```

- a) Hello
- b) World
- c) HelloWOrld
- d) Compilation Error

48. What will be the output of the following Java code?

```
class Output
{
 public static void main(String args[])
 {
 try
 {
 int a = 0;
 int b = 5;
 int c = a / b;
 System.out.print("Hello");
 }
 catch(Exception e)
 {
 System.out.print("World");
 }
 }
}
```

```
}
```

a) Hello

b) World

c) HelloWorld

d) Compilation Error

49. What will be the output of the following Java code?

```
class Output
{
 public static void main(String args[])
 {
 try
 {
 int a = 0;
 int b = 5;
 int c = b / a;
 System.out.print("Hello");
 }
 }
}
```

a) Hello

b) World

c) HelloWOrld

d) Compilation Error

50. What will be the output of the following Java code?

```
class Output
{
 public static void main(String args[])
 {
 try
 {
 int a = 0;
 int b = 5;
 int c = a / b;
 System.out.print("Hello");
 }
 finally
 {
 System.out.print("World");
 }
 }
}
```

a) Hello

b) World

c) HelloWOrld

d) Compilation Error

51. What will be the output of the following Java code?

```
class Output
{
 public static void main(String args[])
 {
 try
 {
 int a = 0;
 int b = 5;
 int c = b / a;
 System.out.print("Hello");
 }
 catch(Exception e)
 {
 System.out.print("World");
 }
 finally
 {
 System.out.print("World");
 }
 }
}
```

- a) Hello
- b) World
- c) HelloWorld
- d) WorldWorld

52. Which of these classes is used to define exceptions?

- a) Exception
- b) Throwable
- c) Abstract
- d) System

53. Which of these methods return description of an exception?

- a) getException()
- b) getMessage()
- c) obtainDescription()
- d) obtainException()

54. Which of these methods is used to print stack trace?

- a) obtainStackTrace()
- b) printStackTrace()
- c) getStackTrace()
- d) displayStackTrace()

55. Which of these methods return localized description of an exception?

- a) **getLocalizedMessage()**
- b) getMessage()
- c) obtainLocalizedMessage()
- d) printLocalizedMessage()

56. Which of these classes is super class of Exception class?

- a) **Throwable**
- b) System
- c) RunTime
- d) Class

57. What will be the output of the following Java code?

```
class Myexception extends Exception
{
 int detail;
 Myexception(int a)
 {
 detail = a;
 }
 public String toString()
 {
 return "detail";
 }
}
class Output
{
 static void compute (int a) throws Myexception
 {
 throw new Myexception(a);
 }
 public static void main(String args[])
 {
 try
 {
 compute(3);
 }
 catch(Myexception e)
 {
 System.out.print("Exception");
 }
 }
}
```

a) 3

- b) **Exception**
- c) Runtime Error
- d) Compilation Error

58. What will be the output of the following Java code?

```
class Myexception extends Exception
{
 int detail;
 Myexception(int a)
 {
 detail = a;
 }
 public String toString()
 {
 return "detail";
 }
}
class Output
{
 static void compute (int a) throws Myexception
 {
 throw new Myexception(a);
 }
 public static void main(String args[])
 {
 try
 {
 compute(3);
 }
 catch(DevideByZeroException e)
 {
 System.out.print("Exception");
 }
 }
}
```

- a) 3
- b) Exception
- c) Runtime Error
- d) Compilation Error

59. What will be the output of the following Java code?

```
class exception_handling
{
 public static void main(String args[])
 {
 try
 {
 throw new NullPointerException ("Hello");
 System.out.print("A");
 }
 catch(ArithmeticException e)
 {

```



```

 System.out.print("B");
 }
}

```

- a) A
- b) B
- c) Compilation Error**
- d) Runtime Error

60. What will be the output of the following Java code?

```

class Myexception extends Exception
{
 int detail;
 Myexception(int a)
 {
 detail = a;
 }
 public String toString()
 {
 return "detail";
 }
}
class Output
{
 static void compute (int a) throws Myexception
 {
 throw new Myexception(a);
 }
 public static void main(String args[])
 {
 try
 {
 compute(3);
 }
 catch(Exception e)
 {
 System.out.print("Exception");
 }
 }
}

```

- a) 3
- b) Exception**
- c) Runtime Error
- d) Compilation Error

61. What will be the output of the following Java code?

```

class exception_handling

```

```

{
 public static void main(String args[])
 {
 try
 {
 int a = args.length;
 int b = 10 / a;
 System.out.print(a);
 try
 {
 if (a == 1)
 a = a / a - a;
 if (a == 2)
 {
 int c = {1};
 c[8] = 9;
 }
 }
 catch (ArrayIndexOutOfBoundsException e)
 {
 System.out.println("TypeA");
 }
 catch (ArithmeticException e)
 {
 System.out.println("TypeB");
 }
 }
 }
}

```

Note : Execution command line : \$ java exception\_handling one

a) TypeA

b) TypeB

**c) Compilation Error**

d) Runtime Error