

HIGH RISK PRODUCT SPECIFICATIONS

Name of Product - 14 Mil Powder free Latex High Risk Gloves.

Name of Manufacturer - Innovative Gloves Co. Ltd. Hatyai, Thailand.

Base Material - Natural Rubber Latex.

Characteristics - Non-Sterile, Ambidextrous Beaded Cuff.

Available Sizes - Small, Medium, Large, X-Large, XX-Large.

Surface - Textured.

Surface Treatment - Mild Washing with Chlorine Solution and Extensive Washing.

Color - Blue.

Total Residue Content - < 2.0 Milligrams per glove.

Total Extractable protein content

< 50µ gram/ gram of glove

Physical Specifications:

| Size | Length(mm/inch) | Thickness(mm) Single Wall | | | |
|-----------|-----------------|---------------------------|--------------------------|--------------------------|-----------|
| | | Tip Textured Surface | Palm textured Surface | Cuff Textured Surface | Width(mm) |
| Small | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 85±5 |
| Medium | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 95±5 |
| Large | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 105±5 |
| X-Large | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 115±5 |
| XX-Large | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 120±3 |
| XXX-Large | 300±10 | 0.37±0.01 | 0.28±0.01 | 0.21±0.01 | 125±3 |



Tensile (ASTM D412 & EN 455-2)

Before Aging

| Tensile(MPA) | Elongation(%) | Force At Break(N) |
|--------------|---------------|-------------------|
| 21 Mpa Min. | 700 Min. | ≥ 6 N |

After Accelerated Aging

| Tensile(MPA) | Elongation(%) | Force At Break(N) | |
|--------------|---------------|-------------------|--|
| 18 Mpa Min. | 500 Min. | ≥ 6 N | |

Packaging

| Packaging (Normal) | 50±1 pieces in one Dispenser Box/Poly Bag,10 Dispenser Box in one Carton. |
|--------------------------------|--|
| Labeling on Dispenser (Normal) | Product Name, Size, Lot no. Quantity, Manufacturer's address, Warning about Latex Allergy. |
| Labeling on Carton (Normal) | Product Name, Size, Lot no. Quantity, Country of Origin. |

Container Loadability (No MOQ in manufacturer owned brand in standard Packaging)

20 FCL=980 Cartons.

40 FCL=1980 Cartons.

Certification















EN455-1-2-3