

Program:

```
#include <stdio.h>
#include <stdlib.h>
// Node structure definition
struct Node {
    int data;
    struct Node* next;
};
// Queue structure definition
struct Queue {
    struct Node* front;
    struct Node* rear;
};
// Function prototypes
struct Node* createNode(int data);
void initializeQueue(struct Queue* queue);
void enqueue(struct Queue* queue, int data);
int dequeue(struct Queue* queue);
void displayQueue(struct Queue* queue);
int main() {
    struct Queue queue;
    int choice, element;
    initializeQueue(&queue);
    while (1) {
        printf("\nQueue Operations Menu:\n");
        printf("1. Enqueue\n");
        printf("2. Dequeue\n");
        printf("3. Display\n");
        printf("4. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);
        switch (choice) {
            case 1:
                printf("Enter element to enqueue: ");
                scanf("%d", &element);
                enqueue(&queue, element);
                break;
            case 2:
                element = dequeue(&queue);
                if (element != -1)
                    printf("Dequeued element: %d\n", element);
                break;
            case 3:
```

```

displayQueue(&queue);
break;
case 4:
exit(0);
default:
printf("Invalid choice! Please enter a valid option.\n");
}
}
return 0;
}
// Function to create a new node
struct Node* createNode(int data) {
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
if (!newNode) {
printf("Memory allocation error\n");
exit(1);
}
newNode->data = data;
newNode->next = NULL;
return newNode;
}
// Function to initialize the queue
void initializeQueue(struct Queue* queue) {
queue->front = NULL;
queue->rear = NULL;
}
// Function to enqueue an element to the queue
void enqueue(struct Queue* queue, int data) {
struct Node* newNode = createNode(data);
if (queue->rear == NULL) {
queue->front = queue->rear = newNode;
printf("Element enqueued: %d\n", data);
return;
}
queue->rear->next = newNode;
queue->rear = newNode;
printf("Element enqueued: %d\n", data);
}
// Function to dequeue an element from the queue
int dequeue(struct Queue* queue) {
if (queue->front == NULL) {
printf("Error: Queue underflow. Cannot dequeue element.\n");
return -1;
}
}

```

```
struct Node* temp = queue->front;
int dequeuedElement = temp->data;
queue->front = queue->front->next;
if (queue->front == NULL) {
    queue->rear = NULL;
}
free(temp);
return dequeuedElement;
}

// Function to display the queue elements
void displayQueue(struct Queue* queue) {
    if (queue->front == NULL) {
        printf("Queue is empty.\n");
        return;
    }
    printf("Queue elements: ");
    struct Node* temp = queue->front;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}
```