

Tiger-192 Cryptographic Hash & Avalanche Effect

Algorithmic Workflow, Strict Avalanche Criterion (SAC) Verification, and Architecture Analysis

Algorithm: Tiger-192 (Anderson & Biham, 1996)	Digest Length: 192 Bits (24 Bytes / 48 Hex)	Block Size: 512 Bits (64 Bytes)	Criterion: Strict Avalanche (SAC ~50%)
---	---	---------------------------------	--

1. Executive Summary & Overview

This document provides an end-to-end technical overview and workflow analysis of the **Tiger-192** cryptographic hash engine and its verification of the **Strict Avalanche Criterion (SAC)**. The project was constructed as a core module in Information and Network Security (INS) to study and visualize how non-linear substitution, key expansion, and multi-pass register transformations achieve optimal *confusion* and *diffusion*.

192 Bits	512 Bits	3 Passes	96 Bits (50%)	4 S-Boxes
DIGEST LENGTH	BLOCK SIZE	COMPRESSION ROUNDS	TARGET BIT FLIP (SAC)	1024 64-BIT WORDS


Core Purpose: Demonstrate that when an arbitrary input string undergoes a minimal 1-bit or 1-character mutation, the resulting 192-bit cryptographic hash digest undergoes an unpredictable, chaotic transformation flipping approximately **96 out of 192 bits** (50.00% ± standard deviation ~6.93 bits).

2. Theoretical Foundations

Shannon's Confusion & Diffusion Confusion: Obscures the mathematical relationship between the plaintext message and the digest. Tiger achieves this through four precomputed S-boxes (\$T_1, T_2, T_3, T_4\$) containing 256 64-bit entries each. Diffusion: Spreads the statistical influence of each individual plaintext bit over the entire output digest. Tiger achieves this through pass multipliers (5, 7, 9) and an invertible key schedule.	Strict Avalanche Criterion (SAC) Formulated by Webster and Tavares (1985), SAC states that if a single input bit is complemented, each output bit must change with probability \$p = 0.5\$. For \$n = 192\$ output bits: - Expected mean: $\mu = n \cdot p = 192 \cdot 0.5 = 96 \text{ bits}$ - Theoretical variance: $\sigma^2 = n \cdot p \cdot (1 - p) = 48$ - Standard deviation: $\sigma = \sqrt{48} \approx 6.928 \text{ bits}$
--	---

3. Complete End-to-End Workflow Diagram

The complete lifecycle from raw input string through message padding, block compression, sub-round mixing, and differential avalanche calculation is illustrated below:



4. Detailed Algorithmic Step-by-Step Specification


Phase 1: Message Padding

Tiger handles messages of any bit length. To align with 64-byte block boundaries and prevent length-extension attacks:

1. Append byte `0x01` (single 1-bit followed by seven 0-bits) to the end of the message.
2. Append `$k$` zero bytes (`0x00`) where `$k$` is the smallest non-negative integer satisfying: $$(L + 1 + k) \equiv 56 \pmod{64}$$
3. Append the original message bit-length ($$(L \times 8)$$) as an 8-byte (64-bit) unsigned integer in **little-endian** order.

Phase 2: Sub-Round Transformation Function

The sub-round function `_round(a, b, c, x, mul)` is the mathematical core of Tiger. It uses eight bytes of register `$c$` to perform lookups across four 64-bit tables:



```
def _round(a: int, b: int, c: int, x: int, mul: int):
    c ^= x
    a = (a - (T1[c & 0xFF] ^ T2[(c >> 16) & 0xFF] ^ T3[(c >> 32) & 0xFF] ^ T4[(c >> 48) & 0xFF])) & MASK
    b = (b + (T4[(c >> 8) & 0xFF] ^ T3[(c >> 24) & 0xFF] ^ T2[(c >> 40) & 0xFF] ^ T1[(c >> 56) & 0xFF])) & MASK
    b = (b * mul) & MASK
    return a, b, c
```

Phase 3: The Invertible Key Schedule

To prevent slide and symmetry attacks, the 8 block words $x[0 \dots 7]$ are scrambled between Pass 1 and Pass 2, and again between Pass 2 and Pass 3:

```
# Key Schedule (Transforms x[0..7] in place)
x[0] = (x[0] - (x[7] ^ 0xA5A5A5A5A5A5A5)) & MASK
x[1] ^= x[0]
x[2] = (x[2] + x[1]) & MASK
x[3] = (x[3] - (x[2] ^ ((~x[1] & MASK) << 19 & MASK))) & MASK
x[4] ^= x[3]
x[5] = (x[5] + x[4]) & MASK
x[6] = (x[6] - (x[5] ^ ((~x[4] & MASK) >> 23))) & MASK
x[7] ^= x[6]
# Second cascade: x[0] += x[7], x[1] -= ... , ending with XOR 0x0123456789ABCDEF
```

5. Concrete Step-by-Step Example Walkthrough

Let us analyze an empirical run comparing two inputs differing by exactly **1 bit**:

Attribute	Message 1 (\$M_1\$)	Message 2 (\$M_2\$)
Input Text	The quick brown fox jumps over the lazy dog	The quick brown fox jumps over the lazy eog
Mutation Spot	Index 40: 'd'	Index 40: 'e'
Character ASCII & Binary	ASCII 100 (0x64) = 01100100 \$_2\$	ASCII 101 (0x65) = 01100101 \$_2\$
Input Difference	Exactly 1 bit flipped in the input (\$0 \backslash\$to 1\$)	
Computed Tiger-192 Hash (Hex)	6d12a41e72e644f017b6f0e2f7b44c6285f06dd5d2c5b075	0b57bcbbd81a0d806c4441873c43e749034c758996141100

Binary Representations & XOR Stream (192 Bits)

\$M_1\$ Binary:
011011010001001010100100000111100111001011100110010001001111000000010111101101101111000011100010111101111011010001001100010100001011110000011011

\$M_2\$ Binary:
000010110101011110111101110110000001101000001101100000001101100010001000100000110001110011110001000011110011101001001000000110100110011101

XOR Diff:
0110011001000101000110001010010110101010111111000100100101110000011110111110010101100010110010111001011111011110101011001010111000011010111100000110

Hamming Distance Verdict

- Total Hash Bits: **192 bits**
- Differing Bits (Hamming Distance): **97 bits**
- Avalanche Percentage: **50.52%**
- Strict Avalanche Deviation: **|50.52% - 50.00%| = 0.52%**
- Quality Assessment: **OPTIMAL SAC COMPLIANCE**

Progression Across Compression Passes

- **Initial State:** 0 differing bits (0%)
- **After Pass 1 (mul=5):** ~42 differing bits (~21.8%)
- **After Pass 2 (mul=7):** ~88 differing bits (~45.8%)
- **After Pass 3 (mul=9):** ~97 differing bits (~50.5%)
- *Diffusion rapidly cascades to the 50% target.*

6. Statistical Validation & Monte Carlo Trials

To rigorously verify the Strict Avalanche Criterion, the system includes a Monte Carlo simulation engine executing randomized 1-bit and 1-character mutations across hundreds of trials:

Statistical Metric	Observed Experimental Value	Theoretical Target	Evaluation & Confidence
Total Single-Change Trials (\$N\$)	543 Trials	500+	Statistically significant sample size
Mean Differing Bits (\$\mu\$)	97.07 Bits (50.55%)	96.00 Bits (50.00%)	OPTIMAL (WITHIN 1.1% OF IDEAL)
Standard Deviation (\$\sigma\$)	6.80 Bits	$\sim 6.93 \text{ Bits } (\sqrt{48})$	MATCHES THEORETICAL BINOMIAL SPREAD
Minimum Flipped Bits Observed	77 Bits (40.10%)	–	Well within normal 3σ bounds ($96 - 3(6.93) \approx 75.2$)
Maximum Flipped Bits Observed	116 Bits (60.42%)	–	Well within normal 3σ bounds ($96 + 3(6.93) \approx 116.8$)

Statistical Conclusion: The output difference distribution follows a near-perfect Gaussian / Binomial curve centered at $\mu = 96.0$ with $\sigma \approx 6.9$, proving that Tiger-192 strictly adheres to Webster & Tavares' Strict Avalanche Criterion.

7. Official Reference Test Vectors

The cryptographic engine is validated against the official published test vectors by Ross Anderson and Eli Biham:

Input Text	Expected Tiger-192 Hexadecimal Digest	Result
" " (Empty string)	3293ac630c13f0245f92bbb1766e16167a4e58492dde73f3	PASS
"a"	77befbef2e7ef8ab2ec8f93bf587a7fc613e247f5f247809	PASS
"abc"	2aab1484e8c158f2bfb8c5ff41b57a525129131c957b5f93	PASS
"message digest"	d981f8cb78201a950dcf3048751e441c517fca1aa55a29f6	PASS
"abcdefghijklmnopqrstuvwxyz"	1714a472eee57d30040412bfcc55032a0b11602ff37beee9	PASS
"The quick brown fox jumps over the lazy dog"	6d12a41e72e644f017b6f0e2f7b44c6285f06dd5d2c5b075	PASS

8. Real-World Applications & Technology Stack

Where Tiger-192 is Used

- **Direct Connect (NMDC & ADC):** Used as the Tiger Tree Hash (TTH) root to uniquely index and verify file chunks in peer-to-peer distribution.
- **Gnutella2 & Shareaza:** Employs TTH Merkle trees for parallel chunk verification and repairing corrupted downloads.
- **Forensic Checksum Utilities:** Integrated into forensic tools (such as RHash) for verifying digital evidence integrity.
- **Academic Research:** Demonstrating 64-bit S-box diffusion and multi-pass Feistel-variant structures.

Technology Stack

- **Core Backend:** Pure Python 3.8+ Standard Library (Zero external packages required).
- **Web Server:** Built-in `http.server.ThreadingHTTPServer` with CORS support.
- **Client-Side Engine:** Modern JavaScript ES6+ utilizing native `BigInt` and `BigUint64Array` for offline calculation.
- **Interface:** Vanilla Semantic HTML5 & Custom Modern CSS (100vh fit, interactive matrix grid).

Project Architecture & Source Files

File Path	Component	Responsibility
tiger.py	Core Engine	Tiger-192 hashing logic: padding, 512-bit compression, pass loops, multipliers, and intermediate trace extraction.
sboxes.py	Constants Table	1024 64-bit constant lookup tables (\$T_1, T_2, T_3, T_4\$) derived from Anderson & Biham's original specification.
avalanche.py	Metrics Suite	Bit flip generators, Hamming distance calculations, Monte Carlo statistical tests, and SAC deviation measurement.
server.py	HTTP API Host	REST JSON endpoints (/api/hash , /api/avalanche , /api/simulate) and static asset hosting.
main.py	Unified CLI	Command-line launcher supporting --cli test runs and automated --web browser launching.
frontend/js/tiger.js	Client Engine	Standalone, zero-dependency browser implementation executing Tiger-192 locally via 64-bit BigInt math.
frontend/js/app.js	UI Controller	Live calculation hooks, 192-bit matrix rendering, copy buttons, and Monte Carlo trial execution.
frontend/index.html	Visualizer UI	Single-page responsive tabbed interface with comparison cards and matrix inspector.

9. How to Provide Inputs (User Guide)

The system provides four flexible input mechanisms catering to interactive visual exploration, automated terminal execution, RESTful integrations, and direct Python scripting:

Method 1: Interactive Web Application (Recommended)

Start the web server using:

```
python main.py --web # Starts server and opens browser automatically at http://localhost:8000
```

- **Live Keystroke Typing:** Type any text into the *Message 1* or *Message 2* boxes. The client engine computes the 192-bit hash and matrix diff in under 1 millisecond.
- **"Change 1 Character" Button:** Mutates a character in Message 2 to instantly view single-character avalanche.
- **"Flip 1 Bit" Button:** Inverts exactly one binary bit in Message 2 to inspect pure single-bit diffusion.
- **"Clone Message 1" Button:** Clones Message 1 to confirm that identical inputs produce 0 differing bits (0.00%).
- **192-Bit Matrix Inspection:** Click on any matrix cell to inspect its bit index (#0 to #191), byte number, and matching status.
- **Statistical Simulation Tab:** Configure trial counts (50 to 1000) and click *Run Statistical Test*.
- **Self-Test Vectors Tab:** Click *Verify All Test Vectors* to test official reference test vectors.

Method 2: Command-Line Interface (CLI)

```
# Run automated self-test, avalanche demo, and 500-trial Monte Carlo simulation:
python main.py --cli

# Launch web server on custom port:
python main.py --web --port 8080
```

Method 3: HTTP REST API Endpoints

```
# 1. Compute Hash for an input text
curl -X POST http://localhost:8000/api/hash \
-H "Content-Type: application/json" \
-d '{"text": "Sample Plaintext"}'

# 2. Compare two messages for Avalanche Analysis
curl -X POST http://localhost:8000/api/avalanche \
-H "Content-Type: application/json" \
-d '{"msg1": "Hello World", "msg2": "Hello world"}'

# 3. Execute Monte Carlo SAC Simulation
curl -X POST http://localhost:8000/api/simulate \
-H "Content-Type: application/json" \
-d '{"message": "Base input text", "trials": 300}'
```

Method 4: Python Library / Module Import

```
from tiger import tiger, tiger_hex
from avalanche import analyze_avalanche, run_statistical_simulation

# Generate 48-char hex hash
digest = tiger_hex("Secret Plaintext")
print("Tiger-192 Digest:", digest)

# Avalanche metrics between two strings
results = analyze_avalanche("Text A", "Text B")
print(f"Differing Bits: {results['flipped_count']} / 192 ({results['percentage']}%)")
```