

Project Name

Project ID:2020MP000

Review -III

Group Members

RA1611003030000 Name of first candidate

RA1611003030000 Name of second candidate

RA1611003030000 Name of third candidate

RA1611003030000 Name of fourth candidate

Supervised By:

Dr. XXX

Department of Computer Science & Engineering

Faculty of Engineering & Technology

SRM Institute of Science & Technology



March 18, 2021



Table of Contents I

- 1 Abstract
- 2 Literature Survey
- 3 Identification of Research Gap and Problem
- 4 Expected Impact on Academics/ Industry
- 5 Methodology of the Project Work
- 6 Detailed Design

Table of Contents II

7 Major Inputs (Infrastructure) Required

8 Results Obtained

9 References

Name of the sections are project specific . This is given only for the reference.

Literature Survey



This is how we can add references to the content

- Distributed system's reliability is an important design requirement for improving current distributed systems or designing the new ones.
- Reliability refers both to a system's vulnerability to different kinds of failures and its ability to survive from them [4].
- A system can be configured to be fault tolerant by demonstrating rigorous behavior that encourages the recovery-friendly action [1].
- Checkpoint and rollback recovery are well-acknowledged strategies for addressing distributed systems reliability [3], [2].

Expected Impact on Academics/ Industry

-
-
-

This is how we can add math symbols in the Presentation

Let us assume that we are having two sets named P & Q, then notation \leftrightarrow expresses the set of relations between P and Q as

$$P \leftrightarrow Q = \mathbb{P}(P \times Q)$$

where \times is known as the Cartesian product of set P and set Q. A mapping of element $p \in P$ and $q \in Q$ in a relation $R \in P \leftrightarrow Q$ is recorded as $p \mapsto q$. The domain of a relation $R \in P \leftrightarrow Q$ is the set of elements of P that R relates to some elements in Q expressed as

$$\text{dom}(R) = \{p \mid p \in P \wedge \exists q . (q \in Q \wedge p \mapsto q \in R)\}$$

content...

Major Inputs (Infrastructure) Required

-
-
-

Implementation

This is the example of how we can add figures, give captions, refer the figures. Also we can check how to insert columns in the frame.

- The run-time representation of an object program in the logical address space consists of data and program areas as shown in Fig 1.
- A compiler for a language like C++ on an operating system like Linux might subdivide memory in this way.




Figure: Typical subdivision of run-time memory into code and data areas

Results Obtained

content...

References I



M. Jandl, A. Szep, R. Smeikal, and K. M. Göschka.

Increasing availability by sacrificing data integrity-a problem statement.

In *Proceedings of the 38th Annual Hawaii International Conference on System Sciences*, pages 291c–291c. IEEE, 2005.



D. Manivannan and M. Singhal.

Quasi-synchronous checkpointing: Models, characterization, and classification.

IEEE Transactions on Parallel and Distributed Systems, 10(7):703–713, 1999.




D. Manivannan and M. Singhal.

Asynchronous recovery without using vector timestamps.

Journal of Parallel and Distributed Computing, 62(12):1695–1728, 2002.



SRM
INSTITUTE OF SCIENCE & TECHNOLOGY
Deemed to be University u/s of UGC Act, 1956

-  M. T. Özsu and P. Valduriez.
Principles of distributed database systems.
Springer Science & Business Media, 2011.