

AI ASSISTED CODING (ASSIGNMENT-11.1)

Name: S.Vishnu Teja

Roll No: 2503A52720

Batch: 24

#Q1

Task: Use AI to generate a Stack class with push, pop, peek, and is_empty methods.

Sample Input Code:

```
class Stack:
```

```
    pass
```

Prompt: generate a code on Stack class with push, pop, peek, and is_empty methods.

Code:

```
class Stack:
```

```
    def __init__(self):
```

```
        self.items = []
```

```
    def push(self, item):
```

```
        self.items.append(item)
```

```
    def pop(self):
```

```
        if self.is_empty():
```

```
            return None
```

```
        return self.items.pop()
```

```
    def peek(self):
```

```
        if self.is_empty():
```

```
            return None
```

```

        return self.items[-1]

    def is_empty(self):
        return len(self.items) == 0

stack = Stack()
stack.push(10)
stack.push(20)
print("Top element:", stack.peek())
print("Popped element:", stack.pop())
print("Is stack empty?", stack.is_empty())

```

Output:

```

PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/T11.py"
Top element: 20
Popped element: 20
Is stack empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>

```

#Q2

Task: Use AI to implement a Queue using Python lists.

Sample Input Code:

```

class Queue:

    pass

```

Prompt: generate a code to implement a Queue using python list.

Code:

```

class Queue:
    def __init__(self):
        self._items = []

    def enqueue(self, item):
        """Add an item to the rear of the queue."""
        self._items.append(item)

    def dequeue(self):

```

```

    if self.is_empty():
        return None

    return self._items.pop(0)

def peek(self):
    if self.is_empty():
        return None

    return self._items[0]

def is_empty(self):
    return len(self._items) == 0

if __name__ == "__main__":
    queue = Queue()

    print("Is queue empty?", queue.is_empty())

    queue.enqueue(10)
    queue.enqueue(20)
    queue.enqueue(30)

    print("Queue after enqueueing 10, 20, 30:", queue._items)

    print("Front item:", queue.peek())

    print("Dequeued item:")

    print(queue.dequeue())

    print("Front item after dequeue:", queue.peek())

    print("Is queue empty?", queue.is_empty())

```

output:

```

PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.2.py"
Is queue empty? True
Queue after enqueueing 10, 20, 30: [10, 20, 30]
Front item: 10
Dequeued item:
10
Front item after dequeue: 20
Is queue empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>

```

#Q3

Task: Use AI to generate a Singly Linked List with insert and display

methods.

Sample Input Code:

```
class Node:
```

```
    pass
```

```
class LinkedList:
```

```
    pass
```

Prompt: generate a code on singly linked list with insert and display methods.

Code:

```
class Node:
```

```
    def __init__(self, data):
```

```
        self.data = data
```

```
        self.next = None
```

```
class LinkedList:
```

```
    def __init__(self):
```

```
        self.head = None
```

```
    def insert(self, data):
```

```
        new_node = Node(data)
```

```
        if self.head is None:
```

```
            self.head = new_node
```

```
            return
```

```
        current = self.head
```

```
        while current.next is not None:
```

```
            current = current.next
```

```
        current.next = new_node
```

```
    def display(self):
```

```
        current = self.head
```

```
        values = []
```

```
        while current is not None:
```

```

        values.append(str(current.data))

        current = current.next

    print(" -> ".join(values) if values else "The list is empty.")

if __name__ == "__main__":
    linked_list = LinkedList()

    linked_list.insert(10)

    linked_list.insert(20)

    linked_list.insert(30)

    print("Linked list:")

    linked_list.display()

```

Output:

```

PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.3.py"
Linked list:
10 -> 20 -> 30
PS C:\Users\chait\OneDrive\Desktop\AIAC> 

```

#Q4

Task: Use AI to create a BST with insert and in-order traversal methods.

Sample Input Code:

```
class BST:
```

```
    pass
```

Prompt: generate a code on BST with insert and in-order traversal methods.

Code:

```
class Node:
```

```
    def __init__(self, data):
```

```
        self.data = data
```

```
        self.left = None
```

```
        self.right = None
```

```
class BST:
```

```
    def __init__(self):
```

```
        self.root = None
```

```

def insert(self, data):
    """Insert a value into the tree."""
    self.root = self._insert(self.root, data)

def _insert(self, node, data):
    if node is None:
        return Node(data)
    if data < node.data:
        node.left = self._insert(node.left, data)
    elif data > node.data:
        node.right = self._insert(node.right, data)
    return node

def in_order(self):
    values = []
    self._in_order(self.root, values)
    return values

def _in_order(self, node, values):
    if node is not None:
        self._in_order(node.left, values)
        values.append(node.data)
        self._in_order(node.right, values)

if __name__ == "__main__":
    bst = BST()
    for value in (50, 30, 70, 20, 40, 60, 80):
        bst.insert(value)
    print("In-order traversal:", bst.in_order())

```

output:

```

PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.4.py"
In-order traversal: [20, 30, 40, 50, 60, 70, 80]
PS C:\Users\chait\OneDrive\Desktop\AIAC>

```

#Q5

Task: Use AI to implement a priority queue using Python's heapq module.

Sample Input Code:

```
class PriorityQueue:  
    pass
```

Prompt: generate a code to implement a priority queue using Python's heapq module.

Code:

```
import heapq
```

```
class PriorityQueue:  
    def __init__(self):  
        self._items = []  
  
    def insert(self, item):  
        """Add an item to the priority queue."""  
        heapq.heappush(self._items, item)  
  
    def remove(self):  
        """Remove and return the item with the highest priority."""  
        return heapq.heappop(self._items)  
  
    def peek(self):  
        """Return the highest-priority item without removing it."""  
        return self._items[0]  
  
    def is_empty(self):  
        return len(self._items) == 0
```

```

if __name__ == "__main__":
    queue = PriorityQueue()
    for item in (5, 1, 3, 2, 4):
        queue.insert(item)

    print("Priority order:", end=" ")
    while not queue.is_empty():
        print(queue.remove(), end=" ")

```

output:

```

PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t11.5.py"
Priority order: 1 2 3 4 5
PS C:\Users\chait\OneDrive\Desktop\AIAC>

```

#Q6

Task: Use AI to implement a double-ended queue using `collections.deque`.

Sample Input Code:

```
class DequeDS:
```

prompt: generate a code to implement a double-ended queue using `collections.deque`.

code:

```

from collections import deque

class DoubleEndedQueue:
    """A double-ended queue (deque)."""

    def __init__(self):
        """Create an empty deque."""
        self._items = deque()

    def add_front(self, item):
        """Add an item to the front of the deque."""

```

```

        self._items.appendleft(item)

def add_rear(self, item):
    """Add an item to the rear of the deque."""
    self._items.append(item)

def remove_front(self):
    """Remove and return the front item, or None if empty."""
    if self.is_empty():
        return None
    return self._items.popleft()

def remove_rear(self):
    """Remove and return the rear item, or None if empty."""
    if self.is_empty():
        return None
    return self._items.pop()

def is_empty(self):
    """Return True when the deque has no items."""
    return len(self._items) == 0

if __name__ == "__main__":
    queue = DoubleEndedQueue()

    queue.add_rear(10)
    queue.add_rear(20)
    queue.add_front(5)
    print("Deque after adding 10, 20 at the rear and 5 at the front:", queue._items)

```

```
print("Removed from front:", queue.remove_front())
print("Removed from rear:", queue.remove_rear())
print("Deque after removals:", queue._items)
print("Is deque empty?", queue.is_empty())
```

output:

```
PS C:\Users\chait\OneDrive\Desktop\AIAC> & C:/Users/chait/AppData/Local/Python/pythoncore-3.14-64/python.exe "c:/Users/chait/OneDrive/Desktop/AIAC/AIAC LAB 7.1/AIAC LAB 4/AIAC LAB-11.1/t6.py"
Deque after adding 10, 20 at the rear and 5 at the front: deque([5, 10, 20])
Removed from front: 5
Removed from rear: 20
Deque after removals: deque([10])
Is deque empty? False
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```

Q7

Task: Real-Time Application Challenge – Choose the Right Data Structure

Scenario:

Your college wants to develop a Campus Resource Management System that handles:

1. Student Attendance Tracking – Daily log of students entering/exiting the campus.
2. Event Registration System – Manage participants in events with quick search and removal.
3. Library Book Borrowing – Keep track of available books and their due dates.
4. Bus Scheduling System – Maintain bus routes and stop connections.
5. Cafeteria Order Queue – Serve students in the order they arrive.

Student Task:

☐ For each feature, select the most appropriate data structure from the list below:

o Stack

- o Queue
- o Priority Queue
- o Linked List
- o Binary Search Tree (BST)
- o Graph
- o Hash Table
- o Deque

- Justify your choice in 2–3 sentences per feature.
- Implement one selected feature as a working Python program with AI-assisted code generation.

Expected Output:

- A table mapping feature → chosen data structure → justification.
- A functional Python program implementing the chosen feature with comments and docstrings.

Prompt: Create a simple Python Event Registration System using a Hash Table (dictionary). Include student registration, searching, deleting, and displaying records using Student ID. Add comments, docstrings, and sample output. Keep the code beginner-friendly and menu-driven.

Code:

```
"""Simple event registration system backed by a hash table (dictionary)."""
```

```
registrations = {}
```

```
def register():
```

```
    """Register or update a student's event registration."""
```

```
    student_id = input("Enter Student ID: ").strip()
```

```
    if not student_id:
```

```
        print("Student ID cannot be empty.")
```

```
    return
```

```
name = input("Enter Student Name: ").strip()
event = input("Enter Event Name: ").strip()
registrations[student_id] = [name, event]
print("Registration successful!")
```

```
def search():
    """Search for a student using Student ID."""
    student_id = input("Enter Student ID: ").strip()
    if student_id in registrations:
        name, event = registrations[student_id]
        print("Name:", name)
        print("Event:", event)
    else:
        print("Student not found.")
```

```
def remove():
    """Remove a student's registration."""
    student_id = input("Enter Student ID: ").strip()
    if student_id in registrations:
        del registrations[student_id]
        print("Registration removed!")
    else:
        print("Student not found.")
```

```
def display():
    """Display all registered students."""
    if not registrations:
        print("No registrations found.")
    return
```

```
for student_id, (name, event) in registrations.items():  
    print(student_id, name, event)
```

```
def main():
```

```
    """Run the event registration menu."""
```

```
    while True:
```

```
        print("\n1. Register")
```

```
        print("2. Search")
```

```
        print("3. Remove")
```

```
        print("4. Display")
```

```
        print("5. Exit")
```

```
    choice = input("Enter choice: ").strip()
```

```
    if choice == "1":
```

```
        register()
```

```
    elif choice == "2":
```

```
        search()
```

```
    elif choice == "3":
```

```
        remove()
```

```
    elif choice == "4":
```

```
        display()
```

```
    elif choice == "5":
```

```
        print("Thank you!")
```

```
        break
```

```
    else:
```

```
        print("Invalid choice")
```

```
if __name__ == "__main__":
```

main()

output:

```
1. Register
2. Search
3. Remove
4. Display
5. Exit
Enter choice: 1
Enter Student ID: 101
Enter Student Name: chaithra
Enter Event Name: coding contest
Registration successful!

1. Register
2. Search
3. Remove
4. Display
5. Exit
Enter choice: 1
Enter Student ID: 102
Enter Student Name: anjali
Enter Event Name: hackathon
Registration successful!

1. Register
2. Search
3. Remove
4. Display
5. Exit
Enter choice: 4
101 chaithra coding contest
102 anjali hackathon

1. Register
2. Search
3. Remove
4. Display
5. Exit

Enter choice: 2
Enter Student ID: 101
Name: chaithra
Event: coding contest

1. Register
2. Search
3. Remove
4. Display
5. Exit
Enter choice: 3
Enter Student ID: 102
Registration removed!

1. Register
2. Search
3. Remove
4. Display
5. Exit
Enter choice: 5
Thank you!
```

Q8

Task: Smart E-Commerce Platform – Data Structure

Challenge

An e-commerce company wants to build a Smart Online Shopping System with:

1. Shopping Cart Management – Add and remove products dynamically.
2. Order Processing System – Orders processed in the order they are placed.
3. Top-Selling Products Tracker – Products ranked by sales count.
4. Product Search Engine – Fast lookup of products using product ID.

5. Delivery Route Planning – Connect warehouses and delivery locations.

Student Task:

☐ For each feature, select the most appropriate data structure from the list below:

- o Stack
- o Queue
- o Priority Queue
- o Linked List
- o Binary Search Tree (BST)
- o Deque

☐ Justify your choice in 2–3 sentences per feature.

☐ Implement one selected feature as a working Python program with AI-assisted code generation.

Expected Output:

☐ A table mapping feature → chosen data structure → justification.

☐ A functional Python program implementing the chosen feature with comments and docstrings.

Prompt: Create a simple Python Smart E-Commerce System using suitable data structures. Implement shopping cart, order processing, top-selling products, product search, and delivery planning. Add comments, docstrings, and sample output.

Code:

```
# Smart E-Commerce System
```

```
# Data Structure: Deque
```

```
from collections import deque
```

```
cart = deque()
```

```
def add_product(product):  
    """Add a product to the shopping cart."""  
    cart.append(product)  
    print(product, "added to cart.")
```

```
def remove_product():  
    """Remove the last product from the shopping cart."""  
    if cart:  
        product = cart.pop()  
        print(product, "removed from cart.")  
    else:  
        print("Cart is empty.")
```

```
def display_cart():  
    """Display all products in the cart."""  
    print("Shopping Cart:", list(cart))
```

```
# Main program  
add_product("Laptop")  
add_product("Headphones")  
add_product("Mouse")
```

```
display_cart()
```

```
remove_product()
```

display_cart()

output:

```
C:\Desktop\AIAC>python AIAC.py
Laptop added to cart.
Headphones added to cart.
Mouse added to cart.
Shopping Cart: ['Laptop', 'Headphones', 'Mouse']
Mouse removed from cart.
Shopping Cart: ['Laptop', 'Headphones']
PS C:\Users\chait\OneDrive\Desktop\AIAC>
```