

GE23131-Programming Using C-2024

Quiz navigation



[Show one page at a time](#)

[Finish review](#)

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 22 October 2024, 4:25 PM
Duration	62 days 1 hour

Question 1

Correct

Marked out of
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {int a,b;
4 scanf("%d %d",&a,&b);
5 int c,d;
6 c=a%10;
7 d=b%10;
8 if(d==c)
9 {printf("true");
10 }
11 else
12 {printf("false");}
13 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If ***n*** is even and in the inclusive range of **6** to **20**, print **Weird**
- If ***n*** is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

Input Format

A single line containing a positive integer, ***n***.

Constraints

$$1 \leq n \leq 100$$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {int a;
4  scanf("%d",&a);
5  if(a%2==1)
6  {printf("Weird");}
7  else
8  {if(a>=2 && a<5)
9   {printf("Not Weird");}
10  else if(a>=6 && a<=20)
11  {printf("Wierd");}
12  else
13  {printf("Not Weird");}}}
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 [Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes
Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main()
3  {int a,b,c;
4   scanf("%d %d %d",&a,&b,&c);
5   if((a*a)+(b*b)==(c*c))
6   {printf("yes");}
7   else if((b*b)+(c*c)==(a*a))
8   {printf("yes");}
9   else if((c*c)+(a*a)==(b*b))
10  {printf("yes");}
11  else
12  {printf("no");}}
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review