

Microsoft Windows [Version 10.0.19045.2486]  
(c) Microsoft Corporation. All rights reserved.

C:\Users\Vishnu>sqlplus

SQL\*Plus: Release 10.2.0.1.0 - Production on Mon Feb 6 17:01:16 2023

Copyright (c) 1982, 2005, Oracle. All rights reserved.

Enter user-name: scott

Enter password:

Connected to:  
Oracle Database 10g Enterprise Edition Release 10.2.0.1.0 - Production  
With the Partitioning, OLAP and Data Mining options

SQL> -- Pre-requisite

SQL> SET LINESIZE 200;

SQL> SET PAGESIZE 40;

SQL>

SQL> -- Question 1

SQL> DROP TABLE Agent;

Table dropped.

SQL> DROP TABLE Orders;

DROP TABLE Orders

\*

ERROR at line 1:

ORA-00942: table or view does not exist

SQL>

SQL> CREATE TABLE Agent(agent\_code varchar(5), agent\_name varchar(10), working\_area varchar(15), commision number(2,2), phone\_no varchar(10), country varchar(10));

Table created.

SQL> CREATE TABLE Orders(ord\_num varchar(3), ord\_amount number, advance\_amount number, ord\_date date, cust\_code varchar(4), agent\_code varchar(5), description varchar(20));

Table created.

SQL> INSERT ALL

2 INTO Agent(agent\_code, agent\_name, working\_area, commision, phone\_no, country) VALUES ('Ac001','Ramesh','Bangalore',.15,'0331234567','India')

3 INTO Agent(agent\_code, agent\_name, working\_area, commision, phone\_no, country) VALUES ('Ac002','Dinesh','Bangalore',.25,'0331234568',NULL)

4 INTO Agent(agent\_code, agent\_name, working\_area, commision, phone\_no, country) VALUES ('Ac003','Suresh','Mumbai',.35,'0331234569','London')

5 INTO Agent(agent\_code, agent\_name, working\_area, commision, phone\_no, country) VALUES ('Ac004','Kamlesh','New Jersey',.68,'0331234564',NULL)

6 INTO Agent(agent\_code, agent\_name, working\_area, commision, phone\_no, country) VALUES ('Ac005','Kartik','Chennai',.73,'0331234563','India')

7 SELECT \* FROM dual;

5 rows created.



5 rows created.

```
SQL> INSERT ALL
  2     INTO Orders(ord_num, ord_amount, advance_amount, ord_date, cust_code, agent_code, description) VALUES ('004', 200, 3000, '15-aug-2020', 'C004', 'Ac001', 'Masala Kulcha')
  3     INTO Orders(ord_num, ord_amount, advance_amount, ord_date, cust_code, agent_code, description) VALUES ('007', 600, 5000, '17-sep-2020', 'C006', 'Ac003', 'Biryani')
  4     INTO Orders(ord_num, ord_amount, advance_amount, ord_date, cust_code, agent_code, description) VALUES ('008', 700, 100, '19-feb-2019', 'C007', 'Ac005', NULL)
  5     INTO Orders(ord_num, ord_amount, advance_amount, ord_date, cust_code, agent_code, description) VALUES ('009', 10000, 600, '21-mar-2010', 'C009', 'Ac008', 'Masala Dosa')
  6     INTO Orders(ord_num, ord_amount, advance_amount, ord_date, cust_code, agent_code, description) VALUES ('010', 20, 600, '21-apr-2012', 'C006', 'Ac005', NULL)
  7 SELECT * FROM dual;
```

5 rows created.

```
SQL>
SQL> SELECT * FROM Agent;
```

AGENT	AGENT_NAME	WORKING_AREA	COMMISSION	PHONE_NO	COUNTRY
Ac001	Ramesh	Bangalore	.15	0331234567	India
Ac002	Dinesh	Bangalore	.25	0331234568	
Ac003	Suresh	Mumbai	.35	0331234569	London
Ac004	Kamlesh	New Jersey	.68	0331234564	
Ac005	Kartik	Chennai	.73	0331234563	India

```
SQL> SELECT * FROM Orders;
```

ORD	ORD_AMOUNT	ADVANCE_AMOUNT	ORD_DATE	CUST	AGENT	DESCRIPTION
004	200	3000	15-AUG-20	C004	Ac001	Masala Kulcha
007	600	5000	17-SEP-20	C006	Ac003	Biryani
008	700	100	19-FEB-19	C007	Ac005	
009	10000	600	21-MAR-10	C009	Ac008	Masala Dosa
010	20	600	21-APR-12	C006	Ac005	

```
SQL>
SQL> SELECT ord_num, ord_amount, ord_date, cust_code, agent_code FROM Orders WHERE agent_code IN (SELECT agent_code FROM Agent WHERE (working_area = 'Bangalore'));
```

ORD	ORD_AMOUNT	ORD_DATE	CUST	AGENT
004	200	15-AUG-20	C004	Ac001

```
SQL> SELECT ord_num, ord_amount, ord_date, cust_code, agent_code FROM Orders WHERE agent_code IN (SELECT agent_code FROM Agent WHERE (agent_name = 'Ramesh'));
```

ORD	ORD_AMOUNT	ORD_DATE	CUST	AGENT
004	200	15-AUG-20	C004	Ac001

```
SQL>
SQL> DROP TABLE Agent;
```





SQL> DROP TABLE Agent;

Table dropped.

SQL> DROP TABLE Orders;

Table dropped.

SQL>  
SQL> -- Question 2  
SQL> DROP TABLE employees;  
DROP TABLE employees  
\*  
ERROR at line 1:  
ORA-00942: table or view does not exist

SQL>  
SQL> CREATE TABLE employees(employee\_id number(3,0), first\_name varchar(10), last\_name varchar(10), email varchar(15), phone\_number varchar(10), hire\_date date, job\_id varchar(5), salary number, manager\_id number, department\_id number);

Table created.

SQL> INSERT ALL  
2 INTO employees(employee\_id, first\_name, last\_name, email, phone\_number, hire\_date, job\_id, salary, manager\_id, department\_id) VALUES (700, 'Hasmukh', 'Patel', 'hp@gmail.com', '7003216160', '15-aug-2020', 'Hp003', 7000, NULL, 90)  
3 INTO employees(employee\_id, first\_name, last\_name, email, phone\_number, hire\_date, job\_id, salary, manager\_id, department\_id) VALUES (800, 'Kamlesh', 'Paul', 'kp@gmail.com', '7003216170', '17-feb-2020', 'Kp004', 8000, 506, 90)  
4 INTO employees(employee\_id, first\_name, last\_name, email, phone\_number, hire\_date, job\_id, salary, manager\_id, department\_id) VALUES (900, 'Dinesh', 'Gandhi', 'dp@yahoo', '9136278563', '19-mar-2101', 'Dg006', 20000, 508, 80)  
5 INTO employees(employee\_id, first\_name, last\_name, email, phone\_number, hire\_date, job\_id, salary, manager\_id, department\_id) VALUES (701, 'Suresh', 'Modi', 'sm@dg.com', '9187653294', '20-apr-2015', 'Sm009', 15000, NULL, 80)  
6 SELECT 1 from dual;

4 rows created.

SQL>  
SQL> SELECT \* FROM employees;

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	PHONE_NUMB	HIRE_DATE	JOB_I	SALARY	MANAGER_ID	DEPARTMENT_ID
700	Hasmukh	Patel	hp@gmail.com	7003216160	15-AUG-20	Hp003	7000		90
800	Kamlesh	Paul	kp@gmail.com	7003216170	17-FEB-20	Kp004	8000	506	90
900	Dinesh	Gandhi	dp@yahoo	9136278563	19-MAR-01	Dg006	20000	508	80
701	Suresh	Modi	sm@dg.com	9187653294	20-APR-15	Sm009	15000		80

SQL>  
SQL> SELECT employee\_id, manager\_id, first\_name, last\_name FROM employees WHERE employee\_id IN (SELECT employee\_id FROM employees WHERE employee\_id = manager\_id);

no rows selected



```
SQL> SELECT employee_id, manager_id, first_name, last_name FROM employees WHERE manager_id != null;
```

no rows selected

```
SQL>
SQL> DROP TABLE employees;
```

Table dropped.

```
SQL>
SQL> -- Question 3
SQL> DROP TABLE salesman;
DROP TABLE salesman
      *
ERROR at line 1:
ORA-00942: table or view does not exist
```

```
SQL> DROP TABLE Orders;
DROP TABLE Orders
      *
ERROR at line 1:
ORA-00942: table or view does not exist
```

```
SQL>
SQL> CREATE TABLE salesman(salesman_id varchar(8), name varchar(15),city varchar(15),commission float);
```

Table created.

```
SQL> CREATE TABLE Orders(ord_no number, purch_amt number, ord_date date, customer_id varchar(5), salesman_id varchar(8));
```

Table created.

```
SQL> INSERT ALL
2      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@06', 'Lakshmi', 'Kolkata', .5)
3      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@09', 'Ganesh', 'London', .6)
4      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@90', 'Dinesh', 'London', .3)
5      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@10', 'Joseph', 'Chennai', .6)
6      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@19', 'Mahesh', 'Hyderabad', .65)
7      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@26', 'Paul Adam', 'London', .1)
8      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@67', 'Rahul', 'Delhi', .4)
9  SELECT 1 FROM dual;
```

7 rows created.

```
SQL> INSERT ALL
2      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (123, 600, '20-aug-2010', '003cd', 'si123@19')
3      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (576, 750, '20-feb-2018', '004cd', 'si123@19')
4      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (579, 800, '20-may-2012', '004cd', 'si123@26')
```



```
SQL> INSERT ALL
2      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@06', 'Lakshmi', 'Kolkata', .5)
3      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@09', 'Ganesh', 'London', .6)
4      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@90', 'Dinesh', 'London', .3)
5      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@10', 'Joseph', 'Chennai', .6)
6      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@19', 'Mahesh', 'Hyderabad', .65)
7      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@26', 'Paul Adam', 'London', .1)
8      INTO salesman(salesman_id, name ,city ,commission ) VALUES ('si123@67', 'Rahul', 'Delhi', .4)
9  SELECT 1 FROM dual;
```

7 rows created.

```
SQL> INSERT ALL
2      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (123, 600, '20-aug-2010', '003cd', 'si123@19')
3      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (576, 750, '20-feb-2018', '004cd', 'si123@19')
4      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (579, 800, '20-may-2012', '004cd', 'si123@26')
5      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (600, 60000, '20-jan-2021', '006cd', 'si123@10')
6      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (700, 745, '26-jan-2021', '007cd', 'si123@09')
7      INTO Orders(ord_no, purch_amt, ord_date, customer_id, salesman_id) VALUES (800, 860, '29-jan-2019', '007cd', 'si123@26')
8  SELECT 1 FROM dual;
```

6 rows created.

```
SQL>
SQL> SELECT * FROM salesman;
```

SALESMAN	NAME	CITY	COMMISSION
si123@06	Lakshmi	Kolkata	.5
si123@09	Ganesh	London	.6
si123@90	Dinesh	London	.3
si123@10	Joseph	Chennai	.6
si123@19	Mahesh	Hyderabad	.65
si123@26	Paul Adam	London	.1
si123@67	Rahul	Delhi	.4

7 rows selected.

```
SQL> SELECT * FROM Orders;
```

ORD_NO	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN
123	600	20-AUG-10	003cd	si123@19
576	750	20-FEB-18	004cd	si123@19
579	800	20-MAY-12	004cd	si123@26
600	60000	20-JAN-21	006cd	si123@10
700	745	26-JAN-21	007cd	si123@09
800	860	29-JAN-19	007cd	si123@26

SQL> SELECT \* FROM Orders;

ORD_NO	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN
123	600	20-AUG-10	003cd	si123@19
576	750	20-FEB-18	004cd	si123@19
579	800	20-MAY-12	004cd	si123@26
600	60000	20-JAN-21	006cd	si123@10
700	745	26-JAN-21	007cd	si123@09
800	860	29-JAN-19	007cd	si123@26

6 rows selected.

SQL>

SQL> SELECT \* FROM Orders WHERE salesman\_id IN (SELECT salesman\_id FROM salesman WHERE name = 'Paul Adam');

ORD_NO	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN
800	860	29-JAN-19	007cd	si123@26
579	800	20-MAY-12	004cd	si123@26

SQL> SELECT \* FROM Orders WHERE salesman\_id IN (SELECT salesman\_id FROM salesman WHERE city = 'London');

ORD_NO	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN
700	745	26-JAN-21	007cd	si123@09
800	860	29-JAN-19	007cd	si123@26
579	800	20-MAY-12	004cd	si123@26

SQL>

SQL> DROP TABLE salesman;

Table dropped.

SQL> DROP TABLE Orders;

Table dropped.

SQL>