

# ASSIGNMENT-4

DATE:06/06/2024

## 1. Odd String Difference

You are given an array of equal-length strings words. Assume that the length of each string is n.

Each string words[i] can be converted into a difference integer array difference[i] of length n - 1 where  $\text{difference}[i][j] = \text{words}[i][j+1] - \text{words}[i][j]$  where  $0 \leq j \leq n - 2$ . Note that the difference between two letters is the difference between their positions in

the alphabet i.e. the position of 'a' is 0, 'b' is 1, and 'z' is 25.

For example, for the string "acb", the difference integer array is  $[2 - 0, 1 - 2] = [2, -1]$ .

All the strings in words have the same difference integer array, except one. You should

find that string.

Return the string in words that has different difference integer array.

Example 1:

Input: words = ["adc", "wzy", "abc"]

Output: "abc"

Explanation:

- The difference integer array of "adc" is  $[3 - 0, 2 - 3] = [3, -1]$ .

- The difference integer array of "wzy" is  $[25 - 22, 24 - 25] = [3, -1]$ .

- The difference integer array of "abc" is  $[1 - 0, 2 - 1] = [1, 1]$ .

The odd array out is  $[1, 1]$ , so we return the corresponding string, "abc".

Example 2:

Input: words = ["aaa", "bob", "ccc", "ddd"]

Output: "bob"

Explanation: All the integer arrays are  $[0, 0]$  except for "bob", which corresponds to  $[13,$

$-13]$ .

Constraints:

$3 \leq \text{words.length} \leq 100$

$n == \text{words}[i].\text{length}$

$2 \leq n \leq 20$

words[i] consists of lowercase English letters.

**CODING:**

```
def odd_string_difference(words):
    n = len(words[0])
    # Calculate the difference integer array for the first word
    diff0 = [ord(words[0][i + 1]) - ord(words[0][i]) for i in range(n - 1)]

    # Iterate over the rest of the words and compare their difference arrays with the first word
    for word in words[1:]:
        diff = [ord(word[i + 1]) - ord(word[i]) for i in range(n - 1)]
        if diff != diff0:
            return word

# Example usage
words1 = ["adc", "wzy", "abc"]
print(odd_string_difference(words1))

words2 = ["aaa", "bob", "ccc", "ddd"]
print(odd_string_difference(words2))
```

## OUTPUT:

```
"C:\Users\jacin\PycharmProjects\BAA-Design analysis of algorithm\.venv\Scripts\python.exe" "C:\Users\jacin\AppData\Roaming\JetBrains\PyCharmCE2023.3\bin\python.exe"
abc
bob
Process finished with exit code 0
```

## 2. Words Within Two Edits of Dictionary

You are given two string arrays, queries and dictionary. All words in each array comprise

of lowercase English letters and have the same length.

In one edit you can take a word from queries, and change any letter in it to any other letter. Find all words from queries that, after a maximum of two edits, equal some word

from dictionary.

Return a list of all words from queries, that match with some word from dictionary after a

maximum of two edits. Return the words in the same order they appear in queries.

Example 1:

Input: queries = ["word", "note", "ants", "wood"], dictionary = ["wood", "joke", "moat"]

Output: ["word", "note", "wood"]

Explanation:

- Changing the 'r' in "word" to 'o' allows it to equal the dictionary word "wood".
- Changing the 'n' to 'j' and the 't' to 'k' in "note" changes it to "joke".
- It would take more than 2 edits for "ants" to equal a dictionary word.- "wood" can remain unchanged (0 edits) and match the corresponding dictionary word.

Thus, we return ["word", "note", "wood"].

Example 2:

Input: queries = ["yes"], dictionary = ["not"]

Output: []

Explanation:

Applying any two edits to "yes" cannot make it equal to "not". Thus, we return an empty array.

Constraints:

1 <= queries.length, dictionary.length <= 100

n == queries[i].length == dictionary[j].length

$1 \leq n \leq 100$

All queries[i] and dictionary[j] are composed of lowercase English letters.

#### 2453. Destroy Sequential Targets

You are given a 0-indexed array nums consisting of positive integers, representing targets

on a number line. You are also given an integer space.

You have a machine which can destroy targets. Seeding the machine with some nums[i]

allows it to destroy all targets with values that can be represented as  $\text{nums}[i] + c * \text{space}$ ,

where c is any non-negative integer. You want to destroy the maximum number of targets

in nums.

Return the minimum value of nums[i] you can seed the machine with to destroy the maximum number of targets.

Example 1:

Input: nums = [3,7,8,1,1,5], space = 2

Output: 1

Explanation: If we seed the machine with nums[3], then we destroy all targets equal to

1,3,5,7,9,...

In this case, we would destroy 5 total targets (all except for nums[2]).

It is impossible to destroy more than 5 targets, so we return nums[3].

Example 2:

Input: nums = [1,3,5,2,4,6], space = 2

Output: 1

Explanation: Seeding the machine with nums[0], or nums[3] destroys 3 targets.

It is not possible to destroy more than 3 targets.

Since nums[0] is the minimal integer that can destroy 3 targets, we return 1.

Example 3:

Input: nums = [6,2,5], space = 100

Output: 2

Explanation: Whatever initial seed we select, we can only destroy 1 target. The minimal

seed is nums[1]. Constraints:

$1 \leq \text{nums.length} \leq 105$

$1 \leq \text{nums}[i] \leq 109$

$1 \leq \text{space} \leq 109$

**CODING:**

```

1 def words_within_two_edits(queries, dictionary):
2     def generate_edits(word):
3         edits = set()
4         # One edit away
5         for i in range(len(word)):
6             for j in range(26):
7                 new_word = word[:i] + chr(97 + j) + word[i + 1:]
8                 edits.add(new_word)
9         # Two edits away
10        for w in edits.copy():
11            for i in range(len(w)):
12                for j in range(26):
13                    new_word = w[:i] + chr(97 + j) + w[i + 1:]
14                    edits.add(new_word)
15        return edits
16
17    dictionary_set = set(dictionary)
18    result = []
19    for word in queries:
20        edits = generate_edits(word)
21        result = []
22        for word in queries:
23            edits = generate_edits(word)
24            if any(edit in dictionary_set for edit in edits):
25                result.append(word)
26    return result
27
28 # Example usage
29 queries1 = ["word", "note", "ants", "wood"]
30 dictionary1 = ["wood", "joke", "moat"]
31 print(words_within_two_edits(queries1, dictionary1))
32
33 queries2 = ["yes"]
34 dictionary2 = ["not"]
35 print(words_within_two_edits(queries2, dictionary2))

```

## OUTPUT:

```

"C:\Users\jacin\PycharmProjects\OAA-Design analysis of algorithm\.venv\Scripts\python.exe" "C:\Users\jacin\AppData\Roaming\JetBrains\PyCharmCE2023.
['word', 'note', 'wood']
[]
Process finished with exit code 0

```

## CODING:

```
def destroy_sequential_targets(nums, space):
    nums.sort()
    max_targets = 0
    min_seed = float('inf')
    for num in nums:
        targets = (num - nums[0]) // space + 1
        if targets > max_targets:
            max_targets = targets
            min_seed = num
    return min_seed

nums1 = [3, 7, 8, 1, 1, 5]
space1 = 2
print(destroy_sequential_targets(nums1, space1))

nums2 = [1, 3, 5, 2, 4, 6]
space2 = 2
print(destroy_sequential_targets(nums2, space2))

nums3 = [6, 2, 5]
space3 = 100
print(destroy_sequential_targets(nums3, space3))
```

## OUTPUT:

```
"C:\Users\jacin\PycharmProjects\DAA-Design analysis of algorithm\.venv\Scripts\python.exe" "C:\Users\jacin\AppData\Roaming\JetBrains\PyCharmCE2023.
7
4
2
Process finished with exit code 0
```

### 3. Next Greater Element IV

You are given a 0-indexed array of non-negative integers `nums`. For each integer in `nums`,

you must find its respective second greater integer.

The second greater integer of `nums[i]` is `nums[j]` such that:

$j > i$

$nums[j] > nums[i]$

There exists exactly one index  $k$  such that  $nums[k] > nums[i]$  and  $i < k < j$ .

If there is no such `nums[j]`, the second greater integer is considered to be -1.

For example, in the array `[1, 2, 4, 3]`, the second greater integer of 1 is 4, 2 is 3, and that

of 3 and 4 is -1.

Return an integer array `answer`, where `answer[i]` is the second greater integer of `nums[i]`.

Example 1:

Input: nums = [2,4,0,9,6]

Output: [9,6,6,-1,-1]

Explanation:

0th index: 4 is the first integer greater than 2, and 9 is the second integer greater than 2, to

the right of 2.

1st index: 9 is the first, and 6 is the second integer greater than 4, to the right of 4.

2nd index: 9 is the first, and 6 is the second integer greater than 0, to the right of 0.

3rd index: There is no integer greater than 9 to its right, so the second greater integer is

considered to be -1.

4th index: There is no integer greater than 6 to its right, so the second greater integer is

considered to be -1.

Thus, we return [9,6,6,-1,-1].

Example 2:

Input: nums = [3,3]

Output: [-1,-1]

Explanation:

We return [-1,-1] since neither integer has any integer greater than it.

Constraints:

$1 \leq \text{nums.length} \leq 105$

$0 \leq \text{nums}[i] \leq 109$

2455. Average Value of Even Numbers That Are Divisible by Three

Given an integer array nums of positive integers, return the average value of all even integers that are divisible by 3.

Note that the average of n elements is the sum of the n elements divided by n and rounded down to the nearest integer.

Example 1: Input: nums = [1,3,6,10,12,15]

Output: 9

Explanation: 6 and 12 are even numbers that are divisible by 3.  $(6 + 12) / 2 = 9$ .

Example 2:

Input: nums = [1,2,4,7,10]

Output: 0

Explanation: There is no single number that satisfies the requirement, so return 0.

Constraints:

$1 \leq \text{nums.length} \leq 1000$

$1 \leq \text{nums}[i] \leq 1000$

You are given two positive integers n and target.

An integer is considered beautiful if the sum of its digits is less than or equal to target.

Return the minimum non-negative integer x such that n + x is beautiful. The input will be

generated such that it is always possible to make n beautiful.

Example 1:

Input: n = 16, target = 6

Output: 4

Explanation: Initially n is 16 and its digit sum is  $1 + 6 = 7$ . After adding 4, n becomes 20

and digit sum becomes  $2 + 0 = 2$ . It can be shown that we can not make n beautiful with

adding non-negative integer less than 4.

Example 2:

Input:  $n = 467$ , target = 6

Output: 33

Explanation: Initially  $n$  is 467 and its digit sum is  $4 + 6 + 7 = 17$ . After adding 33,  $n$  becomes 500 and digit sum becomes  $5 + 0 + 0 = 5$ . It can be shown that we can not make

$n$  beautiful with adding non-negative integer less than 33.

Example 3:

Input:  $n = 1$ , target = 1

Output: 0

Explanation: Initially  $n$  is 1 and its digit sum is 1, which is already smaller than or equal to target.

Constraints:

$1 \leq n \leq 10^{12}$

$1 \leq \text{target} \leq 150$

The input will be generated such that it is always possible to make  $n$  beautiful.

**CODING:**

```
def next_greater_element(nums):
    stack = []
    result = [-1] * len(nums)
    for i in range(len(nums) - 1, -1, -1):
        while stack and stack[-1] <= nums[i]:
            stack.pop()
        if stack:
            result[i] = stack[-1]
        stack.append(nums[i])
    return result

nums1 = [2, 4, 0, 9, 6]
print(next_greater_element(nums1))
nums2 = [3, 3]
print(next_greater_element(nums2))

def average_value(nums):
    total_sum = 0
    count = 0

    for num in nums:
        if num % 2 == 0 and num % 3 == 0:
```



```

        if num % 2 == 0 and num % 3 == 0:
            total_sum += num
            count += 1
    if count == 0:
        return 0
    return total_sum // count
nums1 = [1, 3, 6, 10, 12, 15]
print(average_value(nums1))
nums2 = [1, 2, 4, 7, 10]
print(average_value(nums2))
def beautiful_number(n, target):
    digit_sum = sum(int(digit) for digit in str(n))
    if digit_sum <= target:
        return 0
    return max(0, (target - digit_sum) // 9 + 1) * 9
n1, target1 = 16, 6
print(beautiful_number(n1, target1))
n2, target2 = 467, 6
print(beautiful_number(n2, target2))
n3, target3 = 1, 1
print(beautiful_number(n3, target3))

```

### OUTPUT:



```

"C:\Users\jacin\PycharmProjects\DAA-Design analysis of algorithm\.venv\Scripts\python.exe" "C:\Users\jacin\AppData\Roaming\JetBrains
[4, 9, 9, -1, -1]
[-1, -1]
9
0
0
>

```

#### 4. Minimum Addition to Make Integer Beautiful

You are given two positive integers  $n$  and  $target$ .

An integer is considered beautiful if the sum of its digits is less than or equal to  $target$ .

Return the minimum non-negative integer  $x$  such that  $n + x$  is beautiful. The input will be

generated such that it is always possible to make  $n$  beautiful.

Example 1:

Input:  $n = 16$ ,  $target = 6$

Output: 4

Explanation: Initially  $n$  is 16 and its digit sum is  $1 + 6 = 7$ . After adding 4,  $n$  becomes 20

and digit sum becomes  $2 + 0 = 2$ . It can be shown that we can not make  $n$  beautiful with

adding non-negative integer less than 4.

Example 2:

Input:  $n = 467$ ,  $target = 6$

Output: 33

Explanation: Initially  $n$  is 467 and its digit sum is  $4 + 6 + 7 = 17$ . After adding 33,  $n$  becomes 500 and digit sum becomes  $5 + 0 + 0 = 5$ . It can be shown that we can not make

$n$  beautiful with adding non-negative integer less than 33.

Example 3:

Input:  $n = 1$ ,  $target = 1$

Output: 0

Explanation: Initially  $n$  is 1 and its digit sum is 1, which is already smaller than or equal

to target.

Constraints:

- $1 \leq n \leq 10^{12}$
- $1 \leq target \leq 150$
- The input will be generated such that it is always possible to make  $n$  beautiful.

### CODING:

```
3 usages
1  def makeIntegerBeautiful(n: int, target: int) -> int:
2      def digit_sum(num: int) -> int:
3          return sum(int(digit) for digit in str(num))
4      x = 0
5      while digit_sum(n + x) > target:
6          x += 1
7      return x
8
9  n = 16
10 target = 6
11 print(makeIntegerBeautiful(n, target)) # Output: 4
12 n = 467
13 target = 6
14 print(makeIntegerBeautiful(n, target)) # Output: 33
15 n = 1
16 target = 1
17 print(makeIntegerBeautiful(n, target)) # Output: 0
```

### OUTPUT:

```
C:\Users\vinot\PycharmProjects\pythor
4
33
0

Process finished with exit code 0
```

### 5. Sort Array by Moving Items to Empty Space

You are given an integer array `nums` of size  $n$  containing each element from 0 to  $n - 1$  (inclusive). Each of the elements from 1 to  $n - 1$  represents an item, and the element 0 represents an empty space.

In one operation, you can move any item to the empty space. `nums` is considered to be

sorted if the numbers of all the items are in ascending order and the empty space is either

at the beginning or at the end of the array.

For example, if  $n = 4$ , `nums` is sorted if:

- `nums = [0,1,2,3]` or
- `nums = [1,2,3,0]`

...and considered to be unsorted otherwise.

Return the minimum number of operations needed to sort `nums`.

Example 1:

Input: `nums = [4,2,0,3,1]`

Output: 3

Explanation:

- Move item 2 to the empty space. Now, `nums = [4,0,2,3,1]`.
- Move item 1 to the empty space. Now, `nums = [4,1,2,3,0]`.
- Move item 4 to the empty space. Now, `nums = [0,1,2,3,4]`. It can be proven that 3 is the minimum number of operations needed.

Example 2:

Input: `nums = [1,2,3,4,0]`

Output: 0

Explanation: `nums` is already sorted so return 0.

Example 3:

Input: `nums = [1,0,2,4,3]`

Output: 2

Explanation:

- Move item 2 to the empty space. Now, `nums = [1,2,0,4,3]`.
- Move item 3 to the empty space. Now, `nums = [1,2,3,4,0]`.

It can be proven that 2 is the minimum number of operations needed.

Constraints:

- $n == \text{nums.length}$
- $2 \leq n \leq 105$
- $0 \leq \text{nums}[i] < n$
- All the values of `nums` are unique.

2460. Apply Operations to an Array

You are given a 0-indexed array `nums` of size  $n$  consisting of non-negative integers.

You need to apply  $n - 1$  operations to this array where, in the  $i$ th operation (0-indexed), you will apply the following on the  $i$ th element of `nums`:

- If `nums[i] == nums[i + 1]`, then multiply `nums[i]` by 2 and set `nums[i + 1]` to 0. Otherwise, you skip this operation.

After performing all the operations, shift all the 0's to the end of the array.

- For example, the array `[1,0,2,0,0,1]` after shifting all its 0's to the end, is `[1,2,1,0,0,0]`.

Return the resulting array.

Note that the operations are applied sequentially, not all at once.

Example 1:

Input: `nums = [1,2,2,1,1,0]`

Output: `[1,4,2,0,0,0]`

Explanation: We do the following operations:

- $i = 0$ : `nums[0]` and `nums[1]` are not equal, so we skip this operation.
- $i = 1$ : `nums[1]` and `nums[2]` are equal, we multiply `nums[1]` by 2 and change `nums[2]` to 0. The array becomes `[1,4,0,1,1,0]`.

- i = 2: nums[2] and nums[3] are not equal, so we skip this operation.
- i = 3: nums[3] and nums[4] are equal, we multiply nums[3] by 2 and change nums[4] to 0. The array becomes [1,4,0,2,0,0].
- i = 4: nums[4] and nums[5] are equal, we multiply nums[4] by 2 and change nums[5] to 0. The array becomes [1,4,0,2,0,0].

After that, we shift the 0's to the end, which gives the array [1,4,2,0,0,0]. Example 2:

Input: nums = [0,1]

Output: [1,0]

Explanation: No operation can be applied, we just shift the 0 to the end.

Constraints:


- $2 \leq \text{nums.length} \leq 2000$
- $0 \leq \text{nums}[i] \leq 1000$

**CODING:**

```
def min_operations_to_sort(nums):
    n = len(nums)
    empty_index = nums.index(0)
    if empty_index == 0:
        return sum(1 for i in range(1, n) if nums[i] != i)
    elif empty_index == n - 1:
        return sum(1 for i in range(n - 1) if nums[i] != i)
    else:
        return sum(1 for i in range(1, n) if nums[i] != i) + 1

nums1 = [4, 2, 0, 3, 1]
print(min_operations_to_sort(nums1))
nums2 = [1, 2, 4, 3, 0]
print(min_operations_to_sort(nums2))
nums3 = [1, 0, 2, 3]
print(min_operations_to_sort(nums3))
```

**OUTPUT:**



```
"C:\Users\jacin\PycharmProjects\DAA-Design analysis of algorithm\.venv\Scripts\python.exe" "C:\Users\jacin\AppData\Roaming\JetBrains
4
3
2
Process finished with exit code 0
```