Installing Docker on Amazon Linux 2

The procedure to install Docker on AMI 2 (Amazon Linux 2) running on an EC2 instance is as follows:

1) Login into the remote AWS server using the ssh command or using putty:
$ ssh ec2-user@ec2-ip-address-dns-name-here

2) Apply pending updates using the yum command:
$ sudo yum update

3) Search for Docker package:
$ sudo yum search docker

4) Get version information:
$ sudo yum info docker

Getting Docker version

5) Install docker, run:
$ sudo yum install docker



Amazon Linux 2: Install docker command

6) Add group membership for the default ec2-user so you can run all docker commands without using the sudo command:

$ sudo usermod -a -G docker ec2-user
$ id ec2-user
# Reload a Linux user's group assignments to docker w/o logout
$ newgrp docker

7) For docker-compose, try any one of the following commands:

```
# Get pip3
sudo yum install python3-pip

# Then run any one of the following
sudo pip3 install docker-compose # with root access

OR

pip3 install --user docker-compose # without root access for security reasons

OR

wget https://github.com/docker/compose/releases/latest/download/docker-compose-$(uname -s)-$(uname -m)
sudo mv docker-compose-$(uname -s)-$(uname -m) /usr/local/bin/docker-compose
sudo chmod -v +x /usr/local/bin/docker-compose
```

How to install docker-compose in Amazon Linux

8) Enable docker service at AMI boot time:

$ sudo systemctl enable docker.service

9) Start the Docker service:

$ sudo systemctl start docker.service

Verification

Now that both required software is installed, we need to make sure it is working. Hence, type the following commands.

Finding status

Get the docker service status on your AMI instance, run:
$ sudo systemctl status docker.service

Outputs:

```
● docker.service - Docker Application Container Engine
  Loaded: loaded (/usr/lib/systemd/system/docker.service; enabled; vendor preset: disabled)
  Active: active (running) since Wed 2021-09-08 05:03:52 EDT; 18s ago
    Docs: https://docs.docker.com
 Process: 3295 ExecStartPre=/usr/libexec/docker/docker-setup-runtimes.sh (code=exited, status=0/SUCCESS)
 Process: 3289 ExecStartPre=/bin/mkdir -p /run/docker (code=exited, status=0/SUCCESS)
Main PID: 3312 (dockerd)
   Tasks: 9
  Memory: 39.9M
  CGroup: /system.slice/docker.service
          └─3312 /usr/bin/dockerd -H fd:// --containerd=/run/containerd/c...

Sep 08 05:03:51 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:51 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:51 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:51 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:52 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:52 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:52 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:52 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Sep 08 05:03:52 amazon.example.local systemd[1]: Started Docker Applicatio...
Sep 08 05:03:52 amazon.example.local dockerd[3312]: time="2021-09-08T05:03...
Hint: Some lines were ellipsized, use -l to show in full.
```

Getting docker version info on Amazon Linux

- The docker-compose is installed in the '/usr/local/bin' directory and may not be on your PATH settings. To see current PATH settings run the echo command/printf command:

  ```
  $ echo "$PATH"
  ```

- To add /usr/local/bin/ path to your bash startup file such as ~/.profile or ~/.bash_profile using the export command:

  ```
  $ export PATH=$PATH:/usr/local/bin
  ```

- Another option for developers is to use the find command to locate the docker-compose file as follows:

  ```
  $ sudo find / -name "docker-compose" -ls
  ```

See docker version:

$ docker version

Also verify that docker-compose install was a success on AMI 2 by running the following command:
$ docker-compose version



Getting docker version on AMI using the ssh client

How to control docker service

Use the systemctl command as follows:

```
sudo systemctl start docker.service #<-- start the service
sudo systemctl stop docker.service #<-- stop the service
sudo systemctl restart docker.service #<-- restart the service
sudo systemctl status docker.service #<-- get the service status
```

Creating your first Docker project

Make a new project folder using the mkdir command and cd into it using the cd command. For instance:

```
$ mkdir static-website-1
$ cd static-website-1
```

Use the echo command as follows to create a new index.html for our project:

```
$ echo 'Docker Training Apache static site' > index.html
```

Make a new Dockerfile using a text editor such as nano command or vim command:

```
$ vim Dockerfile
```

Append the following config for your Amazon Linux container:

```
FROM rockylinux/rockylinux:latest

MAINTAINER DevOpsTrainer
LABEL Remarks="Linux test image for installing static webpage with Apache2"

# Install apache2 with less
RUN yum -y update && \
yum -y install httpd && \
yum clean all

# Sample index.html for test
COPY index.html /var/www/html/index.html

# Port and set entry point for container
EXPOSE 80
ENTRYPOINT /usr/sbin/httpd -DFOREGROUND
```

Build docker:

$ sudo docker build -t staticsite01 .

Outputs:

```
Sending build context to Docker daemon  3.072kB
Step 1/7 : FROM rockylinux/rockylinux:latest
latest: Pulling from rockylinux/rockylinux
ecce7a433753: Pull complete
Digest: sha256:98dcf3fbe75741058c16ece621f5917e0ff52d9333073e6389c5de8efaa3d5c4
Status: Downloaded newer image for rockylinux/rockylinux:latest
 ---> 86f02aa837b3
Step 2/7 : MAINTAINER nixCraft
 ---> Running in 7f4f35c8d95a
Removing intermediate container 7f4f35c8d95a
 ---> e40cd8411b69
Step 3/7 : LABEL Remarks="CentOS 8 test image for installing ng with Apache2"
 ---> Running in 31bf348db2fb
Removing intermediate container 31bf348db2fb
 ---> 28accfe0f9ff
Step 4/7 : RUN yum -y update && yum -y install httpd && yum clean all
 ---> Running in f588730a294f
Rocky Linux 8 - AppStream                  6.2 MB/s |  10 MB     00:01
Rocky Linux 8 - BaseOS                     6.7 MB/s | 7.7 MB     00:01
Rocky Linux 8 - Extras                     59 kB/s |  12 kB     00:00
Dependencies resolved.
================================================================================
 Package             Arch     Version                Repo      Size
================================================================================
Upgrading:
 gzip                x86_64   1.9-13.el8_5           baseos    166 k
 libreport-filesystem   x86_64   2.9.5-15.el8.rocky.6.3     baseos     20 k
 openssl-libs        x86_64   1:1.1.1k-6.el8_5       baseos    1.5 M
 vim-minimal         x86_64   2:8.0.1763-16.el8_5.13     baseos    574 k
 zlib                x86_64   1.2.11-18.el8_5        baseos    101 k
Installing dependencies:
 openssl             x86_64   1:1.1.1k-6.el8_5       baseos    708 k
Installing weak dependencies:
 openssl-pkcs11      x86_64   0.4.10-2.el8           baseos     65 k

Transaction Summary
================================================================================
Install  2 Packages
Upgrade  5 Packages

Total download size: 3.1 M
.....
..
.....
  rocky-logos-httpd-85.0-3.el8.noarch

Complete!
27 files removed
Removing intermediate container f588730a294f
```

List images:

```
$ sudo docker images
REPOSITORY              TAG     IMAGE ID       CREATED         SIZE
staticsite01            latest  51c5c08cf14d   3 minutes ago   232MB
rockylinux/rockylinux   latest  86f02aa837b3   6 weeks ago     205MB
```

Run docker:

```
$ sudo docker run -d -p 80:80 --name staticsite01 staticsite01
$ sudo docker ps
$ sudo docker port staticsite01
$ curl 127.0.0.1:80
```

Summing up

That is all for now. You learned how to install Docker on AMI 2 and deploy Apache 2 as the Docker container for a static website. Use the following command to get an overview of available commands:

```
$ docker help
$ docker --help
```

For specific client examples please see the man page for the specific Docker command using the man command. For instance:

```
$ man docker-build
$ man docker-run
```