vishruthi@localhost:~/reverdig

```
[vishruthi@localhost reverdig]$ vi rev.sh
[vishruthi@localhost reverdig]$ ./rev.sh
Enter a number: 1234
Reversed number: 4321
[vishruthi@localhost reverdig]$
```

vishruthi@localhost:~/reverdig — /usr/bin/vim rev.sh

```
#1/bin/bash
read -p "Enter a number: " num
rev=0
temp=$num
while [ $temp -ne 0 ]
do
        digit=$(( temp % 10 ))
        rev=$(( rev * 10 + digit ))
        temp=$(( temp /10 ))

done
echo "Reversed number: $rev"
```

vishruthi@localhost:~

```
[vishruthi@localhost ~]$ vi marks.dat
[vishruthi@localhost ~]$ vi marks.awk
[vishruthi@localhost ~]$ gawk -f marks.awk marks.dat
NAME SUB-1 SUB-2 SUB-3 SUB-4 SUB-5 SUB-6 STATUS
-----------------------------------------------
REN 40 55 66 77 55 77 FAIL
TOM 60 67 84 92 90 60 PASS
RAM 90 95 84 87 56 70 PASS
LIN 60 70 65 78 90 87 PASS
-----------------------------------------------
[vishruthi@localhost ~]$
```

vishruthi@localhost:~ — vi marks.awk

```
BEGIN {
print "NAME SUB-1 SUB-2 SUB-3 SUB-4 SUB-5 SUB-6 STATUS"
print"-----------------------------------------------"
}
{
status = "PASS"
for(i=2; i<=7; i++)
if($i < 45 )
status="FAIL"
print $1, $2, $3, $4, $5, $6, $7, status
}
END {
print "-----------------------------------------"
}
```