

sonatype nexus repository

Community Edition

Search components

🔔

🔄

🔗

👤

Settings

Repository

Repositories

Blob Stores

Data Store

Proprietary Repositories

Content Selectors

Cleanup Policies

Routing Rules

Security

Support

System

IQ Server

Repositories

Select Recipe

Create Repository: maven2 (hosted)

Name:

A unique identifier for this repository

yap-processor-pk

Online:

☒ If checked, the repository accepts incoming requests

Maven 2

Version policy:

What type of artifacts does this repository store?

Release

Release

Snapshot

Mixed

Content Disposition:

Add Content-Disposition header as 'Attachment' to disable some content from being inline in a browser.

Inline

Storage

Blob store:

Blob store used to store repository contents

default

Strict Content Type Validation:

sonatype nexus repository

Community Edition

Search components

🔔

🔄

🔗

👤

Settings

Repository

Repositories

Blob Stores

Data Store

Proprietary Repositories

Content Selectors

Cleanup Policies

Routing Rules

Security

Support

System

IQ Server

Repositories

Select Recipe

Create Repository: maven2 (hosted)

Storage

Blob store:

Blob store used to store repository contents

default

Strict Content Type Validation:

☒ Validate that all content uploaded to this repository is of a MIME type appropriate for the repository format

Hosted

Deployment policy:

Controls if deployments of and updates to artifacts are allowed

Allow redeploy

Allow redeploy

Disable redeploy

Read-only

Cleanup

Cleanup Policies:

Components that match any of the Applied policies will be deleted

Available

Applied

Filter

🏠

🔑

👤

Vault

Dashboard

Secrets Engines

Access

Policies

Tools

Monitoring

Client Count

Seal Vault

Secrets Engines

Filter by engine type

Filter by engine name

Enable new engine +

cubbyhole/

cubbyhole\_67f84171

per-token private secret storage

kv/

v2\_kv\_aca97bd3

soar/

v2\_kv\_3cfd58b4

Vault

Dashboard

Secrets Engines

Access

Policies

Tools

Monitoring

Client Count

Seal Vault

< Back to main navigation

Policies

ACL Policies

< Back to main navigation

Policies

ACL Policies

Create Secret

JSON

Path for this secret

Names with forward slashes define hierarchical path structures.

yap-admin

Secret data

1

JSON is unparseable. Fix linting errors to avoid data discrepancies.

Show secret metadata

Save

Cancel

ACL Policies

Filter policies

Create ACL policy +

default

...

yap-admin-policy

...

yap-auth-keycloak-policy

...

yap-auth-policy

...

yap-cards-policy

...

yap-customers-policy

...

yap-document-policy

...

ACL policies / Create

Create ACL Policy

Name

yap-cards-policy

How to write a policy

Upload file

Policy

1

path "kv/data/yap-cards" {

2

3

capabilities = ["read","delete","list","update","create"]

4

5

}

Create policy

Cancel

Back to main navigation

Authentication

Authentication Methods

Multi-Factor Authentication

OIDC Provider

Organization

Groups

Entities

Back to main navigation

Authentication

Authentication Methods

Multi-Factor Authentication

OIDC Provider

Organization

Groups

Entities

## Authentication Methods

Filter by auth type

Filter by auth name

Enable new method +

kubernetes/

auth\_kubernetes\_92a1d77a

...

token/

auth\_token\_46088ca4

...

role-yap-cards

Delete role

Edit role >

Alias name source

serviceaccount\_uid

Audience

Bound service account names

cards-dev-yap

Bound service account namespace selector

Bound service account namespaces

dev

Tokens

Generated Token's Bound CDRs

Generated Token's Explicit Maximum TTL

0

Generated Token's Maximum TTL

0

Do Not Attach 'default' Policy To Generated Tokens

false

Maximum Uses of Generated Tokens

0

Generated Token's Period

0

Generated Token's Policies

yap-cards-policy

Generated Token's Initial TTL

0

Generated Token's Type

default