COMPUTER NETWORKS LAB

Understanding Transport and Network Layer using Wireshark WEEK 6

NAME: VISHWA MEHUL MEHTA

SRN: PES2UG20CS389

SECTION: F

DATE: 09/04/2022

I. UDP and DNS:

1.

```
vishwa@vishwa-VirtualBox:~/Documents$ dig www.pluralsight.com
; <<>> DiG 9.16.1-Ubuntu <<>> www.pluralsight.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<-- opcode: QUERY, status: NOERROR, id: 58981
;; flags: qr rd ra; QUERY: 1, ANSWER: 3, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;; www.pluralsight.com. IN A

;; ANSWER SECTION:
www.pluralsight.com. 60 IN CNAME www.pluralsight.com.cdn.cloudflare.net.
www.pluralsight.com.cdn.cloudflare.net. 299 IN A 104.19.162.127
www.pluralsight.com.cdn.cloudflare.net. 299 IN A 104.19.161.127

;; Query time: 43 msec
;; SERVER: 127.0.0.53#53(127.0.0.53)
;; WHEN: Sun Apr 03 16:12:14 IST 2022
;; MSG SIZE rcvd: 132</pre>
```

2.

```
File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help


| Image: Comparison of the Comparison of the
```

The UDP segment headers expected are:

Source Port Number - 2 bytes, Destination Port Number - 2 bytes, Length - 2 bytes, Checksum - 2 bytes and rest are payload.


4.

As per the above mentioned predictions the headers in the UDP segment are as shown:



5.

The UDP checksum covers UDP header and the UDP data.




II. TCP:

9.



11.

3-Way Handshake:



HTTP POST:

1336 24.005572280	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 [ACK] Seq=1 Ack=1667157 Win=32768 Len=0
1337 24.005572299	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 [ACK] Seq=1 Ack=1669265 Win=32768 Len=0
1338 24.005572318	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 [ACK] Seq=1 Ack=1672185 Win=32768 Len=0
1339 24.005572336	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1675105 Win=32768 Len=0
1340 24.005572355	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 [ACK] Seq=1 Ack=1678025 Win=32768 Len=0
1341 24.005579306	10.0.2.15	128.2.131.88	TCP	11734 47020 → 80 [PSH, ACK] Seq=1683865 Ack=1 Win=64240 Len=11680 [
1342 24.005618622	10.0.2.15	128.2.131.88	TCP	866 47020 → 80 ACK Seq=1695545 Ack=1 Win=64240 Len=812 TCP seq
+ 1343 24.005784431	10.0.2.15	128.2.131.88	HTTP	6460 POST /Lab2/lab2b.html HTTP/1.1 (text/plain)
1344 24.005902632	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 [ACK] Seg=1 Ack=1680133 Win=32768 Len=0
1345 24.005902677	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1681757 Win=32768 Len=0
1346 24.005902699	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1683865 Win=32768 Len=0
1347 24.005902725	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1686785 Win=32768 Len=0
1348 24.005902749	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1689705 Win=32768 Len=0
1349 24.005902773	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seg=1 ACK=1692625 Win=32768 Len=0
1350 24.005902799	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1695545 Win=32768 Len=0
1351 24.005902827	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1697817 Win=32768 Len=0
1352 24.005960867	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1700737 Win=32768 Len=0
1353 24.005960909	128.2.131.88	10.0.2.15	TCP	60 80 → 47020 ACK Seq=1 Ack=1702763 Win=32768 Len=0
1354 24.888724139	128.2.131.88	10.0.2.15	HTTP	929 HTTP/1.1 200 OK (text/html)
1355 24.888747250	10.0.2.15	128.2.131.88	TCP	54 47020 → 80 [ACK] Seg=1702763 Ack=876 Win=63875 Len=0
1356 29.842406571		10.0.2.15	TCP	60 80 → 47020 [FIN, ACK] Seg=876 Ack=1702763 Win=32768 Len=0
1357 29.842744021		128.2.131.88	TCP	54 47020 → 80 [FIN, ACK] Seg=1702763 Ack=877 Win=63875 Len=0

Client:-


IP Address: 10.0.2.15

Port: 47008

Server IP Address: 128.2.131.88

Server Port number: 80

13.



A. TCP Basics:


14.


Sequence Number of TCP SYN:

Relative: 0

Raw: 2410673663

The absolute sequence number is the raw sequence number given in the packet info.






Sequence Number of the SYNACK segment: 0

Acknowledgement field in SYNACK: 1


The server determines the acknowledgement using the sequence number of the next expected packet.

The acknowledgement and the syn bits are set to 1 which determines that it is a SYNACK segment.

16.



Sequence Number of HTTP POST TCP segment: 1696357



Segments: 118, 119, 122, 123, 126, 128

Segment sequence numbers: 1, 2921, 5841, 8761, 11681, 14601

Segment Acknowledgements: 120, 121, 124, 125, 127, 129


Round Trip Time (RTT) is the measure of how long it takes for a very small packet to travel across the network and for an acknowledgement of that packet to be returned.

Using the formula,

EstimatedRTT = $(1 - \alpha)$ · EstimatedRTT + α · SampleRTT

Where, $\alpha = 0.125$

Segment Number	Sample RTT	Estimated RTT
118	0.00047034	0.00047034
119	0.00019179	0.00043552
122	0.00041038	0.00043237
123	0.00018495	0.00040144
126	0.00017051	0.00037257
128	0.00016633	0.00034679



0110 = Header Length: 24 bytes (6)

▶ Flags: 0x012 (SYN, ACK)

Window size value: 32768


[Calculated window size: 32768] Checksum: 0x0582 [unverified] [Checksum Status: Unverified]

Urgent pointer: 0

- ▶ Options: (4 bytes), Maximum segment size
- [SEQ/ACK analysis]
- | [Timestamps]

Minimum buffer space available is 32768. The lack of buffer does not throttle the sender due to effective congestion avoidance.

19.



No segments have been retransmitted.

20.

The receiver acknowledges about 2920 packets after every 2 segments sent. There were no delayed ACKs found as there was no congestion in the network.

21.


Total file size = 17,82,579.2 bytes

Total download time = (29.842 - 24.888)s = 4.954s

Throughput = 17,82,579.2 / 4.954 = 3,59,826.24 bytes/s = 351.39 KBps

B. TCP Statistics:

22.




The most common packet length is in the range of 40-79 bytes.

The second-most common packet length range is 2560-5119 bytes.

The length of packets <40 bytes is 0 as the minimum header length is 40 bytes and any packet with <40 bytes contains no data.

Navigate to "Statistics -> Packet Lengths" to get the information. 23.



Average Throughput = 2053845/29.844 = 68819.36 bytes/s= 0.065 MBps Packets captured in the session = 1358

Total bytes = 2053845

Go to "Statistics -> Capture File Properties" to find the above observations.


24.

									P_1.pcapng					_ 0
IPv4 · 6	IPv6 T	CP · 10	UDP ·	15										
ddress B	Packet	ts B	ytes	Packets A → B	Е	ytes A → B	Packets B → A	В	ytes B → A	Rel Start	Duration	Bits/s A → B	Bits/s B → A	
		31			16						15.5912			99
														11
														5,3
														3,9
			8,576		16									63
5.82.103.10	D	4	288		2	143		2	145	9.963252	0.2426	4,71	5	4,7
	idress B 2.168.145 8.2.131.8 1.120.208. 8.30.52.1 1.117.237.	ddress B Packe 2.168.145.51	Iddress B Packets B 12.168.145.51 31 18.2.131.88 1,264 1.120.208.123 11 18.30.52.100 21 1.117.237.239 27	dress B Packets Bytes 12.168.145.51 31 3.328 18.64 2.035 k 1.120.208.123 11 2.110 18.30.52.100 21 4.276 1.17.237.239 27 8.576	idress B Packets Bytes Packets A → B 12.168.145.51 31 3,328 12.2163.168 1,264 2,035 k 1.120.208.123 11 2,110 18.30.52.100 21 4,276 1.117.237.239 27 8,576	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Idress B Packets Bytes Packets A → B Bytes A → B Packets B → A 12.168.145.51 31 3,228 16 1,393 1.26 1,2035 k 612 1,993 k 6 1.120.208.123 11 2,110 5 1,580 1,580 1,283 1,22,120 11 933 1,117.237.239 27 8,576 16 1,938	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Idress B Packets Bytes Packets A B Bytes A B Packets B → A Bytes B → A Rel Start Duration 12.168.145.51 31 3,228 16 1,393 15 1,935 0,000000 15.5912 12.213.186 1,264 2,035 k 612 1,993 k 652 41 k 0,338871 29.5046 1.120.208.123 11 2,110 5 1,580 6 530 12.12968 0.7930 18.30.52.100 21 4,276 11 933 10 3,343 1.576460 6.7222 1.117.237.239 27 8,576 16 1,938 11 6,363 6.597846 6.7222	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Idress B Packets Bytes Packets A → B Bytes A → B Packets B → A Bytes B → A Rel Start Duration Bits/s A → B Bits/s B → A 12.168.145.51 31 3.328 16 1.393 15 1.935 0.000000 15.5912 714 12.213.186 1.264 2.035 k 612 1.993 k 652 41 k 0.338871 29.5046 540 k 1.120.208.123 11 2.110 5 1.580 6 530 1.219968 0.7930 15 k 18.30.52.100 21 4,276 11 933 10 3,343 1.376460 6.7222 1,110 1.117.237.239 27 8,576 16 1,938 11 6,638 6.597846 0.8345 18 k


The local host conversed with the remote host with IP address 128.2.131.88 the most. 612 packets were sent to the remote host and 652 packets were sent from the remote host.

III. Congestion Control:

25.



26.




Slow start phase begins: 0.402s

Slow start phase ends: 0.440s

IV. The Network Layer:

27.



29.

Datagram Length: 45 bytes

Upper Layer Protocol: IPv4

IP Address Fields:-

Src: 10.0.2.15

No. Time Source

Dest: 192.168.145.51

31.

140		Source	Destination	11000001	Leng
	1 0.000000000	10.0.2.15	192.168.145.51	DNS	
	2 0.149398431	192.168.145.51	10.0.2.15	DNS	
→	7 0.886451862	10.0.2.15	192.168.145.51	DNS	
-	8 0.177090132	192.168.145.51	10.0.2.15	DNS	
>	Frame 7: 89 bytes	on wire (712 bits),	89 bytes captured (71	2 bits) (on in
•	Ethernet II, Src:	PcsCompu_83:72:38 (0)	8:00:27:83:72:38), Ds	t: Realt	ekU_1
-		Version 4, Src: 10.0	.2.15, Dst: 192.168.1	45.51	
	0100 = Ver	rsion: 4			
	0101 - Hos	der Length: 20 hytes	(5)		

Destination

Protocol Leng

```
0100 ... = Version: 4
... 0101 = Header Length: 20 bytes (5)

Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 75
Identification: 0xd5fe (54782)

Flags: 0x4000, Don't fragment
Fragment offset: 0
Time to live: 64
Protocol: UDP (17)
Header checksum: 0x06b9 [validation disabled]
[Header checksum status: Unverified]
Source: 10.0.2.15
Destination: 192.168.145.51
```


TTL: 64

OS: Linux Mint 20.3 Cinnamon

OS Version: 5.2.7

V. ICMP:

32.



When traceroute was used:-

First Destination Port: 33434

Second Destination Port: 33435

Third Destination Port: 33436


And so on...

Destination Port number increases by 1 every hop.

36.

To inspect the ICMP reply packet ping was used instead of traceroute as the traceroute was not showing any proper routes to be examined.

```
vishwa@vishwa-VirtualBox: ~
 File Edit View Search Terminal Tabs Help
             vishwa@vishwa-VirtualBox: ~
                                                                 vishwa@vishwa-VirtualBox: ~
                                                                                                          .
Fil
vishwa@vishwa-VirtualBox:~$ ping www.regjeringen.no
PING www.regjeringen.no (104.18.3.141) 56(84) bytes of data.
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=1 ttl=59 time=6.22 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=2 ttl=59 time=7.59 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp seq=3 ttl=59 time=9.46 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seg=4 ttl=59 time=7.87 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp seq=5 ttl=59 time=6.36 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=6 ttl=59 time=7.21 ms 64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=7 ttl=59 time=4.89 ms 64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=8 ttl=59 time=3.31 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp seq=9 ttl=59 time=5.74 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=10 ttl=59 time=7.32 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=11 ttl=59 time=9.60 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=12 ttl=59 time=7.23 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=13 ttl=59 time=6.03 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=14 ttl=59 time=7.64 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=15 ttl=59 time=9.21 ms
64 bytes from 104.18.3.141 (104.18.3.141): icmp_seq=16 ttl=59 time=6.74 ms
--- www.regjeringen.no ping statistics ---
16 packets transmitted, 16 received, 0% packet loss, time 15039ms
rtt min/avg/max/mdev = 3.307/7.026/9.597/1.603 ms
```



ICMP Type: 0

ICMP Code: 0

Identifiers: 1(BE), 256(LE)

Sequence numbers: 1(BE), 256(LE)

37.

Timestamp from icmp data is mentioned to relate to the sent packets.

Both ping and traceroute screenshots are pasted above for reference.

Ping does not show the port numbers for every hop unlike traceroute.