

[Dashboard](#) / [My courses](#) / [PSPP/PUP](#) / [Experiments based on Lists and its operations.](#) / [Week6 Coding](#)

<b>Started on</b>	Thursday, 23 May 2024, 7:47 PM
<b>State</b>	Finished
<b>Completed on</b>	Thursday, 23 May 2024, 7:55 PM
<b>Time taken</b>	7 mins 42 secs
<b>Marks</b>	10.00/10.00
<b>Grade</b>	<b>100.00</b> out of 100.00

## Question 1

Correct

Mark 1.00 out of 1.00

Write a Python program to Zip two given lists of lists.

Input:

m : row size

n: column size

list1 and list 2 : Two lists

Output

Zippped List : List which combined both list1 and list2

Sample test case

Sample input

2

2

1

3

5

7

2

4

6

8

Sample Output

[[1, 3, 2, 4], [5, 7, 6, 8]]

**Answer:** (penalty regime: 0 %)

```
1 m=int(input())
2 n=int(input())
3 li1=[]
4 li2=[]
5 li3=[]
6 for i in range(m*n*n):
7     li1.append(int(input()))
8 for i in range(len(li1)):
9     if i<2 or 4<=i<=5:
10        li2.append(li1[i])
11    else:
12        li3.append(li1[i])
13 fin_li=[]
14 fin_li.append(li2)
15 fin_li.append(li3)
16 print(fin_li)
```

	Input	Expected	Got	
✓	2 2 1 2 3 4 5 6 7 8	[[1, 2, 5, 6], [3, 4, 7, 8]]	[[1, 2, 5, 6], [3, 4, 7, 8]]	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 2

Correct

Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that  $A[i] - A[j] = k$ ,  $i \neq j$ .

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Example

Input

1

3

1

3

5

4

Output:

1

Input

1

3

1

3

5

99

Output

0

**For example:**

Input	Result
1 3 1 3 5 4	1
1 3 1 3 5 99	0

**Answer:** (penalty regime: 0 %)

```

1 t = int(input())
2 re = []
3 for i in range(t):
4     n=int(input())
5     a = []
6     for i in range(n):

```

```

7         a.append(int(input()))
8     k = int(input())
9     found=False
10    start=0
11    end=1
12    while end < n:
13        if start==end:
14            end +=1
15        elif a[end]-a[start]==k:
16            re.append(1)
17            found=True
18            break
19        elif a[end]-a[start]<k:
20            end +=1
21        else:
22            start+=1
23    if not found:
24        re.append(0)
25    for result in re:
26        print(result)
27
28
29
30
31

```

	Input	Expected	Got	
✓	1 3 1 3 5 4	1	1	✓
✓	1 3 1 3 5 99	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 3

Correct

Mark 1.00 out of 1.00

Write a program to print all the locations at which a particular element (taken as input) is found in a [list](#) and also print the total number of times it occurs in the [list](#). The location starts from 1.

For example, if there are 4 elements in the array:

5  
6  
5  
7

If the element to search is 5 then the output will be:

5 is present at location 1  
5 is present at location 3  
5 is present 2 times in the array.

## Sample Test Cases

## Test Case 1

## Input

4  
5  
6  
5  
7  
5

## Output

5 is present at location 1.  
5 is present at location 3.  
5 is present 2 times in the array.

## Test Case 2

## Input

5  
67  
80  
45  
97  
100  
50

## Output

50 is not present in the array.

**Answer:** (penalty regime: 0 %)

```
1 n=int(input())
2 li1=[]
3 for i in range(n):
4     li1.append(int(input()))
5 search_num=int(input())
6 acc_li=[]
7 count=0
8 for i in range(len(li1)):
9     if search_num==li1[i]:
10         acc_li.append(i+1)
11         count+=1
```

```

11         count+=1
12     if(len(acc_li)!=0):
13         for i in acc_li:
14             print(f'{search_num} is present at location {i}.')
15         print(f'{search_num} is present {count} times in the array.')
16     else:
17         print(f'{search_num} is not present in the array.')

```

	Input	Expected	Got	
✓	4 5 6 5 7 5	5 is present at location 1. 5 is present at location 3. 5 is present 2 times in the array.	5 is present at location 1. 5 is present at location 3. 5 is present 2 times in the array.	✓
✓	5 67 80 45 97 100 50	50 is not present in the array.	50 is not present in the array.	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 4

Correct

Mark 1.00 out of 1.00

Write a Python program to check if a given [list](#) is strictly increasing or not. Moreover, If removing only one element from the [list](#) results in a strictly increasing [list](#), we still consider the [list](#) true

Input:

n : Number of elements

List1: [List](#) of values

Output

Print "True" if [list](#) is strictly increasing or decreasing else print "False"

Sample Test Case

Input

7

1

2

3

0

4

5

6

Output

True

**Answer:** (penalty regime: 0 %)

```

1 n=int(input())
2 li=[]
3 for i in range(n):
4     li.append(int(input()))
5 li.sort()
6 res=all(i<j for i,j in zip(li,li[1:]))
7 print(res)

```

	Input	Expected	Got	
✓	7 1 2 3 0 4 5 6	True	True	✓



	Input	Expected	Got	
✓	4 2 1 0 -1	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1

2

2

3

4

Output:

1 2 3 4

Example Input:

6

1

1

2

2

3

3

Output:

1 2 3

**For example:**

Input	Result
5 1 2 2 3 4	1 2 3 4
6 1 1 2 2 3 3	1 2 3

**Answer:** (penalty regime: 0 %)

```

1 n=int(input())
2 li=[int(input()) for i in range(n)]
3 x=set(li)
4 y=list(x)
5 y.sort()
6 z=' '.join(map(str,y))

```

```
5     .join('mp\set', 'y',  
7     | print(z)
```

	Input	Expected	Got	
✓	5 1 2 2 3 4	1 2 3 4	1 2 3 4	✓
✓	6 1 1 2 2 3 3	1 2 3	1 2 3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Consider a program to insert an element / item in the sorted array. Complete the logic by filling up required code in editable section. Consider an array of size 10. The eleventh item is the data is to be inserted.

## Sample Test Cases

## Test Case 1

## Input

1  
3  
4  
5  
6  
7  
8  
9  
10  
11  
2

## Output

ITEM to be inserted:2  
After insertion array is:

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11

## Test Case 2

## Input

11  
22  
33  
55  
66  
77  
88  
99  
110  
120  
44

## Output

ITEM to be inserted:44  
After insertion array is:

11  
22  
33  
44

55  
66  
77  
88  
99  
110  
120

**Answer:** (penalty regime: 0 %)

```

1 | li=[int(input()) for i in range(10)]
2 |
3 | n=int(input())
4 | li.append(n)
5 | li.sort()
6 | print(f'ITEM to be inserted:{n}')
7 | print('After insertion array is:')
8 | for i in li:
9 |     print(i)

```

	Input	Expected	Got	
✓	1 3 4 5 6 7 8 9 10 11 2	ITEM to be inserted:2 After insertion array is: 1 2 3 4 5 6 7 8 9 10 11	ITEM to be inserted:2 After insertion array is: 1 2 3 4 5 6 7 8 9 10 11	✓
✓	11 22 33 55 66 77 88 99 110 120 44	ITEM to be inserted:44 After insertion array is: 11 22 33 44 55 66 77 88 99 110 120	ITEM to be inserted:44 After insertion array is: 11 22 33 44 55 66 77 88 99 110 120	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

## Question 7

Correct

Mark 1.00 out of 1.00

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the  $p^{\text{th}}$  element of the [list](#), sorted ascending. If there is no  $p^{\text{th}}$  element, return 0.

**Example**

$n = 20$

$p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if  $p = 3$ , then 4 is returned. If  $p > 6$ , 0 would be returned.

**Constraints**

$1 \leq n \leq 10^{15}$

$1 \leq p \leq 10^9$

The first line contains an integer  $n$ , the number to factor.

The second line contains an integer  $p$ , the 1-based index of the factor to return.

**Sample Case 0****Sample Input 0**

10

3

**Sample Output 0**

5

**Explanation 0**

Factoring  $n = 10$  results in {1, 2, 5, 10}. Return the  $p = 3^{\text{rd}}$  factor, 5, as the answer.

**Sample Case 1****Sample Input 1**

10

5

**Sample Output 1**

0

**Explanation 1**

Factoring  $n = 10$  results in {1, 2, 5, 10}. There are only 4 factors and  $p = 5$ , therefore 0 is returned as the answer.

**Sample Case 2****Sample Input 2**

1

1

**Sample Output 2**

1

**Explanation 2**

Factoring  $n = 1$  results in {1}. The  $p = 1^{\text{st}}$  factor of 1 is returned as the answer.

**For example:**

Input	Result
10 3	5
10 5	0

Input	Result
1 1	1

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 p=int(input())
3 li=[]
4 for i in range(1,n+1):
5     if(n%i==0):
6         li.append(i)
7 if(p<=len(li)):
8     print(li[p-1])
9 else:
10    print(0)
```

	Input	Expected	Got	
✓	10 3	5	5	✓
✓	10 5	0	0	✓
✓	1 1	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

## Sample Test Cases

## Test Case 1

## Input

7  
23  
45  
23  
56  
45  
23  
40

## Output

23 occurs 3 times  
45 occurs 2 times  
56 occurs 1 times  
40 occurs 1 times

**Answer:** (penalty regime: 0 %)

```

1 n=int(input())
2 li=[int(input()) for i in range(n)]
3 fin_li=[]
4 li2=[]
5 for i in li:
6     if i not in li2:
7         li2.append(i)
8 for i in li2:
9     x=li.count(i)
10    print(f'{i} occurs {x} times')
```

	Input	Expected	Got	
✓	7 23 45 23 56 45 23 40	23 occurs 3 times 45 occurs 2 times 56 occurs 1 times 40 occurs 1 times	23 occurs 3 times 45 occurs 2 times 56 occurs 1 times 40 occurs 1 times	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.





Question 9

Correct

Mark 1.00 out of 1.00

Output is a merged array without duplicates.

**Input Format**

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

**Output Format**

Display the merged array

**Sample Input 1**

5  
1  
2  
3  
6  
9  
4  
2  
4  
5  
10

**Sample Output 1**

1 2 3 4 5 6 9 10

**Answer:** (penalty regime: 0 %)

```
1 n=int(input())
2 li1=[int(input()) for i in range(n)]
3 y=int(input())
4 li2=[int(input()) for i in range(y)]
5 finLi=[]
6 for i in li1:
7     if i not in finLi:
8         finLi.append(i)
9 for i in li2:
10    if i not in finLi:
11        finLi.append(i)
12 finLi.sort()
13 x=' '.join(map(str,finLi))
14 print(x)
```

	Input	Expected	Got	
✓	5 1 2 3 6 9 4 2 4 5 10	1 2 3 4 5 6 9 10	1 2 3 4 5 6 9 10	✓
✓	7 4 7 8 10 12 30 35 9 1 3 4 5 7 8 11 13 22	1 3 4 5 7 8 10 11 12 13 22 30 35	1 3 4 5 7 8 10 11 12 13 22 30 35	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

`arr=[1,2,3,4,6]`

- the sum of the first three elements,  $1+2+3=6$ . The value of the last element is 6.
- Using zero based indexing, `arr[3]=4` is the pivot between the two subarrays.
- The index of the pivot is 3.

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq \text{arr}[i] \leq 2 \times 10^4$ , where  $0 \leq i < n$
- It is guaranteed that a solution always exists.

The first line contains an integer  $n$ , the size of the array `arr`.

Each of the next  $n$  lines contains an integer, `arr[i]`, where  $0 \leq i < n$ .

Sample Case 0

Sample Input 0

4  
1  
2  
3  
3

Sample Output 0

2

Explanation 0

- The sum of the first two elements,  $1+2=3$ . The value of the last element is 3.
- Using zero based indexing, `arr[2]=3` is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

3  
1  
2  
1

Sample Output 1

1

Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, `arr[1]=2` is the pivot between the two subarrays.
- The index of the pivot is 1.

**For example:**

Input	Result
4 1 2 3 3	2
3 1 2 1	1

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 x=[int(input()) for i in range(n)]
3
4 a=sum(x)
5 l=0
6 k=a-x[0]
7 for i in range(1,n):
8     l+=x[i-1]
9     k-=x[i]
10 if l==k:
11     print(i)
12     break
```

	Input	Expected	Got	
✓	4 1 2 3 3	2	2	✓
✓	3 1 2 1	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ Week6\_MCQ

Jump to...

Tuples ▶