



Basic of Networking


VISHWANATH M S
VISHWACLOUDLAB.COM

ISO/OSI Reference Model



Layered Packet Format

- Nth layer control info is passed as N-1th layer data.




Major Concepts in Network

- **Same Network – Switch**
- **Different Network -- Router**

- **PC – Traffic Generator**
 - Switch and Router **DOES NOT generate** Traffic, they only **manage** it

- **IP Address** – Its an tool used by PC for sending packets from Source to Destination

Network Diagram



Basic Networking continued.....

Two types of IP address

IPv4 – 32 bit

IPv6 – 128 bit

Binary to Decimal Conversation

0000 0000 → 0 – Min Value

1111 1111 → 255 – Max Value

IPv4 address format

X	.X	.X	.X
8bit	8bit	8bit	8bit
1 st Octet	2 nd Octet	3 rd Octet	4 th Octet
00000000.00000000.00000000.00000000			

Binary to Decimal Conversion & ViceVersa

Find Decimal value of below Binary octets

Eg1: - 10010001

Eg2: - 11100011

2 ⁷	2 ⁶	2 ⁵	2 ⁴	2 ³	2 ²	2 ¹	2 ⁰
128	64	32	16	8	4	2	1

Eg1: - 1*128 + 0*64 + 0*32 + 1*16 + 0*8 + 0*4 + 0*2 + 1*1 → 128+16+1 = 145

Eg2: - 1 1 1 0 0 0 1 1 → 128+64+32+2+1 = 227

Eg3: - 1 1 0 0 1 1 0 0 → ???

Eg4: - 1 0 1 0 1 0 1 0 → ???

Slide 7

v1

binary to Decimal conversion

vishwanath.murthy@gmail.com, 1/30/2019

IP address V4

An IP address is a 32-bit address and are unique.

The address space of IPv4 is 2^{32} or 4,294,967,296.

11100111 11011011 10001011 01101111

231.219.139.111

IP Address IPV4

CLASS A – 0.0.0.0 to 127.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS B – 128.0.0.0 to 191.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS C – 192.0.0.0 to 223.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS D – 224.0.0.0 to 239.255.255.255 --- USED FOR MULTICAST

CLASS E – 240.0.0.0 to 255.255.255.255 --- USED FOR RESEARCH

Class A - 00000000 to 01111111

Class B - 10000000 to 10111111

Class C - 11000000 to 11011111

Class D - 11100000 to 11101111

Class E - 11110000 to 11111111

IP Address Classes

RFC 791 defines the IP protocol.

	First byte	Second byte	Third byte	Fourth byte
Class A	0 to 127			
Class B	128 to 191			
Class C	192 to 223			
Class D	224 to 239			
Class E	240 to 255			

Note: -- The valid addresses in class A start from 1 to 126. Network 0.0.0.0 is defined for use as a broadcast address and 127.0.0.0 is reserved for use as loopback address.

Default Subnet Mask

Class A – 255.0.0.0 – 11111111.00000000.00000000.00000000 -- /8

Class B – 255.255.0.0 – 11111111. 11111111.00000000.00000000 -- /16

Class C – 255.255.255.0 – 11111111. 11111111. 11111111.00000000 -- /24

CLASS A – 0.0.0.0 to 127.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS B – 128.0.0.0 to 191.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS C – 192.0.0.0 to 223.255.255.255 --- USED FOR PUBLIC NETWORK, UNICAST TRAFFIC

CLASS D – 224.0.0.0 to 239.255.255.255 --- USED FOR MULTICAST

CLASS E – 240.0.0.0 to 255.255.255.255 --- USED FOR RESEARCH

Roles of Router, Switch and PC

- **Router** → Determines the path to the different destination Network
- **Switch** → Transports the traffic from SRC and DST on **same network** on HIGH SPEED
- **PC** → Determines whether the SRC IP and DST IP are **SAME** or **DIFFERENT** network.

SRC – Source

DST -- Destination

PC determines whether Src IP and Dst Ip are in same or Diff network

PC does an “BINARY AND” operation between

SRC IP BINARY AND SRC SUBNETMASK

&

DST IP BINARY AND SRC SUBNETMASK

0 AND 0 = 0

0 AND 1 = 0

1 AND 0 = 0

1 AND 1 = 1

PC - Operations

Example:1 Src IP – 10.40.30.20 and Dst IP – 10.80.10.30

Src IP **AND** Src SubnetMask

00001010. 00101000.00011110.00010100 → 10.40.30.20 – Src IP

11111111. 00000000.00000000.00000000 → 255.0.0.0 -- Src Subnet mask

00001010. 00000000.00000000.00000000 → 10.0.0.0

10.0.0.0/8 is the Network ID for “10.40.30.20”

DST IP AND Src SubnetMask

00001010. 01010000.00001010.00011110 → 10.80.10.30 – DST IP

11111111. 00000000.00000000.00000000 → 255.0.0.0 -- SRC Subnet Mask

00001010. 00000000.00000000.00000000 → 10.0.0.0 ← Result

10.0.0.0/8 is the Network ID for “10.80.10.30”

	First byte
Class A	0 to 127
Class B	128 to 191
Class C	192 to 223
Class D	224 to 239
Class E	240 to 255

0 AND 0 = 0

0 AND 1 = 0

1 AND 0 = 0


1 AND 1 = 1

CONCLUSION of AND operation:

Since the network ID's of the SRC IP and DST IP are the same they are in the **same network**.

Traffic flow for Same Network

- PC1: Requests for MAC ID of the PC2 to the switch
- SW01: Does an Broadcast for the first time only
- PC2: Replies to the broadcast with its MAC ID
- SW01: passess the info to PC1
- PC1: Send data to PC2.
- PC2: Replies to the data to PC1



PC - Operations

Example:2 Src IP – 10.40.30.20 and Dst IP – 11.81.11.31
Src IP AND Src SubnetMask

00001010. 00101000.00011110.00010100 – 10.40.30.20

11111111. 00000000.00000000.00000000 – 255.0.0.0

00001010. 00000000.00000000.00000000 – 10.0.0.0

Statement → 10.0.0.0/8 is the Network ID for “10.40.30.20”

DST IP AND Src SubnetMask

00001011. 01010001.00001011.00011111 – 11.81.11.31

11111111. 00000000.00000000.00000000 – 255.0.0.0

00001011. 00000000.00000000.00000000 – 11.0.0.0

Statement → 11.0.0.0/8 is the Network ID for “11.81.11.31”

	First byte
Class A	0 to 127
Class B	128 to 191
Class C	192 to 223
Class D	224 to 239
Class E	240 to 255

Results:

The Network ID's are different, so they are in different network.

PC - Operations

Example:3 Src IP – 10.40.30.20 and Dst IP – 172.100.10.30

Src IP AND Src SubnetMask

00001010. 00101000.00011110.00010100 → 10.40.30.20

11111111. 00000000.00000000.00000000 → 255.0.0.0

00001010. 00000000.00000000.00000000 → 10.0.0.0

10.0.0.0/8 is the Network ID for “10.40.30.20”

DST IP AND Src SubnetMask

10101100. 01100100.00001010.00011110 → 172.100.10.30

11111111. 00000000.00000000.00000000 → 255.0.0.0

10101100. 00000000.00000000.00000000 → 172.0.0.0/8

172.0.0.0/8 is the Network ID for “172.100.10.30”

	First byte
Class A	0 to 127
Class B	128 to 191
Class C	192 to 223
Class D	224 to 239
Class E	240 to 255

Results:

The Network ID's are different, so they are in different network.

PC – Operations – Example -4

Example:4 Src IP **172.100.10.30** and DST IP – **192.168.25.20**

Since the SRC ip is Class B , we have to consider Class B subnet mask

Source

172.100.10.30 → SRC IP

255.255.0.0 → SRC Subnet Mask

172.100.0.0/16

Destination


192.168.25.20 → DST IP

255.255.0.0 → SRC Subnet Mask


192.168.0.0/16

Traffic flow for Different Network

- PC1: Requests for MAC ID of the default Router(Default Gateway)
- SW01: Does Broadcast for the first time to get the MAC ID of the Router interface
- RT: Replies to the Broadcast with its MAC ID
- SW01: Replies to the PC1 with MAC ID of the Router
- PC1: Send's Packet to RT to forward it to the DST network (PC3)
- RT: Checks the Routing Table for the forwarding of the packet.
- RT: Sends an Broadcast request to the switch (SW02) to get the MAC ID of the PC3 for first time
- PC3: replies the Broadcast
- RT: Forwards the request to the PC3.



Netid and Hostid



In classful addressing, an IP address in class A, B and C is divided into two parts netid and hostid. These parts are varying length, depending on the class of the address.

Conclusion of the AND operation

- If the 1st Octet in CLASS A is same for both SRC IP and DST IP , then they are in the same network, if not they are in Different Network.
- If the 1st & 2nd Octet in CLASS B is same for both SRC IP and DST IP , then they are in the same network, if not they are in Different Network.
- If the 1st, 2nd & 3rd Octet in CLASS C is same for both SRC IP and DST IP , then they are in the same network, if not they are in Different Network.

Some Example

20.30.40.50 & 20.20.30.10 -- ????

They are in the CLASS-A network and the 1st octet is same, means they are in the same N/W.

200.30.10.10 & 200.31.10.20 -- ????

They are in Class-c and the 1st 3 Byte is NOT same. – Diff Network

150.140.130.120 & 150.140.120.130 -- ????

They are in the Class-B and 1st 2 Octet are SAME. Hence they are in same Network

First and Last Usable IP & Broadcast IP

Src IP AND Src SubnetMask -- 10.40.30.20 AND 255.0.0.0

00001010. 00101000.00011110.00010100

11111111. 00000000.00000000.00000000

00001010. 00000000.00000000.00000000

10.0.0.0/8 is the Network ID for "10.40.30.20"


First IP –NW ID → 00001010.00000000.00000000.00000000 – 10.0.0.0

First Usable IP → 00001010.00000000.00000000.00000001 – 10.0.0.1

Last Usable IP → 00001010.11111111.11111111.11111110 – 10.255.255.254

Broadcast IP → 00001010.11111111.11111111.11111111 – 10.255.255.255

Summary




IPV4
Class A -- 0.0.0.0 to 127.255.255.255
Class B -- 128.0.0.0 to 191.255.255.255
Class C -- 192.0.0.0 to 223.255.255.255
Class D -- 224.0.0.0 to 239.255.255.255 -- used for Multicast
Class E -- 240.0.0.0 to 255.255.255.255 -- Used for Research and Military

src -- 10.40.50.61 and DST -- 10.190.200.3

IP ADD AND subnet MASK

	SRC	DST
10.40.50.61 AND 255.0.0.0	00001010.40.50.61 11111111.0.0.0 ----- 00001010.0.0.0 10.0.0.0/8 -- N/w ID	00001010.190.200.3 11111111.0.0.0 ----- 00001010.0.0.0 10.0.0.0/8 -- N/W ID



Default Subnet MASK

C-A 255.0.0.0 -- 11111111.00000000.00000000.00000000 -- /8
1st octet. 2nd . 3rd . 4th
C-B -- 255.255.0.0 -- 11111111.11111111.00000000.00000000 -- /16
C-C -- 255.255.255.0 -- 11111111.11111111.11111111.00000000 -- /24

8 bit == Network ID
24 bits = Host ID. -- 2^{24} == 16 M

Problem

Scenario 1 .

Customer 1 wants 5000 IP's in a single network

Customer 2 wants 10000 IP's in a single network

Number of Networks and Hosts Per each Network

CLASS A ---- NNNNNNNN.HHHHHHHH.HHHHHHHH.HHHHHHHH

Subnet Mask - 255 . 0 . 0 . 0

$2^8 = 0-126$

$2^{24} = 16,777,216$

CLASS B ---- NNNNNNNN.NNNNNNNN.HHHHHHHH.HHHHHHHH

SubnetMask - 255 . 255 . 0 . 0

$2^{16} = (128-191) * 256 = 16K$

$2^{16} = 65,536$

CLASS C ---- NNNNNNNN.NNNNNNNN.NNNNNNNN.HHHHHHHH

subnetMask - 255 . 255 . 255 . 0

$2^{24} = (192-223) * 256 * 256 = 2M$

$2^8 = 256$

H == HOST == IP ADDRESS == VM ==
Laptop == Desktop

Solution to the Problem

Scenario 1 .

Customer 1 wants 5000 IP's in a single network

Customer 2 wants 10000 IP's in a single network

Solution.

Provide each Customer with a CLASS B network.

140.140.0.0/16

140.141.0.0/16

Problem Due to IPV4 Classes

- In networking world, if we need to control traffic , it can be done in an controlled way Between DIFFERENT NETWORK.
- It's very very TOUGH to control traffic within the same network.
- Means Class A and B are having huge Amount of HOSTS in each network, and we would start wasting IP's by assign each network to individual Customers.
- Solution to this Problem is **“SUBNETTING”**