



CitizenMCP

Greek Government Transparency & Open Data, as an MCP Service

A public, hosted service that gives AI assistants and applications direct, structured access to Greece's official transparency register (Diavgeia) and national open-data catalog (data.gov.gr) — no accounts, no paperwork, no scraping.

Document type

Service Report — Client Overview

Prepared for

Prospective & existing clients

Date

August 2026

Service endpoint

`citizen-mcp.nickdandis96.workers.dev`

Contents

1 Executive Summary

2 What CitizenMCP Is

3 Data Sources & Coverage

4 Full Endpoint / Tool Reference

5 Access, Authentication & Fair Use

6 Technical Architecture

7 Infrastructure & Where It Runs

8 Reliability & Verification

9 Roadmap

A companion product, **BusinessMCP**, covers business-registry, e-invoicing, and labor data for commercial/professional use cases and is documented in a separate report.

1. Executive Summary

CitizenMCP is a hosted, always-on server that speaks the **Model Context Protocol (MCP)** — the emerging open standard that lets AI assistants (Claude, and any other MCP-compatible client) call out to external tools and data sources during a conversation. Point an MCP-compatible assistant at CitizenMCP's web address, and it gains the ability to search, retrieve, and reason over two official Greek government data sources in real time, with no manual copy-pasting, screen-scraping, or file exports.

18

TOOLS EXPOSED

2

DATA SOURCES

0

ACCOUNTS
REQUIRED

24/7

AVAILABILITY

In one sentence: CitizenMCP turns Diavgeia (Greece's public-sector decision transparency register) and data.gov.gr (the national open-data catalog) into something an AI assistant can query directly and conversationally, instead of a human having to search government portals by hand.

Who it's for

- **Journalists & researchers** tracking public procurement, ministerial decisions, or budget acts.
- **Civic-tech and transparency organizations** building tools or dashboards on top of public-sector data.
- **Analysts and data scientists** who want to pull open datasets (statistics, registries, spatial/administrative data) straight into an AI-assisted workflow.
- **Anyone building an AI agent or application** that needs to answer questions grounded in verifiable Greek public-sector data rather than the model's general knowledge.

Why it matters

Diavgeia and data.gov.gr are both legally mandated, authoritative sources — every Greek public-sector decision above a certain threshold must be published to Diavgeia with a unique tracking code (ΑΔΑ) to be valid, and data.gov.gr is the government's own open-data clearinghouse. CitizenMCP doesn't replace these systems; it makes them reachable by an AI agent in the same structured way a human would use their web UI — but faster, and composable into larger automated workflows.

2. What CitizenMCP Is

The short version

CitizenMCP is a small piece of hosted infrastructure — a single web address — that an AI assistant connects to the same way it would connect to any other capability. Once connected, the assistant can call a fixed set of well-defined actions ("tools"), such as "search Diavgeia decisions issued by the Ministry of Finance in the last month" or "find open datasets about renewable energy production." The service does the work of talking to the underlying government API, and returns clean, structured results back to the assistant.

Why MCP, specifically

The Model Context Protocol is a standard, not a proprietary integration. Any MCP-compatible client — Claude, other AI assistants, custom agent frameworks — can connect to CitizenMCP using the same configuration format, without bespoke integration work per client. This is the same reason USB replaced a different cable for every peripheral: one interface, many consumers.

What it is not

- It is not a data warehouse or a copy of government data — every call is a live pass-through to the official source, so results are always current.
- It does not require Diavgeia or data.gov.gr accounts, API keys, or registration for normal use — both underlying sources are public by law.
- It is not scoped to citizen/transparency data only forever — it is one of two currently-available domain bundles (the other, **BusinessMCP**, covers business/tax data) in a product line designed to grow by adding further domain bundles rather than becoming one all-purpose server.

3. Data Sources & Coverage

3.1 Diavgeia Open · No key required

What it is: Diavgeia ("Δι@ύγεια", meaning "transparency/clarity") is the Greek government's official decision-publication register, in continuous operation for roughly 15 years. By law, every administrative act, decision, procurement award, appointment, or budget commitment issued by a Greek public body — ministries, municipalities, hospitals, universities, state agencies — must be uploaded to Diavgeia and assigned a unique tracking code (**ΑΔΑ**) to take legal effect. It is the single richest, most complete public record of what the Greek state actually does, day to day.

What CitizenMCP exposes: the full read surface of Diavgeia's public API — full-text and filtered decision search, individual decision lookup and revision history, the organizational directory (ministries down to individual units), signer/official lookup, and the underlying classification taxonomy (decision types, subject dictionary, official positions) needed to build precise queries. See the full list in Section 4.

3.2 data.gov.gr (CKAN Open Data Catalog) Open · Optional token

What it is: Greece's national open-data portal, run on the widely-used CKAN platform (the same software underpinning open-data portals in the UK, US, and EU institutions). It currently catalogs roughly **22,500 datasets and 87,000 downloadable resources from 482 publishing organizations** — everything from municipal budgets to environmental measurements to statistical series.

What CitizenMCP exposes: catalog search and dataset detail lookup, plus a capability that goes beyond simply pointing at a file: `ckan_get_resource_data` downloads a dataset's actual CSV/XLS/XLSX resource and parses it into rows on the fly, so an AI assistant can analyze the real numbers inside a spreadsheet — not just its title and description — without a human ever having to open Excel.

Note on scope: Geodata.gov.gr (the national geospatial/WMS service) was evaluated for inclusion but dropped from this bundle in August 2026 after repeated connectivity checks found the service unreachable, and because raw GeoJSON is a poor fit for a conversational interface even when the service is up. It can be reconsidered if the upstream service becomes reliably available.

4. Full Endpoint / Tool Reference

Every row below is a distinct callable action exposed to a connected AI assistant, matching what a developer would call an "endpoint" in a conventional REST API.

4.1 Diavgeia — 15 tools

Tool	Purpose
<code>diavgeia_search_decisions</code>	Advanced filtered search over published decisions (organization, unit, decision type, date range, signer, subject, etc.)
<code>diavgeia_simple_search_decisions</code>	Free-text search across decisions, for quick lookups without building structured filters
<code>diavgeia_get_decision</code>	Retrieve a single decision by its AΔA tracking code, with full metadata and document links
<code>diavgeia_get_decision_version_log</code>	Retrieve the revision/correction history of a published decision
<code>diavgeia_list_decision_types</code>	List the full taxonomy of decision types (e.g. procurement award, appointment, budget commitment)
<code>diavgeia_get_decision_type_details</code>	Get the detailed definition and required fields for one decision type
<code>diavgeia_search_organizations</code>	Search the directory of public-sector organizations
<code>diavgeia_get_organization</code>	Retrieve a single organization's summary record
<code>diavgeia_get_organization_details</code>	Retrieve full profile details for an organization
<code>diavgeia_get_organization_units</code>	List the sub-units belonging to an organization
<code>diavgeia_get_unit</code>	Retrieve a single organizational unit's record
<code>diavgeia_get_signer</code>	Look up a signing official's record
<code>diavgeia_list_positions</code>	List official positions/roles used in the signer directory
<code>diavgeia_get_dictionary</code>	Retrieve subject/keyword dictionary entries used to classify decisions
<code>diavgeia_list_search_terms</code>	List valid search term/filter values for building precise queries

4.2 data.gov.gr / CKAN — 3 tools

Tool	Purpose
------	---------

ckan_search_datasets	Free-text search across the ~22,500-dataset open-data catalog
ckan_get_dataset	Retrieve a dataset's full metadata and list of downloadable resources
ckan_get_resource_data	Download a CSV/XLS/XLSX resource and parse it into paginated rows for direct analysis (up to 500 rows per page)

5. Access, Authentication & Fair Use

5.1 No accounts, no keys

Both Diavgeia and data.gov.gr are open-read government services by law and by design, so CitizenMCP requires **no login, API key, or registration** for normal use. A client simply points an MCP configuration at the service's public web address:

```
{
  "mcpServers": {
    "citizen-mcp": {
      "url": "https://citizen-mcp.nickdandis96.workers.dev"
    }
  }
}
```

An optional, free data.gov.gr token can be supplied on the server side to raise CKAN's rate ceiling for high-volume use — this is a deployment-level configuration choice, not something an individual user needs to obtain.

5.2 Fair-use rate limiting

To keep the public service responsive for everyone, requests are limited to **30 per 60 seconds per caller IP address**. This is enforced at Cloudflare's network edge — before a request even reaches the application logic — so an over-limit caller gets a fast, cheap rejection rather than tying up server resources. This ceiling is generous for interactive, conversational use; it is intended to prevent bulk-scraping abuse, not to constrain normal usage.

6. Technical Architecture

6.1 Request lifecycle

Each incoming HTTP request follows a fixed pipeline:

1. **CORS preflight** handling, so any browser-based MCP client can connect directly without a proxy.
2. **Path validation** — only the root path serves the MCP protocol; anything else (including OAuth-discovery probes some clients send speculatively) returns a clean 404 rather than a response that could be misread as "this server requires login."
3. **Edge rate-limit check** against the caller's IP.
4. **A fresh, isolated MCP server instance** is constructed for that single request and both tool sets (Diavgeia, CKAN) are registered onto it.
5. The request is handed to the **MCP Streamable HTTP transport**, which parses the JSON-RPC-based MCP message, dispatches to the requested tool, and streams the structured result back.
6. CORS response headers are applied and the response is returned.

Stateless by design: No session state is kept between requests. Every call is self-contained, which keeps the service simple to reason about, trivially horizontally scalable, and free of session-affinity or "which server has my session" concerns.

6.2 Shared core library

CitizenMCP's tool logic is not implemented directly in the worker — it is imported from a shared, internal core library (`@my-mcp/core`) that also powers the companion BusinessMCP product. This gives three concrete benefits:

- **One client per government service, reused everywhere it's needed** — Diavgeia's client code, for example, is shared verbatim between CitizenMCP and BusinessMCP rather than duplicated.
- **A single, consistent HTTP resilience layer** (see 6.3) underlies every government API call, so improvements to retry/timeout behavior benefit every tool at once.
- **Strict input validation** on every tool call via schema validation (Zod), so malformed requests are rejected with a clear error before any government API is even contacted.

6.3 Resilient outbound networking

Every outbound call to Diavgeia or data.gov.gr goes through a shared HTTP client with production-grade resilience behavior, not a bare `fetch()`:

- **Timeouts** — 15 seconds by default, so a slow upstream never hangs a request indefinitely.

- **Automatic retry with backoff** — transient failures (HTTP 429 "too many requests" and 5xx server errors) are retried up to twice with exponential backoff, honoring the server's own `Retry-After` header when it provides one.
- **Normalized error reporting** — any failure that isn't recovered is surfaced to the calling assistant as a clear, typed error including the failing URL, HTTP status, and a snippet of the response body, rather than an opaque stack trace.

6.4 Protocol & transport

CitizenMCP speaks MCP's **Streamable HTTP** transport — the current standard transport for remote MCP servers, superseding the older Server-Sent-Events-only approach. The implementation (`WebStandardStreamableHTTPServerTransport`) is built entirely on Web Standard APIs (the same `Request` / `Response` primitives used in browsers), which is what allows the exact same code to run unmodified on Cloudflare Workers, and, if ever needed, on Node.js, Deno, or Bun.

6.5 Codebase & quality practices

- Written in TypeScript with strict type-checking across the whole codebase.
- Automated test suites (Vitest) cover the shared HTTP client and each service client, including fixture-based tests against captured real API responses.
- Linting and formatting are enforced repo-wide (ESLint + Prettier) to keep the codebase consistent as it grows.

7. Infrastructure & Where It Runs

7.1 Cloudflare Workers

CitizenMCP is deployed as a **Cloudflare Worker** — code that runs in Cloudflare's global edge network rather than on a single server in a single data center. Practically, this means:

- **Global reach with low latency** — a request is handled by the Cloudflare location closest to the caller, out of Cloudflare's 300+ point-of-presence network, rather than always routing back to one origin server.
- **No idle server cost or cold-VM startup** — Workers run in lightweight V8 isolates that start in milliseconds, not the full container/VM boot time of traditional server hosting, and there is no idle server sitting around between requests.
- **Automatic scaling** — the platform scales to handle concurrent load without any manual capacity planning on our part.

7.2 Live endpoint

Property	Value
Production URL	<code>https://citizen-mcp.nickdandis96.workers.dev</code>
Transport	MCP Streamable HTTP (single endpoint, root path)
Rate limiting	Cloudflare native edge rate-limit binding
Deployment tooling	Wrangler (Cloudflare's official CLI)

7.3 Deployment model

Deployments are performed via Cloudflare's `wrangler` CLI against the account holding the Worker. Configuration — rate limit thresholds, the worker's name, and platform compatibility settings — lives in a version-controlled `wrangler.toml` file alongside the code, so infrastructure configuration is reviewed and tracked the same way as application code.

8. Reliability & Verification

Before being wired into the service, each upstream government API is independently checked for live reachability from an unrestricted network — not just assumed correct from documentation. As of the most recent verification pass:

Source	Status
Diavgeia	Live and confirmed reachable
data.gov.gr (CKAN)	Live and confirmed reachable — 200 OK on live queries against the production catalog

The shared HTTP client's retry-and-backoff behavior (Section 6.3) further absorbs the kind of brief transient errors that any public government API occasionally produces, so short-lived upstream hiccups are handled automatically rather than surfacing as failures to the end user.

9. Roadmap

The product strategy is to grow by adding further **domain bundles** — additional focused MCP servers, each covering one coherent data domain — rather than folding unrelated services into CitizenMCP itself. This keeps each server's tool set focused and relevant to the clients who install it.

- **Ktimatologio (Hellenic Cadastre) open data** — identified as a strong candidate for a future transparency/open-data addition (land parcel and real-estate registry data), currently blocked on clarifying an access restriction on the upstream service.
- **Geodata.gov.gr** — will be reconsidered for inclusion if the upstream geospatial service becomes reliably reachable.
- Ongoing hardening of retry/error-handling behavior as real-world usage surfaces new edge cases in the upstream APIs.

For business, tax, and labor data, see the companion **BusinessMCP** service report.