



BusinessMCP

Greek Business, Tax & Labor Data, as an MCP Service

A public, hosted service that gives AI assistants and applications direct, structured access to Greece's business registry (ΓΕΜΗ), e-invoicing platform (myDATA), labor system (Ergani), and procurement transparency register (Diavgeia) — with a secure model for handling each service's very different credential requirements.

Document type

Service Report — Client Overview

Prepared for

Prospective & existing clients

Date

August 2026

Service endpoint

`business-mcp.nickdandis96.workers.dev`

Contents

1 Executive Summary

2 What BusinessMCP Is

3 Data Sources & Coverage

4 Full Endpoint / Tool Reference

5 Authentication Models & Credential Security

6 Rate Limiting

7 Technical Architecture

8 Infrastructure & Where It Runs

9 Reliability, Verification & Scope Boundaries

10 Roadmap

A companion product, **CitizenMCP**, covers transparency and open-data use cases and is documented in a separate report.

1. Executive Summary

BusinessMCP is a hosted, always-on server that speaks the **Model Context Protocol (MCP)** — the open standard that lets AI assistants call out to external tools and data sources during a conversation. Point an MCP-compatible assistant at BusinessMCP's web address, and it gains the ability to look up company registry records, retrieve and submit e-invoicing data, query labor/employment records, and search public procurement decisions — the core data surfaces a Greek business, accountant, or vendor typically needs, in one place.

35

TOOLS EXPOSED

4

DATA SOURCES

3

AUTH MODELS,
HANDLED
DISTINCTLY

24/7

AVAILABILITY

In one sentence: BusinessMCP lets an AI assistant look up a company's registry record, check its e-invoicing and tax filings, review labor/employment data, and cross-reference public procurement decisions — using each source's real, official system, with credentials handled securely and never hard-coded or shared beyond their intended scope.

Who it's for

- **Accountants and bookkeepers** who need fast access to myDATA e-invoicing and VAT/E3 data without leaving their workflow.
- **Businesses and their software vendors** needing to submit invoices, classifications, and payment-method data to AADE (the Greek Tax Authority) programmatically.
- **Due-diligence, credit, and compliance teams** looking up a counterparty's ΓΕΜΗ registry status, legal form, and filed documents before doing business with them.
- **Employers, HR teams, and payroll providers** working with Ergani's labor-system data.
- **Anyone building an AI agent** for the Greek business/finance domain that needs grounded, official data rather than the model's general knowledge.

2. What BusinessMCP Is

The short version

BusinessMCP is a single piece of hosted infrastructure that an AI assistant connects to like any other capability. Once connected, it can call a fixed set of well-defined actions — "look up this company by tax number," "retrieve this quarter's issued invoices," "submit this invoice to myDATA," "list Ergani's available services" — against the real, official Greek systems, and return clean, structured results.

Why this is harder than CitizenMCP

Unlike the fully-open transparency data in the companion CitizenMCP product, business and tax data sits behind three genuinely different access-control models — a fully open register, a single shared operator-held key, and credentials that belong to each individual business. BusinessMCP is built to keep those three models explicit and separately handled rather than forcing them into one generic "auth" abstraction, which is what keeps the security properties of each one legible and auditable. Section 5 covers this in full.

What it is not

- It does not hold or have access to your Taxisnet password, your ΓΕΜΗ account, or any credential BusinessMCP itself doesn't need to complete the specific call you ask for.
- It is not a data warehouse — every call is a live pass-through to the official source.
- It does not currently expose Ergani's write operations (work-card submission, schedule declarations) — a deliberate scope decision explained in Section 9, not an oversight.

3. Data Sources & Coverage

3.1 ΓΕΜΗ — Business Registry

Shared operator key

What it is: ΓΕΜΗ (Γενικό Εμπορικό Μητρώο, the General Commercial Registry) is Greece's official business registry — the authoritative record of a company's legal existence, legal form, registration number, status (active/dissolved/etc.), and filed corporate documents.

What BusinessMCP exposes: search by tax number (ΑΦΜ), full company record lookup, retrieval of a company's filed document set, and the registry's reference metadata (legal types, company statuses, and registry offices) needed to interpret results correctly.

3.2 myDATA — e-Invoicing & e-Books

Your own credentials

What it is: myDATA is AADE's (the Greek Tax Authority's) mandatory e-invoicing and digital books platform. Greek businesses are legally required to transmit invoice data through it, and it is the authoritative source for a business's own income, expense, VAT, and E3 (profit/loss classification) records as recorded with the tax authority.

What BusinessMCP exposes: the full ERP-facing surface of myDATA — retrieving issued/received/transmitted documents, income/expense/VAT/E3 summaries, submitting invoices and their income/expense classifications, recording payment methods, and cancelling invoices. This is the single largest and highest-value integration in the service, since myDATA compliance is mandatory for every Greek business.

3.3 Ergani — Labor & Employment

Your own credentials

What it is: Ergani is the Ministry of Labour's digital work-card and employment declaration system, used for hiring/termination declarations, work schedules, and related labor-law compliance records.

What BusinessMCP exposes today: the read-only services catalog. Write operations (submitting a work card, declaring a schedule) are intentionally not yet exposed — see Section 9.

3.4 Diavgeia — Procurement Transparency

Open · No key required

What it is: the same public-sector decision-transparency register described in the CitizenMCP report — every public procurement award, contract, and administrative decision above a legal threshold is published here with a unique tracking code (ΑΔΑ). It is included in BusinessMCP because procurement decisions are directly relevant to vendors, contractors, and anyone tracking public-sector business opportunities or counterparties — a genuinely cross-domain data source shared between both products rather than duplicated as separate implementations.

4. Full Endpoint / Tool Reference

Every row below is a distinct callable action exposed to a connected AI assistant.

4.1 ΓΕΜΗ — 4 tools

Tool	Purpose
<code>gemi_search_company_by_tin</code>	Find a company by its tax identification number (ΑΦΜ)
<code>gemi_get_company</code>	Retrieve a company's full registry record by its ΓΕΜΗ number
<code>gemi_get_company_documents</code>	Retrieve the list of documents filed for a company
<code>gemi_list_metadata</code>	Retrieve reference metadata — legal types, company statuses, registry offices — needed to interpret other results

4.2 myDATA — 13 tools

Tool	Purpose
<code>mydata_request_docs</code>	Retrieve issued/received invoice documents for a date range
<code>mydata_request_transmitted_docs</code>	Retrieve documents transmitted to myDATA by counterparties
<code>mydata_request_my_income</code>	Retrieve the caller's recorded income summary
<code>mydata_request_my_expenses</code>	Retrieve the caller's recorded expense summary
<code>mydata_request_vat_info</code>	Retrieve VAT return/summary information
<code>mydata_request_e3_info</code>	Retrieve E3 (profit/loss classification) information
<code>mydata_send_invoices</code>	Submit one or more invoices to myDATA
<code>mydata_send_income_classification</code>	Submit income classification entries for a transmitted document
<code>mydata_send_expenses_classification</code>	Submit expense classification entries for a received document
<code>mydata_send_payments_method</code>	Record the payment method(s) used for a document
<code>mydata_cancel_invoice</code>	Cancel a previously submitted invoice
<code>mydata_connect</code>	Securely store myDATA credentials once, receiving a reusable token (optional convenience feature)
<code>mydata_forget</code>	Delete a previously stored credential token

4.3 Ergani — 3 tools

Tool	Purpose
<code>ergani_list_services</code>	List the labor-system services and endpoints available through Ergani
<code>ergani_connect</code>	Securely store Ergani credentials once, receiving a reusable token (optional convenience feature)
<code>ergani_forget</code>	Delete a previously stored credential token

4.4 Diavgeia — 15 tools

Tool	Purpose
<code>diavgeia_search_decisions</code>	Advanced filtered search over published decisions
<code>diavgeia_simple_search_decisions</code>	Free-text search across decisions
<code>diavgeia_get_decision</code>	Retrieve a single decision by its ADA tracking code
<code>diavgeia_get_decision_version_log</code>	Retrieve a decision's revision/correction history
<code>diavgeia_list_decision_types</code>	List the taxonomy of decision types (e.g. procurement award)
<code>diavgeia_get_decision_type_details</code>	Get the detailed definition of one decision type
<code>diavgeia_search_organizations</code>	Search the directory of public-sector organizations
<code>diavgeia_get_organization</code>	Retrieve an organization's summary record
<code>diavgeia_get_organization_details</code>	Retrieve full organization profile details
<code>diavgeia_get_organization_units</code>	List an organization's sub-units
<code>diavgeia_get_unit</code>	Retrieve a single organizational unit's record
<code>diavgeia_get_signer</code>	Look up a signing official's record
<code>diavgeia_list_positions</code>	List official positions/roles used in the signer directory
<code>diavgeia_get_dictionary</code>	Retrieve subject/keyword dictionary entries
<code>diavgeia_list_search_terms</code>	List valid search term/filter values

5. Authentication Models & Credential Security

BusinessMCP deliberately keeps three different auth patterns explicit rather than hiding them behind one generic mechanism, because they have genuinely different security and operational properties.

5.1 Diavgeia — fully open

No credentials of any kind. Identical to CitizenMCP's model — the underlying data is public by law.

5.2 ΓΕΜΗ — single shared operator key

ΓΕΜΗ requires an `api_key` that is manually approved per-applicant by KY ΓΕΜΗ (the registry operator). BusinessMCP holds one such key on the server side as a Cloudflare Worker *secret* — never a plain configuration value, never visible in deployment logs or exported configuration — and every caller of the public service shares that one key and its quota. Individual users never see or handle this key themselves.

5.3 myDATA & Ergani — your own credentials

These credentials belong to an individual business or employer (a Taxisnet-issued subscription key for myDATA; a username/password pair for Ergani) — there is no shared server-side key that could possibly work here, since the whole point is that the data returned is specific to whoever's credentials are used. BusinessMCP supports two ways to supply them:

1. **Pass credentials directly on each call.** Nothing is stored; simplest model, at the cost of resending credentials with every request.
2. **Connect once, reuse a token.** Call `mydata_connect` or `ergani_connect` a single time; the credentials are encrypted and stored server-side, and the response is an opaque `credentialToken` to use on subsequent calls instead of the raw credentials. Call `mydata_forget` / `ergani_forget` at any time to permanently delete the stored value.

How the connect-once storage is secured: credentials are encrypted with **AES-256-GCM** (an industry-standard authenticated encryption cipher) using the platform's native WebCrypto implementation before being written to Cloudflare KV (a distributed key-value store). The encryption key itself is held only as a Worker secret, never in code or configuration. Rotating that key is a deliberate, available operation that invalidates every previously-issued token at once — an intentional "revoke everything" capability, not a failure mode.

This connect-once system is entirely optional — if the underlying storage isn't configured for a given deployment, the `connect` / `forget` tools simply don't appear, and raw-credential calls continue to work exactly as before. Nothing about core functionality depends on it.

6. Rate Limiting

BusinessMCP runs two independent, edge-enforced rate limiters, because ΓEMH's constraint is fundamentally different in kind from ordinary fair-use limiting:

Limiter	Scope	Ceiling
Diavgeia (general)	Per caller IP address	30 requests / 60 seconds
ΓEMH	Global — shared across every caller of the service, not per-IP	8 requests / 60 seconds

Why ΓEMH is different: the 8 requests/minute ceiling is not a policy choice by this service — it is the hard quota KY ΓEMH itself places on the single approved API key BusinessMCP holds, applied to that key's total usage regardless of who or what is calling it. The global limiter simply enforces upstream reality at the edge rather than letting requests fail further downstream. Raising this ceiling requires KY ΓEMH granting a higher quota on the key itself, not a configuration change on our side.

Both limiters run on Cloudflare's native edge rate-limit binding, checked before a request reaches any application logic — an over-limit call is rejected cheaply and immediately.

7. Technical Architecture

7.1 Request lifecycle

1. **CORS preflight** handling for direct browser-based MCP clients.
2. **Path validation** — only the root path serves MCP; everything else, including speculative OAuth-discovery probes some clients send, returns a clean 404.
3. **Edge rate-limit checks** — both the general and the ΓEMH-specific limiter, as applicable.
4. **A fresh MCP server instance** is constructed per request, with all four tool sets (Diavgeia, ΓEMH, myDATA, Ergani) registered.
5. The **credential store** is wired in from the Worker's KV binding and encryption key, if configured, enabling the connect-once flow for that request.
6. The request is handled by the **MCP Streamable HTTP transport**, dispatched to the requested tool, and the structured result streamed back with CORS headers applied.

Stateless, with one deliberate exception: like CitizenMCP, each request is otherwise independent and self-contained. The one piece of state BusinessMCP persists across requests and callers by design is the encrypted credential store in Cloudflare KV — that persistence is the entire point of the connect-once convenience flow described in Section 5.3.

7.2 Shared core library

All four service clients, the credential-encryption module, and the shared HTTP resilience layer live in an internal core library (`@my-mcp/core`) shared with CitizenMCP. Diavgeia's client and tool set, in particular, are the exact same code running in both services — not a duplicate reimplementations.

7.3 Resilient outbound networking

Every outbound call to ΓEMH, myDATA, and Ergani goes through the same resilient HTTP client described in the CitizenMCP report: 15-second timeouts, automatic retry with exponential backoff on 429/5xx responses (honoring `Retry-After` when provided), and errors normalized into a consistent, informative shape rather than raw exceptions.

7.4 Protocol & transport

BusinessMCP speaks MCP's **Streamable HTTP** transport, implemented entirely on Web Standard APIs (`WebStandardStreamableHTTPServerTransport`) — the same transport implementation used by CitizenMCP, portable across Cloudflare Workers, Node.js, Deno, and Bun.

7.5 Codebase & quality practices

- TypeScript throughout, with strict type-checking.
- Automated test suites (Vitest) for the shared HTTP client and each service client, including fixture-based tests against captured real API responses (ΓΕΜΗ's client, notably, has been exercised end-to-end against production with a real approved API key).
- Repo-wide linting and formatting (ESLint + Prettier).
- Input schemas for every tool are strictly validated (Zod) before any government or tax-authority API is contacted.

8. Infrastructure & Where It Runs

8.1 Cloudflare Workers

BusinessMCP is deployed as a **Cloudflare Worker**, running in Cloudflare's global edge network rather than a single-location server:

- **Global reach with low latency** — requests are handled at the nearest Cloudflare location to the caller.
- **No idle server cost or cold-VM startup** — lightweight V8 isolates start in milliseconds.
- **Automatic scaling** under load, with no manual capacity planning required.

8.2 Live endpoint

Property	Value
Production URL	<code>https://business-mcp.nickdandis96.workers.dev</code>
Transport	MCP Streamable HTTP (single endpoint, root path)
Rate limiting	Two independent Cloudflare native edge rate-limit bindings
Credential storage	Cloudflare KV, AES-256-GCM encrypted at rest
Deployment tooling	Wrangler (Cloudflare's official CLI)

8.3 Secrets management

The GEMH API key and the credential-store encryption key are both provisioned as Cloudflare Worker secrets via `wrangler secret put` — a mechanism specifically designed so sensitive values never appear in source control, deployment configuration files, or dashboard exports. Everything else — rate-limit thresholds, worker naming, platform compatibility settings — lives in a version-controlled `wrangler.toml` alongside the application code.

9. Reliability, Verification & Scope Boundaries

9.1 Verification status

Source	Status
Diavgeia	Live and confirmed reachable
ΓΕΜΗ	Verified end-to-end with a real, approved production API key — every client method exercised against production successfully
myDATA	All endpoints confirmed live and correctly wired on both production and sandbox hosts; a fully credentialed sandbox round-trip is the one remaining verification step, pending sandbox registration
Ergani	Portal and sandbox confirmed live and reachable

9.2 Deliberate scope boundary: Ergani write operations

Ergani's write operations — submitting a digital work card, declaring a work schedule — are intentionally **not yet exposed** through BusinessMCP. The read-only services catalog is available today; write endpoints will be added once their exact live payload format has been independently confirmed against production. This is a deliberate safety-first decision, not a gap discovered by accident: submitting incorrect labor-law compliance data has real legal consequences for a business, so this integration ships once it's verified, not before.

9.3 Resilience in practice

The shared HTTP client's retry-and-backoff behavior (Section 7.3) absorbs the kind of brief transient errors any public-sector API occasionally produces, so short upstream hiccups are handled automatically rather than surfacing as failures.

10. Roadmap

- **myDATA credentialed sandbox smoke test** — the last verification step before treating the write path (invoice submission, classifications) as fully production-hardened.
- **Ergani write operations** — work-card submission and schedule declarations, once their live payload shape is confirmed (see Section 9.2).
- The product strategy is to keep growing via focused **domain bundles** rather than folding unrelated services into BusinessMCP — new business-relevant sources will be evaluated against that principle before being added here specifically.

For transparency and open-data use cases, see the companion **CitizenMCP** service report.