

Example:

```
interface IA{
    void method1(); //public abstract
}

interface IB extends IA{
    void method2();
}

class SubB implements IB
{ @Override
    public void method1()
    { System.out.println("OR M1 of IA "); }

    @Override
    public void method2()
    { System.out.println("OR m2 of IB "); }
}

class InterfaceDemo
{
    public static void main(String args[])
    {
        IA ia=new SubB();
    }
}
```

```
        ia.method1();
        // ia.method2(); CE

        IB ib=new SubB( );
        ib.method2();
        ib.method1();
    }
}
```

Note:

- A class can be extends by a class
- A class can't be extended by more than one class
- A class can be implemented by an interface
- A class can be implemented by more than one interface
- A class can be extends by class and can be implemented by one or more interface but in this case extends to be used first


```
class A{ }
class B{ }
interface C{ }
interface E{ }
```

- 1.class D extends A{ } //valid
- 2.class D extends A,B{ } //invalid
- 3.class D extends A implements C{ } //valid
- 4.class D implements C extends A{ } // invalid
- 5.class D implements C extends A,B{ } //invalid
- 6.class D implements C,E extends A{ } //invalid
- 7.class D extends A implements C,E{ } //valid

Q:Why Java doesn't support multiple inheritance using classes .

Ans : Diamond problem

```
class A {  
    int x=10;  
}  
  
class B extends A {  
    void m1()  
    { S.o.pln(x); }  
}  
  
class C extends A {  
    void m1()  
    {S.o.pln(x); }  
}  
  
class D extends B,C {  
    void m2( )  
    { m1(); }  
    p s v main(String args[ ])  
    { D d=new D();  
      d.m2();  
    }  
}
```



Q: Why java doesn't support to create an object for abstract class or an interface ?

Ans : Just bcz abstract and interface will have abstract methods.

- Abstract methods will not have body or implementation
- If we call abstract methods can do nothing that's way abstract methods also known as do nothing method
- If any class is defined with abstract methods then those classes are restricted to create an object for them

Final Modifiers:

- In c and c++ in order to make any variable value as constant then we have to make use of "const" keyword
 - `const int x=10;`
`x=x+10; //Error`
- In Java there is not keyword "const" rather we have to user "final"
 - `final int X=10;`

X=X+10; //Error

With the help of final modifier then we declare

1. Declare Variables
2. We can Define Methods
3. We can Define Classes

Final Methods :

- if we define any method with final modifier then those methods are not overridden ,but those are inherited.

Final Classes:

- Defining a class with “final” modifier.
- Final classes are not inherited . but we can an Object and we access the members of the classes using object possible .

Example on final Methods:

```
class Test
{
    final void method1()
    {System.out.println("M1 of Test "); }
}
```

class Testing extends Test

```
{
    public static void main(String args[])
    {
```

```
        Testing t=new Testing();
            t.method1();
    }
}
```

Example 2:

```
class Test
{
    final void method1()
    {System.out.println("M1 of Test "); }
}
class Testing extends Test
{
    @Override
    void method1()
    { System.out.println("OR m1 of Test"); }
}
```

Example on final Class:

```
final class A
{
    int x=10;
    void method1()
    { System.out.println("M1 of A"); }
}

class B
{
    public static void main(String args[])
    {
        A a=new A();
        System.out.println("x val is : "+a.x);
    }
}
```

```
        a.method1();  
    }  
}
```

Example 2:

```
final class A
```

```
{ }
```

```
class B extends A{ }
```

```
E:\Java_Online11\INTERFACE>javac FinalClass2.java
```

```
FinalClass2.java:3: error: cannot inherit from final A
```

```
class B extends A{ }
```

```
//TQ2.java
```

```
abstract class TestIQ
```

```
{
```

```
    final abstract void method1();
```

```
    abstract void method2();
```

```
}
```

Note: illegal combination of modifiers: abstract and final

```
//TQ.java
```

```
final abstract class TestIQ
```

```
{    abstract void method2(); }
```

Note: illegal combination of modifiers:

abstract and final,

abstract and static

private and abstract

protected and abstract

//TQ3.java

interface IA

```
{  
    static abstract void method1();  
    final abstract void method2();  
}
```

//TQ4.java

interface IA

```
{  
    public void method1(); //valid  
    private abstract void method2(); //invalid  
    protected abstract void method3(); //invalid  
}
```