

IS 9401 (Part 18) : 2000

भारतीय मानक
नदी घाटी परियोजनाओं में कार्य मापन की पद्धतियाँ
(बाँध और संरचनाएँ)

भाग 18 चादर पाइलिंग

Indian Standard

METHOD OF MEASUREMENT OF WORK IN
RIVER VALLEY PROJECTS (DAMS AND
APPURTENANT STRUCTURES)

PART 18 SHEET PILING

ICS 93.160

© BIS 2000

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

August 2000

Price Group 1

FOREWORD

This Indian Standard (Part 18) was adopted by the Bureau of Indian Standards, after the draft finalized by the Measurement of Works of River Valley Projects Sectional Committee had been approved by the Water Resource Division Council.

In measurement of works relating to river valley projects, a large diversity of methods exist according to local practices. The lack of conformity creates complications regarding measurements and payments. This standard is therefore being formulated in different parts, covering each type of work separately. This part is intended to provide a uniform basis for measuring the work done in respect of sheet piling works in river valley projects.

There is no ISO Standard on the subject. This standard has been prepared based on indigenous manufacturer's data/practices prevalent in the field in India.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

METHOD OF MEASUREMENT OF WORK IN RIVER VALLEY PROJECTS (DAMS AND APPURTENANT STRUCTURES)

PART 18 SHEET PILING

1 SCOPE

This standard (Part 18) covers the method of measurement of sheet piling work in river valley projects (dams and appurtenant structures).

2 REFERENCE

The following standard contains provisions which through reference in this text, constitutes provisions of this standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below:

<i>IS No.</i>	<i>Title</i>
9401 (Part 2) : 1982	Method of measurement of work in river valley projects (dams and appurtenant structures): Part 2 Dewatering

3 GENERAL RULES

3.1 Clubbing of Items

Items may be clubbed together if the break up of the clubbed items conforms to the description of the individual items stated in this standard.

3.2 Recording of Dimensions

In recording dimensions, the order shall be consistent and generally in the sequence of length, width and depth or thickness.

3.3 Description of Items and Methodology of Construction

The description of each item shall unless otherwise stated, include shape, type, size, thickness and weight per square metre where applicable. It shall also include where necessary, conveyance and delivery, handling, loading, unloading, storing, fabrication, hoisting, all formwork and scaffolding, all tools, equipment and labour for finishing to required shape and size, setting, fitting and fixing in position, cutting and return of unused materials, dismantling of the equipment and taking it back, etc.

The sheet piles shall be driven true to plumb and along the line as indicated in relevant drawings. In case it is not possible to follow the line, or cut-off, as indicated in the drawings due to any unavoidable circumstances, the sheet pile line may be diverted at right angles, again turned at 90° and taken parallel to the original line and then joined at right angles as per the drawings. As the effectiveness of the cut-off depends upon the verticality and consequent interlocking of sheet piles, special care should be taken to drive piles vertically and no deviations from the true plumb should be allowed. In case any pile goes out of plumb the same has to be pulled out and another pile driven in its place after making sure that the preceding piles are not disturbed from their verticality. No separate measurement will be made for such withdrawal and re-driving of the sheet piles.

3.4 Units of Measurement

All work shall be measured net in decimal system as fixed in its place subject to the following limitations, unless otherwise stated:

- Linear dimensions to the nearest 0.01 m; and
- Weight to the nearest 0.1 kg.

3.5 Work to be Measured Separately

3.5.1 Work executed in the following conditions shall be measured separately :

- Work in under-water/wet and dry land,
- Work in liquid mud/marshy land, and
- Work under tides.

3.5.2 The level of high and low weather tides and ground water table, where occurring shall be stated.

3.5.3 Wherever springs or special situations are encountered and dewatering is resorted to, it shall be measured in accordance with IS 9401(Part 2).

4 BILL OF QUANTITIES

4.1 The bill of quantities shall fully describe the materials and workmanship and accurately represent the work to be executed.

4.2 A general description of the nature of the site shall be stated. For works near river banks, reservoirs or sea

front, the maximum and minimum water levels shall be stated.

4.3 Information on ground water conditions shall be stated.

4.4 The available information as to the strata through which sheet piling is to be carried out shall be stated or reference records of bores shall be provided.

4.5 If sheet piles are to be provided from any level other than ground level, it shall be stated.

4.6 The cut-off level of the top of the sheet piles be clearly specified. The level and location of the reference bench marks shall also be provided.

4.7 The item shall include any extra excavation filling and/or ramming required at the time of construction for the movement of cranes and other equipment at the site.

4.8 Bringing plant to the site and erecting it, dismantling and taking it back, shall be measured separately as lump sum items or shall be deemed to be included in the items pertaining to the sheet piling work.

4.9 Shifting of plant and equipment at site of work shall be included in the item of sheet piles.

4.10 Special anchors, structural steel ties, braces, and supports, coffer dams dewatering and any other temporary work to be carried out for the purpose of sheet piling shall be deemed to have been measured and paid under sheet piling unless these are expressly identified, and measured under separate items.

5 METHOD OF MEASUREMENT OF STEEL SHEET PILES

5.1 Supply of sheet piles shall be measured either by weight or area in square metres. The description of the item shall include the cross-sectional shape, size, type, unit weight, sectional modulus and composition of material. It shall also include details of fabrication of junction pile, tapered piles, such as lengthening by means of welding, riveting, drilling, or cutting holes, joining or fixing of structural rolled steel sections, handling and transportation to the site and the like. Piles exceeding 12 m in length shall be

described separately stating the lengths in further stages of 3 m.

5.2 All struts, ground anchors (anchor bolts, anchor plates, turn buckles, etc) walings, tie rods and piling ancillaries, etc, shall be measured separately by weight in accordance with relevant Indian Standards.

5.3 When sheet piles are to be painted prior to driving, such painting shall be measured in square metres obtained by multiplying the length by the perimeter of the fabricated sheet pile measured along the profile (as enlarged flat surface) for specified number of coats and thickness in microns. Description of items shall include the method of preparation of surface, number of coats (that is thickness), mode of painting, and the like.

5.4 Lifting, handling, pitching, engaging through interlocks or clutches of adjacent sheet shall not be measured separately.

5.5 Pile driving shall be measured in square metres obtained by multiplying the length of the pile in soil, or up to cut-off level, whichever is specified, and the nominal width of pile from center-to-center of clutches, or by weight as the case may be.

5.6 Wherever sheet piles are to be driven under/in water necessitating use of special hammers and/or loader frames such piles shall be described and measured separately.

5.7 In case of defective driving and installation of piles necessitating extraction of piles already driven, and re-driving, no separate measurement shall be taken.

5.8 No separate measurement shall be made for driving piles through varying strata.

5.9 Driving corner piles and junction piles shall be measured separately.

5.10 Cutting or drilling through steel sheet piles shall not be measured. The disposal of cut length shall be described.

5.11 Extraction of piles other than described in 5.7 shall be measured separately including operations such as lifting, handling and removing from site.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. WRD 23 (251).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002
Telephones : 323 01 31, 323 33 75, 323 94 02

Telegrams : Manaksanstha
(Common to all offices)

Regional Offices :

Telephone

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110 002

{ 323 76 17
323 38 41

Eastern : 1/14 C. I.T. Scheme VII M, V. I. P. Road, Kankurgachi
CALCUTTA 700 054

{ 337 84 99, 337 85 61
337 86 26, 337 91 20

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022

{ 60 38 43
60 20 25

Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600 113

{ 235 02 16, 235 04 42
235 15 19, 235 23 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
MUMBAI 400 093

{ 832 92 95, 832 78 58
832 78 91, 832 78 92

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.
LUCKNOW. NAGPUR. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.