Indian Standard SPECIFICATION FOR SURFACE BOXES FOR SLUICE VALVES (First Revision)

Third Reprint AUGUST 1992

UDC 621.646.5-758.1:628.146

© Copyright 1979

BUREAU OF INDIAN STANDARDS MANAK BHAYAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard SPECIFICATION FOR SURFACE BOXES FOR SLUICE VALVES (First Revision)

Sanitary Appliances and Water Fittings Sectional Committee, BDC 3

Chairman

SHRI V. D. DESAI

Members

ADVISER

Shri B. B. Rau (Alternate)
Shri H. R. Badyal
Shri K. D. Biswas (Alternate)
Shri M. K. Basu

ORRI W. IV. DASO

Shri D. S. Chabhal

SHRI T. RAMASUBRAMANIAN (Alternate)
SHRI S. P. CHAKRABARTI Central

SHRI S. K. SHARMA (Alternate)

CHIEF ENGINEER

SHRI K. RAMACHANDRAN (Alternate)
CHIEF ENGINEER Tami

CHIEF ENGINEER U. P. Ja
SUPERINTENDING ENGINEER (Alternate)

CHIEF ENGINEER (WATER) DRAINAGE ENGINEER (Alternate)

SHRI L. M. CHOUDHARY

SHRI I. CHANDRA (Alternate)
CITY ENGINEER

HYDRAULIC ENGINEER (Alternate)

Representing

Municipal Corporation of Greater Bombay, Bombay

Central Public Health & Environmental Engineering Organization (Ministry of Works & Housing)

Indian Iron & Steel Co Ltd, Calcutta

Central Glass & Ceramic Research Institute (CSIR), Ahmadabad

Directorate General of Technical Development, New Delhi

Ilternate)
Central Building Research Institute (CSIR),
Roorkee

Public Health Engineering Department, Government of Kerala, Trivandrum

rnate)
Tamil Nadu Water Supply & Drainage Board,
Madras

U. P. Jal Nigam, Lucknow

Municipal Corporation of Delhi, Delhi
)
Public Health Engineering Department, Govern-

ment of Haryana, Chandigarh

Municipal Corporation of Greater Bombay,
Bombay

(Continued on page 2)

Copyright 1979

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 3950 - 1979

(Continued from page 1)

Members

SHRI H. N. DALLAS

LALA G. C. DAS SHRIT, R. DE DIRECTOR

SHRI A. M. KEMBHAVI (Alternate)

SHRI B. R. N. GUPTA

SHRIK. V. KRISHNAMURTHY (Alternate) SHRI M. T. KANSE

SHRI S. R. KSHIRSAGAR

SHRI R. C. REDDY (Alternate) SHRI K. LAKSHMINARAYANAN SHRI A. SHARIFF (Alternate)

SHRI P. S. RAJVANSHI

SHRI RANJIT SINGH DR A. V. R. RAO

SHRI P. JAGANATH RAO SHRI M. MOOSA SULAIMAN (Alternate)

SHRIR. K. SOMANY

SUPERINTENDING SURVEYOR OF WORKS (NDZ) SURVEYOR OF WORKS I (NDZ)

(Alternate) SHRI D. AJITHA SIMHA, Director (Civ Engg) Representing

Indian Institute of Architects, Bombay

National Test House, Calcutta

Institution of Engineers (India), Calcutta Bombay Potteries & Tiles Ltd, Bombay

Engineer-in-Chief's Branch (Army Headquarters)

Directorate General of Supplies & Disposals, New Delhi

National Environmental Engineering Research Institute (CSIR), Nagpur

Hindustan Shipyard Ltd, Vishakhapatnam

Public Health Engineering Department, Government of Rajasthan, Jaipur Railway Board (Ministry of Railways)

National Buildings Organization, New Delhi E.I.D. - Parry Ltd, Madras

Hindustan Sanitaryware

& Industries Ltd. Bahadurgarh Central Public Works Department, New Delhi

Director General, ISI (Ex-officio Member)

Secretary

SHRI S. P. MAGGU Assistant Director (Civ Engg), ISI

Water Works Fittings Subcommittee, BDC 3:5

Convener

SHRIK. D. MULEKAR

Municipal Corporation of Greater Bombay, Bombay

M/s Goverdhan Das P. A., Calcutta

Members

SHRI T. M. KANDAWALA (Alternate to

Shri K. D. Mulekar) SHRI J. R. AGGARWAL

SHRI YASH RAJ AGGARWAL (Alternate) Indian Valve Co Ltd, Calcutta SHRI K, K. BHATTACHARYYA

SHRI A. K. BHATTACHARYYA (Alternate)

CHIEF ENGINEER Bangalore Water Supply & Sewerage Board, Bangalore

SUPERINTENDING ENGINEER (Alternate)

(Continued on page 7)

Indian Standard SPECIFICATION FOR SURFACE BOXES FOR SLUICE VALVES (First Revision)

0. FOREWORD

- 0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 4 May 1979, after the draft finalized by the Sanitary Appliances and Water Fittings Sectional Committee had been approved by the Civil Engineering Division Council.
- 0.2 Surface box is a deep metal frame with a lid fixed in the ground with the lid level at the surface to give access to underground fittings, such as a valve or hydrant. Surface boxes are made in different patterns and sizes to suit stop valves, sluice valves, hydrant, etc. This standard covers the requirements for cast iron surface boxes for use with sluice valves on service pipes and water mains. This standard was first published in 1966. In this revision the tolerances on various dimensions of surface boxes have been incorporated.
- 0.3 This standard is one of a series of Indian Standards on water fittings. Other standards published so far in the series are given on page 8.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 The standard lays down the requirements for cast iron surface boxes for use with sluice valves with valve caps, conforming to IS: 780-1969† and IS: 2906-1969‡ for use on service pipes and water mains.

^{*}Rules for rounding off numerical values (revised).
†Specification for sluice valves for water works purposes (50 to 300 mm size) (fourth

[†]Specification for sluice valves for water works purposes (350 to 1200 mm size) (first revision).

IS: 3950 - 1979

2. MATERIALS

- 2.1 Frame Cast iron used in the manufacture of surface boxes shall be of a quality of not less than Grade FG 150 of IS: 210-1978*.
- **2.2 Hinge Pin** Hinge pin shall be made of galvanized mild steel conforming to IS: 280-1972†. The galvanizing shall be done in accordance with IS: 2629-1966‡.

3. MANUFACTURE AND WORKMANSHIP

3.1 Surface boxes shall be clearly cast to the specified dimensions. The castings shall be sound, clean and free from porosity, blow holes, hard spots, cold shuts and chills. They shall be well dressed and fettled, and also free from voids due to shrinkage, gas inclusions or other causes.

4. CONSTRUCTION

- 4.1 The surface boxes shall be made in accordance with the details given in Fig. 1.
- 4.2 Cover The upper surface of the covers shall be designed with an adequate non-slip surface which shall, unless otherwise specified, include the letter 'W' cast therein. The design may also include such other letters as may be agreed to between the purchaser and the manufacturer.

5. DIMENSIONS AND TOLERANCES

- 5.1 Dimensions Dimensions shall conform to those specified in Fig. 1.
- **5.2 Tolerances** The following tolerances shall be allowed on the dimensions:
 - a) On dimensions up to and including 10 mm + 2 mm
 - b) On dimensions above 10 mm up to and including 50 mm \pm 2 mm
 - c) On dimensions over 50 mm ± 5 mm


6. MASS

6.1 The minimum mass of surface boxes shall be 33 kg.

^{*}Specification for grey iron castings (third revision).

[†]Specification for mild steel wire for general engineering purposes (second revision).

Recommended practice for hot-dip galvanizing of iron and steel.



All dimensions in millimetres.

Fig. 1 A Typical Illustration of a Rectangular Surface Box for Sluice Valve

IS: 3950 - 1979

7. INSPECTION

7.1 The manufacturers shall afford all reasonable facilities for carrying out inspection during the course of manufacture and facilities shall be given to the purchaser, if he so desires, to carry out inspection of the surface boxes to his order before the application of any coating

8. PROTECTIVE COATING

8.1 Surface boxes shall be thoroughly cleaned and dried and then coated by being dipped in a bath containing a composition having a bitumen or tar base. The coating shall be smooth and tenacious so as not to flow when exposed to a temperature of 63°C and shall not be so brittle as to chip off at a temperature of 15°C.

9. MARKING

- 9.1 Each surface box shall cast on them the following information:
 - a) Manufacturer's name and trade-mark, and
 - b) The word 'W' or any other letter as agreed to between the purchaser and the manufacturer.
- 9.1.1 Each surface box may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors may be obtained from the Indian Standards Institution.

(Continued from page 2)

Members

Representing

Railway Board, Northern Railway Headquarters,

Public Health Engineering Department, Kerala CHIEF ENGINEER

State, Trivandrum

Tamil Nadu Water Supply & Drainage Board, CHIEF ENGINEER Madras

U. P. Jal Nigam, Lucknow CHIEF ENGINEER

SUPERINTENDING ENGINEER (Alternate) CHIEF ENGINEER (WATER) Delhi Municipal Corporation, Delhi

DEPUTY CHIEF ENGINEER (Alternate)

SHRI J. V. GADGIL Indian Iron & Steel Co Ltd, Kulti Shri M. L. Kaura Engineers India Ltd, New Delhi

National Environmental Engineering Research SHRI A, RAMAN Institute, Nagpur

New Delhi

SHRI R. C. REDDY (Alternate)

SHRI RANJIT SINGH

SHRI K. K. SONI (Alternate) Kirloskar Brothers Ltd, Kirloskarvadi Shri K. Sathyanarayana

SHRI S. R. PATKAR (Alternate)

SHRI D. K. SEHGAL Leader Engineering Works, Jullundur SHRI O. P. WADHWA (Alternate)

Public Health Engineering Department, Govern-SHRI J. L. SETHI ment of Haryana, Rohtak

SHRI A. N. MEHENDALE (Alternate) SHRIRAMESHCHANDRAH, THAKKAR Geeta Iron & Brass Works, Bajuva

SHRI NAND KUMAR H. THAKKAR (Alternate) Directorate General of Supplies & Disposals, SRRI T. N. UBOVEJA

New Delhi

SHRIE, UMMERKUTTY (Alternate)

BUREAU OF INDIAN STANDARDS

1	4	e	a	d	a	u	a	rt	e	rs	:

Manak Bhavan, 9 Bahadur Shah Zafar Marg.	NEW DELHI 1 10002
Telephones: 331 01 31, 331 13 75	Telegrams: Manaksanstha (Common to all Offices)
Regional Offices:	Telepho ne
Central: Manak Bhavan, 9 Bahadur Shah Zaf NEW DELHI 110002	far Marg, (331 01 31 331 13 75
*Eastern: 1/14 C. I. T. Scheme VII M, V. I. Maniktola, CALCUTTA 700054	P. Road, 36 24 99
Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 2 18 43 { 3 16 41
Southern: C. I. T. Campus, MADRAS 60011	3 {41 24 42 41 25 19 41 29 16
†Western: Manakalaya, E9 MIDC, Marol, An BOMBAY 400093	
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpu AHMADABAD 380001	ur. { 2 63 48 } 2 63 49
‡Peenya Industrial Area 1st Stage, Bangalore BANGALORE 560058	
Gangotri Complex, 5th Floor, Bhadbhada Roa BHOPAL 462003	d, T. T. Nagar, `-6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHW, 53/5, Ward No. 29, R.G. Barua Road, 5th Bye GUWAHATI 781003	
5-8-56C L. N. Gupta Marg (Nampally Station HYDERABAD 500001	•
R14 Yudhister Marg, C Scheme, JAIPUR 302	(0 90 32
117/418 B Sarvodaya Nagar, KANPUR 20800	$\begin{cases} 21 & 68 & 76 \\ 21 & 82 & 92 \end{cases}$
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421. University P.O., Palayam TRIVANDRUM 695035	∫6 21 04
Inspection Offices (With Sale Point):	
Pushpanjali, First Floor, 205-A West High Cou Shankar Nagar Square, NAGPUR 440010	
Institution of Engineers (India) Building, 133. PUNE 411005	2 Shivaji Nagar, 5 24 35
*Sales Office in Calcutta is at 5 Chowringhee App	roach, P. O. Princep 27 68 00

^{*}Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. Princep 27 68 00 Street, Calcutta 700072

‡Sales Office in Bangalore is at Unity Building, Narasimharaja Square, 22 36 71 Bangalore 560002

[†]Sales Office in Bombay is at Novelty Chambers, Grant Road, 89 65 28 Bombay 400007