

भारतीय मानक

नदी घाटी परियोजनाओं में कार्यमापन की पद्धति
(बाँध और सम्बद्ध संरचनाएँ)

भाग 1 नींव उत्खनन

(पहला पुनरीक्षण)

Indian Standard

METHOD OF MEASUREMENT OF WORKS IN
RIVER VALLEY PROJECTS
(DAMS AND APPURTENANT STRUCTURES)

PART 1 EXCAVATION FOR FOUNDATION

(*First Revision*)

ICS 93.160

© BIS 1999

BUREAU OF INDIAN STANDARDS

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

FOREWORD

This Indian Standard (Part 1) (First Revision) was adopted by the Bureau of Indian Standards after the draft finalized by the Measurement of Works of River Valley Projects Sectional Committee had been approved by the River Valley Division Council.

In measurement of quantities, in construction of river valley projects a large diversity of methods exists at present according to local practices. Lack of uniformity creates complication regarding measurement and payments. This standard has been formulated in various parts, covering each type of work separately and Part 1 is intended to provide a uniform basis for measurement of excavation for foundation in the construction of river valley projects.

This standard was first published in 1982. The revision has been taken up in the light of experience gained during its usage and to align it with current field practices. A number of standards have been published for measurement of different works undertaken in River Valley Projects and this revision is also intended to harmonize the earlier version with those parts which have been published since 1982.

In reporting the result of measurements made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'.

Indian Standard

METHOD OF MEASUREMENT OF WORKS IN RIVER VALLEY PROJECTS (DAMS AND APPURTENANT STRUCTURES)

PART 1 EXCAVATION FOR FOUNDATION

(First Revision)

1 SCOPE

This standard (Part 1) covers the method of measurement of excavation for foundation in river valley projects (dams and appurtenant structures).

2 REFERENCES

The following standard contains provisions which through reference in this text, constitutes provision of this standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below:

<i>IS No.</i>	<i>Title</i>
9401 (Part 2) : 1982	Method of measurement of works in river valley projects (dams and appurtenant structures) : Part 2 Dewatering

3 GENERAL

3.1 In case of measurement of proposed work, the dimensions are read from drawings and then worked up, that is, reduced to length, area, or volume in recognized units of measurements for the particular item. In case of assessment of executed work, the dimensions are measurements in the field. Calculations of length, area, volume, weight, etc, are made on the basis of these dimensions and payments are made accordingly. Where measurements of a number of units are the same it is the usual practice to take measurements of one unit and multiply the calculated length, area or volume by the number of units.

3.2 Clubbing of Items

Items may be clubbed together provided that the break up of items is on the basis of detailed description of items stated in the standard.

3.3 Booking of Dimensions

In booking dimensions, order shall be consistent and

generally in the sequence of length, width, and height or depth or thickness.

3.4 Dimensions

Unless otherwise stated, all work shall be measured net in decimal system, as fixed in its place as given in 3.4.1 to 3.4.3

3.4.1 Linear dimensions shall be measured to the nearest 0.01 m.

3.4.2 Areas shall be worked out to the nearest 0.01 m².

3.4.3 Volumes shall be worked out to the nearest 0.01 m³.

3.5 Description of Items

The description of each item shall include conveyance, delivery, handling, loading, unloading, storing, rehandling, etc, including all inputs for finishing to required shape and size.

3.6 Work to be Measured Separately

Work executed in the following conditions shall be measured separately:

- a) Work in or under water;
- b) Work in liquid mud/marshy land;
- c) Work under tides; and
- d) Work in any other specific condition.

3.6.1 The level and the timings of high and low water tides, where occurring, shall be stated.

3.6.2 Wherever dewatering is resorted to, it shall be measured in accordance with Part 2 of this standard.

3.7 Measurements are closely linked with detailed drawings, description of items and specifications of the work. These should, therefore, be very clear and properly worded and the order of precedence shall be sanctioned drawings, approved specifications and specified description of items.

4 MEASUREMENT OF IRREGULAR AREAS AND VOLUMES

4.1 Irregular areas shall be divided into a number of figures of known area, say, triangles, rectangles, etc. The remaining part (which cannot be formed into a triangle or a regular figure) shall be evaluated on common basis by Simpsons rule, or average ordinate rule.

4.2 In case of an irregular volume the volume shall be determined by Prismoidal formula.

5 MEASUREMENT OF EXCAVATION FOR FOUNDATION

5.1 General

5.1.1 All excavation for foundation shall be classified into the following four broad heads for purposes of measurements:

- a) *Overburden* — shall consist of all kinds of strata which can be removed without blasting, including boulders not exceeding 0.5 m^3 in volume.
- b) *Rock (blasting permitted)* — shall consist of all kinds of strata which cannot be removed without blasting and boulders exceeding 0.5 m^3 in volume.
- c) *Rock (Blasting not permitted)* — shall consist of all kinds of strata where blasting is not permitted.
- d) *Rock (in restricted spaces)* — shall consist of excavation in shafts, faults, seams, feather edges, etc.

5.1.2 If excavated materials are required to be stacked for any special requirement, the percentage to be deducted from apparent volume of stack shall be as follows :

Overburden	20 percent
Rock	40 percent

5.1.3 The item of excavation shall be measured either with distinct lead and lifts or distinct lead only.

5.1.4 Shoring and staging, if required, may be measured separately or included in the main work but the method of measurement shall be clearly specified.

5.1.5 Due to site conditions, if excavation according to drawing is not practicable, due allowance shall be given for working dimensions which may also include additional excavation in slope to maintain stability of soil, dewatering arrangements and working space.

5.1.6 If the excavated soil is to be disposed of at a

place other than specified dump areas this may form a separate item.

5.1.7 Any activity, such as upheaving, blowing in, etc, to be measured separately under the item of excavation shall be clearly specified.

5.1.8 Excavation shall be measured by taking cross sections at intervals of 5 metres generally in the original position before starting of the work and after its completion. This interval may be reduced in undulating and uneven site conditions. However, in isolated and special cases, excavation shall be measured by taking off dimensions of pit excavated.

5.1.9 Existing natural cavities, caverns, man made excavations like wells, etc, within the excavated location shall be deducted from the final measurement.

5.2 Excavation

5.2.1 Surface Excavation or Dressing

- a) Surface excavation, dressing, trimming or levelling not exceeding 300 mm in depth shall be measured in square metres giving average depth of excavation work.
- b) Surface excavation, dressing, trimming or levelling exceeding 300 mm in depth shall be measured in cubic metres.
- c) The measurement shall be made to the pay line as shown in the drawing or actually excavated whichever is less (see 5.1.6).
- d) If any clearance in excavation beyond the foundation area is to be allowed, the extent of such clearance should be specified and the same should be included in the measurement.
- e) Dental excavation shall be measured separately.

5.2.2 Excavation of Trenches

- a) If the section of trench is $150 \text{ mm} \times 150 \text{ mm}$ or less, the measurement shall be in running metres specifying the section.
- b) If the section of the trench is greater than $150 \text{ mm} \times 150 \text{ mm}$ but less than $300 \text{ mm} \times 300 \text{ mm}$ the measurement shall be in square metres of cross section giving the average depth.
- c) If the section of the trench is greater than $300 \text{ mm} \times 300 \text{ mm}$ measurement shall be in cubic metres.

5.2.3 Additional Lead and Lift

5.2.3.1 Additional lead shall be given for all excavation of foundation for cases where material has to be thrown beyond initial lead (see 5.1.3).

5.2.3.2 Lead for the purpose of measurement shall be the shortest practical route from the centre of gravity of the borrow pit or foundation to the centre of gravity of the bank or location where the excavated materials have been dumped.

5.2.3.3 All items of foundation excavation work beyond initial lift shall be measured separately as given in 5.2.3.4.

5.2.3.4 The lift shall be taken as the vertical distance from the centre of gravity of the heaped materials from the ground level plus the depth of centre of gravity of the borrow pit or foundation from the same ground level.

5.2.4 *Excavation of Old Foundation*

The unit of measurement shall be cubic metres. The nature of work to be done shall be specified clearly.

5.2.5 *Puddling*

The unit of measurement shall be cubic metres. The nature of puddling work shall be clearly specified.

5.2.6 *Underpinning*

The unit of measurement of excavation for underpinning shall be in cubic metres. The work shall be described in detail stating the length, width and depth of the excavated trench requiring underpinning.

5.2.7 *Overbreaks*

Overbreaks extending beyond pay line of excavation shall not be measured. Only such overbreaks shall be measured separately, the occurrence of which is unavoidable resulting from adverse geological conditions due to concealed joints, faults and other structural defects in rock and not due to negligence or lack of reasonable care and skill in excavation.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc : No. RVD 23 (242)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 323 01 31, 323 94 02, 323 33 75

Telegrams: Manaksanstha
(Common to
all offices)

Regional Offices:

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 323 76 17 323 38 41
Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	{ 337 84 99, 337 85 61 337 86 26, 337 86 62
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022	{ 60 38 43 60 20 25
Southern : C. I. T Campus, IV Cross Road, CHENNAI 600113	{ 235 02 16, 235 04 42 235 15 19, 235 23 15
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	{ 832 92 95, 832 78 58 832 78 91, 832 78 92
Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. PATNA. PUNE. THIRUVANANTHAPURAM.	