

HW2__Lin

zhengzhi lin

2019.9.5

P3

For solo workers, version control helps them track every single step they made, and help them remember every decision they've made. For group workers, version control simply makes cooperating easier for each other, because by version control, they can know the progress on each one and the team can adjust to make things more efficient.

P4

```
library(dplyr)
```

```
## Warning: package 'dplyr' was built under R version 3.5.1
```

```
##
```

```
## Attaching package: 'dplyr'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##      filter, lag
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      intersect, setdiff, setequal, union
```

```
url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/Sensory.dat"
operator <- read.table(url,fill = TRUE)
op_dat <- as.matrix(operator[-c(1:2),])
for (i in 1:10) {
  t <- op_dat[3*i-1,1:5]
  t <- c(i,t)
  op_dat[3*i-1,] <- t
  m <- op_dat[3*i,1:5]
  m <- c(i,m)
  op_dat[3*i,] <- m
}
op_dat <- as.data.frame(op_dat)
names(op_dat) <- c('item','operator1','operator2','operator3','operator4','operator5')
op_dat[,2:6] <- op_dat[,2:6] %>% mutate_if(is.factor, as.character)
op_dat[,2:6] <- op_dat[,2:6] %>% mutate_if(is.character, as.numeric)
head(op_dat)
```

```
##   item operator1 operator2 operator3 operator4 operator5
## 3    1         4.3       4.9       3.3       5.3       4.4
## 4    1         4.3       4.5       4.0       5.5       3.3
## 5    1         4.1       5.3       3.4       5.7       4.7
## 6    2         6.0       5.3       4.5       5.9       4.7
## 7    2         4.9       6.3       4.2       5.5       4.9
## 8    2         6.0       5.9       4.7       6.3       4.6
```

```
op_dat %>% str() %>% summary()
```

```
## 'data.frame':   30 obs. of  6 variables:
## $ item      : Factor w/ 10 levels "1","10","2","3",...: 1 1 1 3 3 3 4 4 4 5 ...
## ..- attr(*, "names")= chr  "3" "4" "5" "6" ...
## $ operator1: num  4.3 4.3 4.1 6 4.9 6 2.4 3.9 1.9 7.4 ...
## $ operator2: num  4.9 4.5 5.3 5.3 6.3 5.9 2.5 3 3.9 8.2 ...
## $ operator3: num  3.3 4 3.4 4.5 4.2 4.7 2.3 2.8 2.6 6.4 ...
## $ operator4: num  5.3 5.5 5.7 5.9 5.5 6.3 3.1 2.7 4.6 6.8 ...
## $ operator5: num  4.4 3.3 4.7 4.7 4.9 4.6 2.4 1.3 2.2 6 ...
```

```
## Length Class Mode
##      0    NULL  NULL
```

```
url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/LongJumpData.dat"
olympic <- read.table(url,fill = TRUE)
olympic <- as.matrix(olympic)
oly_dat <- rbind(olympic[-1,1:2],olympic[-1,3:4],olympic[-1,5:6],olympic[-1,7:8])
oly_dat <- as.data.frame(oly_dat)
names(oly_dat) <- c("year","Long Jump")
#oly_table <- oly_dat %>% summarize(mean=mean(`Long Jump`),var=var(`Long Jump`))
oly_dat <- oly_dat[-c(23,24),]
oly_dat <- oly_dat %>% mutate_if(is.factor,as.character) %>% mutate_if(is.character,as.numeric)
head(oly_dat)
```

```
##   year Long Jump
## 1   -4   249.75
## 2    0   282.88
## 3    4   289.00
## 4    8   294.50
## 5   12   299.25
## 6   20   281.50
```

```
oly_dat %>% str() %>% summary()
```

```
## 'data.frame':   22 obs. of  2 variables:
## $ year      : num  -4 0 4 8 12 20 24 28 32 36 ...
## $ Long Jump: num  250 283 289 294 299 ...
```

```
## Length Class Mode
##      0    NULL  NULL
```

```
url <- 'https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/BrainandBodyWeight.dat'
weight <- read.table(url,fill = TRUE)
weight <- as.matrix(weight[-1,1:6])
weight_dat <- rbind(weight[,1:2],weight[,3:4],weight[,5:6])
weight_dat <- as.data.frame(weight_dat[-nrow(weight_dat),])
names(weight_dat) <- c("Body Wt","Brain Wt")
weight_dat <- weight_dat %>% mutate_if(is.factor,as.character) %>% mutate_if(is.character,as.numeric)
head(weight_dat)
```

```
##   Body Wt Brain Wt
## 1   3.385    44.5
## 2   0.480    15.5
## 3   1.350     8.1
## 4 465.000   423.0
## 5  36.330   119.5
## 6  27.660   115.0
```

```
weight_dat %>% str() %>% summary()
```

```
## 'data.frame':   62 obs. of  2 variables:
## $ Body Wt : num  3.38 0.48 1.35 465 36.33 ...
## $ Brain Wt: num  44.5 15.5 8.1 423 119.5 ...
```

```
## Length Class Mode
##      0  NULL  NULL
```

```
url <- 'https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/tomato.dat'
tomato <- read.csv(url,sep = '\t')
tomato <- tomato %>% mutate_if(is.factor,as.character)
```

```
## Warning in Ops.factor(left): '-' not meaningful for factors
```

```
## Warning in Ops.factor(left, right): '<' not meaningful for factors
```

```
##      X.this.needs.reformatting.to.read.into.Splus
## [1,]                                         NA
## [2,]                                         NA
## [3,]                                         NA
```

```
size <- paste(tomato[1,])
size <- strsplit(size," ")
size <- size[[1]][size[[1]]!=""]
size <- as.numeric(size[1:3])
size <- as.vector(size)

ife <- paste(tomato[2,])
ife <- strsplit(ife,' ')
ife <- ife[[1]][ife[[1]]!=""]
ife[2:4] <- strsplit(ife[2:4],',')
name <- as.matrix(rep(ife[[1]],3))
```

```

ife <- rbind(ife[[2]],ife[[3]],ife[[4]])
ife <- ife %>%
  cbind(name) %>%
  cbind(c(1000,2000,3000))

pusa <- paste(tomato[3,])
pusa <- strsplit(pusa, ' ')
pusa <- pusa[[1]][pusa[[1]]!=""]
pusa[2:4] <- strsplit(pusa[2:4],',')
name <- as.matrix(rep(pusa[[1]],3))
pusa <- rbind(pusa[[2]],pusa[[3]],pusa[[4]])
pusa <- pusa %>%
  cbind(name) %>%
  cbind(c(1000,2000,3000))
tomato_dat <- rbind(pusa,ife)
tomato_dat <- tomato_dat %>% as.data.frame()
colnames(tomato_dat) <- c('1st','2nd','3rd','name','plant density')
tomato_dat <- tomato_dat[,c("name","plant density",'1st','2nd','3rd')]

tomato_dat[,2:5] <- tomato_dat[,2:5] %>%
  mutate_if(is.factor,as.character) %>%
  mutate_if(is.character,as.numeric)

head(tomato_dat)

```

```

##           name plant density 1st  2nd  3rd
## 1 PusaEarlyDwarf      1000  8.1  8.6 10.1
## 2 PusaEarlyDwarf      2000 12.7 13.7 11.5
## 3 PusaEarlyDwarf      3000 14.4 15.4 13.7
## 4       Ife\\#1      1000 16.1 15.3 17.5
## 5       Ife\\#1      2000 16.6 19.2 18.5
## 6       Ife\\#1      3000 20.8 18.0 21.0

```

```

tomato_dat %>% str() %>% summary()

```

```

## 'data.frame':  6 obs. of  5 variables:
## $ name      : Factor w/ 2 levels "Ife\\#1","PusaEarlyDwarf": 2 2 2 1 1 1
## $ plant density: num  1000 2000 3000 1000 2000 3000
## $ 1st        : num  8.1 12.7 14.4 16.1 16.6 20.8
## $ 2nd        : num  8.6 13.7 15.4 15.3 19.2 18
## $ 3rd        : num  10.1 11.5 13.7 17.5 18.5 21

## Length Class  Mode
##      0    NULL  NULL

```

P5

```

library(dplyr)
plants <- read.csv('plants.csv')
plants <- plants %>%

```

```

select(Foliage_Color,pH_Min,pH_Max) %>%
na.omit() %>%
mutate(
  pH_Mean=(pH_Min+pH_Max)/2
) %>%
select(Foliage_Color,pH_Mean)

t <- lm(formula=pH_Mean~Foliage_Color,data=plants)
summary(t)

```

```

##
## Call:
## lm(formula = pH_Mean ~ Foliage_Color, data = plants)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -1.63750 -0.33410  0.00061  0.31590  2.01590
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      5.99939    0.05951  100.810 < 2e-16 ***
## Foliage_ColorGray-Green  0.41261    0.12312   3.351 0.000841 ***
## Foliage_ColorGreen      0.18471    0.06294   2.935 0.003430 **
## Foliage_ColorRed        0.16311    0.27594   0.591 0.554617
## Foliage_ColorWhite-Gray  0.44505    0.18924   2.352 0.018914 *
## Foliage_ColorYellow-Green -0.06189    0.13440  -0.461 0.645275
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.5389 on 826 degrees of freedom
## Multiple R-squared:  0.0234, Adjusted R-squared:  0.01749
## F-statistic: 3.958 on 5 and 826 DF,  p-value: 0.00149

```

```

test <- aov(pH_Mean~Foliage_Color,data = plants)
summary(test)

```

```

##              Df Sum Sq Mean Sq F value  Pr(>F)
## Foliage_Color    5   5.75  1.1495   3.958 0.00149 **
## Residuals      826 239.88  0.2904
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```