

HW4__Lin__Zhengzhi

zhengzhi lin

2019.9.22

problem 4

The first one way is to code regularly, by creating a lot variables. This way of coding is easy at when doing the project, but it is hard to review. The second way is using pipe to avoid creating variables, this makes code clean and tidy, easy to read and review.

problem 5

```
library(dplyr)
```

```
## Warning: package 'dplyr' was built under R version 3.5.1
```

```
##
```

```
## Attaching package: 'dplyr'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
## filter, lag
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
## intersect, setdiff, setequal, union
```

```
url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/Sensory.dat"
operator <- read.table(url, fill = TRUE)
op_dat <- as.matrix(operator[-c(1:2), ])
for (i in 1:10) {
  t <- op_dat[3 * i - 1, 1:5]
  t <- c(i, t)
  op_dat[3 * i - 1, ] <- t
  m <- op_dat[3 * i, 1 : 5]
  m <- c(i, m)
  op_dat[3 * i, ] <- m
}
op_dat <- op_dat %>% as.data.frame() %>% rename(item = V1,
  operator1 = V2, operator2 = V3, operator3 = V4, operator4 = V5,
  operator5 = V6) %>%
  mutate_if(is.factor, as.character) %>% mutate_if(is.character, as.numeric )
head(op_dat)
```

```
## item operator1 operator2 operator3 operator4 operator5
## 1 1 4.3 4.9 3.3 5.3 4.4
## 2 1 4.3 4.5 4.0 5.5 3.3
```

```
## 3      1      4.1      5.3      3.4      5.7      4.7
## 4      2      6.0      5.3      4.5      5.9      4.7
## 5      2      4.9      6.3      4.2      5.5      4.9
## 6      2      6.0      5.9      4.7      6.3      4.6
```

```
op_dat %>% str() %>% summary()
```

```
## 'data.frame': 30 obs. of 6 variables:
## $ item      : num 1 1 1 2 2 2 3 3 3 4 ...
## $ operator1: num 4.3 4.3 4.1 6 4.9 6 2.4 3.9 1.9 7.4 ...
## $ operator2: num 4.9 4.5 5.3 5.3 6.3 5.9 2.5 3 3.9 8.2 ...
## $ operator3: num 3.3 4 3.4 4.5 4.2 4.7 2.3 2.8 2.6 6.4 ...
## $ operator4: num 5.3 5.5 5.7 5.9 5.5 6.3 3.1 2.7 4.6 6.8 ...
## $ operator5: num 4.4 3.3 4.7 4.7 4.9 4.6 2.4 1.3 2.2 6 ...
```

```
## Length Class Mode
##      0    NULL  NULL
```

```
url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/LongJumpData.dat"
olympic <- read.table(url, fill = TRUE)
olympic <- olympic[- 1, ]
o1 <- olympic[, 1 : 2] %>% rename(year = V1, "Long jump" = V2) %>%
  mutate_if(is.factor, as.character) %>% mutate_if(is.character, as.numeric)
o2 <- olympic[, 3 : 4] %>% rename(year = V3, "Long jump" = V4) %>%
  mutate_if(is.factor, as.character) %>% mutate_if(is.character, as.numeric)
o3 <- olympic[, 5 : 6] %>% rename(year = V5, "Long jump" = V6) %>%
  mutate_if(is.factor, as.character) %>%
  mutate_if(is.character, as.numeric)
o4 <- olympic[, 7 : 8] %>% rename(year = V7, "Long jump" = V8) %>%
  mutate_if(is.factor, as.character) %>%
  mutate_if(is.character, as.numeric)

oly_dat <- o1 %>%
  bind_rows(o2) %>% bind_rows(o3) %>% bind_rows(o4)
head(oly_dat)
```

```
##   year Long jump
## 1   -4    249.75
## 2    0    282.88
## 3    4    289.00
## 4    8    294.50
## 5   12    299.25
## 6   20    281.50
```

```
oly_dat %>% str() %>% summary()
```

```
## 'data.frame': 24 obs. of 2 variables:
## $ year      : num -4 0 4 8 12 20 24 28 32 36 ...
## $ Long jump: num 250 283 289 294 299 ...
```

```
## Length Class Mode
##      0    NULL  NULL
```

```

url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/BrainandBodyWeight.dat"
weight <- read.table(url, fill = TRUE)
weight <- weight[- 1, 1 : 6]
w1 <- weight[, 1 : 2] %>% rename("Body Wt" = V1, "Brain Wt" = V2) %>%
  mutate_if(is.factor, as.character) %>% mutate_if(is.character, as.numeric)
w2 <- weight[, 3 : 4] %>% rename("Body Wt" = V3, "Brain Wt" = V4) %>%
  mutate_if(is.factor, as.character) %>% mutate_if(is.character, as.numeric)
w3 <- weight[, 5 : 6] %>% rename("Body Wt" = V5, "Brain Wt" = V6) %>%
  mutate_if(is.factor, as.character) %>%
  mutate_if(is.character, as.numeric)
weight_dat <- w1 %>%
  bind_rows(w2) %>% bind_rows(w3)
head(weight_dat)

```

```

##   Body Wt Brain Wt
## 1   3.385    44.5
## 2   0.480    15.5
## 3   1.350     8.1
## 4 465.000   423.0
## 5  36.330   119.5
## 6  27.660   115.0

```

```
weight_dat %>% str() %>% summary()
```

```

## 'data.frame':   63 obs. of  2 variables:
## $ Body Wt : num  3.38 0.48 1.35 465 36.33 ...
## $ Brain Wt: num  44.5 15.5 8.1 423 119.5 ...

```

```

## Length Class Mode
##      0  NULL  NULL

```

```

url <- "https://www2.isye.gatech.edu/~jeffwu/wuhamadabook/data/tomato.dat"
tomato <- read.csv(url, sep = "\t")
tomato <- tomato %>% mutate_if(is.factor, as.character)

```

```
## Warning in Ops.factor(left): '-' not meaningful for factors
```

```
## Warning in Ops.factor(left, right): '<' not meaningful for factors
```

```

##      X.this.needs.reformatting.to.read.into.Splus
## [1,]                                     NA
## [2,]                                     NA
## [3,]                                     NA

```

```

size <- paste(tomato[1, ])
size <- strsplit(size, " ")
size <- size[[1]][size[[1]] != ""]
size <- as.numeric(size[1 : 3])
size <- as.vector(size)

```

```

ife <- paste(tomato[2, ])
ife <- strsplit(ife, " ")
ife <- ife[[1]][ife[[1]] != ""]
ife[2 : 4] <- strsplit(ife[2: 4], ",")
name <- as.matrix(rep(ife[[1]], 3))
ife <- rbind(ife[[2]], ife[[3]], ife[[4]])
ife <- ife %>%
  cbind(name) %>%
  cbind(c(1000, 2000, 3000))

pusa <- paste(tomato[3, ])
pusa <- strsplit(pusa, " ")
pusa <- pusa[[1]][pusa[[1]] != ""]
pusa[2 : 4] <- strsplit(pusa[2:4], ",")
name <- as.matrix(rep(pusa[[1]], 3))
pusa <- rbind(pusa[[2]], pusa[[3]], pusa[[4]])
pusa <- pusa %>%
  cbind(name) %>%
  cbind(c(1000, 2000, 3000))
tomato_dat <- rbind(pusa, ife)
tomato_dat <- tomato_dat %>% as.data.frame()
colnames(tomato_dat) <- c("1st", "2nd", "3rd", "name", "plant density")
tomato_dat <- tomato_dat[, c("name", "plant density", "1st", "2nd", "3rd")]

tomato_dat[, 2 : 5] <- tomato_dat[, 2 : 5] %>%
  mutate_if(is.factor, as.character) %>%
  mutate_if(is.character, as.numeric)

head(tomato_dat)

```

```

##           name plant density  1st  2nd  3rd
## 1 PusaEarlyDwarf      1000  8.1  8.6 10.1
## 2 PusaEarlyDwarf      2000 12.7 13.7 11.5
## 3 PusaEarlyDwarf      3000 14.4 15.4 13.7
## 4       Ife\\#1      1000 16.1 15.3 17.5
## 5       Ife\\#1      2000 16.6 19.2 18.5
## 6       Ife\\#1      3000 20.8 18.0 21.0

```

```
tomato_dat %>% str() %>% summary()
```

```

## 'data.frame':  6 obs. of  5 variables:
## $ name      : Factor w/ 2 levels "Ife\\#1","PusaEarlyDwarf": 2 2 2 1 1 1
## $ plant density: num  1000 2000 3000 1000 2000 3000
## $ 1st        : num  8.1 12.7 14.4 16.1 16.6 20.8
## $ 2nd        : num  8.6 13.7 15.4 15.3 19.2 18
## $ 3rd        : num  10.1 11.5 13.7 17.5 18.5 21

## Length Class Mode
##      0    NULL  NULL

```

Problem 6

```
library(ggplot2)
```

```
## Warning: package 'ggplot2' was built under R version 3.5.1
```

```
library(gridExtra)
```

```
## Warning: package 'gridExtra' was built under R version 3.5.3
```

```
##
```

```
## Attaching package: 'gridExtra'
```

```
## The following object is masked from 'package:dplyr':
```

```
##
```

```
##      combine
```

```
dat_ori <- readRDS("HW4_data.rds", refhook = NULL)
```

```
dat <- dat_ori[1:13,]
```

```
#my function
```

```
func_stat <- function(){
```

```
  mean <- mean(dat$dev1)
```

```
  mean2 <- mean(dat$dev2)
```

```
  sd <- sqrt(var(dat$dev1))
```

```
  sd2 <- sqrt(var(dat$dev2))
```

```
  correlation <- cor(dat$dev1, dat$dev2)
```

```
  tab <- as.data.frame(cbind(mean, mean2, sd, sd2, correlation))
```

```
  names(tab) <- c("dev1 mean", "dev2 mean", "dev1 sd", "dev2 sd", "correlation")
```

```
  return(tab)
```

```
}
```

```
func_stat()
```

```
##   dev1 mean dev2 mean  dev1 sd  dev2 sd correlation
```

```
## 1  35.91715  80.07891 11.15726 13.32958   0.9681702
```

```
p <- ggplot(data = dat)
```


```
p1 <- p + geom_boxplot(aes(y = dev1)) + ggtitle("boxplot for dev1")
```

```
p2 <- p + geom_boxplot(aes(y = dev2)) + ggtitle("boxplot for dev2")
```



```
p3 <- p + geom_violin(aes(x = "", y = dev1)) + ggtitle("violin plot for dev2")
```

```
p4 <- p + geom_violin(aes(x = "", y = dev2)) + ggtitle("violin plot for dev2")
```

```
grid.arrange(p1, p2, ncol = 2)
```



```
grid.arrange(p3, p4, ncol = 2)
```



Problem 7

Reimann sum is .8556252

```
func.1 <- function(x){
  y <- exp(- x ^ 2 / 2)
  return(y)
}
x <- seq(0, 1, by = 1e-6)
sum(func.1(x) * (1e-6))
```

```
## [1] 0.8556252
```


Problem 8

One of solutions is $x = -3.930114$

```
library(ggplot2)
func <- function(x){
  y <- 3 ^ x - sin(x) + cos(5 * x)
  return(y)
}
```

```
d_func <- function(x){
  y <- 3 ^ x * log(3) - cos(x) - 5 * sin(5 * x)
  return(y)
}

ggplot(data = data.frame(x = 0,y = 0), mapping = aes(x = x)) +
  stat_function(fun = func) +
  xlim(-5, 2.5) +
  geom_abline(intercept = 0, slope = 0, colour = "red")
```



```
x_0 <- -2.5
eps <- 1e-6
x <- x_0
while (abs(func(x)-0) > eps) {
  x <- x - func(x)/d_func(x)
}
x
```

```
## [1] -3.930114
```