

ebb-ai · Claude Code plugin

Vitalii Borovyk

ebb-ai · Claude Code plugin

A one-command install that turns any Claude Code session into a cost-aware, grid-aware AI workload scheduler. Defer non-urgent LLM tasks (overnight summaries, batch analyses, scheduled compliance scans) to cheap off-peak windows — ~50% cost savings via Batch APIs, smoother data-center load, and an auditable carbon receipt for every dispatch.

ebb-ai ships a Claude Code plugin that wires the ebb-ai MCP server and three slash commands into your CLI in one step.

Install

1. Add the marketplace (this repo)

```
claude plugin marketplace add Vitalini/ebb-ai
```

2. Install the plugin

```
claude plugin install ebb-ai
```

That's it. Restart `claude` and the plugin is live. Full command surface:

Command	Purpose
<code>/ebb-ai:defer <task> --by <when></code>	Queue a deferrable LLM task
<code>/ebb-ai:plan <task> --by <when></code>	Preview the chosen window, no commit
<code>/ebb-ai:check [<id> \ --all]</code>	List or detail of queued tasks
<code>/ebb-ai:cancel <id> \ --all</code>	Remove a task (or all queued/scheduled)
<code>/ebb-ai:expedite <id></code>	Run now, bypass the carbon window
<code>/ebb-ai:reschedule <id> --by <new></code>	Change the deadline, re-score
<code>/ebb-ai:retry <id></code>	Re-dispatch a failed task
<code>/ebb-ai:grid <zone></code>	Just look at the grid, no task involved

Plus a skill, `carbon-aware-coding`, which teaches Claude when to reach for `/ebb-ai:defer` automatically — for example when you say “*do this later*” or “*by tomorrow*”.

The plugin auto-configures the `ebb-ai` MCP server via `npx -y @ebb-ai/mcp` on first invocation, so no separate `claude mcp add` step is needed.

Persistence (new in v0.7.1)

Tasks queued via `/ebb-ai:defer` are persisted to `~/.ebb-ai/queue.db` (SQLite) by default. The queue survives Claude Code restarts, is shared across MCP hosts (Claude Code, Claude Desktop, Cursor), and can be inspected from the CLI:

```
npx @ebb-ai/cli list
```

To override the path: set `EBB_DB_PATH=/some/where/queue.db` in the plugin’s `.mcp.json` env block (or your shell). Use `EBB_DB_PATH=:memory:` to opt out of persistence (mainly useful for tests).

Actually dispatching tasks

The MCP server **queues** tasks but does not run a clock. Actual dispatch at the chosen window requires the **ebb tick daemon**:

```
npm install -g @ebb-ai/cli
ebb install      # registers launchd (macOS) / systemd (Linux)
                  cron-tick
ebb status       # confirm the tick is wired
```

Until the daemon is installed, tasks sit queued and you can dispatch them manually with `ebb tick --once`. This is a known v0.7.1 sharp edge — the plugin install path doesn’t auto-install the daemon yet (adds reasonably-scary system-level state). v0.8 will offer an interactive opt-in.

Result delivery

Three options to get the result back after a task completes:

1. **Poll** — `/ebb-ai:check <task_id>` returns the LLM response under `result` once the receipt is written.
2. **File output** — pass `--output <abs-path>` at defer time. The dispatcher writes `{ taskId, result, receipt }` as JSON to that path on completion. Pair with `tail -f` or a file-watcher to get a desktop-grade “task done” surface.
3. **CLI inbox** — point `--output` at `~/.ebb-ai/inbox/<id>.json`; a tiny `fswatch / entr` loop can pick it up and forward to Telegram, email, macOS notifications — your choice.

Example

```
> /ebb-ai:defer "Summarize today's GitHub notifications" --by 4h
--region US-CAL-CISO
```

```
Deferred ✓
  task id      7f3a2b9e
  scheduled for in 3h, 22:15 UTC
  est. carbon  0.34 g CO2e
  savings      38% cleaner than running now
  band         clean
  check status /ebb-ai:check 7f3a2b9e
```

Three hours later:

```
> /ebb-ai:check 7f3a2b9e
status      completed
region      US-CAL-CISO
scheduled   22:15 UTC (4h ago)
completed   22:15:08 UTC
estimated   0.34 g CO2e
actual      0.31 g CO2e (-9%)
result      <the summary>
```

What ships in the plugin

```
ebb-ai/
├── .claude-plugin/
│   └── plugin.json
├── .mcp.json
├── commands/
│   ├── defer.md
│   ├── check.md
│   └── grid.md
└── skills/
    └── carbon-aware-coding/
        └── SKILL.md
```

The `.mcp.json` declares an `ebb-ai` MCP server that runs `npx -y @ebb-ai/mcp`. That npm package is the same `@ebb-ai/mcp` you would otherwise install yourself — the plugin just makes the wiring one command instead of three.

Without the plugin

If you do not want the slash commands and just want the MCP server itself, you can still install it directly:

```
claude mcp add ebb-ai npx -- -y @ebb-ai/mcp
```

You will get the three MCP tools (`get_grid_forecast`, `schedule_task`, `check_queue_status`) but not the slash-command shortcuts or the carbon-aware-coding skill.

License

Apache-2.0. See [LICENSE](#).