Predicting the Next Category and Region of a Visit

Speaker cards v2: 13 main slides, about 16 minutes of talk, about 14 minutes for questions

Slot: 30 minutes *including* questions. First talk of the symposium, right after the 8:15 opening. Audience: wireless networking and mobility management, not machine learning. Deck: `slides/main.pdf`. Footer numbers 1–12 are the main slides; backups B1–B11 follow.

Time marks	end of S2b ≈ 3:20 · end of S4 ≈ 6:20 · end of S7 ≈ 11:15 · end of S9 ≈ 13:25 · end ≈ 16:30
If short of time	trim S3 and S5, never S2b, S7 or S10
Three sentences never cut	the 2-point margin fixed in advance (S4) · "deficits, not ties" (S7) · "one pass costs more compute; the gain is operational" (S10)
Jump to a backup	Bk is PDF page $13 + k$ (B1 = 14 … B11 = 24): type the number, Enter

S1 · Title — 20 s

On screen: title, three authors, NESPeD-LAB / UFV.

SAY

- "Good morning. I am Vitor Hugo, from the Federal University of Viçosa, in Brazil. This is joint work with Germano dos Santos and Fabrício Silva."
- "We ask whether one model can predict both what kind of place a person visits next, and in which neighborhood."

S2 · One person's day, and two questions — 90 s

On screen: schematic map, two boxes, a definition line.

Rehearse aloud. It wins or loses the room at 8:30.

SAY

- "On a location-based social network such as Gowalla, people share the places they visit. Each shared visit is a check-in: a place, which this literature calls a point of interest, and a time."
- "Here is one person's day: nine check-ins. Coffee, gym, office, lunch. The tenth is the question."
- "A large body of work predicts the exact next place; Texas alone has about a hundred and sixty thousand of them. We predict two properties of the next visit instead."
- "What kind of place: one of seven types, such as food, shopping, nightlife. And which neighborhood: a census tract in the U.S., a *mahalle* in Istanbul; from 520 in Istanbul to 8,501 in California."
- "Both are things a service can act on. The kind of place says what the user will want. The neighborhood says where to prepare: cache content where the user is heading, provision capacity before demand arrives. Over many users, that is where demand is heading."
- "Handover prediction already enables anticipatory adaptation at the radio cell; Vielhaus and colleagues showed it here at MobiWac in 2022. Our unit is a different one: the neighborhood. A census tract is not a cell, and we claim nothing about cells or handover."

IF ASKED "Is that a real user?" No. It is a schematic of the input format, not a case from the data.

NEVER "nobody needs the next place"; "easier"; "most work"; a tract is "coarser" than a cell (the paper never compares sizes).

S2b · Two models, or one? — 90 s

On screen: two options, the gap line, the question in a box, the short answer.

SAY

- "The reference point is one dedicated model per question: two things to train, version and serve."
- "Multi-task learning puts both in one model: one artifact to train, version and deploy, and the two tasks might help each other. But sharing has a cost: the shared parameters can settle on a compromise that is good for neither task, helping one while hurting the other."

- "The field increasingly models several granularities at once, but in those systems, such as MCMG and HMT-GRN, category and region are helpers for predicting the exact next place. To our knowledge, predicting a fine-grained region as an answer in its own right, next to category and with no next-place target, is underexplored."
- "So this is our question: can one model predict both, and what does it cost?"
- "The short answer, so you can decide whether to keep listening: yes, at a measured price. On the neighborhood question, one model outperforms a dedicated model at the two largest datasets and is at most 0.87 points behind at the other four. On the kind-of-place question, the two are within half a point, and how we represent a visit mattered more than one model versus two. Here is how."

NEVER "known to fail"; "first"; "few multi-task models"; "one cost" or "cheaper".

S3 · Check2HGI: a fourth level below the place 100 s

On screen: one line on place embeddings, the Check2HGI diagram, two lines.

SAY

- "A model cannot read a place name; it needs a vector per input. Place embeddings learn one vector per place, so that similar or nearby places sit close together. Deep Graph Infomax learns them on a network of places. Hierarchical Graph Infomax adds the geography: place, then region, then city. Both give one vector per place. So two visits to the same coffee shop, Tuesday morning and Saturday night, look identical to the model."
- "We add a fourth level below the place: the check-in itself. Each visit gets its own 64-dimensional vector, built from its place's category, the hour and day of week, and four elapsed-time values, such as the time since the previous visit."
- *[point left to right]* "Reading the figure left to right: each check-in becomes a vector; those vectors are pooled into their place; and the place, region and city levels sit on top. This per-visit vector is what our model reads. The magenta copy is a shuffled graph, used only as a training signal."
- "Two things to keep. The graph is trained without the task labels: it never sees the next category or the next region. And it is built from the past alone: edges between consecutive visits run forward in time only."

IF ASKED "Is it pre-trained?" The per-visit vectors come from an unsupervised graph trained on the same data; it is not an external pre-trained encoder.

S4 · How it was measured 80 s

On screen: five rows: Regions, Split, Scored, Repeated, Decided.

SAY

- "Before the results, how we measured. Regions are census tracts, or *mahalle* in Istanbul: 520 in Istanbul to 8,501 in California."
- "We split by user: the prediction models never train on a test user's visits. The representation is the exception, and I come back to it in the limits."
- "Category is scored with macro-F1, which counts the seven categories equally; always predicting the most common one scores between 5.7 and 7.3. Region is scored with Acc@10: is the true region among the model's top ten? A random top ten is right at most about two percent of the time."
- "Each configuration is trained twenty times: four seeds, five folds each."
- **Never cut:** "And for region we wrote down what counts as not worse, two Acc@10 points, before we saw any result. Two points is below the level at which a service that acts on which neighborhood will be busy would behave differently."

S5 · Result 1: the representation 100 s

On screen: six-row table, check-in level vs place level (HGI).

SAY

- "First result, and the most controlled one: only the input changes. Same model, same folds, same windows."

- "With a vector per visit instead of per place, next-category prediction improves at all six datasets and in every fold, by 0.23 to 2.81 points."
- "The gain is larger at the three smaller datasets and under one point at the three largest. At Florida the fold-to-fold spread is larger than the gap, and the paired test does not separate the two."
- **Say this before anyone asks:** "And to be clear: a control that simply adds the raw per-visit features to the place vector gains as much or more at Alabama and Florida, and less at Arizona; we ran it at three datasets. What the graph adds beyond those features, this control does not separate." (Backup B9.)

NUMBERS AL +1.62, AZ +2.58, Istanbul +2.81 · Florida +0.23, fold sd 0.42, $p = 0.067$.

IF ASKED "These numbers differ slightly from slide 7." This table is one seed; slide 7 averages four. CA and TX place cells: their row matching could not be checked from what is on disk; do not defend them as verified pairs. Both gains are under one point.

S6 · One model for two tasks 95 s

On screen: the model figure; four short lines on the right.

SAY

- "Now the one model. In multi-task learning, one model does several jobs at once by sharing most of its parts. The risk: whatever the two tasks share can settle on a compromise worse for each than a dedicated model would be."
- "Here is how this model is built. Each task has its own input and its own small encoder, with no shared weights. The category task reads the window of per-visit vectors. The region task reads the same visits, each represented by the vector of its region."
- "Both go into the shared trunk, the only place where the two tasks meet. In the trunk, attention lets each task read the other's features, while each keeps its own weights. So the tasks share by exchanging information, not by owning layers in common."
- "The region task also keeps a private spatial path that the category task never touches: it keeps what is purely spatial out of the exchange."
- "Whether one model holds up against two is the next slide."

NEVER count blocks or widths; "the private path was added because of negative transfer" (untested).

S7 · One model, two answers: the price 100 s

On screen: Dedicated vs Joint; green = outperforms; bold = the larger.

SAY

- "This is the price of one model instead of two."
- "On region, the joint model outperforms the dedicated model at the two largest datasets, Texas and California, by about one point, in twenty of twenty folds. At the other four it is behind by at most 0.87 points, inside the two-point margin we fixed in advance."
- "Those four are deficits, not ties: each interval lies below zero, Istanbul only just. The intervals are in a backup slide."
- "On category, the joint model is ahead at Florida. The other five differences are small, in both directions, and unresolved; every interval is within half a point."
- **The thesis sentence:** "The trade is a measured one and not a free substitution."
- "Two cautions, with the numbers. The joint model is also the larger model, and this design does not separate size from sharing. And California has more regions than Texas and a smaller gain, so that pattern is an observation, not a law."

NUMBERS region: Texas +1.21, California +1.06 (20 of 20 folds); largest deficit Alabama −0.87 · category: Florida +0.19 (19 of 20 folds).

IF ASKED "Your Δ is not the difference of the columns." Δ is the paired mean over the four seeds, so it can differ from the rounded columns in the second decimal.

NEVER "ties", "matches", "no difference", "the same" for the four region cells.

S8 · And against published systems 70 s

On screen: four externals vs Dedicated vs Joint; bold best, underline second; a four-line legend.

SAY

- "Four published systems, all run on our data. POI-RGNN predicts the next category; we re-implemented it. HMT-GRN is a multi-task model for next place and next regions: we kept its multi-task structure, removed the next-place parts, and ran it on our windows and folds, read at its best epoch like our models. STAN is a next-location attention model, re-implemented with its own representations, and adapted to rank regions. ReHDM is a reference under its own published split."
- "Both our models, the dedicated and the joint, are above every system we compared against; the joint model by at least 4.11 points on category and 3.55 on region. That margin includes the representation's advantage, so it is not evidence for sharing."

IF ASKED "Do they run on your folds?" Only HMT-GRN runs on our windows and folds; STAN and ReHDM use their own splits. The 3.55 is against STAN at Florida on its own split; on our folds the closest is HMT-GRN at Florida, 3.78.

NEVER "both our models by at least four points". The margins are the joint model's only.

S9 · What a service would receive 60 s

On screen: three labelled lines and a caveat box.

SAY

- "What would a service receive? First, time to act: half of the next visits come within under half an hour in Florida, and within five and a half hours in Istanbul; five to twenty-seven percent come more than three days later."
- "Second, a shortlist. Ask the model for its ten most likely neighborhoods. In California, with eight and a half thousand neighborhoods, the true one is in that list sixty-four percent of the time; in Texas, sixty-six. That is the Acc@10 you saw on slide seven, read as a hit rate."
- "For scale, a transition table with no learning already gets fifty-one to seventy-two; the model is four to ten points above it."
- "We built and evaluated no such service. This is motivation, not a measured result."

NEVER any distance in kilometers; "24 minutes" (the median is about 26: say "under half an hour").

S10 · What it costs, and four limits 95 s

On screen: parameters and the compute sentence (left), four limits (right).

SAY

- "What does one model cost? The joint model is larger than the two dedicated models combined: 4.2 million parameters against 1.9 million at Alabama, 5.2 against 2.8 at California, and one forward pass costs more compute than running the two small models. The gain is operational, not compute: one artifact to train, version and deploy, and two answers."
- Limit 1: "The representation is trained once over all users. Rebuilding it per fold from training users only moved the dedicated models by at most 0.17 macro-F1 and 0.13 Acc@10, at one seed and at the datasets checked."
- Limit 2: "Epoch selection reads the fold the score is read on, so absolute scores are optimistic. The joint-versus-dedicated comparison is affected far less."
- Limit 3: "The vector of a visit is built from the visits before it and nothing after. That costs context a two-way model would have. It is also what keeps any visit vector from carrying its own target, so I would not trade it."
- Limit 4: "The joint model is larger, so the two region gains may come from size rather than from sharing. This design does not separate them, and I do not credit sharing for them. What does not depend on that is the result itself: one model, both answers, at these levels."

IF ASKED latency or energy: "About five million parameters and a window of nine visits per query. We did not measure latency or energy."

S11 · Conclusion 70 s

On screen: Built / Measured / Not shown / Next, and the tagline.

SAY

- "To conclude. We built two things: a check-in-level representation that extends hierarchical graph infomax from the place to the individual visit, and one model that answers both questions."
- "What we measured: on region the joint model outperforms the dedicated model at Texas and California and stays inside the two-point margin elsewhere, as deficits, not ties; on category the two are within half a point. The trade is measured, not free."
- "What this does not show is that sharing is the cause: on category the representation matters more than one model versus two, and the region gains may come from size."
- "The results are promising on the point a service cares about, one model carrying both answers at a measured price, and they leave room to work: a search for the joint model at Texas and California, separating size from sharing, and measuring how far a miss lands, inside a service that uses the shortlist."
- Close: "What a user will do next, and where, from one model instead of two. Thank you."

NEVER "a new approach"; "unified model"; "in one forward pass instead of two" (the joint pass costs more compute).

S12 · Thank you 20 s

On screen: Questions? Code, data, funders.

SAY

- "The code, the model, the representation, the baselines and the statistical tests are public at this link, and both datasets are public. This work was supported by FAPEMIG, CNPq and CAPES. I am happy to take questions."
- **Leave this slide up during questions.** Jump to a backup only when needed, then come back.

Questions: the prepared answers

Question	Answer	Slide
"Your numbers do not match the paper." *(most likely: the PDF is in the proceedings)*	"The paper mixed sources from different versions; the corrected values come from the delivered build." For the HMT-GRN column: "the paper read HMT-GRN at a fixed final epoch; here it is read at its best validation epoch, the same rule as our models." That correction *favors* the competitor. Example if asked: "the Istanbul place-level cell was computed on an older build; matched on the same rows the gain is 2.81." The message survives: a gain at all six datasets and every fold. Do not apologize or dramatize.	S8
"Isn't it just a bigger model?" *(this room will ask)*	First, the paper-level answer: "Possibly. The design does not separate size from sharing, so we declare it rather than claim transfer. The claim is about the model: one artifact gives both answers, inside the margin, and above the dedicated model at the two largest datasets." **Only if pressed** ("did you test it?"): "One single-seed control at California, not in the paper: a dedicated region model at the joint model's parameter count scores 0.41 above it, so at California the gain measures capacity. Texas has no matched control." Never deny it was run; never put it on a slide.	S10
"How do you know a visit vector does not see its target?"	By the mechanism: each visit node draws only on the visits before it, in training and at readout, and the graph is trained without the task labels.	B4
"Do the external systems run on your folds?"	"Only HMT-GRN runs on our windows and folds. STAN and ReHDM use their own splits."	B7
"Where does the 2-point margin come from? Is that standard?"	Not a convention of this field. Non-inferiority margins come from clinical trials, where the margin is fixed in advance from what matters in practice (TOST, Lakens 2017). Ours was written before any result: two points is below the level at which a service acting on which neighborhood will be busy would behave differently. The seed-to-seed standard deviation of the paired difference is 0.02 to 0.16, far below the margin.	B2
"Why not one point?"	"At one point, Istanbul, Arizona and Florida would still pass; Alabama would not."	B10
"Would a Markov chain do this?"	A first-order Markov chain over regions gets 51.23 to 72.47 Acc@10; the joint model exceeds it by 4.1 to 10.0 at every dataset. Say the narrowest first: Florida, +4.07. Talk only about *our* margin over the floor; at its best epoch HMT-GRN is above the floor too.	B3
"Isn't this just the timestamp added to the place vector?" *(the most dangerous one)*	Largely, yes, on category: a control that adds the raw features to the place vector gains as much or more at Alabama and Florida, less at Arizona (+1.73 / +1.70 / +1.02). What the graph adds beyond that, this control does not separate.	B9
"Why not give the vector its neighbors, or later visits?"	Nearby places are already linked at the place level. What is excluded on purpose is the user's *later* visits: letting them in is exactly what would let a vector carry its target.	B4
"Does it work for new places or new users?"	Not without retraining: the representation is trained on each dataset's graph (transductive). An inductive variant that embeds unseen places and users is future work.	none

Question	Answer	Slide
"Then what is multi-task learning for?"	On category the representation moves the score more than the choice between one model and two. Whether the exchange between tasks adds anything beyond it is not separated here. What one model gives for certain is operational.	B6
"Was the tuning fair?"	The dedicated category model received the wider search; the joint model at Texas and California uses a configuration transferred from the other datasets. Where the searches differ, it favors the dedicated model.	none
"What does one model instead of two cost?"	4.2 M vs 1.9 M parameters (AL), 5.2 M vs 2.8 M (CA), against the two dedicated models combined; one pass costs more compute.	B5
"Does the gain grow with the number of regions?"	No. California has more regions than Texas and a smaller gain. An observation, not a law.	B8
"And the confidence intervals?"	The twelve cells with 90% intervals.	B10
"Why census tracts and not a grid?"	A grid cell is the usual target; we use official neighborhood-scale units, 520 to 8,501 per dataset.	B1
"How far off are the misses, in kilometers?" *(rehearse: it comes as a friendly question)*	"Not measured. It needs per-visit predictions the evaluation path does not keep. It is the first thing we would measure for a service." **Never give a distance.**	none
"Latency? Energy? Can it run on the edge?"	"About five million parameters and a window of nine visits per query. We did not measure latency or energy."	none
"You split by user, not by time. Drift? Retraining?"	"The split is by user and not by time, so the evaluation does not measure drift or the effect of sporadic events." The upside: the prediction models never saw the test users.	none
"Gowalla is from 2009–2011."	Istanbul comes from Massive-STEPS, a recent collection, and Gowalla is the standard benchmark of this line. What matters is the pattern that repeats across continents and periods.	none
"Privacy: the representation was trained on everyone."	Server side, on the operator's own logs; no privacy mechanism is claimed. Limit 1 measures the effect: rebuilding it with training users only moved the dedicated models by at most 0.17 macro-F1 and 0.13 Acc@10, at one seed and the datasets checked.	S10
"Only four runs?"	Each seed is a full five-fold cross-validation: twenty trained models per configuration. The standard deviation of the paired difference is 0.02 to 0.16 across the four seeds.	S4
"Who would consume this?"	Name the consumer: load and demand anticipation at neighborhood level, caching, capacity planning, by an operator or a city service.	S9

Never say

- "beats" or "wins". The verb is **outperforms**.
- "first", "a new approach", "few multi-task models". The paper says the pair as end targets is *underexplored*, and its novelty is the combination.
- "known to fail". Sharing *can* cost; this paper measures it for this pair.
- "ties", "matches", "no difference" for the four region cells. They are deficits inside a registered margin.
- "in one forward pass instead of two" or "cheaper". The joint pass costs more compute.
- Any distance in kilometers. Handover or cell-level gains as a claim.
- "Both our models by at least four points". The margins on S8 belong to the joint model.
- "The Markov floor beats the external systems".
- "The gain comes from sharing".
- Any number read from the printed paper where the deck shows a different one. Use the slide.

On the day

- 8:30 in Paris is 4:30 in Brasília (France leaves summer time on 25 Oct).
- Arrive before the 8:15 opening and test the projector with the PDF. The deck is 16:9.
- Carry the PDF on a USB stick and in the cloud.
- The program publishes no room or chair. Introduce yourself to the chair before the session.
- Leave slide 12 (code, data, funders) on screen during questions.