

# 15) Cross-Validation

Vitor Kamada


February 2018

## Tables, Graphics, and Figures from **An Introduction to Statistical Learning**



James et al. (2017): Chapters: 5.1, 5.3.1, 5.3.2,  
5.3.3

# Training Set vs Validation or Hold-out Set


Randomly division in two part:



## Random Split (10x)



# Leave-One-Out Cross-Validation (LOOCV)




$\{(x_2, y_2), \dots, (x_n, y_n)\} \rightarrow \text{Training Set}$

$(x_1, y_1) \rightarrow \text{Validation Set}$

$$MSE_1 = (y_1 - \hat{y}_1)^2$$

$$CV_{(n)} = \frac{1}{n} \sum_{i=1}^n MSE_i$$

# LOOCV: mpg on hp ...



# LOOCV: Computationally Expensive?


$$CV_{(n)} = \frac{1}{n} \sum_{i=1}^n \left( \frac{y_i - \hat{y}_i}{1 - h_i} \right)^2$$

$$h_i = \frac{1}{n} + \frac{(x_i - \bar{x})^2}{\sum_{i=1}^n (x_i - \bar{x})^2}$$




# k-Fold Cross-Validation

$$CV_{(k)} = \frac{1}{k} \sum_{i=1}^k MSE_i$$



# 10-fold CV: mpg on hp ...



# Cross-Validation on Classification Problems


$$CV_{(n)} = \frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i)$$

$$\log\left(\frac{p}{1-p}\right) = \beta_0 + \beta_1 X_1 + \beta_2 X_1^2 + \beta_3 X_2 + \beta_4 X_2^2$$


Test Error Rates: 20.1% and 19.7%

Bayes Error Rate: 13.3%

Degree=1




Degree=2




# Test Error Rates: 16% and 16.2%



Degree=3



Degree=4



# Test (brown), Training (blue), and 10-fold CV Error (black)



```
attach(Auto); set.seed(1); train=sample(392,196)
```

```
lm.fit=lm(mpg~horsepower,data=Auto,subset=train)  
mean((mpg-predict(lm.fit,Auto))[-train]^2)
```

**26.14**

```
lm.fit2=lm(mpg~poly(horsepower,2),data=Auto,subset=train)  
mean((mpg-predict(lm.fit2,Auto))[-train]^2)
```

**19.82**

```
lm.fit3=lm(mpg~poly(horsepower,3),data=Auto,subset=train)  
mean((mpg-predict(lm.fit3,Auto))[-train]^2)
```

**19.78**

```
set.seed(2); train=sample(392,196)
```

```
lm.fit=lm(mpg~horsepower,subset=train)  
mean((mpg-predict(lm.fit,Auto))[-train]^2)
```

**23.3**

```
lm.fit2=lm(mpg~poly(horsepower,2),data=Auto,subset=train)  
mean((mpg-predict(lm.fit2,Auto))[-train]^2)
```

**18.9**

```
lm.fit3=lm(mpg~poly(horsepower,3),data=Auto,subset=train)  
mean((mpg-predict(lm.fit3,Auto))[-train]^2)
```

**19.3**



# LOOCV in R

```
library(boot); lm.fit=glm(mpg~horsepower,data=Auto)  
cv.err=cv.glm(Auto,glm.fit); cv.err$delta
```

**24.23151**

**24.23114**

```
cv.error=rep(0,5)  
for (i in 1:5){  
  glm.fit=glm(mpg~poly(horsepower,i),data=Auto)  
  cv.error[i]=cv.glm(Auto,glm.fit)$delta[1] }  
cv.error
```

**24.23**

**19.25**

**19.33**

**19.42**

**19.03**

## k-Fold Cross-Validation in R

```
set.seed(17); cv.error.10=rep(0,10)
for (i in 1:10){
  glm.fit=glm(mpg~poly(horsepower,i),data=Auto)
  cv.error.10[i]=cv.glm(Auto,glm.fit,K=10)$delta[1]
}
cv.error.10
```

**24.20 19.19 19.3 19.34 18.88**

**19.02 18.9 19.71 18.95 19.50**