Selects

Consulta JIRA meus tickets Gatekeeper

```
project = Gatekeeper and  text ~ "vendas" and reporter = vitor.adriao


issuetype = Chamado
AND category IN ("Torre maxPedido")
AND assignee = vitor.adriao
AND created >= 2025-12-01
AND created <= 2025-12-19
ORDER BY assignee ASC

Organizações = "00008 - CASA NORTE LTDA" AND summary ~ "sincronização" ORDER BY created DESC
```

Consultar devoluções - RESUMO DE VENDAS - BANCO NUVEM - OERPS

```
SELECT CODUSUR,
DTENT DATA,
SUM(VLDEVOLUCAO - DECODE (OBTER_PARAMETRO('REDUZIRST_DADOS_RELATORIO', NULL, 'N'),'S',NVL (VLST, 0),0) - DECODE (OBTER_PARAMETRO('REDUZIRIPI_DADOS_RELATORIO', NULL, 'N'),'S',NVL (VLIPI, 0),0)) AS VLDEVOL
FROM ( SELECT DISTINCT
ERP_MXSNFENT.DTENT,
ERP_MXSNFENT.CODUSURDEVOL CODUSUR,
ROUND(NVL (ERP_MXSMOV.QT, 0) *
(( NVL(ERP_MXSMOV.PUNIT, 0) +
NVL (ERP_MXSMOV.VLFRETE, 0) +
NVL (ERP_MXSMOV.VLOUTRASDESP, 0) +
NVL (ERP_MXSMOV.VLFRETE_RATEIO, 0) +
NVL (ERP_MXSMOV.VLOUTROS, 0)) - NVL (ERP_MXSMOV.VLREPASSE, 0)),2) VLDEVOLUCAO,
```

```
ROUND(NVL (ERP_MXSMOV.QT, 0) * NVL (ERP_MXSMOV.ST, 0),2) VLST,
ROUND(NVL (ERP_MXSMOV.QT, 0) * NVL (ERP_MXSMOV.VLIPI, 0),2) VLIPI
FROM ERP_MXSNFENT
INNER JOIN ERP_MXSESTCOM
ON ERP_MXSNFENT.NUMTRANSENT = ERP_MXSESTCOM.NUMTRANSEN
T
INNER JOIN ERP_MXSMOV
ON ERP_MXSESTCOM.NUMTRANSENT = ERP_MXSMOV.NUMTRANSENT
INNER JOIN MXSPRODUT
ON MXSPRODUT.CODPROD = ERP_MXSMOV.CODPROD
WHERE ERP_MXSNFENT.CODOPERACAO != 2
AND ERP_MXSMOV.CODOPERACAO != 2
AND ERP_MXSNFENT.DTENT BETWEEN TRUNC(TO_DATE('01/06/2025', 'd
d/MM/yyyy')) AND TRUNC(TO_DATE('30/06/2025', 'dd/MM/yyyy'))
AND ERP_MXSNFENT.CODUSURDEVOL = 334
AND ERP_MXSNFENT.CODFILIAL IN (3)
)
GROUP BY CODUSUR, DTENT;
```

Caso o maxPedido ainda exigir horário automático, a sincronização automática pode estar fazendo com que seja obrigatório:

```
DELETE FROM MXSPARAMETRO WHERE NOME  IN ('BLK_CONN_PRIMEIR
ACONEXAO', 'BLK_CONN_INTERVALOCONEXAO', 'BLK_CONN_PRIMEIRAC
ONEXAO_TZ', 'BLK_CONN_QTDEPEDPENDENTE', 'BLK_CONN_QTDEORCPE
NDENTE', 'FORCAR_JORNADA', 'VALIDA_FUSO_DATAAUTOMATICO', 'BLO
QUEIA PED_FORA_JORNADA','UTILIZA_CHECKIN_CHECKOUT', 'VALIDA_FU
SO_DATA_AUTOMATICO', 'GPS_EDGE_BLOCK', 'GPS_EDGE_METERS_SIZ
E','BLOQ_VENDA_FORA_HORARIO_COM', 'HABILITA_SYNC_AUTOMATICA');
```

Carga Banco Nuvem

```
DECLARE
BEGIN
UPDATE MXSCOB
SET ATUALIZID = TO_NUMBER(TO_CHAR(sysdate, 'RRRRMMDDHH24MIS
S')),
DTATUALIZ = sysdate
WHERE CODOPERACAO != 2;
END;
```

Consultar versão do banco nuvem

```
SELECT * FROM MXSVERSAOBD ORDER BY DTATUALIZACAO DESC;
```

Consultar produtos positivados no mês

```
SELECT COUNT(DISTINCT CODPROD) FROM MXSPRODUTPOS WHERE T
RUNC(DTPOSITIVACAO) BETWEEN  TO_DATE ('01/04/2024', 'DD/MM/YYY
Y') AND TO_DATE ('30/04/2024', 'DD/MM/YYYY') AND CODUSUARIO IN(S
ELECT CODUSUARIO FROM MXSUSUARIOS WHERE CODUSUR = 73);
```

Consultar tabelas que estão subindo

```
select count(1), tabela from pcmxsintegracao where status =-1 group by ta
bela order by count(1) desc;
```

Rastro

```
SELECT* FROM MXS_EVENTS E WHERE DATA_HORA_EVENTO BETWEEN
'2023-08-15T00:00:00' AND '2023-08-15T23:59:59';
SELECT* FROM MXS_EVENTS E WHERE DATA_HORA_EVENTO BETWEEN
'2023-08-15T00:00:00' AND '2023-08-15T23:59:59' AND CODCLI IN(249
```

```
28, 63550, 24759, 58927, 26667, 46696, 28461, 59581, 28641, 59489, 578
68);

SELECT * FROM MXS_RASTREAMENTOS WHERE id = 32442;
SELECT * FROM MXS_RASTREAMENTOS ORDER BY DATA_HORA_ENVIO_A
CEITO ASC;

SELECT * FROM MXS_EVENTS ORDER BY DATA_HORA_EVENTO ASC;
```

Validação MXSPRODUT

```
SELECT
   P.CODPROD,

   -- Status de Chaves Estrangeiras e Joins
   CASE
      WHEN P.CODFORNEC IS NULL THEN 'P.CODFORNEC AUSENTE'
      WHEN F.CODFORNEC IS NULL THEN 'P.CODFORNEC INEXISTENTE E
M MXSFORNEC'
      ELSE NULL
   END AS STATUS_CODFORNEC,
   CASE
      WHEN P.CODSEC IS NULL THEN 'P.CODSEC AUSENTE'
      WHEN S.CODSEC IS NULL THEN 'P.CODSEC INEXISTENTE EM MXSS
ECAO'
      ELSE NULL
   END AS STATUS_CODSEC,
   CASE
      WHEN P.CODEPTO IS NULL THEN 'P.CODEPTO AUSENTE'
      WHEN D.CODEPTO IS NULL THEN 'P.CODEPTO INEXISTENTE EM MX
SDEPTO'
      ELSE NULL
   END AS STATUS_CODEPTO,

   -- Status de colunas da tabela MXSPRODUT (P)
   CASE
```

```
        WHEN P.DTEXCLUSAO IS NOT NULL THEN 'P.DTEXCLUSAO PREENC
HIDA'
        ELSE NULL
    END AS STATUS_P_DTEXCLUSAO,
    CASE
        WHEN P.ENVIARFORCAVENDAS <> 'S' THEN 'P.ENVIARFORCAVENDA
S != S'
        ELSE NULL
    END AS STATUS_P_ENVIARFORCAVENDAS,
    CASE
        WHEN P.REVENDA <> 'S' THEN 'P.REVENDA != S'
        ELSE NULL
    END AS STATUS_P_REVENDA,
    CASE
        WHEN P.CODOPERACAO = 2 THEN 'P.CODOPERACAO = 2'
        ELSE NULL
    END AS STATUS_P_CODOPERACAO,

    CASE
        WHEN F.CODFORNEC IS NOT NULL AND F.CODOPERACAO = 2 THEN
'MXSFORNEC.CODOPERACAO = 2'
        ELSE NULL
    END AS STATUS_F_CODOPERACAO,
    CASE
        WHEN F.CODFORNEC IS NOT NULL AND F.REVENDA <> 'S' THEN 'M
XSFORNEC.REVENDA != S' -- Pendência se REVENDA não for 'S'
        ELSE NULL
    END AS STATUS_F_REVENDA,

    CASE
        WHEN S.CODSEC IS NOT NULL AND S.CODOPERACAO = 2 THEN 'MX
SSECAO.CODOPERACAO = 2'
        ELSE NULL
    END AS STATUS_S_CODOPERACAO,


    CASE
        WHEN D.CODEPTO IS NOT NULL AND D.CODOPERACAO = 2 THEN 'M
```

```
XSDEPTO.CODOPERACAO = 2'
        ELSE NULL
    END AS STATUS_D_CODOPERACAO,

    -- STATUS_GERAL consolidado com todas as verificações
    CASE
        WHEN P.CODFORNEC IS NULL OR F.CODFORNEC IS NULL OR -- P.CO
DFORNEC ausente ou não encontrado em MXSFORNEC
            P.CODSEC IS NULL OR S.CODSEC IS NULL OR      -- P.CODSEC au
sente ou não encontrado em MXSSECAO
            P.CODEPTO IS NULL OR D.CODEPTO IS NULL OR    -- P.CODEPTO
ausente ou não encontrado em MXSDEPTO
            P.DTEXCLUSAO IS NOT NULL OR                  -- P.DTEXCLUSAO pre
enchida
            P.ENVIARFORCAVENDAS <> 'S' OR                -- P.ENVIARFORCAVE
NDAS diferente de 'S'
            P.REVENDA <> 'S' OR                          -- P.REVENDA diferente de
'S'
            P.CODOPERACAO = 2 OR                         -- P.CODOPERACAO igual
a 2
            F.CODOPERACAO = 2 OR                         -- MXSFORNEC.CODOPER
ACAO igual a 2 (se F existir)
            S.CODOPERACAO = 2 OR                         -- MXSSECAO.CODOPERA
CAO igual a 2 (se S existir)
            D.CODOPERACAO = 2 OR                         -- MXSDEPTO.CODOPERA
CAO igual a 2 (se D existir)
            F.REVENDA <> 'S'                             -- MXSFORNEC.REVENDA difer
ente de 'S' (se F existir)
        THEN 'PENDENCIA ENCONTRADA'
        ELSE 'OK'
    END AS STATUS_GERAL
FROM
    MXSPRODUT P
LEFT JOIN
    MXSFORNEC F ON P.CODFORNEC = F.CODFORNEC
LEFT JOIN
    MXSSECAO S ON P.CODSEC = S.CODSEC
LEFT JOIN
```

```
    MXSDEPTO D ON P.CODEPTO = D.CODEPTO
WHERE
    P.CODPROD IN (284445) -- Substitua X pela sua lista de códigos de pro
duto ou subconsulta
;
```

Histórico

```
TRUNC(DATA) >= TRUNC(SYSDATE,'DD') - 60);

update mxshistoricopedc set codoperacao = 1 where trunc(data) between t
runc(to_date('01/06/2023','dd/mm/yyyy')) and trunc(to_date('05/09/202
3','dd/mm/yyyy'));

select * from mxshistoricopedi where numped in (select numped from mxs
historicopedc where codcli in (7697) and trunc(data) between trunc(to_dat
e('01/06/2023','dd/mm/yyyy')) and trunc(to_date('05/09/2023','dd/mm/yyy
y')));
update mxshistoricopedi set codoperacao = 1 where trunc(data) between tr
unc(to_date('01/06/2023','dd/mm/yyyy')) and trunc(to_date('05/09/2023','d
d/mm/yyyy'));
```

```
select * from mxsmixclientes where codcli in (7697) and trunc(dtsaida) bet
ween trunc(to_date('01/03/2023','dd/mm/yyyy')) and trunc(to_date('05/09/
2023','dd/mm/yyyy')) and codoperacao != 2 order by dtatualiz desc;
```

Identificar região de cliente

```
SELECT C.CODPRACA, R.NUMREGIAO, C.CODCLI, CLIENTE
FROM MXSCLIENT C
INNER JOIN MXSPRACA P
ON P.CODPRACA = C.CODPRACA
INNER JOIN MXSREGIAO R
```

```
ON R.NUMREGIAO = P.NUMREGIAO
WHERE CODCLI IN();
```

Verificação para cotas na nuvem

```
-------------VERIFICACAO PARA COTAS NA NUVEM
--VERIFICANDO COTA
SELECT (QTESTGER-QTBLOQUEADA-QTPENDENTE-QTRESERV) AS ESTO
QUEDISP, MXSEST.* FROM MXSEST WHERE CODPROD IN(7072);
SELECT * FROM MXSPRODUSUR WHERE CODCLI IN(19483) AND CODPRO
D IN(7072, 7081);
SELECT ID_PEDIDO, NUMPED, DATA, PJSON.CODPRODUTO, PJSON.DESC
RICAO, PJSON.QUANTIDADE,
PJSON.PRECOVENDA
FROM MXSINTEGRACAOPEDIDO PED_TAB,
JSON_TABLE(OBJETO_JSON, '$.Produtos[*]'
COLUMNS (ROW_NUMBER FOR ORDINALITY,
        CODPRODUTO  VARCHAR(10) PATH '$.Codigo',
        DESCRICAO  VARCHAR(2000) PATH '$.Descricao',
        QUANTIDADE VARCHAR(10) PATH '$.Quantidade',
        PRECOVENDA VARCHAR (100) PATH '$.PrecoVenda'
)) PJSON
WHERE PED_TAB.CODUSUR IN(1206) AND PED_TAB.CODCLI IN(6001) AND
PJSON.CODPRODUTO IN(8269);
```