FAIRCHILD
SEMICONDUCTOR®

IGBT

SGH80N60UFD

Ultrafast IGBT

General Description

Fairchild's UFD series of Insulated Gate Bipolar Transistors (IGBTs) provides low conduction and switching losses. The UFD series is designed for applications such as motor control and general inverters where high speed switching is a required feature.

Features

- High speed switching
- Low saturation voltage : $V_{CE(sat)}$ = 2.1 V @ I_C = 40A
- High input impedance
- CO-PAK, IGBT with FRD : t_{rr} = 50ns (typ.)

Applications

AC & DC motor controls, general purpose inverters, robotics, and servo controls.



TO-3P



Absolute Maximum Ratings

T_C = 25°C unless otherwise noted

Symbol	Description		SGH80N60UFD	Units
V_{CES}	Collector-Emitter Voltage		600	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Collector Current	@ T_C = 25°C	80	A
	Collector Current	@ T_C = 100°C	40	A
$I_{CM\ (1)}$	Pulsed Collector Current		220	A
I_F	Diode Continuous Forward Current	@ T_C = 100°C	25	A
I_{FM}	Diode Maximum Forward Current		280	A
P_D	Maximum Power Dissipation	@ T_C = 25°C	195	W
	Maximum Power Dissipation	@ T_C = 100°C	78	W
T_J	Operating Junction Temperature		-55 to +150	°C
T_{stg}	Storage Temperature Range		-55 to +150	°C
T_L	Maximum Lead Temp. for Soldering Purposes,/8" from Case for 5 Seconds		300	°C

Notes :
(1) Repetitive rating : Pulse width limited by max. junction temperature

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$(IGBT)	Thermal Resistance, Junction-to-Case	--	0.64	°C/W
$R_{\theta JC}$(DIODE)	Thermal Resistance, Junction-to-Case	--	0.83	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	--	40	°C/W

Electrical Characteristics of the IGBT T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Off Characteristics						
BV_{CES}	Collector-Emitter Breakdown Voltage	V_{GE} = 0V, I_C = 250uA	600	--	--	V
$\Delta B_{VCES}/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	V_{GE} = 0V, I_C = 1mA	--	0.6	--	V/°C
I_{CES}	Collector Cut-Off Current	V_{CE} = V_{CES}, V_{GE} = 0V	--	--	250	uA
I_{GES}	G-E Leakage Current	V_{GE} = V_{GES}, V_{CE} = 0V	--	--	± 100	nA
On Characteristics						
$V_{GE(th)}$	G-E Threshold Voltage	I_C = 40mA, V_{CE} = V_{GE}	3.5	4.5	6.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C = 40A, V_{GE} = 15V	--	2.1	2.6	V
		I_C = 80A, V_{GE} = 15V	--	2.6	--	V
Dynamic Characteristics						
C_{ies}	Input Capacitance	V_{CE} = 30V, V_{GE} = 0V, f = 1MHz	--	2790	--	pF
C_{oes}	Output Capacitance		--	350	--	pF
C_{res}	Reverse Transfer Capacitance		--	100	--	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 300 V, I_C = 40A, R_G = 5Ω, V_{GE} = 15V, Inductive Load, T_C = 25°C	--	23	--	ns
t_r	Rise Time		--	50	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	90	130	ns
t_f	Fall Time		--	50	150	ns
E_{on}	Turn-On Switching Loss		--	570	--	uJ
E_{off}	Turn-Off Switching Loss		--	590	--	uJ
E_{ts}	Total Switching Loss		--	1160	1500	uJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 300 V, I_C = 40A, R_G = 5Ω, V_{GE} = 15V, Inductive Load, T_C = 125°C	--	30	--	ns
t_r	Rise Time		--	55	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	150	200	ns
t_f	Fall Time		--	160	250	ns
E_{on}	Turn-On Switching Loss		--	630	--	uJ
E_{off}	Turn-Off Switching Loss		--	940	--	uJ
E_{ts}	Total Switching Loss		--	1580	2000	uJ
Q_g	Total Gate Charge	V_{CE} = 300 V, I_C = 40A, V_{GE} = 15V	--	175	250	nC
Q_{ge}	Gate-Emitter Charge		--	25	40	nC
Q_{gc}	Gate-Collector Charge		--	60	90	nC
L_e	Internal Emitter Inductance	Measured 5mm from PKG	--	14	--	nH

Electrical Characteristics of DIODE T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
V_{FM}	Diode Forward Voltage	I_F = 25A	T_C = 25°C	--	1.4	1.7	V
			T_C = 100°C	--	1.3	--	
t_{rr}	Diode Reverse Recovery Time	I_F = 25A, di/dt = 200A/us	T_C = 25°C	--	50	95	ns
			T_C = 100°C	--	105	--	
I_{rr}	Diode Peak Reverse Recovery Current		T_C = 25°C	--	4.5	10	A
			T_C = 100°C	--	8.5	--	
Q_{rr}	Diode Reverse Recovery Charge		T_C = 25°C	--	112	375	nC
			T_C = 100°C	--	420	--	



Fig 1. Typical Output Characteristics



Fig 2. Typical Saturation Voltage Characteristics



Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level



Fig 4. Load Current vs. Frequency



Fig 5. Saturation Voltage vs. V_{GE}



Fig 6. Saturation Voltage vs. V_{GE}



Fig 7. Capacitance Characteristics



Fig 8. Turn-On Characteristics vs. Gate Resistance



Fig 9. Turn-Off Characteristics vs. Gate Resistance



Fig 10. Switching Loss vs. Gate Resistance



Fig 11. Turn-On Characteristics vs. Collector Current



Fig 12. Turn-Off Characteristics vs. Collector Current



Fig 13. Switching Loss vs. Collector Current



Fig 14. Gate Charge Characteristics



Fig 15. SOA Characteristics



Fig 16. Turn-Off SOA Characteristics



Fig 17. Transient Thermal Impedance of IGBT



Fig 18. Forward Characteristics



Fig 19. Reverse Recovery Current



Fig 20. Stored Charge



Fig 21. Reverse Recovery Time

Package Dimension

TO-3P



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT™	ImpliedDisconnect™	PACMAN™	SPM™
ActiveArray™	FACT Quiet Series™	ISOPLANAR™	POP™	Stealth™
Bottomless™	FAST®	LittleFET™	Power247™	SuperSOT™-3
CoolFET™	FASTr™	MicroFET™	PowerTrench®	SuperSOT™-6
CROSSVOLT™	FRFET™	MicroPak™	QFET™	SuperSOT™-8
DOME™	GlobalOptoisolator™	MICROWIRE™	QS™	SyncFET™
EcoSPARK™	GTO™	MSX™	QT Optoelectronics™	TinyLogic™
E^2CMOS^{TM}	HiSeC™	MSXPro™	Quiet Series™	TruTranslation™
$EnSigna^{TM}$	I^2C™	OCX™	RapidConfigure™	UHC™
Across the board. Around the world.™		OCXPro™	RapidConnect™	UltraFET®
The Power Franchise™		OPTOLOGIC®	SILENT SWITCHER®	VCX™
Programmable Active Droop™		OPTOPLANAR™	SMART START™	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.