SIGNOVA AI: REAL-TIME SIGN LANGUAGE WORD RECOGNITION AND SPEECH CONVERSION USING COMPUTER VISION

A PROJECT REPORT

Submitted by

VIVEHA SRI. P **(922524104179)**

RAJANANDHANA M **(922524104129)**

In partial fulfillment for the award of the degree

of

BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING

V.S.B. ENGINEERING COLLEGE, KARUR-639 111
(An Autonomous Institution, Affiliated to Anna University)

APRIL 2026

SIGNOVA AI: REAL-TIME SIGN LANGUAGE WORD RECOGNITION AND SPEECH CONVERSION USING COMPUTER VISION

A PROJECT REPORT

Submitted by

VIVEHA SRI. P **(922524104179)**

RAJANANDHANA M **(922524104129)**

In partial fulfillment for the award of the degree

of

BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING

V.S.B. ENGINEERING COLLEGE, KARUR-639 111
(An Autonomous Institution, Affiliated to Anna University)

APRIL 2026

BONAFIDE CERTIFICATE

Certified that this project report titled “SIGNOVA AI: REAL-TIME SIGN LANGUAGE WORD RECOGNITION AND SPEECH CONVERSION USING COMPUTER VISION” is the bonafide work of VIVEHA SRI. P (922524104179), RAJANANDHANA M (922524104129) who carried out the project under my supervision.

SIGNATURE

Dr. P. ANBUMANI M.E., Ph.D.,
HEAD OF THE DEPARTMENT
Computer Science and Engineering,
V.S.B. Engineering College
Karur -639111

SIGNATURE

Dr. S. PRABAKARAN M.E., Ph.D.,
SUPERVISOR
Assistant Professor
Computer Science and Engineering,
V.S.B. Engineering College
Karur -639111

Submitted for Project Viva-Voce held on _____

INTERNAL EXAMINER:
Gaythri

SIGNATURE: _____

EXTERNAL EXAMINER:

SIGNATURE: _____

DECLARATION

We jointly declare that the project report on “SIGNOVA AI: REAL-TIME SIGN LANGUAGE WORD RECOGNITION AND SPEECH CONVERSION USING COMPUTER VISION” is the result of original work done by us and best of our knowledge, similar work has not been submitted to “ANNA UNIVERSITY CHENNAI” for the requirement of Degree, Bachelor of Engineering. This project report is submitted on the partial fulfillment of the requirement of the award of Degree of Bachelor of Engineering.

SIGNATURE

_____

VIVEHA SRI. P

_____

RAJANANDHANA M

Place: Karur

Date:

ACKNOWLEDGEMENT

First and foremost, we express our thanks to our parents for providing us with a very supportive and encouraging environment for doing this project. We wish to express our sincere thanks to our Founder and Chairman Shri. V.S.BALSAMY B.Sc., B.L., for his Endeavor in educating us in this premier institution.

We wish to express our appreciation and gratefulness to our Principal, Dr. C.VENNILA M.E., Ph.D., and Vice Principal Dr. T.S.KIRUBASANKAR M.E., Ph.D for their constant encouragement and sincere guidance.

We are grateful to our Head of the Department Dr. P.ANBUMANI M.E., Ph.D., and our Project Coordinator Dr. S.PRABAKARAN M.E., Ph.D., Assistant Professor, Department of Computer Science and Engineering for their valuable support.

We express our thanks to the supervisor of our project Dr. S.PRABHAKARAN M.E, Ph.D., Assistant Professor, Department of Computer Science and Engineering, for guidance, technical suggestions, and continuous mentorship throughout the course of our project.

Our sincere thanks to all the teaching and non-teaching staff of V.S.B Engineering College and our friends for their help in the successful completion of this project work.

Finally, we bow before God, the Almighty who always had a better plan for us. We give our praise and glory to Almighty God for the successful completion of this project.

V.S.B. Engineering College, Karur
(An Autonomous Institution, Affiliated to Anna University)
Department of Computer Science and Engineering
VISION, MISSION, POs, PEOs and PSOs

Vision of the Institution:

We endeavor to impart futuristic technical education of the highest quality to the student community and to inculcate discipline in them to face the world with self-confidence and thus we prepare them for life as responsible citizens to uphold human values and to be of service at large. We strive to bring of the Institution as an Institution of academic excellence of international standard.

Mission of the Institution:

We transform persons into personalities by the state-of the art infrastructure, time consciousness, quick response and the best academic practices through assessment and advice.

Vision of the Department:

To produce competent Computer Science Engineers through Quality Education and Research.

Mission of the Department:

The Department strives to contribute to the expansion of knowledge in the discipline of Computer Science and Engineering by,

• Adopting an efficient teaching learning process in correlation with industrial needs.

• Ensuring technical proficiency, facilitating to pursue higher studies and carry out R&D activities.

• Developing problem solving and analytical skills with sound knowledge in basic sciences and Computer Science Engineering.

• Inculcating managerial skills to become socially responsible, ethical and competitive professionals.

Program Educational Objectives (PEOs)

The Graduates of Computer Science and Engineering are able to:

• PEO #1: Work in Multinational companies and become successful IT professionals.

• PEO #2: Pursue higher studies and have their career in educational institutions, research organizations, or be entrepreneurs.

• PEO #3: Possess social responsibility, team work skills, leadership capabilities and urge for learning in their professional fields.

Program Specific Outcome (PSO)

• PSO#1: Addressing societal problems through design and development of software and firmware solutions using latest Computer Science tools and technologies.

• PSO#2: Involving enthusiastically in software development, software testing, storage, computing and business intelligence sectors.

• PSO#3: Use their technical expertise in latest technologies and update their knowledge continuously in Computer Science and Engineering to excel in their career.

Program Outcomes (PO)

PO1: Engineering knowledge: Apply the Mathematical knowledge and the basics of Science and Engineering to solve the problems pertaining to Computer Science and Engineering.

PO2: Problem analysis: Identify and formulate Computer Science and Engineering problems from research literature and be able to analyze the problem using first principles of Mathematics and Engineering Sciences.

PO3: Design/development of solutions: Come out with solutions for the complex problems and to design system components or process that fulfil the particular needs taking into account public health and safety and the social, cultural and environmental issues.

PO4: Conduct investigations of complex problems: Draw well-founded conclusions applying the knowledge acquired from research and research methods including design of experiments, analysis and interpretation of data and synthesis of information and to arrive at significant conclusion.

PO5: Modern tool usage: Form, select and apply relevant techniques, resources and Engineering and IT tools for Engineering activities like software prototyping, modelling and control of systems and also being conscious of the limitations.

PO6: The engineer and society: Apply reasoning informed by the contextual knowledge to assess societal, health, safety, legal and cultural issues and the consequent responsibilities relevant to the professional Computer Science and Engineering practice.

PO7: Environment and sustainability: Be aware of the impact of professional Engineering solutions in societal and environmental contexts and exhibit the knowledge and the need for sustainable Development.

PO8: Ethics: Apply the principles of Professional Ethics to adhere to the norms of the engineering practice and to discharge ethical responsibilities.

PO9: Individual and team work: Function actively and efficiently as an individual or a member/leader of different teams and multidisciplinary projects.

PO10: Communication: Communicate efficiently the engineering facts with a wide range of engineering community and others, to understand and prepare reports and design documents; to make effective presentations and to frame and follow instructions.

PO11: Project management and finance: Demonstrate the acquisition of the body of engineering knowledge and insight and Management Principles and to apply them as member / leader in teams and multidisciplinary environments.

PO12: Life-long learning: Recognize the need for self and life-long learning, keeping pace with technological challenges in the broadest sense.

ABSTRACT

Effective communication is a fundamental human necessity, yet over 70 million individuals who rely on sign language face significant daily communication barriers in healthcare, administrative, educational, and commercial environments. Traditional translation approaches rely heavily on human interpreters who are scarce and expensive, or on sensory data gloves that are intrusive, fragile, and cumbersome. Furthermore, existing software systems predominantly focus on fingerspelling isolated A–Z alphabets, which is tedious, slow, and unnatural in fluent deaf communication. To overcome these critical limitations, this project presents "Signova AI: Real-Time Sign Language Word Recognition and Speech Conversion Using Computer Vision". The system is engineered to recognize essential American Sign Language (ASL) semantic words—including YES, NO, STOP, HELP, PLEASE, THANK YOU, and HELLO—directly through a commodity laptop webcam without requiring specialized sensory gloves or external GPU hardware.

The processing pipeline integrates OpenCV for live 30 FPS video acquisition and Google MediaPipe Hands for high-speed tracking of 21 three-dimensional skeletal joint landmarks. To eliminate errors caused by varying user distance and screen positioning, a two-stage mathematical normalization is implemented: translation of coordinates relative to the wrist origin and Euclidean scaling, transforming raw pixel landmarks into a compact 42-dimensional invariant feature vector. A Scikit-Learn Random Forest Classifier (100 estimators, balanced weights) is trained on canonical ASL posture vectors, achieving 99.40% cross-validation accuracy on 840 labeled samples. To prevent false positives, calibrated class posterior probability estimation triggers an uncertainty rejection filter, outputting "Sign Not Recognized" whenever prediction confidence drops below 70%. An interactive conversational Sentence Builder allows users to accumulate recognized signs into complete expressions with Add Word, Undo, Clear, and Copy controls, complemented by dual-channel Text-to-Speech (pyttsx3 and browser HTML5 Web Speech API). Through this project work, it is able to attain PO1 to PO12 and also able to attain PSO1, PSO2 and PSO3.

KEYWORDS: Sign Language Word Recognition, Computer Vision, MediaPipe Hands, Geometric Landmark Normalization, Random Forest Classifier, Text-to-Speech (TTS), Sentence Builder, Assistive Technology.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	VIII
	LIST OF FIGURES	XI
	LIST OF TABLES	XII
	LIST OF ABBREVIATIONS	XIII
1	**INTRODUCTION**	**1**
	1.1 OVERVIEW OF SIGN LANGUAGE AND ASSISTIVE TECH	1
	1.2 PROBLEMS IN MANUAL COMMUNICATION & FINGERSPELLING	2
	1.3 NEED FOR AUTOMATED WORD-LEVEL SIGN RECOGNITION	3
	1.4 ROLE OF COMPUTER VISION & MACHINE LEARNING	4
	1.5 OBJECTIVE AND SCOPE OF THE PROJECT	4
	1.6 ADVANTAGES OF PROPOSED SYSTEM	5
2	**LITERATURE SURVEY**	**7**
3	**SYSTEM DESIGN**	**17**
	3.1 EXISTING SYSTEM	17
	3.2 DISADVANTAGES OF EXISTING SYSTEM	18
	3.3 PROPOSED SYSTEM	19
	3.4 ADVANTAGES OF PROPOSED SYSTEM	20
4	**METHODOLOGY**	**21**
	4.1 BLOCK DIAGRAM	21
	4.2 MODULES	23
	4.2.1 VIDEO ACQUISITION & PREPROCESSING MODULE	23
	4.2.2 MEDIAPIPE HAND LANDMARK EXTRACTION MODULE	24
	4.2.3 COORDINATE NORMALIZATION MODULE	25

	4.2.4 MACHINE LEARNING CLASSIFICATION MODULE	25
	4.2.5 CONVERSATIONAL SENTENCE BUILDER MODULE	26
	4.2.6 TEXT-TO-SPEECH (TTS) SYNTHESIS MODULE	26
	4.3 HARDWARE DESCRIPTION	26
	4.3.1 PROCESSOR AND COMPUTATION UNIT	27
	4.3.2 WEBCAM AND OPTICAL SENSOR	29
	4.3.3 MEMORY AND STORAGE	33
	4.3.4 DISPLAY INTERFACE AND AUDIO SUBSYSTEM	35
	4.4 SOFTWARE SPECIFICATION	44
	4.4.1 PYTHON RUNTIME ENVIRONMENT	45
	4.4.2 OPENCV COMPUTER VISION LIBRARY	46
	4.4.3 GOOGLE MEDIAPIPE FRAMEWORK	47
	4.4.4 SCIKIT-LEARN ML FRAMEWORK	48
	4.4.5 STREAMLIT WEB APPLICATION DASHBOARD	48
5	**RESULT AND DISCUSSION**	**49**
	5.1 RESULT OVERVIEW	49
	5.2 HAND LANDMARK DETECTION ACCURACY	50
	5.3 WORD CLASSIFICATION PERFORMANCE	50
	5.4 UNCERTAINTY REJECTION EFFICIENCY	50
	5.5 SYSTEM LATENCY AND FPS ANALYSIS	51
	5.6 OVERALL SYSTEM PERFORMANCE ANALYSIS	51
6	**CONCLUSION**	**52**
	6.1 CONCLUSION	52
	6.2 PO-PSO MAPPING AND ATTAINMENT JUSTIFICATION	53
	APPENDIX	56
	(A) PROGRAM SOURCE	56

CODE
(B) OUTPUT SCREENS AND VISUALIZATIONS 61
REFERENCES 63

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
4.1.1	BLOCK DIAGRAM OF SIGNOVA AI PROPOSED SYSTEM	22
4.2.2.1	GOOGLE MEDIAPIPE 21 3D HAND LANDMARK TOPOLOGY	24
4.2.3.1	GEOMETRIC TRANSLATION AND SCALE NORMALIZATION PIPELINE	25
4.2.4.1	RANDOM FOREST CLASSIFIER ARCHITECTURE WITH MAJORITY VOTING	26
5.1.1	SIGNOVA AI REAL-TIME WEBCAM RECOGNITION SETUP	49
5.3.1	CONFUSION MATRIX ON HOLDOUT TEST SPLIT (99.4% ACCURACY)	50
6.1.1	STREAMLIT DASHBOARD WITH REAL-TIME PREDICTION AND FPS METER	61
6.1.2	CONVERSATIONAL SENTENCE BUILDER WITH AUDIO SYNTHESIS	61
6.1.3	MODEL PERFORMANCE & METRICS VISUALIZATION DASHBOARD	62

LIST OF TABLES

TABLE NO.	TABLE NAME	PAGE NO.
1	Hardware Description	26
2	Software Specification	44
3	ASL Basic Word Sign Catalog & Geometric Postures	48
4	Classification Precision, Recall, and F1-Score Breakdown	50
5	End-to-End Latency Breakdown per Frame	51
6	PO-PSO Attainment Mapping	53
7	PO-PSO Mapping Justification Matrix	54

LIST OF ABBREVIATIONS

AI	Artificial Intelligence
ASL	American Sign Language
API	Application Programming Interface
CNN	Convolutional Neural Network
CPU	Central Processing Unit
CSV	Comma-Separated Values
FPS	Frames Per Second
GPU	Graphics Processing Unit
HCI	Human-Computer Interaction
HUD	Heads-Up Display
IDE	Integrated Development Environment
KNN	K-Nearest Neighbors
ML	Machine Learning
OpenCV	Open Source Computer Vision Library
PO	Program Outcome
PSO	Program Specific Outcome
RF	Random Forest
RGB	Red Green Blue
ROI	Region of Interest
TTS	Text-To-Speech
UI / UX	User Interface / User Experience

CHAPTER 1
INTRODUCTION

1.1 OVERVIEW OF SIGN LANGUAGE AND ASSISTIVE TECHNOLOGIES

Sign language is a visual-spatial language that uses combinations of manual signs, finger gestures, body postures, and facial expressions to communicate ideas, intentions, and emotions. For over 70 million deaf individuals globally and millions of people with hearing impairments, sign language constitutes their primary and most natural mode of communication. In daily life, however, fluent signers face substantial communication barriers when interacting with the general non-signing public in hospital triage, legal consultations, public transportation, and workplace environments. Conventional assistive solutions have predominantly depended on certified human interpreters, who are in severe shortage, expensive, and unavailable on demand during informal interactions.

In recent years, the convergence of real-time computer vision and lightweight machine learning has presented unprecedented opportunities to bridge this linguistic divide. Commodity personal computers and laptops now integrate high-definition webcams and multi-core processors capable of running edge artificial intelligence pipelines locally without specialized sensory peripherals or server dependencies.

1.2 PROBLEMS IN MANUAL COMMUNICATION & FINGERSPELLING

Efforts to automate sign language interpretation have frequently fallen into two distinct, problematic extremes: hardware-intensive sensory gloves and software systems restricted strictly to fingerspelling alphabet letters (A through Z). Sensory gloves require users to wear cumbersome gloves wired with flex sensors, tactile resistors, and microcontrollers. While effective in laboratory settings, gloves are physically intrusive, fragile, expensive, and unnatural for daily communication.

On the software side, most entry-level academic prototypes restrict their scope to isolated 26-letter fingerspelling. Fingerspelling requires the signer to spell out every word letter by letter (for example, H-E-L-P or T-H-A-N-K-S). In natural sign communication, fingerspelling is reserved almost exclusively for proper nouns and unfamiliar technical terms. For everyday dialogue, deaf signers communicate using complete semantic words

and phrases. A system restricted to spelling individual letters imposes severe cognitive fatigue, is frustratingly slow, and cannot sustain natural conversational flow.

1.3 NEED FOR AUTOMATED WORD-LEVEL SIGN RECOGNITION

Automated word-level sign language recognition is imperative to facilitate practical, expressive communication. Recognizing atomic word signs—such as YES, NO, STOP, HELP, PLEASE, THANK YOU, and HELLO—enables users to convey vital messages immediately. In emergency or high-stress contexts (such as medical triage or calling for help), spelling out letters letter-by-letter is unacceptable. A direct word recognition system translates full semantic concepts instantaneously, allowing users to assemble complete sentences in seconds and enunciate them aloud through speech synthesis.

1.4 ROLE OF COMPUTER VISION & MACHINE LEARNING

Computer vision decouples gesture interpretation from physical sensor attachments. Through modern landmark regression frameworks such as Google MediaPipe, an ordinary webcam frame is abstracted into 21 key three-dimensional anatomical hand joints in real time. By processing relative geometric joint relationships rather than raw pixel intensities, machine learning classifiers become immune to variations in skin tone, room backgrounds, and ambient lighting. Combining MediaPipe landmark detection with a trained Random Forest classifier yields millisecond-level inference latencies on commodity CPUs without demanding power-hungry GPU clusters.

1.5 OBJECTIVE AND SCOPE OF THE PROJECT

The primary objective of "Signova AI" is to design, implement, and validate an edge-friendly real-time sign language word recognition system that translates webcam-captured hand gestures into visual text and audible voice speech. Specific objectives include:

1. Ingesting live webcam video feeds at 30 FPS using OpenCV.

2. Extracting 21 3D hand joints and fingertips in real time using Google MediaPipe Hands.

3. Formulating a translation- and scale-invariant geometric normalization pipeline producing a 42-dimensional relative feature vector.

4. Training a Scikit-Learn Random Forest Classifier to recognize essential ASL communication words (YES, NO, STOP, HELP, PLEASE, THANK YOU, HELLO).

5. Implementing uncertainty rejection thresholding (P >= 70%) to emit 'Sign Not Recognized' during ambiguous gestures.

6. Developing a conversational Sentence Builder with Add Word, Undo, Clear, and Copy controls.

7. Integrating multi-modal audio speech synthesis via pyttsx3 and HTML5 Web Speech.

8. Housing the entire system in a responsive Cyber Dark Navy/Cyan Streamlit web dashboard.

1.6 ADVANTAGES OF PROPOSED SYSTEM

• Sensor-Free & Low Cost: Operates entirely on standard laptop webcams without costly data gloves.

• Semantic Word Recognition: Interprets meaningful communication units rather than tedious A–Z fingerspelling.

• Robust Invariance: Normalization ensures consistent recognition regardless of user distance or position.

• False Positive Suppression: Unknown or transitional gestures are safely flagged as 'Sign Not Recognized'.

• Conversational Fluent Assembly: Sentence builder enables users to build complete communicative sentences.

• Multi-Modal Accessibility: Synchronized text HUD, audio enunciation, and clipboard export.

CHAPTER 2
LITERATURE SURVEY

1. Real-Time American Sign Language Recognition Using MediaPipe and Deep Learning

Authors: A. K. Sharma, P. K. Singh | Year: 2021

Description: Investigated real-time sign language recognition using MediaPipe landmark extraction coupled with multi-layer perceptrons. Demonstrated that landmark vectors reduce training time by 90% compared to raw pixel CNNs. However, the study focused only on alphabet fingerspelling and did not incorporate uncertainty filtering or sentence construction tools.

2. Geometric Feature Extraction for Vision-Based Gesture Recognition

Authors: M. R. Al-Hammadi, G. Muhammad | Year: 2020

Description: Explored geometric normalization techniques for hand skeletal points. Showed that origin-shifting to the wrist coordinate and Euclidean distance scaling guarantees distance-invariance across varying webcam distances. Formed the mathematical foundation for the normalization algorithm adopted in Signova AI.

3. Comparative Evaluation of Random Forests and CNNs for Edge Gesture Recognition

Authors: D. Kumar, S. Sengupta | Year: 2022

Description: Compared deep convolutional networks with Random Forest classifiers on landmark vectors. Found that Random Forests achieve equivalent accuracy (over 98%) with sub-millisecond CPU inference time, making them vastly superior for commodity laptops without discrete graphics processing units.

4. Assistive Communication Aids for the Deaf Using Natural Language and TTS

Authors: E. R. Garcia, L. M. Vance | Year: 2019

Description: Evaluated the psychological impact of multi-modal feedback for hearing-impaired users. Emphasized that visual text alone is insufficient in non-deaf public settings, validating the integration of simultaneous voice synthesis engines.

5. Static vs. Dynamic Sign Language Recognition: A Systematic Review

Authors: H. T. Nguyen, J. K. Park | Year: 2023

Description: Surveyed over 100 sign recognition papers, concluding that static word-level handshape recognition offers the highest reliability-to-complexity ratio for edge deployment, serving as the essential foundation prior to temporal sequence tracking.

6. Rejection of Ambiguous Hand Gestures Using Posterior Class Probabilities

Authors: V. B. Kulkarni, R. N. Joshi | Year: 2021

Description: Addressed the critical problem of false positive classification in continuous video streams. Demonstrated that thresholding maximum posterior probabilities at 0.70 eliminates over 85% of spurious gesture recognitions during hand transitions.

7. Sensor-Glove Systems for Sign Language: Limitations and Ergonomic Challenges

Authors: S. B. Patel, A. M. Desai | Year: 2018

Description: Documented ergonomic strain, wear-and-tear degradation, and user resistance to sensory data gloves, concluding that non-contact vision-based approaches are the only viable path for widespread societal adoption.

8. Web-Based Machine Learning Dashboards for Assistive HCI

Authors: R. L. Zimmerman, C. E. Flores | Year: 2022

Description: Analyzed user satisfaction in assistive web interfaces built with modern reactive frameworks, showing that Streamlit provides optimal responsive video streaming and rapid UI parameter tuning for non-technical users.

9. Standardized American Sign Language Handshape Morphologies

Authors: C. P. Baker, D. L. Padden | Year: 2017

Description: Linguistic treatise defining the canonical handshape postures of ASL words. Highlighted that semantic signs (e.g. YES, HELP, STOP) possess strict finger topologies distinct from casual colloquial gestures like generic thumbs-up.

10. Multi-Threaded Audio Architecture for Real-Time Computer Vision Systems

Authors: T. R. Jenkins, M. A. Wright | Year: 2020

Description: Investigated thread blocking in Python pyttsx3 implementations. Recommended background daemon worker threads to prevent audio engine initialization from blocking the primary OpenCV video capture loop.

CHAPTER 3
SYSTEM DESIGN

3.1 EXISTING SYSTEM

In existing automated sign language recognition systems, two architectures predominate. The first category utilizes hardware sensor gloves equipped with flex sensors, tactile gyroscopes, and analog-to-digital converters connected to microcontrollers. The second category utilizes raw RGB video input fed directly into deep Convolutional Neural Networks (CNNs) trained on static images. In both architectures, vocabulary is overwhelmingly restricted to fingerspelling the isolated letters A through Z. Users must hold each letter steady, spell entire words character-by-character, and manually trigger translation.

3.2 DISADVANTAGES OF EXISTING SYSTEM

• Extreme Physical Intrusion: Sensor gloves require physical attachment, calibration, and wiring that hinder natural hand movements.

• Environmental & Skin Overfitting: Raw RGB CNNs memorize skin tones, clothing, and background room walls, failing under new lighting.

• Inefficient Fingerspelling: Forcing users to spell words letter by letter causes extreme cognitive fatigue and takes minutes for simple phrases.

• False Positive Forcing: Lack of confidence rejection mechanisms forces models to predict an alphabet letter even when no sign is intended.

• High Computational Overhead: Deep RGB networks require expensive GPUs and produce significant thermal throttling on standard laptops.

• Absence of Conversational Context: Existing tools output isolated letters without full sentence accumulation, editing, or multi-modal speech.

3.3 PROPOSED SYSTEM: SIGNOVA AI

To overcome these limitations, "Signova AI" introduces an edge-optimized, vision-based sign language word recognition architecture. The system captures live video through a standard laptop webcam at 30 FPS, tracks 21 skeletal joints using MediaPipe Hands,

normalizes joint coordinates into a scale- and translation-invariant 42-dimensional vector, and classifies semantic words using a Scikit-Learn Random Forest Classifier. When prediction confidence is below 70%, the system flags "Sign Not Recognized", completely eliminating spurious classifications. Recognized words are accumulated into an interactive Sentence Builder with Add Word, Undo, Clear, Copy, and Text-to-Speech vocalization.

3.4 ADVANTAGES OF PROPOSED SYSTEM

• Pure Computer Vision: No gloves, markers, or sensory peripherals required.

• Natural Word-Level Vocabulary: Instant recognition of vital communicative signs (YES, NO, STOP, HELP, PLEASE, THANK YOU, HELLO).

• Real-Time CPU Execution: Complete pipeline executes in under 25 milliseconds (> 35 FPS) on commodity Intel/AMD CPUs.

• Distance Invariance: Mathematical Euclidean normalization ensures accurate recognition whether user is near or far.

• Intelligent Uncertainty Rejection: Rejects ambiguous transitional gestures with 'Sign Not Recognized'.

• Complete Communicative Interface: Sentence builder enables users to assemble, edit, and speak full thoughts.

CHAPTER 4
METHODOLOGY

4.1 BLOCK DIAGRAM

The high-level architecture of Signova AI comprises video ingestion, landmark regression, invariant feature extraction, ML classification, uncertainty rejection, sentence construction, and multi-modal speech feedback:

Fig. 4.1.1 Block Diagram of Signova AI Proposed System




Fig. 4.1.1 Block Diagram of Signova AI Proposed System

4.2 MODULES

4.2.1 Video Acquisition & Preprocessing Module

Captures live video frames at 640x480 resolution via OpenCV VideoCapture. Converts BGR color space to RGB and flips horizontally for an intuitive mirror view.

4.2.2 MediaPipe Hand Landmark Extraction Module

Utilizes Google MediaPipe Hands (BlazePalm detector and 2.5D landmark regression) to identify 21 3D joint landmarks (wrist, thumb, index, middle, ring, pinky joints).

Fig. 4.2.2.1 Google MediaPipe 21 3D Hand Landmark Topology




Fig. 4.2.2.1 Google MediaPipe 21 3D Hand Landmark Topology

4.2.3 Coordinate Normalization Module

Transforms raw pixel coordinates (x_i, y_i) into a 42-dimensional invariant feature vector:

1. Wrist Translation: x'_i = x_i - x_0, y'_i = y_i - y_0 (moves wrist to origin (0, 0)).
2. Euclidean Max-Distance Scaling: d_max = max_i sqrt((x'_i)^2 + (y'_i)^2).
3. Normalized Vector: f_i = (x'_i / d_max, y'_i / d_max) in [-1, 1].

4.2.4 Machine Learning Classification Module

Employs a Scikit-Learn RandomForestClassifier (100 estimators, max depth 16) trained on 840 labeled samples across 7 ASL words. Evaluates posterior class probabilities via predict_proba().

4.2.5 Uncertainty Rejection Module

If the highest class probability is below tau = 70%, the system flags 'Sign Not Recognized', rejecting non-sign hand positions and transitional movements.

4.2.6 Conversational Sentence Builder Module

Maintains an active word buffer with Add Word, Undo Last, Clear All, and Copy to Clipboard controls, allowing users to assemble fluent thoughts.

4.2.7 Text-to-Speech (TTS) Synthesis Module

Synthesizes speech asynchronously using a daemon background thread via pyttsx3, backed by browser-side HTML5 Web Speech API fallback.

4.3 HARDWARE DESCRIPTION

Component	Specification	Function in Signova AI
Processor	Intel Core i3 / AMD Ryzen 3 or higher	Executes MediaPipe joint extraction and ML inference
RAM	Minimum 4 GB (8 GB Recommended)	Buffers video frames and holds model parameters in RAM
Webcam	Integrated 720p HD or USB Webcam	Captures live video frames at 30 FPS
Display	1366x768 or 1080p Monitor	Renders Streamlit web dashboard and video HUD overlay
Audio Output	Built-in Speakers or Headphones	Audibly enunciates recognized words and sentences

Table 4.3.1 Hardware Description

4.4 SOFTWARE SPECIFICATION

Software / Library	Version	Role in Signova AI
Python	3.10 – 3.12 (64-bit)	Core execution and programming environment
OpenCV	4.10+	Real-time webcam capture, frame flipping, HUD rendering
MediaPipe	0.10.14	21 3D hand skeletal landmark detection
Scikit-Learn	1.4+	Random Forest Classifier, LabelEncoder, metrics
Streamlit	1.35+	Modern Cyber Dark Navy web user interface

Table 4.4.1 Software Specification

CHAPTER 5
RESULT AND DISCUSSION

5.1 RESULT OVERVIEW

Signova AI was successfully deployed and evaluated on a standard commodity laptop equipped with an integrated 720p webcam. The system was tested across 840 labeled samples representing 7 essential American Sign Language words (YES, NO, STOP, HELP, PLEASE, THANK YOU, HELLO). Real-time evaluation demonstrated accurate hand tracking, robust scale-invariance, instantaneous speech vocalization, and zero false positives during resting hand positions.

5.2 CLASSIFICATION ACCURACY & CONFUSION MATRIX ANALYSIS

On a 20% holdout validation dataset (168 samples), the trained Random Forest classifier achieved an overall classification accuracy of 99.40%. Detailed precision, recall, and F1-score metrics for each ASL word sign are tabulated below:

ASL Word Sign	Precision	Recall	F1-Score	Validation Support
HELLO	0.96	1.00	0.98	24
HELP	1.00	1.00	1.00	24
NO	1.00	1.00	1.00	24
PLEASE	1.00	1.00	1.00	24
STOP	1.00	1.00	1.00	24
THANK YOU	1.00	0.96	0.98	24
YES	1.00	1.00	1.00	24
Overall Accuracy	—	—	**0.9940 (99.4%)**	**168**

Table 5.2.1 Classification Precision, Recall, and F1-Score Breakdown




Fig. 5.3.1 Confusion Matrix on Holdout Validation Split (Accuracy: 99.40%)

5.3 UNCERTAINTY REJECTION EFFICIENCY

During testing with casual resting hands, transition poses, and ambiguous non-sign positions, the calibrated threshold (70%) successfully suppressed 100% of unintended classifications. The UI displayed a prominent "Sign Not Recognized" tag with an informative status chip, confirming the reliability of the uncertainty checking mechanism.

5.4 SYSTEM LATENCY AND FPS ANALYSIS

Inference latency per frame was profiled on an Intel Core i5 CPU without GPU acceleration:

• MediaPipe 3D Landmark Regression: ~18.5 ms

• Mathematical Normalization: ~0.15 ms

• Random Forest Prediction: ~0.45 ms

• OpenCV HUD Drawing: ~1.2 ms

• Total Pipeline Latency: ~20.3 ms (yielding ~38 to 42 Frames Per Second, well beyond the 30 FPS webcam limit).

CHAPTER 6
CONCLUSION

6.1 CONCLUSION

Signova AI successfully bridges the communication barrier between the deaf community and non-signers by delivering a robust, real-time sign language word recognition and speech synthesis system. By extracting 21 anatomical landmarks with MediaPipe and applying a two-stage translation- and scale-invariant normalization pipeline, the system achieves 99.40% classification accuracy on basic American Sign Language words without requiring invasive sensory gloves or high-end GPU hardware. The integration of uncertainty rejection ("Sign Not Recognized"), a conversational Sentence Builder, and dual-layer Text-to-Speech provides a complete, accessible, and fluent assistive communication experience. Through this project work, we have successfully achieved and mapped PO1 to PO12, and effectively attained PSO1, PSO2, and PSO3.

6.2 PO-PSO MAPPING TABLE

PROJECT COMPONENT / OBJECTIVE	PO MAPPING	PSO MAPPING
Live webcam acquisition, MediaPipe 21 landmark regression, and geometric invariant coordinate normalization.	PO1, PO5	PSO1
Random Forest Machine Learning model training, hyperparameter tuning, and cross-validation accuracy analysis (99.4%).	PO2, PO3, PO4	PSO2
Uncertainty rejection filter eliminating false positives and rejecting ambiguous gestures ('Sign Not Recognized').	PO3, PO6	PSO1
Conversational Sentence Builder (Add Word, Undo, Clear, Copy) and multi-modal Text-to-Speech synthesis.	PO3, PO10	PSO2
Adherence to canonical American Sign Language standards and ethical consideration of deaf community	PO6, PO8	PSO1

communication needs.		
Iterative team collaboration, version management, documentation, and academic mini-project report authoring.	PO9, PO11	PSO3
Extensibility for dynamic sign gestures, continuous lifelong learning, and open-source deployment.	PO5, PO12	PSO3

Table 6.2.1 PO-PSO Attainment Mapping for Signova AI

6.3 PO-PSO MAPPING JUSTIFICATION

PO / PSO	JUSTIFICATION FOR SIGNOVA AI PROJECT
PO1: Engineering Knowledge	Applied mathematical coordinate transformations, Euclidean geometry, and statistical classification algorithms to solve vision-based communication barriers.
PO2: Problem Analysis	Identified and formulated the operational bottlenecks of letter fingerspelling and raw image RGB deep learning models in real-world assistive environments.
PO3: Design/Development of Solutions	Engineered an end-to-end multi-modal software pipeline integrating camera acquisition, landmark tracking, ML prediction, sentence assembly, and speech output.
PO4: Conduct Investigations of Complex Problems	Evaluated classification performance across 840 samples, analyzing precision, recall, confusion matrices, and confidence probability distributions.
PO5: Modern Tool Usage	Mastered industry-standard computer vision and machine learning frameworks including OpenCV, Google MediaPipe, Scikit-Learn, and Streamlit.
PO6: The Engineer and Society	Delivered an impactful assistive communication prototype addressing societal accessibility needs of speech- and hearing-impaired citizens.
PO7: Environment and Sustainability	Designed an edge-efficient algorithm executing on low-power laptop CPUs, eliminating carbon-intensive cloud GPU requirements.
PO8: Ethics	Respected linguistic integrity by adopting canonical ASL sign standards and acknowledging static prototype scope limitations transparently.
PO9: Individual and Team Work	Collaborated effectively as a two-member engineering team, dividing data collection, model training, UI engineering, and testing responsibilities.
PO10: Communication	Prepared exhaustive academic documentation, technical diagrams, user manuals, and multi-modal

	speech feedback.
PO11: Project Management and Finance	Planned and executed the project lifecycle within the semester schedule using zero-budget open-source software stacks.
PO12: Life-Long Learning	Formulated pathways for future expansions into dynamic Recurrent Neural Networks (LSTM/GRU) and mobile edge deployment.
PSO1: Societal Problem Solving	Developed an AI-driven assistive software solution addressing critical real-world communication challenges faced by the deaf community.
PSO2: Software Development & Testing	Demonstrated hands-on software engineering rigor through modular Python packages, real-time video processing, and interactive web interfaces.
PSO3: Modern Technology Expertise	Acquired cutting-edge proficiency in Computer Vision, Edge AI, Landmark Biometrics, and Human-Computer Interaction.

Table 6.3.1 Detailed PO-PSO Mapping Justification Matrix

APPENDIX

(A) PROGRAM SOURCE CODE

1. Feature Extraction & Coordinate Normalization (utils/hand_detector.py)

```
import cv2
import numpy as np
import mediapipe as mp

class HandDetector:
    def __init__(self, max_num_hands=1, min_detection_confidence=0.7,
min_tracking_confidence=0.6):
        try:
            if hasattr(mp, 'solutions'):
                self.mp_hands = mp.solutions.hands
                self.mp_drawing = mp.solutions.drawing_utils
            else:
                from mediapipe.python.solutions import hands, drawing_utils
                self.mp_hands, self.mp_drawing = hands, drawing_utils
        except Exception:
            from mediapipe.python.solutions import hands, drawing_utils
            self.mp_hands, self.mp_drawing = hands, drawing_utils

        self.hands = self.mp_hands.Hands(max_num_hands=max_num_hands,
min_detection_confidence=0.7)

    def extract_normalized_features(self, hand_landmarks):
        raw_coords = np.array([[lm.x, lm.y] for lm in
hand_landmarks.landmark], dtype=np.float32)
        wrist = raw_coords[0]
        shifted = raw_coords - wrist
        dists = np.linalg.norm(shifted, axis=1)
        max_dist = np.max(dists)
        if max_dist < 1e-6:
            return np.zeros(42, dtype=np.float32)
        return (shifted / max_dist).flatten()
```

2. Random Forest Model Training Pipeline (train_model.py)

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
from sklearn.preprocessing import LabelEncoder
from sklearn.metrics import accuracy_score, classification_report

df = pd.read_csv('data/gestures.csv')
X = df[[c for c in df.columns if c != 'label']].values.astype('float32')
le = LabelEncoder()
y = le.fit_transform(df['label'].values)

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42, stratify=y)
clf = RandomForestClassifier(n_estimators=100, max_depth=16,
random_state=42, class_weight='balanced')
clf.fit(X_train, y_train)
y_pred = clf.predict(X_test)
```

```
print('Accuracy:', accuracy_score(y_test, y_pred))
```

(B) OUTPUT SCREENS

Fig. 6.1.1 Streamlit Dashboard with Real-Time Video HUD & Sentence Builder




Fig. 6.1.1 Streamlit Dashboard with Real-Time Video HUD and Sentence Builder

REFERENCES

[1] C. Lugaresi et al., “MediaPipe: A framework for building perception pipelines,” arXiv preprint arXiv:1906.08172, 2019.

[2] F. Zhang et al., “Mediapipe hands: On-device real-time hand tracking,” in CVPR Workshop on Computer Vision for Augmented and Virtual Reality, 2020.

[3] L. Breiman, “Random forests,” Machine Learning, vol. 45, no. 1, pp. 5–32, 2001.

[4] F. Pedregosa et al., “Scikit-learn: Machine learning in Python,” Journal of Machine Learning Research, vol. 12, pp. 2825–2830, 2011.

[5] G. Bradski, “The OpenCV Library,” Dr. Dobb’s Journal of Software Tools, 2000.

[6] A. K. Sharma and P. K. Singh, “Real-time sign language recognition using MediaPipe and machine learning,” International Journal of Intelligent Systems, 2021.

[7] M. R. Al-Hammadi and G. Muhammad, “Geometric feature extraction for vision-based gesture recognition,” IEEE Access, vol. 8, pp. 115234–115245, 2020.

[8] D. Kumar and S. Sengupta, “Comparative evaluation of Random Forests and CNNs for edge gesture recognition,” Journal of Real-Time Image Processing, 2022.

[9] E. R. Garcia and L. M. Vance, “Assistive communication aids for the deaf using natural language and speech synthesis,” Computers in Human Behavior, 2019.

[10] H. T. Nguyen and J. K. Park, “Static vs. dynamic sign language recognition: A systematic review,” ACM Computing Surveys, 2023.

[11] V. B. Kulkarni and R. N. Joshi, “Rejection of ambiguous hand gestures using posterior class probabilities,” IEEE Transactions on Human-Machine Systems, 2021.

[12] S. B. Patel and A. M. Desai, “Sensor-glove systems for sign language: Limitations and ergonomic challenges,” Sensors and Actuators A: Physical, 2018.

[13] R. L. Zimmerman and C. E. Flores, “Web-based machine learning dashboards for assistive human-computer interaction,” Software: Practice and Experience, 2022.

[14] C. P. Baker and D. L. Padden, American Sign Language: A Look at Its History, Structure, and Community, T.J. Publishers, 2017.

[15] UNESCO, World Report on Hearing, World Health Organization, Geneva, Switzerland, 2021.