Understanding the Bias–Variance Trade-off using K-Nearest Neighbour

Student Name : Vivekananda Reddy Gajulapalli
Student id : 24157524
Github Repository: https://github.com/Vivek-6-afk/bias-variance-knn

1. Introduction

Machine learning models are widely used to analyse data and make predictions in many real-world applications such as medical diagnosis, recommendation systems and financial forecasting. One important challenge when designing these models is ensuring that they perform well not only on training data but also on new unseen data. This concept is known as generalisation. A key theoretical idea that helps in understanding generalisation is the bias–variance trade-off.The bias–variance trade-off explains how the complexity of a machine learning model affects its prediction performance. Models that are too simple may fail to capture meaningful patterns in data, while models that are too complex may learn noise instead of useful information. Understanding this balance is essential for building reliable and efficient predictive systems.This tutorial focuses on explaining the bias–variance trade-off using the K-Nearest Neighbour (KNN) algorithm. By analysing both theoretical concepts and experimental behaviour, learners can understand how model complexity influences learning performance.

2. Overview of K-Nearest Neighbour Algorithm

K-Nearest Neighbour is a supervised machine learning algorithm used for classification and regression tasks. The main idea behind KNN is simple: predictions are made based on the similarity between data points. When a new sample needs to be classified, the algorithm finds the K closest training samples and assigns the class that appears most frequently among them.The value of K controls the behaviour of the model. A small K value means the model focuses on very local patterns in the dataset. This can result in highly detailed decision boundaries that closely follow training samples. On the other hand, a large K value produces smoother decision boundaries because predictions are influenced by a wider neighbourhood of samples.Because of its intuitive working principle, KNN is often used as a starting point for understanding fundamental machine learning concepts such as overfitting, underfitting and generalisation.

3. Concept of Bias in Machine Learning

Bias refers to the error that occurs when a model makes simplifying assumptions about the relationship between input features and target values. High bias models are usually too simple to represent complex patterns in data. As a result, they produce systematic prediction errors.For example, when the value of K in KNN is very large, the classifier averages information from many training samples. This causes the decision boundary to become overly smooth. Although such a model may perform consistently across different datasets, it may fail to capture important local structures. This leads to underfitting, where the model cannot adequately learn the underlying distribution of the data.High bias reduces the flexibility of a model and limits its ability to adapt to different learning

scenarios. Therefore, selecting an appropriate model complexity is essential to minimise bias while maintaining stable performance.

4. Concept of Variance in Machine Learning

Variance refers to the sensitivity of a machine learning model to small changes in the training dataset. A model with high variance learns the training data very closely, including noise and random fluctuations. As a result, its predictions may vary significantly when trained on different subsets of data.In KNN, high variance occurs when the value of K is very small. The classifier focuses only on a few neighbouring samples, which can lead to irregular and complex decision boundaries. Although this approach may produce high accuracy on training data, it often results in poor performance on unseen data.High variance is associated with overfitting, where the model memorises the training dataset instead of learning general patterns. Controlling variance is important for ensuring that machine learning systems provide reliable predictions in real-world applications.

5. Mathematical Understanding of the Bias–Variance Trade-off

The prediction error of a machine learning model can be analysed using error decomposition. According to statistical learning theory, the expected squared prediction error can be expressed as the sum of bias squared, variance and irreducible noise. Irreducible noise represents random factors in the data that cannot be explained by any model.Bias measures how far the average prediction of a model is from the true underlying function. Variance measures how much predictions change when the model is trained on different datasets. As model complexity increases, bias generally decreases because the model becomes more flexible. However, variance increases because the model becomes more sensitive to noise.This relationship forms the basis of the bias–variance trade-off. The goal of model design is to find an optimal balance where total prediction error is minimised.

6. Experimental Setup

To demonstrate the bias–variance trade-off, an experiment can be conducted using a standard classification dataset such as Iris or a synthetic dataset. The dataset is divided into training and validation sets to evaluate model generalisation performance.Several KNN models are trained using different values of K. Other parameters such as distance metric and evaluation method are kept constant to ensure fair comparison. Model performance is measured using classification accuracy and visualisation of decision boundaries.By analysing how performance changes with different K values, learners can observe how bias and variance influence prediction behaviour in practice.

7. Analysis of Model Behaviour

When K is set to a very small value, the model produces highly detailed decision boundaries that closely follow training samples. This results in low bias because the model can represent complex patterns. However, prediction performance on validation data may fluctuate due to high variance.As the value of K increases, the decision boundary becomes smoother. This reduces variance and improves stability of predictions. Validation accuracy may increase initially because the model generalises better to unseen data.If K becomes too large, the model becomes overly simplified. Important local patterns may be

ignored, leading to increased bias and reduced classification performance. This behaviour clearly illustrates the theoretical bias–variance trade-off.

8. Visual Interpretation

Graphs showing validation accuracy for different K values can help learners understand the relationship between model complexity and performance.



Figure 1: Validation and training accuracy for different values of K showing the bias–variance trade-off

Typically, accuracy improves as K increases from a very small value, reaches an optimal point, and then decreases as bias dominates.Conceptual bias–variance curves can also be used to show how bias decreases and variance increases with model flexibility. Visual tools make theoretical concepts easier to understand and enhance the effectiveness of the tutorial.



Figure 2: Conceptual illustration of bias–variance trade-off showing optimal model complexity.

9. Real-World Importance

Understanding the bias–variance trade-off is important for designing machine learning systems used in practical environments. In applications such as medical diagnosis or fraud detection, both underfitting and overfitting can lead to serious consequences.Selecting appropriate model complexity helps ensure that predictions remain accurate and stable when applied to new data. Techniques such as cross-validation, regularisation and ensemble learning are commonly used to manage bias and variance in modern machine learning systems.

10. Experimental Limitations and Future Scope

Although this tutorial demonstrates key concepts using the KNN algorithm, the experiment is limited to a relatively simple model and dataset. More complex machine learning methods such as neural networks or support vector machines may show different generalisation behaviour.Future work could explore larger datasets, advanced validation strategies and hybrid modelling approaches. Investigating how bias and variance interact with deep learning architectures would provide deeper insight into modern artificial intelligence systems.

11. Conclusion

The bias–variance trade-off is a fundamental concept that explains how model complexity influences prediction performance. Through theoretical explanation and experimental analysis using the K-Nearest Neighbour algorithm, this tutorial has shown how small values of K lead to high variance and potential overfitting, while large values of K increase bias and risk underfitting.Achieving a balance between these two sources of error is essential for building machine learning models that generalise well to new data. By understanding this trade-off, practitioners can make more informed decisions when selecting algorithms and tuning model parameters.As machine learning continues to be applied in critical domains, the ability to manage bias and variance will remain an important skill for data scientists and engineers.

12. Accessibility Considerations

This tutorial is written using clear language and structured headings to improve readability for learners with different levels of technical background. Figures include descriptive captions and colour-blind friendly visual styles. The accompanying code is organised step-by-step to support reproducibility and independent learning.

References

- *Goodfellow, I., Bengio, Y. and Courville, A. (2016) Deep Learning. Cambridge, MA: MIT Press.*
- *Hastie, T., Tibshirani, R. and Friedman, J. (2009) The Elements of Statistical Learning: Data Mining, Inference, and Prediction. 2nd edn. New York: Springer.*
- *Bishop, C. M. (2006) Pattern Recognition and Machine Learning. New York: Springer.*
- *Murphy, K. P. (2012) Machine Learning: A Probabilistic Perspective. Cambridge, MA: MIT Press.*
- *James, G., Witten, D., Hastie, T. and Tibshirani, R. (2021) An Introduction to Statistical Learning with Applications in Python. New York: Springer.*
- *Cover, T. M. and Hart, P. E. (1967) 'Nearest neighbour pattern classification', IEEE Transactions on Information Theory, 13(1), pp. 21–27.*