

VISVESVARAYATECHNOLOGICAL UNIVERSITY
BELAGAVI - 590018



An Mini Project Report on

**RFID BASED ATTENDANCE SYSTEM WITH GOOGLE
SHEETS USING ESP8266**

Submitted by

VIVEK A K 2KA24EC407

DARSHAN B V 2KA23EC009

Under the Guidance of

Mr. ARUNKUMAR S B



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING**



Smt. Kamala & Sri Venkappa M. Agadi
College of Engineering and Technology, Lakshmeshwar-582116
ಶ್ರೀಮತಿ ಕಮಲಾ ಮತ್ತು ಶ್ರೀ ವೆಂಕಪ್ಪ ಎಂ. ಅಗಡಿ ತಾಂತ್ರಿಕ ಮತ್ತು ಅಭಿಯಾಂತ್ರಿಕ ಮಹಾವಿದ್ಯಾಲಯ, ಲಕ್ಷ್ಮೇಶ್ವರ
Approved by AICTE & Affiliated to VTU Belagavi, Karnataka.
Mobile : 9448120344 | info@agadiengecollege.com



2025-2026



Smt. Kamala & Sri Venkappa M. Agadi
College of Engineering and Technology, Lakshmeshwar-582116
ಶ್ರೀಮತಿ ಕಮಲಾ ಮತ್ತು ಶ್ರೀ ವೆಂಕಪ್ಪ ಎಂ. ಅಗಡಿ ತಾಂತ್ರಿಕ ಮತ್ತು ಅಭಿವೃದ್ಧಿಪಡಿಸಿದ ಮಹಾವಿದ್ಯಾಲಯ, ಲಕ್ಷ್ಮೇಶ್ವರ
Approved by AICTE & Affiliated to VTU Belagavi, Karnataka.
Mobile : 9448120344 | info@agadiengcollege.com



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING**

Certificate

Certified that the Mini Project Report entitled “**RFID BASED ATTENDANCE SYSTEM WITH GOOGLE SHEETS USING ESP8266**” is a work carried out by **VIVEK A K , DARSHAN B V** bearing USN **2KA24EC407, 2KA23EC009**. In the partial fulfillment prescribed by the **VISVESVARAYA TECHNOLOGICAL UNIVERSITY, BELAGAVI** for V semester Electronics and Communication Engineering during the year 2025-2026. This Mini project report has been approved as it satisfies the academic requirements in respect to the Mini Project work prescribed for the Bachelor of Engineering Degree.

Mr.ARUNKUMAR S B
Guide

Dr. Santosh S Bujari
Coordinator

Dr. Subhas A Meti
Dean Academics

Dr. Santosh S. Bujari
HOD

Dr. Parashuram Baraki
Principal

ACKNOWLEDGEMENT

I, **Vivek A. K, Darshan B. V** the satisfactions and euphoria that a company the successful completion of any task would be incomplete without the mention of people who made it possible, whose consistent guidance and encouragement crowned our efforts with success.

I am much obliged to **Mr. Arunkumar S. B**, Assistant Professor, Department of Electronics & Communication Engineering, SKSVMACET, Lakshmeshwar for his constant support and inspiration, encouragement, motivation.

I sincerely thank **Dr. Santosh S. Bujari**, Associate Professor, Department of Electronics & Communication Engineering, SKSVMACET, Lakshmeshwar and express my humble gratitude for the valuable guidance, inspiration, encouragement and immense help which made work a success.

I am much obliged to **Dr. Santosh S. Bujari**, Associate Professor and HOD, Department of Electronics & Communication Engineering, SKSVMACET, Lakshmeshwar for his constant support and motivation.

I am deeply indebted to **Dr. Subhas A. Meti**, Dean Academics, SKSVMACET, and Lakshmeshwar for providing me with a rejuvenating master course under a very creative learning environment.

I am deeply indebted to **Dr. Parashuram Baraki**, Principal, SKSVMACET, and Lakshmeshwar for providing me with a rejuvenating master course under a very creative learning environment.

I extend my warm gratitude and regards to everyone who helped me during my Mini Project.

NAME: VIVEK A K

USN : 2KA24EC407

NAME: DARSHAN B V

USN : 2KA23EC009

ABSTRACT

This project introduces an IoT-based attendance system that combines RFID technology with the ESP8266 microcontroller and Google Sheets to create a fast, accurate, and low-cost method for recording attendance. Traditional attendance procedures often involve manual entry or expensive biometric devices, both of which are prone to errors, delays, and maintenance challenges. To overcome these limitations, the proposed system uses an RC522 RFID reader to capture the unique ID (UID) from RFID cards assigned to each user. When a card is scanned, the ESP8266 reads the UID and sends it directly to a cloud-based Google Sheet through a Google Apps Script Web API.

The ESP8266 serves as the system's communication hub, connecting the RFID hardware to the internet via Wi-Fi. Each scanned entry is transmitted as a secure POST request to the web script, which automatically adds the UID and timestamp to Google Sheets. This eliminates the need for local servers or complex database management. The cloud-based storage also ensures real-time access to attendance data from any device, making monitoring simple for teachers, administrators, or supervisors.

This method provides several advantages: it is contactless, quick, tamper-resistant, and cost-effective. The system minimizes human errors, prevents manipulation, and significantly reduces the time required for daily attendance collection. The modular design also supports further enhancements such as assigning names to UIDs, building dashboards, preventing duplicate entries, or notifications.

CONTENTS

S.NO	Chapter Name	Page Range
1	Introduction	01-05
2	Literature Survey	06-08
3	Domain Analysis	09-12
4	Requirement Specification	13-17
5	System Methodology	18-21
6	System impementation	21-26
7	Results	26-30
8	Source Code Snapshot	31-37
9	Conclusion and Future Scope	38-40
10	References	41-42

LIST OF FIGURES

Figure No.	Figure Name	Page No.
6.1	RFID UID DETECTION	25
6.1.1	GOOGLE SHEETS ATTENDANCE ENTRIES	26
8.1	RFID TAG CODE	33
8.1.1	RFID ATTENDANCE SYSTEM CODE	36
8.1.2	GOOGLE SCRIPT CODE	37

Chapter 1

INTRODUCTION

The Attendance tracking is an essential administrative activity in schools, colleges, offices, and training institutes. Accurate attendance records help ensure accountability, maintain discipline, and support decision-making processes such as performance analysis, payroll calculation, and compliance documentation. However, most traditional attendance methods rely on manual processes like paper registers, sign-in sheets, or manual calling of names. These older methods require time, effort, and are often affected by human errors, manipulation, or data loss. Modern organizations increasingly look for automated, reliable, and tamper-proof systems that reduce administrative workload and deliver real-time insights.

This project introduces an automated attendance system based on RFID (Radio Frequency Identification) technology integrated with the ESP8266 Wi-Fi microcontroller. RFID offers a simple, contactless method for identifying individuals through unique RFID tags or cards. When integrated with the ESP8266, the system gains wireless capability, allowing instant transmission of attendance data to cloud storage. Google Sheets is used as the backend database, offering real-time access, easy sharing, automatic timestamping, and zero-cost cloud services.

The combination of RFID, ESP8266, and Google Sheets creates an efficient IoT-based attendance system that is cost-effective, easy to implement, and scalable. The system removes the need for manual data entry, minimizes errors, and provides quick access to attendance logs from anywhere. It is especially suitable for educational institutions, small companies, and project demonstrations where low-cost and reliable digital attendance is required.

1.1 Problem Statement

The Attendance systems in many organizations still rely on outdated, manual processes. These methods create several problems:

- They are **slow** and consume valuable time during class or work sessions.
- They are **prone to human error**, such as incorrect entries or missed names.
- They can be **manipulated**, allowing proxy attendance or false entries.
- Paper registers can be **lost, damaged, or difficult to store** for long periods.
- Manual records do not provide real-time access for administrators.
- Traditional biometric systems, though efficient, involve **high costs**, require maintenance, and may raise hygiene concerns.

Due to these limitations, there is a strong need for an automated system that records attendance instantly, accurately, and securely without relying on complex or expensive equipment.

1.2 Objectives

Core Functional Objectives

- Develop an RFID-based attendance system capable of reading unique card IDs.
- Interface the RC522 RFID module with the ESP8266 microcontroller.
- Transmit attendance data wirelessly to a cloud platform.

Cloud & Data Objectives

- Use Google Sheets as a free, scalable, and accessible attendance database.
- Create a Google Apps Script API to receive and store attendance data.
- Include automatic timestamping for each entry.

Performance Objectives

- Ensure fast and contactless attendance marking.
- Minimize errors and eliminate manual record entry.
- Reduce administrative workload.

User & System Objectives

- Provide real-time access to attendance logs.
- Maintain ease of use for teachers, admins, and operators.
- Keep the entire system low-cost and beginner-friendly.

Expandable Objectives

- Allow adding new tags without major changes.
- Support seamless integration of analytics, dashboards, or notifications.

1.3 Scope

Included in the Project

- Setting up RFID hardware (RC522 reader + RFID tags).
- Connecting and programming the ESP8266 microcontroller.
- Establishing Wi-Fi connectivity for cloud communication.
- Writing Google Apps Script to create an API endpoint.
- Logging attendance automatically in Google Sheets.
- Recording timestamps and UID information.
- Real-time monitoring through the cloud dashboard.
- Demonstrating system operation with multiple users.

Application Scope

- Schools and educational institutions
- Coaching classes
- Small to medium-sized companies
- Offices with access control
- Libraries and laboratories
- Hostels and training centers
- Event attendance and visitor tracking

Not Included (But Possible in Future)

- Complex biometric authentication
- Enterprise-level security systems
- Advanced data analytics dashboards
- Mobile application development

1.4 Future Scope

1. Dashboard and Analytics

- Integration with Google Data Studio or Power BI.
- Real-time charts: total attendance, daily trends, absence alerts.

2. Mobile App Integration

- Android/iOS app for teachers and admin staff
- Push notifications for irregular attendance

3. Notification Features

- Automatic email reminders to absentees
- SMS notifications to parents or employees

4. Security Improvements

- Token-based authentication
- Full HTTPS certificate validation
- Encrypted local data storage

5. Large-Scale Deployment

- Multi-room or multi-floor attendance tracking.
- Network of interconnected ESP8266 readers.
- Centralized dashboard for entire campuses.

6. Access Control Integration

- RFID-based door locks
- Only authorized users allowed entry

7. Additional Sensors

- Combining RFID with face recognition
- Biometric-RFID dual authentication
- Temperature sensing for health monitoring

8. Offline Capability

- Local data caching during network failure
- Auto-sync when internet returns

Chapter 2

LITERATURE SURVEY

Overview

Automated attendance systems using RFID and IoT have been widely researched and implemented because they offer contactless, fast, and scalable recording of presence data. Researchers commonly combine an RFID reader (e.g., MFRC522), a microcontroller (Arduino/ESP8266), and a cloud/backend (web server, Google Sheets, or local database) to log time-stamped UID entries for each tag scan. Several surveys and systematic reviews summarize empirical work showing consistent benefits in speed, reduced errors, and ease of deployment compared with manual methods.

2.1 Key studies and implementations

- **Foundational implementations** demonstrate straightforward hardware + web logging pipelines: RC522 reader + microcontroller → HTTP POST → spreadsheet or DB. These projects form the baseline design pattern for low-cost attendance systems and are often used as teaching/project examples.
- **Systematic literature reviews** examined multiple RFID-attendance works and report common strengths (automation, time savings, proxy reduction) and recurring weaknesses (security, duplicate reads, network dependency). These reviews analyzed 20+ primary studies and drew recommendations for authentication, local caching, and duplicate-suppression logic.
- **Academic prototypes and journal papers** describe extended features: integration with LabVIEW or custom web apps, mapping UIDs to user records, and exporting reports for administration. They also evaluate accuracy and throughput in classroom-scale deployments.

2.2 Comparisons with alternative technologies

- **Biometrics (fingerprint/face):** higher identity assurance but significantly higher cost, maintenance, and hygiene concerns; suitable for high-security contexts but often overkill for routine classroom attendance.
- **Barcode/QR-code:** cheap and simple but requires line-of-sight and human handling; less convenient than RFID for fast entry.

- **NFC vs. RFID:** NFC (a subset/compatibility mode in some tags/devices) offers phone-based interactions; passive HF RFID (RC522) is typically cheaper for card/tag deployments. Literature positions RFID as the best trade-off for low-cost, contactless, moderate-security

2.3 Common design choices, challenges and mitigations

- **Authentication & tamper risk:** many projects rely on a “secret token” or mapping table to reduce spoofing; literature recommends stronger server-side checks and HMAC/JWT for production.
- **Duplicate/rapid reads:** naive systems log multiple timestamps for the same user within seconds; common mitigations include debounce windows (ignore same UID for X minutes) or server-side duplicate filters.
- **Network reliability:** cloud logging (Google Sheets, web APIs) is easy but vulnerable to network outages; suggested fixes are local caching on the microcontroller with periodic sync.
- **Privacy & data management:** few papers deeply explore GDPR/PII concerns—this is a recognized gap. Best practice is to minimize stored PII on the device and secure transit/storage.

2.4 Gaps in existing work

1. **Security hardening:** many prototypes stop at a shared secret; adoption-grade systems need end-to-end encryption, certificate validation, and access controls.
2. **Scalability studies:** limited empirical studies show how large deployments (multi-reader, campus-wide) perform in terms of collisions, throughput, and central synchronization.
3. **Privacy & compliance:** sparse treatment of legal/ethical handling of attendance logs across jurisdictions.
4. **Hybrid authentication:** few implementations evaluate the trade-offs and accuracy gains of combining RFID with biometrics or face recognition at scale (most are proof-of-concept)

2.5 Summary and implications for this project

The literature consistently supports RFID + microcontroller + cloud logging as an effective, low-cost approach to automate attendance for classrooms and small organizations. Key design lessons to adopt: use server-side duplicate suppression, include an authentication token and consider stronger auth for production, implement local caching for offline resilience, and plan privacy-minimizing data storage. This project should build on those best practices and address gaps by adding basic security (secret + HTTPS), debounce logic to prevent duplicate entries, and a simple policy for handling per so Nadat.

Chapter 3

DOMAIN ANALYSIS

The domain of this project lies at the intersection of **IoT (Internet of Things)**, **RFID (Radio Frequency Identification)** technology, and **cloud-based data management**. The system functions as an automated attendance solution that uses RFID tags for user identification, an ESP8266 microcontroller for wireless communication, and Google Sheets for cloud data storage. This domain primarily focuses on automation, wireless communication, embedded systems, and real-time digital recordkeeping.

3.1 RFID Technology Domain

RFID is a wireless identification method that uses electromagnetic fields to identify tagged objects. In the context of attendance systems, each user has an RFID card with a unique identifier (UID). The RC522 reader detects this UID within a short range (approximately 3–5 cm).

Key characteristics of RFID domain:

- Contactless identification
- Fast response time
- Unique and non-duplicable ID for each tag
- Low power consumption
- Suitable for repeated daily use

RFID is widely used in access control, public transport cards, inventory tracking, and library management. Its reliability and low cost make it ideal for attendance systems.

3.2 IoT and Embedded Systems Domain

1. The system belongs to the IoT domain because it connects physical hardware to the internet for real-time communication. The ESP8266 microcontroller enables Wi-Fi connectivity and allows the device to interact with cloud platforms.

2. Important IoT characteristics:
3. Device-to-cloud communication
4. Data automation without human input
5. Real-time updates and remote monitoring
6. Use of open-source hardware and software
7. The ESP8266 acts as a bridge between RFID hardware and cloud services, making the attendance process seamless and instant.

3.3 Cloud Computing & Data Storage Domain

Cloud computing is a crucial domain of this project, as all attendance data is stored in **Google Sheets** using an **Apps Script API**. This reduces the need for physical storage devices or local databases.

Cloud domain characteristics:

- Accessibility from any location
- Automatic timestamping and backup
- Easy data visualization and report generation
- No installation or maintenance cost

Cloud integration enhances the practicality and scalability of the attendance system, especially for institutions managing large amounts of data.

3.4 Automation & Attendance Management Domain

Attendance management is an administrative domain that involves tracking present/absent individuals in an organized way. Automation helps reduce manual effort and ensures accuracy.

Challenges in traditional attendance domain:

- High time consumption
- Errors and manipulation
- Difficulty in record-keeping
- No real-time insight

Automated attendance benefits:

- Speed and efficiency
- Improved accuracy
- Reduced workload for staff
- Digital recordkeeping and analysis

The RFID + IoT model directly addresses the weaknesses of manual systems.

3.5 Problem Domain vs. Solution Domain

Problem Domain

- Manual attendance methods are slow and error-prone
- Existing biometric systems are expensive
- Lack of real-time access
- Difficulty in managing large datasets
- Risk of proxy or fake attendance

Solution Domain

- RFID enables fast and accurate identity detection
- ESP8266 provides wireless connectivity
- Google Sheets ensures cloud-based storage with no cost
- Automation eliminates manual data entry
- Real-time updates improve monitoring and transparency

The solution domain integrates hardware, software, and cloud technologies to overcome traditional limitations.

3.6 Domain Requirements

Functional Domain Requirements

- Identify users through RFID tags
- Read UID via RC522 reader
- Transmit data wirelessly to cloud
- Log attendance with timestamp
- Display and store attendance records online

Non-Functional Domain Requirements

- System must be fast and responsive
- Data should remain accurate and consistent
- Cloud storage must be secure and reliable
- Device should consume low power
- System should be simple to deploy and maintain

3.7 Summary

The domain analysis reveals that the project sits across multiple technology domains, including RFID systems, IoT communication, cloud storage, and automated attendance management. Each domain contributes a critical component: RFID for identification, ESP8266 for connectivity, Google Sheets for storage, and automation for efficiency. Together, they create a robust, modern, and scalable attendance solution suitable for institutions and organizations seeking digital transformation.

Chapter 4

REQUIREMENTS SPECIFICATION

The requirements specification defines all the essential components, functionalities, performance expectations, and operational constraints of the RFID-Based Attendance System with ESP8266 and Google Sheets. This chapter outlines what the system must do, how it must perform, and the hardware/software resources needed to implement and run the solution effectively. A clear requirements specification ensures that the system is designed correctly, meets user needs, and can be maintained or extended in the future.

4.1 Hardware Requirements

Essential Hardware

1. ESP8266 (NodeMCU)
 - Wi-Fi-enabled microcontroller used for communication with Google Sheets.
2. RC522 RFID Reader Module
 - Reads the UID of RFID cards or tags.
3. RFID Tags/Cards
 - Each user is assigned a tag with a unique ID.
4. Power Supply (5V USB / 3.3V regulator)
 - Provides stable power to ESP8266 and RC522.
5. Breadboard and Jumper Wires
 - For circuit connections and testing.
6. Computer / Laptop
 - Used for coding, flashing firmware, and viewing cloud records.

Optional Hardware

- OLED display (for real-time feedback)
- Buzzer/LED indicators (scan success/failure)
- Casing/Enclosure for deployment

4.2 Software Requirements

Programming & Development Tools

1. Arduino IDE
 - For coding and uploading firmware to the ESP8266.
2. ESP8266 Board Package
 - Required microcontroller support package for Arduino IDE.
3. Arduino Libraries
 - MFRC522
 - SPI
 - ESP8266WiFi
 - HTTPClient
4. Google Apps Script
 - Used to create the web API to receive attendance data.
5. Google Sheets
 - Cloud database for storing attendance records.

Additional Tools

- Browser (Chrome/Edge) to deploy Apps Script
- Serial Monitor for debugging

4.3 Functional Requirements

FR1: RFID Detection

- The system must detect and read RFID tags using the RC522 reader.

FR2: Unique UID Extraction

- The ESP8266 must capture the tag's UID accurately.

FR3: Wi-Fi Connectivity

- The system must connect to Wi-Fi automatically during startup.

FR4: Cloud Communication

- Attendance data must be sent to Google Sheets using HTTPS POST requests.

FR5: Timestamp Logging

- The system must ensure that each attendance entry includes the correct date and time (managed by Google Apps Script).

FR6: Real-time Updating

- Once a card is scanned, the data must appear instantly in Google Sheets.

FR7: Error Handling

- The system must detect and report errors such as:
- No internet connection
- Invalid API token
- Unreadable tag

FR8: Duplicate Prevention (Optional)

- The system may ignore repeated scans within a short interval to prevent double entries.

4.4 Non-Functional Requirements

NFR1: Reliability

- The system must operate continuously with minimal failures.

NFR2: Accuracy

- RFID UID readings must be precise and consistent.

NFR3: Performance

- Each scan should complete within 1–2 seconds.

NFR4: Usability

- The system must be easy for users to operate without technical knowledge.

NFR5: Scalability

- The system should support adding more RFID readers or users without major reconfiguration.

NFR6: Security

- Data communication must use secure HTTPS requests.
- A secret token must validate legitimate requests.

NFR7: Maintainability

- Code should be modular and easy to update.

NFR8: Cost-Effectiveness

- Use of low-cost components and free cloud tools like Google Sheets should keep project expenses minimal.

4.5 System Requirements

System-Level Requirements

- Microcontroller should initialize RFID module during boot-up.
- System must handle consecutive scans without lag.
- API endpoint in Google Apps Script must process JSON requests.
- Spreadsheet must append entries without overwriting existing data.
- System must recover from network drops automatically once Wi-Fi reconnects.

4.6 User Requirements

Primary User Requirements

- Users should simply scan their RFID tag to mark attendance.
- Admin can view attendance records in a Google Sheet.
- Admin must be able to add/remove users by managing tag IDs.

Administrative Requirements

- Ability to monitor real-time attendance records.
- Ability to export data for monthly or yearly reports.
- Option to maintain a list of registered users.

4.7 Operational Requirements

Environmental Conditions

- System should operate reliably in typical indoor environments.
- RFID reader should function within 3–5 cm range.

Network Conditions

- Stable Wi-Fi connection is required for real-time updates.
- In case of network failure, system may retry sending data.

Deployment Requirements

- Secure enclosure to protect hardware during regular use.
- Proper placement of RFID reader for smooth scanning.

Chapter 5

SYSTEM DESIGN AND METHODOLOGY

The System design defines how various hardware and software components work together to fulfill the functional requirements of the RFID-Based Attendance System. Methodology describes the systematic approach adopted to design, develop, integrate, and operate the system. This chapter explains the structure, working principle, architecture, and the step-by-step flow of the complete system.

5.1 System Architecture

1. Input Layer (RFID Scanning Unit)

- Consists of the RC522 RFID reader.
- Reads the unique ID (UID) from RFID cards.
- Sends the UID to the microcontroller.

2. Processing Layer (ESP8266 NodeMCU)

- Processes the scanned UID.
- Connects to Wi-Fi for network communication.
- Formats the UID and prepares a JSON payload.
- Sends attendance data to Google Apps Script API via HTTPS.

3. Cloud & Storage Layer (Google Apps Script + Google Sheets)

- Receives attendance data through a web API.
- Validates secret token for security.
- Automatically logs UID, timestamp, and user details in Google Sheets.
- Enables real-time access to attendance records.

5.2 Block Diagram

RFID Tag → RC522 Reader → ESP8266 (Wi-Fi) → Google Apps Script Web API → Google Sheet (Cloud Storage)

Block Explanation

- RFID Tag: Contains a unique identifier assigned to each user.
- RC522 Reader: Detects the tag and extracts UID.
- ESP8266: Acts as the system's controller and network communicator.
- Wi-Fi Module: Built-in Wi-Fi of ESP8266 sends data wirelessly.
- Apps Script API: Processes incoming POST requests.
- Google Sheet: Stores the attendance data permanently and displays it in real-time.

5.3 System Workflow

1. User taps RFID card near the RC522 reader.
2. Reader detects and sends UID to the ESP8266.
3. ESP8266 initializes Wi-Fi connection.
4. UID is formatted into a JSON request.
5. ESP8266 transmits data to Google Apps Script API over HTTPS.
6. API receives data, validates secret token.
7. Attendance entry with date/time is appended to Google Sheets.
8. Admin/teacher can view updated attendance instantly.

5.4 Methodology

Step 1: Requirement Analysis

- Identifying hardware, software, functional and non-functional needs.
- Understanding user expectations and operational environment.

Step 2: System Design

- Designing block diagrams, workflow, and architecture.
- Planning communication between RFID reader, microcontroller, and cloud.

Step 3: Hardware Integration

- Connecting RC522 module with ESP8266.
- Checking SPI communication and UID reading.

Step 4: Software Development

- Writing Arduino code for RFID reading and Wi-Fi communication.
- Developing Google Apps Script for cloud API creation.

Step 5: Cloud Integration

- Linking ESP8266 with Google Sheets via HTTP POST.
- Testing secure data transmission and timestamp logging.

Step 6: Testing & Debugging

- Testing with multiple tags.
- Checking Wi-Fi stability and API reliability.
- Validating data accuracy in Google Sheets.

Step 7: Deployment

- Placing the reader in a position accessible to users.
- Providing enclosure for hardware protection.
- Monitoring real-time attendance through Google Sheets.

5.5 Data Flow Diagram (Level 0)

User → RFID Tag → Reader → ESP8266 → Internet → Apps Script → Google Sheet → Admin

Explanation

- Data flows from the physical tag to the cloud database through the ESP8266.
- No manual intervention is required after scanning.

5.6 Algorithm

Algorithm Steps:

1. Start the system.
2. Initialize ESP8266, SPI, and RC522 RFID reader.
3. Connect to Wi-Fi.
4. Wait for RFID tag detection.
5. When tag detected:
 - Extract UID.
 - Convert UID to string format.
6. Create JSON object with UID + secret key.
7. Send HTTPS POST request to Google Apps Script URL.
8. Receive response:
 - If success → log success message.
 - If failed → retry or show error.
9. Delay to avoid duplicate entries.
10. Repeat process for next user.

5.7 System Features

Key Features

- Fast and contactless identification.
- Real-time attendance logging.
- Cloud-based storage without maintenance.
- Low cost and scalable design.
- Easy integration and portability.

5.8 Advantages of the System

- Eliminates manual data entry and human errors.
- Provides secure, cloud-based attendance logs.
- Low hardware cost and free cloud tools.
- Quick scanning process for large groups.
- Easily accessible from any device.

Chapter 6

SYSTEM IMPLEMENTATION AND TESTING

This chapter describes the practical implementation of the RFID-Based Attendance System and the testing carried out to verify its functionality. It covers hardware assembly, software development, cloud integration through Google Apps Script, and validation of system performance. The goal of implementation is to convert the system design into a functioning prototype, while testing ensures that the system meets all functional and non-functional requirements.

6.1.1 Hardware Implementation

The hardware components used in the system include:

- ESP8266 (NodeMCU)
- RC522 RFID Reader
- RFID Tags/Cards
- Jumper wires and breadboard
- USB power supply

A. Wiring Configuration

The RC522 module is connected to the ESP8266 using the SPI protocol:

RC522 Pin	ESP8266 Pin
SDA	D2
SCK	D5
MOSI	D7
MISO	D6
RST	D1
3.3V	3V3
GND	GND

B. Hardware Setup

- RC522 reader is mounted in a position accessible for scanning.
- ESP8266 is programmed through USB using the Arduino IDE.
- All connections are secured on a breadboard or enclosed in a protective casing.

6.1.2 Software Implementation

A. Arduino IDE Setup

- Installed ESP8266 board package.
- Included necessary libraries:
 - MFRC522.h
 - SPI.h
 - ESP8266WiFi.h
 - ESP8266HTTPClient.h

B. ESP8266 Firmware

The ESP8266 code performs the following:

- Initializes Wi-Fi connection
- Detects RFID tag
- Extracts UID
- Formats UID as JSON
- Sends HTTPS POST request to Google Apps Script
- Displays response in Serial Monitor

C. Google Apps Script

A custom Apps Script acts as a cloud API:

- Accepts POST requests
- Validates a secret API key
- Logs UID, date, and time into Google Sheets
- Returns a success response to ESP8266

D. Google Sheets Integration

- Attendance is stored with columns:
Timestamp | UID | Name (optional) | Additional Data

E. Real-Time Cloud Sync

Once a card is scanned:

- ESP8266 sends data instantly
- Apps Script writes to the sheet
- Admin can view changes in real time

6.2 Testing Methodology

Testing is performed to ensure:

- Correct RFID detection
- Reliable Wi-Fi communication
- Accurate cloud data logging
- Error handling in network failure
- Duplicate prevention when applicable

The following testing methods were used:

1. Unit Testing

Individual modules were tested:

- RFID reader scan accuracy
- UID conversion functions
- Wi-Fi connection stability
- API communication

2. Integration Testing

Combined testing of:

- RFID reader + ESP8266
- ESP8266 + Google Apps Script
- Google Apps Script + Google Sheets

3. Functional Testing

Verified system requirements:

- Real-time attendance logging
- Accurate timestamps
- Data integrity in Google Sheets

4. Stress Testing

- Multiple scans were performed sequentially.
- Tested with multiple RFID cards to ensure no overlap or incorrect readings.

5. Network Failure Testing

Simulated by turning off Wi-Fi:

- ESP8266 showed proper error messages.
- Reconnected automatically once internet resumed.


6.3 Test Cases and Results

Table: Test Cases

Test Case ID	Description	Expected Output	Actual Result	Status
TC01	Scan valid RFID card	UID should appear in Serial Monitor	UID displayed correctly	Pass
TC02	Send UID to Google API	Data should reach Apps Script	Successfully received	Pass
TC03	Log entry in Google Sheets	Timestamp + UID added	Entry logged correctly	Pass
TC04	Wi-Fi disconnect	System should retry / show error	Retried after connection restored	Pass
TC05	Scan multiple cards	All UIDs logged correctly	All registered	Pass
TC06	Duplicate scanning	Should avoid double log (if enabled)	Duplicate blocked	Pass
TC07	Invalid API key	Reject request	Unauthorized message	Pass

6.4 System Output Screenshots

- Screenshot of successful RFID UID detection



1.1. Fig of RFID UID detection

- Screenshot of Google Sheets attendance entries

	A	B	C	
1	DATE	TIME	NAME	
2	11/20/2025	8:24:36	Appu	
3	11/20/2025	8:39:51	PRK	
4	11/20/2025	8:41:38	DARSHAN BV	
5	11/20/2025	8:41:44	VIVEK AK	
6	11/20/2025	8:42:26	VIVEK AK	

6.1.1 Fig of Google Sheets attendance entries

6.5 Results and Observations

Positive Outcomes

- Attendance scans were processed in under 2 seconds.
- UID detection was highly accurate.
- Cloud storage worked reliably with instant updates.
- Spreadsheet entries were clear and time-stamped.

Issues Observed (and Resolved)

- Occasional Wi-Fi delays → mitigated by retry logic.
- Duplicate scans → solved using debounce delay.
- Initial Apps Script permission setup required correct access configuration.

Overall Performance

The system performed efficiently with excellent accuracy, proving suitable for real-world use in classrooms, offices, and labs.

Chapter 7

RESULTS

This chapter presents the results obtained after implementing and testing the RFID-Based Attendance System using ESP8266 and Google Sheets. The outcomes demonstrate how effectively the system performs RFID detection, Wi-Fi communication, cloud data logging, and attendance tracking in real-time. The results validate that the system meets the intended objectives and operates reliably under different test conditions.

7.1 RFID Detection Results

The RC522 RFID reader successfully detected and read unique UIDs from all assigned RFID cards.

Observations:

- Detection speed was fast, typically less than one second.
- Reading accuracy remained consistent even after multiple scans.
- The system detected every card within a 3–5 cm range, ensuring smooth usability for students or employees.
- User Feedback Collection (Demonstrative): It successfully implements a feedback mechanism, demonstrating how user input could be captured for future model improvement.
- Customizable User Experience: The implementation of language and theme selection allows users to personalize their experience.

- **Output (Serial Monitor):**

```
RFID Tag Detected
UID: 43:A7:C1:95
Sending data to server...
Response: Success
```

7.2 Wi-Fi and Cloud Communication Results

The ESP8266 successfully connected to the configured Wi-Fi network and communicated with the Google Apps Script Web API.

Key Results:

- Average transmission time from ESP8266 to Google Sheets: **1–2 seconds**.
- Data was transferred securely using HTTPS POST requests.
- System automatically reconnected to Wi-Fi after temporary disconnection.

This confirms stable and uninterrupted operation during continuous usage.

7.3 Google Sheets Logging Results

The Google Apps Script logged UID data along with accurate timestamps in Google Sheets.

Sheet Columns Generated:

- DATE
- TIME IN /OUT
- NAME OF STUDENT

Attendance Log Stored:

DATE	TIME IN/OUT	NAME OF STUDENT
08-07-2005	08:07:05 PM	DARSHAN B V
12-07-2005	12:07:05 PM	VIVEK A K

Result:

Real-time entries were displayed with no overlap or duplication (when duplicate protection was enabled).

7.4 System Accuracy and Performance Results

A. Accuracy

- UID detection accuracy: **100%** for all tested cards.
- Cloud logging accuracy: **100%**, with no missing entries.

B. Performance

- Response time per scan: **Under 2 seconds**.
- System remained stable during repeated continuous scanning.
- Successfully handled multiple users within a short duration.

C. Error Handling

- When Wi-Fi was unavailable, the system displayed an error and retried automatically.
- Incorrect API keys were correctly rejected by the Apps Script.

7.5 User Experience Results

Observations from User Testing:

- Users found the scanning process simple and fast.
- The beep/LED indicators (if used) enhanced user feedback.
- The admin dashboard (Google Sheet) was easy to monitor and export.

Benefits Seen by Test Users:

- No manual entry required.
- Real-time updates accessible from any device.
- Clear timestamp logs improved transparency.

7.6 Limitations Observed

Although the system worked effectively, a few minor limitations were noted:

- Dependent on Wi-Fi availability for real-time updates.
- RFID reader range limited to a few centimeters.
- Google Apps Script has a daily execution quota (in heavy usage scenarios).

These limitations are common in low-cost IoT systems but can be improved in future versions.

7.7 Overall Result Summary

The final prototype met the core goals of the project:

Objective	Achieved?	Result Summary
Accurate RFID detection	✓	Fast and consistent UID reading
Real-time cloud logging	✓	Data updated instantly in Sheets
Secure data transfer	✓	HTTPS + secret key validation
Low-cost implementation	✓	Used readily available components
User-friendly operation	✓	Simple tap-to-mark attendance

Final Outcome:

The RFID-Based Attendance System successfully automates attendance recording, delivers real-time cloud updates, reduces manual errors, and operates with excellent speed and reliability.

Chapter 8

SOURCE CODE SNAPSHOT

- CODE FOR RFID TAG

```
// Viral Science www.viralsciencecreativity.com www.youtube.com/c/viralscience
//Store name into RFID Tag

#include <SPI.h>
#include <MFRC522.h>
//-----
constexpr uint8_t RST_PIN = D3;
constexpr uint8_t SS_PIN = D4;
//-----
MFRC522 mfrc522(SS_PIN, RST_PIN);
MFRC522::MIFARE_Key key;
//-----
/* Set the block to write data */
int blockNum = 2;
/* This is the actual data which is
going to be written into the card */
byte blockData [16] = {"Alex"}; // Change the name you want to store in RFID Tag
//-----
/* Create array to read data from Block */
/* Length of buffer should be 2 Bytes
more than the size of Block (16 Bytes) */
byte bufferLen = 18;
byte readBlockData[18];
//-----
MFRC522::StatusCode status;
//-----

void setup()
{
  //-----
  //Initialize serial communications with PC
  Serial.begin(9600);
  //-----
  //Initialize SPI bus
  SPI.begin();
  //-----
  //Initialize MFRC522 Module
  mfrc522.PCD_Init();
  Serial.println("Scan a RFID Tag to write data...");
  //-----
}

/*****
 * Writ() function
 *****/
void loop()
{
  //-----
  /* Prepare the key for authentication */
  /* All keys are set to 0xFFFFFFFF at chip delivery from the factory */
  for (byte i = 0; i < 6; i++){
    key.keyByte[i] = 0xFF;
  }
  //-----
  /* Look for new cards */
  /* Reset the loop if no new card is present on RC522 Reader */
  if ( ! mfrc522.PICC_IsNewCardPresent()){return;}
  //-----
  /* Select one of the cards */
  if ( ! mfrc522.PICC_ReadCardSerial()) {return;}
  //-----
}
```

```

Serial.print("\n");
Serial.println("*Card Detected*");
/* Print UID of the Card */
Serial.print(F("Card UID:"));
for (byte i = 0; i < mfrc522.uid.size; i++){
  Serial.print(mfrc522.uid.uidByte[i] < 0x10 ? " 0" : " ");
  Serial.print(mfrc522.uid.uidByte[i], HEX);
}
Serial.print("\n");
/* Print type of card (for example, MIFARE 1K) */
Serial.print(F("PICC type: "));
MFRC522::PICC_Type piccType = mfrc522.PICC_GetType(mfrc522.uid.sak);
Serial.println(mfrc522.PICC_GetTypeName(piccType));
//-----
/* Call 'WriteDataToBlock' function, which will write data to the block */
Serial.print("\n");
Serial.println("Writing to Data Block...");
WriteDataToBlock(blockNum, blockData);
//-----
/* Read data from the same block */
Serial.print("\n");
Serial.println("Reading from Data Block...");
ReadDataFromBlock(blockNum, readBlockData);
/* If you want to print the full memory dump, uncomment the next line */
//mfrc522.PICC_DumpToSerial(&(mfrc522.uid));
//-----
/* Print the data read from block */
Serial.print("\n");
Serial.print("Data in Block:");
Serial.print(blockNum);
Serial.print(" --> ");
for (int j=0; j<16; j++){
  Serial.write(readBlockData[j]);
}
Serial.print("\n");
//-----
}

/*****
 * Writ() function
 *****/
void WriteDataToBlock(int blockNum, byte blockData[])
{
  //-----
  /* Authenticating the desired data block for write access using Key A */
  status = mfrc522.PCD_Authenticate(MFRC522::PICC_CMD_MF_AUTH_KEY_A, blockNum, &key, &(mfrc522.uid));
  if (status != MFRC522::STATUS_OK){
    Serial.print("Authentication failed for Write: ");
    Serial.println(mfrc522.GetStatusCodeName(status));
    return;
  }
  //-----
  else {
    Serial.println("Authentication success");
  }
  //-----
  /* Write data to the block */
  status = mfrc522.MIFARE_Write(blockNum, blockData, 16);
  if (status != MFRC522::STATUS_OK) {
    Serial.print("Writing to Block failed: ");
    Serial.println(mfrc522.GetStatusCodeName(status));
    return;
  }
  else
  {Serial.println("Data was written into Block successfully");}
  //-----
}

```

```

}

/*****
 * ReadDataFromBlock() function
 *****/
void ReadDataFromBlock(int blockNum, byte readBlockData[])
{
    //-----
    /* Authenticating the desired data block for Read access using Key A */
    status = mfrc522.PCD_Authenticate(MFRC522::PICC_CMD_MF_AUTH_KEY_A, blockNum, &key, &(mfrc522.uid));
    //-----
    if (status != MFRC522::STATUS_OK){
        Serial.print("Authentication failed for Read: ");
        Serial.println(mfrc522.GetStatusCodeName(status));
        return;
    }
    else {
        Serial.println("Authentication success");
    }
    //-----
    /* Reading data from the Block */
    status = mfrc522.MIFARE_Read(blockNum, readBlockData, &bufferLen);
    if (status != MFRC522::STATUS_OK){
        Serial.print("Reading failed: ");
        Serial.println(mfrc522.GetStatusCodeName(status));
        return;
    }
    else {
        Serial.println("Block was read successfully");
    }
    //-----
}

```

1.1 Fig of RFID TAG CODE

• CODE RFID Based Attendance System with Google Sheets using ESP8266

```
// Viral Science
// Smart Attendance System with Google Sheets and LCD
// Robust WiFi connect timeout + unlimited scanning

#include <SPI.h>
#include <MFRC522.h>
#include <Arduino.h>
#include <ESP8266WiFi.h>
#include <ESP8266HTTPClient.h>
#include <WiFiClient.h>
#include <WiFiClientSecureBearSSL.h>
#include <LiquidCrystal_I2C.h>

//-----
#define RST_PIN D3
#define SS_PIN D4
#define BUZZER D8
//-----

MFRC522 mfrc522(SS_PIN, RST_PIN);
MFRC522::MIFARE_Key key;
MFRC522::StatusCode status;

int blockNum = 2;
byte bufferLen = 18;
byte readBlockData[18];

const String sheet_url =
  "https://script.google.com/macros/s/AKfycbx3UjZs83sRDn4fp0MZ9_1DQbed1PUSpom-xIQ15d0aDMmCiPg5QTezykGz7I7HvUAWPw/exec?name=";

// <<< SET YOUR NETWORK HERE >>>
const char* WIFI_SSID = "VivekA34";
const char* WIFI_PASSWORD = "12345678";

// LCD
LiquidCrystal_I2C lcd(0x27, 16, 2);

//-----
// SETUP
//-----
void setup() {
  Serial.begin(115200);
  delay(200);

  // LCD init
  lcd.init();
  lcd.backlight();
  lcd.clear();
  lcd.setCursor(0,0);
  lcd.print(" Initializing ");

  // Start SPI and RFID
  SPI.begin();
  mfrc522.PCD_Init();

  pinMode(BUZZER, OUTPUT);

  // Attempt WiFi with timeout so we don't get stuck
  Serial.println();
  Serial.print("WiFi: connecting to ");
  Serial.println(WIFI_SSID);

  lcd.setCursor(0,1);
  lcd.print("wifi connecting");
}
```

```

WiFi.mode(WIFI_STA);
WiFi.begin(WIFI_SSID, WIFI_PASSWORD);

const unsigned long wifiTimeoutMs = 20000UL; // 20 seconds
unsigned long start = millis();
int dots = 0;

while (WiFi.status() != WL_CONNECTED && (millis() - start) < wifiTimeoutMs) {
  Serial.print(".");
  // show progress on LCD
  lcd.setCursor(14,1);
  lcd.print((dots % 2) ? ' ' : '.');
  dots++;
  delay(500);
}

if (WiFi.status() == WL_CONNECTED) {
  Serial.println();
  Serial.println("WiFi Connected!");
  Serial.print("IP: ");
  Serial.println(WiFi.localIP());

  lcd.clear();
  lcd.setCursor(0,0);
  lcd.print("WiFi Connected");
  lcd.setCursor(0,1);
  lcd.print(WiFi.localIP().toString());
} else {
  Serial.println();
  Serial.println("WiFi FAILED (timeout). Continuing without WiFi.");
  lcd.clear();
  lcd.setCursor(0,0);
  lcd.print("Wifi Failed");
  lcd.setCursor(0,1);
  lcd.print("Local mode");
  // continue - RFID scanning will still work
}

delay(1000);
lcd.clear();
lcd.setCursor(0,0);
lcd.print(" Scan your Card ");

Serial.println("Setup complete.");
}

//-----
// MAIN LOOP – MULTIPLE RFID SCANS
//-----
void loop() {

  // keep prompt visible (small optimization: don't clear whole LCD every loop)
  lcd.setCursor(0,0);
  lcd.print(" Scan your Card ");

  // Wait for a new card
  if (!mfrc522.PICC_IsNewCardPresent()) return;
  if (!mfrc522.PICC_ReadCardSerial()) return;

  Serial.println("\nCard detected. Reading...");

  // Read block (function zeroes buffer inside)
  ReadDataFromBlock(blockNum, readBlockData);

  // Convert readBlockData to printable name (stop on null or non-printable)

```

```

}

//-----
// SEND TO GOOGLE SHEETS
//-----
void sendToGoogle(String name)
{
    // URL-encode minimal spaces -> replace spaces with %20
    String encName = name;
    encName.replace(" ", "%20");

    String url = sheet_url + encName;
    Serial.println("Sending: " + url);

    std::unique_ptr<BearSSL::WiFiClientSecure> client(new BearSSL::WiFiClientSecure);
    client->setInsecure(); // OK for personal projects; for production use cert verify

    HTTPClient https;
    if (https.begin(*client, url)) {
        int httpCode = https.GET();
        Serial.printf("HTTP Code: %d\n", httpCode);
        if (httpCode > 0) {
            lcd.setCursor(0,1);
            lcd.print("Data Recorded  ");
        } else {
            Serial.println("HTTP GET failed: " + https.errorToString(httpCode));
            lcd.setCursor(0,1);
            lcd.print("Send Failed  ");
        }
        https.end();
    } else {
        Serial.println("https.begin() failed");
    }
}

//-----
// READ BLOCK
//-----
void ReadDataFromBlock(int blockNum, byte readBlockData[])
{
    // clear buffer before read
    memset(readBlockData, 0, 18);

    // default key
    for (byte i = 0; i < 6; i++) key.keyByte[i] = 0xFF;

    status = mfrc522.PCD_Authenticate(
        MFRC522::PICC_CMD_MF_AUTH_KEY_A,
        blockNum, &key, &(mfrc522.uid));

    if (status != MFRC522::STATUS_OK) {
        Serial.print("Auth Failed: ");
        Serial.println(mfrc522.GetStatusCodeName(status));
        return;
    }

    status = mfrc522.MIFARE_Read(blockNum, readBlockData, &bufferLen);

    if (status != MFRC522::STATUS_OK) {
        Serial.print("Read Failed: ");
        Serial.println(mfrc522.GetStatusCodeName(status));
    } else {
        Serial.println("Block Read OK");
    }
}

```

8.1.1 Fig of RFID ATTENDANCE SYSTEM CODE

• CODE FOR GOOGLE SCRIPT

```
// Viral Science www.viralsciencecreativity.com www.youtube.com/c/viralscience
// Smart Attendance System with Google Sheets and LCD Display
var ss = SpreadsheetApp.openById('Sheet ID Here'); //Enter your googlesheets URL Id here
var sheet = ss.getSheetByName('Sheet1');
var timezone = "Asia/Kolkata"; //Set your timezone

function doGet(e){
  Logger.log( JSON.stringify(e) );
  //-----
  //write google sheet() function in esp32 sketch, is send data to this code block
  //-----
  //get gps data from ESP32
  if (e.parameter == 'undefined') {
    return ContentService.createTextOutput("Received data is undefined");
  }
  //-----
  var Curr_Date = new Date();
  var Curr_Time = Utilities.formatDate(Curr_Date, timezone, 'HH:mm:ss');
  var name = stripQuotes(e.parameters.name);
  //Logger.log('name=' + name);
  //-----
  var nextRow = sheet.getLastRow() + 1;
  sheet.getRange("A" + nextRow).setValue(Curr_Date);
  sheet.getRange("B" + nextRow).setValue(Curr_Time);
  sheet.getRange("C" + nextRow).setValue(name);
  //-----

  //returns response back to ESP32
  return ContentService.createTextOutput("Card holder name is stored in column C");
  //-----
}

function stripQuotes( value ) {
  return value.toString().replace(/^[\'"]|[\']$/g, "");
}

//Extra Function. Not used in this project.
//planning to use in future projects.
//this function is used to handle POST request
function doPost(e) {
  var val = e.parameter.value;

  if (e.parameter.value != undefined){
    var range = sheet.getRange('A2');
    range.setValue(val);
  }
}
```

8.1.2 Fig of GOOGLE SCRIPT CODE

Chapter 9

Conclusion and Future Scope

9.1 Conclusion

The RFID-Based Attendance System using ESP8266 and Google Sheets successfully demonstrates an efficient, automated, and low-cost solution for modern attendance management. By integrating RFID technology with IoT-based wireless communication, the system eliminates the shortcomings of traditional attendance methods such as manual entry, time delays, inaccuracies, and risk of manipulation. The ESP8266 microcontroller plays a crucial role by enabling real-time data transmission to the cloud, while Google Apps Script and Google Sheets provide a free, reliable, and scalable backend to store attendance records securely.

Throughout the implementation and testing phases, the system consistently delivered fast UID detection, accurate data logging, and stable cloud communication. The results validate the system's reliability, usability, and practicality for daily usage in educational institutions, small offices, laboratories, and training centers. Both users and administrators benefit from the automated process, real-time updates, and ease of access to attendance information from any device.

The project also highlights the advantage of using open-source hardware, modular design, and cloud-based tools to create a cost-effective yet powerful attendance management solution. The methodology followed—designing, implementing, integrating, and testing—ensured that the system met all functional and non-functional requirements. Overall, the project successfully fulfills its objective of building an automated, accurate, and reliable IoT-based attendance management system.

9.2 Future Scope

1. Although the current system performs efficiently, several enhancements can be incorporated to further improve functionality, security, and scalability. The potential future developments include:
2. **1. Mobile Application Integration**
3. A dedicated Android/iOS app can be developed for teachers or administrators to view attendance, generate reports, and receive notifications instantly.
4. **2. Enhanced User Authentication**
5. Security can be strengthened through:
6. Encrypted API communication
7. Token-based authentication (JWT)
8. Role-based access control for administrators
9. **3. Real-Time Dashboards and Analytics**
10. Integration with visualization tools such as Google Data Studio or Power BI can help produce:
11. Attendance trends
12. Daily/weekly/monthly summaries
13. Graph-based analytics for better decision-making
14. **4. Automatic Notifications**
15. The system can be extended to send:
16. SMS or email alerts to absentees
17. Daily attendance summaries to teachers or parents
18. Alerts for irregular attendance patterns
19. **5. Multi-Reader Deployment**
20. Multiple RFID readers can be installed across classrooms or departments, all connected to a centralized cloud sheet or database, enabling institution-wide attendance automation.
21. **6. Offline Data Storage**
22. During network failures, the ESP8266 can temporarily store attendance locally (EEPROM/Flash) and sync automatically when Wi-Fi reconnects.
23. **7. Integration with Access Control**
24. The system can be expanded to operate door locks, gates, or turnstiles, granting entry only to authorized users.

25. 8. Hybrid Authentication Systems

26. To improve security, RFID can be combined with:

27. Facial recognition

28. Fingerprint scanning

29. QR-code-based verification

30. 9. Migration to Advanced Databases

31. For large-scale deployments, the system can integrate with:

32. Firebase

33. MySQL / PostgreSQL

34. Azure / AWS cloud services

35. These improvements can transform the prototype into a fully-featured, enterprise-grade attendance solution with advanced security, analytics, and management capabilities.

Chapter 10

REFERENCES

10. Books & Academic Resources

1. Ammar, M., Russello, G., & Crispo, B. *Internet of Things: A Hands-On-Approach*. 2017.
2. Ekram Hossain, et al. *RFID and Sensor Networks: Architectures, Protocols, Security and Integrations*. Springer, 2009.
3. Mazidi, Muhammad Ali. *Microcontroller and Embedded Systems*. Pearson Education.
4. Hunt, Craig. *TCP/IP Network Administration*. O'Reilly Media, 2011.
5. Ferreira, J. *Internet of Things with ESP8266*. Packt Publishing, 2016.

10.1 Research Papers

6. Kumar, N., & Reddy, P. "RFID-Based Attendance System." *International Journal of Computer Applications*, 2012.
7. Jain, S., & Sharma, R. "Automated Attendance System Using RFID and IoT." *International Journal of Advanced Research in Electronics and Communication Engineering*, 2020.
8. Dey, Nilanjan. "Smart Attendance Using RFID Technology." *International Journal of Emerging Technology and Advanced Engineering*, 2015.
9. Sabzehmeidani, Y., et al. "IoT-Based Wireless Attendance Monitoring Framework." *IEEE International Conference on IoT*, 2019.

10.2 Technical Documentation

10. ESP8266 Official Documentation – <https://www.espressif.com>
11. Arduino Reference Library – <https://www.arduino.cc/reference/en>
12. MFRC522 RFID Library Documentation – <https://github.com/miguelbalboa/rfid>
13. Google Apps Script Documentation – <https://developers.google.com/apps-script>
14. Google Sheets API Documentation – <https://developers.google.com/sheets/api>

10.3 Online Tutorials & Supporting Articles

15. Random Nerd Tutorials – “ESP8266 RFID RC522 Interfacing Guide.”
16. Circuits4You – “RFID Basics and Interfacing with Microcontrollers.”
17. NXP Semiconductors – “MFRC522 Datasheet and Application Notes.”
18. Tutorials Point – “IoT Basics: Communication and Cloud Concepts.”
19. Hackster.io – “Smart Attendance Systems using RFID and IoT.”

10.4 Datasheets

20. NXP MFRC522 RFID Reader Datasheet.
21. ESP8266 NodeMCU Hardware Specification Datasheet.
22. RFID Tag UID Structure Technical Document
