

Practical 6

Define a RESTful web service that accepts the details to be stored in a database and performs CRUD operation.

Steps:

1. **Create project name→Sam**
2. **Java DB→create table employee(id,emp_name)**
3. **On project→right click→entity class→new entity
name(employee)package(com.emp) →next database source→sample→finish**
4. **In code right click→insert code→add property.Write column name and click ok**
5. **New→other→JSP pages from entity class. Add package name(separate a,b,c) → finish**
6. **New→Restful web services from entity class→entity name→next→package name→click on finish**
7. **Clean and build**
8. **Deploy**

Code:

```
package com.emp;
```

```
import java.io.Serializable;  
import javax.persistence.Entity;  
import javax.persistence.GeneratedValue;  
import javax.persistence.GenerationType;  
import javax.persistence.Id;  
import javax.xml.bind.annotation.XmlRootElement;
```

```
@Entity
```

```
@XmlRootElement
```

```
public class employee implements Serializable {  
    private String emp_name;  
    public void setEmp_name(String emp_name) {  
        this.emp_name = emp_name;  
    }  
    private static final long serialVersionUID = 1L;  
    @Id  
    @GeneratedValue(strategy = GenerationType.AUTO)  
    private Long id;  
    public Long getId() {  
        return id;  
    }  
}
```

```
}  
public void setId(Long id) {  
    this.id = id;  
}  
@Override  
public int hashCode() {  
    int hash = 0;  
    hash += (id != null ? id.hashCode() : 0);  
    return hash;  
}  
@Override  
public boolean equals(Object object) {  
    // TODO: Warning - this method won't work in the case the id fields are not set  
    if (!(object instanceof employee)) {  
        return false;  
    }  
    employee other = (employee) object;  
    if ((this.id == null && other.id != null) || (this.id != null && !this.id.equals(other.id))) {  
        return false;  
    }  
    return true;  
}  
@Override  
public String toString() {  
    return "com.emp.employee[ id=" + id + " ]";  
}}
```

OUTPUT:

← ↻ ⓘ localhost:8080/sam/faces/c/employee/List.xhtml

Create New employee

Emp_name:

Id:

[Save](#)

[Show All employee Items](#)

[Index](#)

← ↻ ⓘ localhost:8080/sam/faces/c/employee/List.xhtml

List

1..2/2

Emp_name	Id	
Samruddhi Surve	1	View Edit Destroy
Diksha	2	View Edit Destroy

[Create New employee](#)

[Index](#)