

Selection



The Selection Problem



- Given an integer k and n elements x_1, x_2, \dots, x_n taken from a total order, find the k -th smallest element in this set.
- Of course, we can sort the set in $O(n \log n)$ time and then index the k -th element.

$k=3$ 7 4 9 6 2 → 2 4 6 7 9


- Can we solve the selection problem faster?

Quick-Select

- Quick-select** is a randomized selection algorithm based on the prune-and-search paradigm:

- Prune:** pick a random element x (called **pivot**) and partition S into
 - L : elements less than x
 - E : elements equal x
 - G : elements greater than x

- Search:** depending on k , either answer is in E , or we need to recur in either L or G



Partition



- We partition an input sequence as in the quick-sort algorithm:
 - We remove, in turn, each element y from S and
 - We insert y into L , E or G , depending on the result of the comparison with the pivot x
- Each insertion and removal is at the beginning or at the end of a sequence, and hence takes $O(1)$ time
- Thus, the partition step of quick-select takes $O(n)$ time

Algorithm *partition*(S, p)

Input sequence S , position p of pivot

Output subsequences L, E, G of the elements of S less than, equal to, or greater than the pivot, resp.

$L, E, G \leftarrow$ empty sequences

$x \leftarrow S.remove(p)$

while $\neg S.empty()$

$y \leftarrow S.remove(S.first())$

if $y < x$

$L.addLast(y)$

else if $y = x$

$E.addLast(y)$

else $\{ y > x \}$

$G.addLast(y)$

return L, E, G

Quick-Select Visualization

- An execution of quick-select can be visualized by a recursion path
 - Each node represents a recursive call of quick-select, and stores k and the remaining sequence

$k=5, S=(7\ 4\ 9\ 3\ 2\ 6\ 5\ 1\ 8)$

$k=2, S=(7\ 4\ 9\ 6\ 5\ 8)$

$k=2, S=(7\ 4\ 6\ 5)$

$k=1, S=(7\ 6\ 5)$


5

© 2004 Goodrich, Tamassia

Selection

5

Expected Running Time



© 2004 Goodrich, Tamassia

Selection

6

Expected Running Time, Part 2

- Probabilistic Fact #1:** The expected number of coin tosses required in order to get one head is two
- Probabilistic Fact #2:** Expectation is a linear function:
 - $E(X + Y) = E(X) + E(Y)$
 - $E(cX) = cE(X)$
- Let $T(n)$ denote the expected running time of quick-select.
- By Fact #2,
 - $T(n) \leq T(3n/4) + bn \cdot (\text{expected \# of calls before a good call})$
- By Fact #1,
 - $T(n) \leq T(3n/4) + 2bn$
- That is, $T(n)$ is a geometric series:
 - $T(n) \leq 2bn + 2b(3/4)n + 2b(3/4)^2n + 2b(3/4)^3n + \dots$
- So $T(n)$ is $O(n)$.
- We can solve the selection problem in $O(n)$ expected time.

© 2004 Goodrich, Tamassia

Selection

7

Deterministic Selection

- We can do selection in $O(n)$ worst-case time.
- Main idea: recursively use the selection algorithm itself to find a good pivot for quick-select:
 - Divide S into $n/5$ sets of 5 each
 - Find a median in each set
 - Recursively find the median of the "baby" medians.

Min size for L

1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5

Min size for G

© 2004 Goodrich, Tamassia

Selection

8