

ECE 8540 Analysis of Tracking Systems
Assignment 1

Vivek Koodli Udupa
C12768888

09/04/2018

1 Aim

Part 1:

To fit a 2D line to the given five (x , y) data points. Construct the appropriate matrices and solve for the line parameters using the Normal Equations.

Part 2:

Follow the same steps as Part 1 but include an extra point (8 , 14). Find out what happens.

Part 3:

Fit a model for the data set that contains the data of 3398 meals eaten by 83 different people. Using the normal equations, formulate the matrices and fit that model to the data.

2 Execution

Part 1 and Part 2

The Dataset for Part 1: (5 , 1); (6 , 1); (7 , 2); (8 , 3); (9 , 5).

The Dataset for Part 2: (5 , 1); (6 , 1); (7 , 2); (8 , 3); (9 , 5); (8 , 14).




Figure 1: Plot of Dataset 1




Figure 2: Plot of Dataset 2

Looking at the plot in Figure 1 and Figure 2, a straight line of the form $y = ax + b$ seems to be a good fit.

Formulating the matrices:

$$A = \begin{bmatrix} x_1 & 1 \\ \ddots & \ddots \\ x_N & 1 \end{bmatrix} \quad (1)$$

$$x = \begin{bmatrix} a \\ b \end{bmatrix} \quad (2)$$

$$b = \begin{bmatrix} y_1 \\ \ddots \\ y_N \end{bmatrix} \quad (3)$$

A is a N x M Matrix,
where N = 5 (Number of data points) and M = 2 (Number of unknowns)

Filling in the matrices with appropriate values for Data set 1, we get:

$$A = \begin{bmatrix} 5 & 1 \\ 6 & 1 \\ 7 & 1 \\ 8 & 1 \\ 9 & 1 \end{bmatrix}$$

$$b = \begin{bmatrix} 1 \\ 1 \\ 2 \\ 3 \\ 5 \end{bmatrix}$$

$$x_{\text{u}} = \begin{bmatrix} a \\ b \end{bmatrix}$$

With the above matrices, we can find x_{u} as :

$$x_{\text{u}} = (A^T A)^{-1} A^T b \quad (4)$$

Using MATLAB for calculations, we get

$$x_{\text{u}} = \begin{bmatrix} -1.00 \\ -4.60 \end{bmatrix}$$

Similarly formulating the matrices for data-set 2, we get:

$$A2 = \begin{bmatrix} 5 & 1 \\ 6 & 1 \\ 7 & 1 \\ 8 & 1 \\ 9 & 1 \\ 8 & 14 \end{bmatrix}$$

$$b2 = \begin{bmatrix} 1 \\ 1 \\ 2 \\ 3 \\ 5 \\ 14 \end{bmatrix}$$

$$x_u2 = \begin{bmatrix} a \\ b \end{bmatrix}$$

Using MATLAB for calculations, we get

$$x_u2 = \begin{bmatrix} 1.8154 \\ -8.6769 \end{bmatrix}$$

Now, we can fit a line of the form

$$y = a * x + b; \quad \text{where } a = x_u(1,1) \text{ and } b = x_u(2,1)$$

(Note: Similar line fit is calculated for data set 2 with its respective values)




Figure 3: Dataset 1 and Dataset 2 Line Fit

Figure 3 shows the dataset plot with fitted line.

Part 3

The data for part 3 of the lab contains 3,398 meals eaten by 83 different people. It has 4 columns and they represent the following:

1. Participant ID
2. Meal ID
3. Number of Bites taken in the meal
4. Number of Kilo calories consumed




Figure 4: Plot of bites VS Kilo-calories per bite

Figure 4 shows the plot of kilo-calories consumed per bite against the total number of bites taken.

The values of the Y-axis is obtained by dividing Column 4 / Column 3 from the given data-set. The values of X-axis are from Column 3 of the Data-set.

The distribution of the given data as shown in Figure 4 is concentrated near the origin and scarce at the farther end of X and Y axes.

We will try to fit a line using the same methods as we used for Part 1 and Part 2, we get:

$$x_{u3} = \begin{bmatrix} -0.1771 \\ 23.4417 \end{bmatrix}$$




Figure 5: Line fit for Part 3 Data-set

Fitting a line using the values obtained gives us the result shown in Figure 5. The line extends way ahead along the X-axis and has high error values for points in the Y-axis. The linear line is not a great fit for this data set.

Power fit with the equation of the form $y = ax^b$ seems to be a better option. Here we have two unknowns (a and b). We have to model the above equation.

$$y = ax^b \quad (5)$$

$$\log(y) = \log(ax^b) \quad (6)$$

$$\log(y) = \log(a) + \log(x^b) \quad \because [\log(mn) = \log(m) + \log(n)] \quad (7)$$

$$\log(y) = \log(a) + b\log(x) \quad \because [\log(m^n) = n\log(m)] \quad (8)$$

Above equation is of the form

$$v = k + bu \quad \text{where} \quad (9)$$

$$v = \log(y) \quad (10)$$

$$k = \log(a) \quad (11)$$

$$u = \log(x) \quad (12)$$

Formulating the Matrices:

$$A = \begin{bmatrix} \log(x_1) & 1 \\ \vdots & \vdots \\ \log(x_N) & 1 \end{bmatrix} \quad (13)$$

$$x = \begin{bmatrix} b \\ a \end{bmatrix} \quad (14)$$

$$b = \begin{bmatrix} \log(y_1) \\ \vdots \\ \log(y_N) \end{bmatrix} \quad (15)$$

Using the solution to the normal equations i.e.

$$x = (A^T A)^{-1} A^T b \quad (16)$$

We get the values of the unknowns as $a = 57.7128$ and $b = -0.4601$. Now we can plot the power fit.




Figure 6: Power Fit

3 Conclusion

Part 1 and Part 2

The raw data-points given for Part 1 and Part 2 of the lab were plotted using MATLAB. Appropriate matrices for solving the line parameters using Normal Equations were constructed and the line fit was plotted. Figure 1 and Figure 2 represents the raw data plot and Figure 3 shows the line fit.

Due to the addition of an extra point (8 , 14), which has a high y-axis value, the y-intercept of the line fit approximately doubled. The unknowns for Part 1 are **a = -1.00** and **b = -4.60** and the unknowns for Part 2 are **a = 1.8154** and **b = -8.6769**.

Part 3

For Part 3 of the lab, the data-set named "83people-all-meals.txt" which was given in the website was imported into MATLAB as a table and then converted into array using the inbuilt function "table2array". Having the data as an array eases the calculation process. Kilo-calories per bite VS bites taken were plotted. Line model was used initially to fit the data. It did not fit well. Later on Power model of the form $y = ax^b$ was used, which seems to be a better fit than the Line model. Figure 5 and Figure 6 represent the Line model and power model fit respectively.

All calculations were performed on MATLAB and the code has been attached in the appendix.

4 Appendix

```
1 close all
2 clear
3
4 %Dataset one
5 px1 = [5, 6, 7, 8, 9];
6 py1 = [1, 1, 2, 3, 5];
7
8 %M = 2, N = length(x)
9
10 A1 = [px1', ones(length(px1),1)]; %A Matrix
11 b1 = py1'; %Leftovers
12
13 x1 = inv(A1' * A1) * A1' * b1 %Calculating the unknowns
14
15 Y1 = x1(1) * px1 + x1(2); %Final Y1
16
17
18 %Plotting the graph
19 figure(1)
20 subplot(1,2,1)
21 plot ( px1, py1, 'x', 'markers',12,'LineWidth',3 ); %
    Given dataset plot
22 hold on
23 plot ( px1 , Y1 , 'r-', 'LineWidth',3);%2d Line fit plot
24 hold off;
25 title('Dataset 1');
26 ylabel('Y values');
27 xlabel('X values');
```



```

28 legend('Given data points', '2D line fit','Location','
        northwest');
29 set(gca,'FontSize',18);
30
31 %Dataset 2
32 px2 = [5, 6, 7, 8, 8, 9];
33 py2 = [1, 1, 2, 3, 14, 5];
34
35 A2 = [px2' , ones(length(px2),1)];
36 b2 = py2';
37
38 x2 = inv(A2' * A2) * A2' * b2
39
40 Y2 = x2(1) * px2 + x2(2);
41
42 %Plotting the Graph
43 subplot(1,2,2)
44 plot ( px2, py2, 'x','markers',12,'LineWidth',3 ); %Given
        dataset plot
45 hold on
46 plot ( px2 , Y2 , 'r-','LineWidth',2); %2d Line fit plot
47 hold off;
48 title('Dataset 2');
49 ylabel('Y values');
50 xlabel('X values');
51 legend('Given data points', '2D line fit','Location','
        northwest');
52 set(gca,'FontSize',18);
53
54 %Part Three ( Power Function)
55
56 %Read the dataset from file into a table
57 Tble = readtable('83people-all-meals.txt');
58
59 %Convert the table into an array
60 A1 = table2array(Tble);
61
62 %Extract the 3rd column(i.e Bites taken)
63 Bites = A1(:,3);
64
65 %Calculate Kilocalories per bite
66 CalBite = A1(:,4) ./ A1(:,3) ;
67
68 %setting up the Matrices
69
70 % y3 = ax^b;

```

```

71 % V = K + bu3
72 % V = log(y3)
73 % K = log(a)
74 % u3 = log(x)
75
76 u3 = log(Bites);
77 v = log(CalBite);
78
79 A3 = [u3 ones(length(Bites),1)];
80 b3 = [v];
81
82 x3 = inv(A3' * A3) * A3' * b3;
83
84 a3 = exp(x3(2,1));
85 b3 = x3(1,1);
86
87 X3 = 0:max(Bites);
88 Y3 = a3 * X3.^b3;
89
90 % Plotting the graph
91 figure(3)
92 plot(Bites, CalBite, 'x', 'markersize',10, 'linewidth',2);
93 hold on;
94 plot(X3, Y3, 'r-', 'LineWidth',4);
95 hold off;
96 xlabel("bites");
97 ylabel("kilo-cal/bite");
98 title("Bites vs kilo-cal/bite - Power Fit");
99 set(gca, 'FontSize',18);
100
101 %Part 3 - Polynomial
102
103 A4 = [Bites ones(length(Bites),1)];
104 b4 = [CalBite];
105 x4 = inv(A4' * A4) * A4' * b4;
106
107 X4 = 0:max(Bites);
108 Y4 = x4(1,1) .* Bites + x4(2,1);
109
110 % Plotting the graph
111 figure(4)
112 plot(Bites, CalBite, 'x', 'markersize',10, 'linewidth',2);
113 hold on;
114 plot(Bites, Y4, 'r-', 'LineWidth',4);
115 hold off;
116 xlabel("bites");

```

```
117 ylabel("kilo-cal/bite");  
118 title("Bites vs kilo-cal/bite - Linear Line Fit");  
119 set(gca,'FontSize',18);
```

-END-