

SESSION 3

1. Create and populate Restaurants

DML commands change rows. This script creates the table and adds five sample records.

```
CREATE TABLE Restaurants (  
  id INT PRIMARY KEY AUTO_INCREMENT, name VARCHAR(100), cuisine VARCHAR(50),  
  rating DECIMAL(2,1), city VARCHAR(80)  
);  
INSERT INTO Restaurants (name,cuisine,rating,city) VALUES  
  ('Spice Villa','Indian',4.3,'Ahmedabad'),('Dragon Bowl','Chinese',4.5,'Ahmedabad'),  
  ('Pizza Point','Italian',3.2,'Surat'),('Taco Town','Mexican',4.1,'Ahmedabad'),  
  ('Sushi House','Japanese',4.7,'Mumbai');
```

2. Update Spice Villa

UPDATE changes matching rows. The WHERE clause is essential so only Spice Villa is changed.

```
UPDATE Restaurants SET rating=4.7 WHERE name='Spice Villa';
```

3. Delete lower-rated restaurants

DELETE removes matching rows. Check candidates with SELECT first.

```
SELECT * FROM Restaurants WHERE rating < 3.5;  
DELETE FROM Restaurants WHERE rating < 3.5;
```

4. Filter and limit

WHERE combines both city and rating conditions. ORDER BY makes “top” deterministic; LIMIT returns only two rows.

```
SELECT * FROM Restaurants  
WHERE city='Ahmedabad' AND rating > 4.0  
ORDER BY rating DESC  
LIMIT 2;
```