

SESSION 8

1. Variables and output

Run SET SERVEROUTPUT ON in SQL*Plus or enable DBMS Output in Oracle SQL Developer.

```
SET SERVEROUTPUT ON;
DECLARE
  v_name VARCHAR2(50):='Aarav'; v_age NUMBER:=22;
BEGIN
  DBMS_OUTPUT.PUT_LINE('Name: '||v_name); DBMS_OUTPUT.PUT_LINE('Age: '||v_age);
END; /
```

2. IF statement

PL/SQL uses IF ... THEN ... ELSE ... END IF.

```
DECLARE v_amount NUMBER:=650;
BEGIN
  IF v_amount > 500 THEN DBMS_OUTPUT.PUT_LINE('Eligible for free delivery');
  ELSE DBMS_OUTPUT.PUT_LINE('Delivery charges apply'); END IF;
END; /
```

3. LOOP 1 to 5

EXIT WHEN controls when the loop stops.

```
DECLARE v_count NUMBER:=1;
BEGIN LOOP
  DBMS_OUTPUT.PUT_LINE(v_count); v_count:=v_count+1;
  EXIT WHEN v_count>5; END LOOP; END; /
```

4. Cursor over PRODUCTS

A cursor processes query rows one by one.

```
DECLARE CURSOR c_products IS SELECT product_name FROM PRODUCTS; v_name PRODUCTS.product_name%TYPE;
BEGIN OPEN c_products; LOOP FETCH c_products INTO v_name; EXIT WHEN c_products%NOTFOUND; DBMS_OUTPUT.PUT_LINE(v_name); EN
```

5. Division-by-zero exception

The exception section handles an error without crashing the block.

```
DECLARE a NUMBER:=10; b NUMBER:=0; result NUMBER;
BEGIN result:=a/b; DBMS_OUTPUT.PUT_LINE(result);
EXCEPTION WHEN ZERO_DIVIDE THEN DBMS_OUTPUT.PUT_LINE('Cannot divide by zero');
END; /
```