


2.) A* Search Algorithm:

A* search is the most commonly known form of best-first search. It uses heuristic function $h(n)$, and cost to reach the node n from the start state $g(n)$. It has combined features of UCS and greedy best-first search, by which it solve the problem efficiently. A* search algorithm finds the shortest path through the search space using the heuristic function. This search algorithm expands less search tree and provides optimal result faster. A* algorithm is similar to UCS except that it uses $g(n)+h(n)$ instead of $g(n)$. In A* search algorithm, we use search heuristic as well as the cost to reach the node. Hence we can combine both costs as following, and this sum is called as a **fitness number**.



Algorithm of A* search:

Step1: Place the starting node in the OPEN list.

Step 2: Check if the OPEN list is empty or not, if the list is empty then return failure and stops.

Step 3: Select the node from the OPEN list which has the smallest value of evaluation function ($g+h$), if node n is goal node then return success and stop, otherwise

Step 4: Expand node n and generate all of its successors, and put n into the closed list. For each successor n' , check whether n' is already in the OPEN or CLOSED list, if not then compute evaluation function for n' and place into Open list.

Step 5: Else if node n' is already in OPEN and CLOSED, then it should be attached to the back pointer which reflects the lowest $g(n')$ value.

Step 6: Return to Step 2.

Advantages:

- A* search algorithm is the best algorithm than other search algorithms.


- A* search algorithm is optimal and complete.
- This algorithm can solve very complex problems.

Disadvantages:

- It does not always produce the shortest path as it mostly based on heuristics and approximation.
- A* search algorithm has some complexity issues.
- The main drawback of A* is memory requirement as it keeps all generated nodes in the memory, so it is not practical for various large-scale problems.


Example: In this example, we will traverse the given graph using the A* algorithm. The heuristic value of all states is given in the below table so we will calculate the $f(n)$ of each state using the formula $f(n) = g(n) + h(n)$, where $g(n)$ is the cost to reach any node from start state.

Here we will use OPEN and CLOSED list.




State	$h(n)$
S	5
A	3
B	4
C	2
D	6
G	0

eg:-



Solution:



Initialization: $\{(S, 5)\}$

Iteration1: $\{(S \rightarrow A, 4), (S \rightarrow G, 10)\}$

Iteration2: $\{(S \rightarrow A \rightarrow C, 4), (S \rightarrow A \rightarrow B, 7), (S \rightarrow G, 10)\}$

Iteration3: $\{(S \rightarrow A \rightarrow C \rightarrow G, 6), (S \rightarrow A \rightarrow C \rightarrow D, 11), (S \rightarrow A \rightarrow B, 7), (S \rightarrow G, 10)\}$

Iteration 4 will give the final result, as $S \rightarrow A \rightarrow C \rightarrow G$ it provides the optimal path with cost 6.

Points to remember:

- A* algorithm returns the path which occurred first, and it does not search for all remaining paths.
- The efficiency of A* algorithm depends on the quality of heuristic.
- A* algorithm expands all nodes which satisfy the condition $f(n) \leq l_i$

Complete: A* algorithm is complete as long as:

- Branching factor is finite.
- Cost at every action is fixed.

Optimal: A* search algorithm is optimal if it follows below two conditions:

- **Admissible:** the first condition requires for optimality is that $h(n)$ should be an admissible heuristic for A* tree search. An admissible heuristic is optimistic in nature.
- **Consistency:** Second required condition is consistency for only A* graph-search.



If the heuristic function is admissible, then A* tree search will always find the least cost path.

Time Complexity: The time complexity of A* search algorithm depends on heuristic function, and the number of nodes expanded is exponential to the depth of solution d . So the time complexity is $O(b^d)$, where b is the branching factor.

Space Complexity: The space complexity of A* search algorithm is $O(b^d)$.

local search method