

Credit Card Fraud Detection

60

Anonymized credit card transactions labeled as fraudulent or genu...

by **Andrea** · last updated 2 months ago

Overview

Kernels

Discussion

Activity

Download (68 MB)

New Notebook

Kernels

Simple LR Accurac...

run 18 days ago

9 votes

Starter Kernel (abo...

run 2 months ago

7 votes

In depth skewed da...

run 7 days ago

6 votes

Discussion

In depth skewed d...

a day ago

4 replies

Detects 83% of fra...

4 days ago

0 replies

Simple LR Accurac...

5 days ago

2 replies

Top Contributors

BrunoGuilh...

1st

Nandy Sin...

2nd

joparga3

3rd

Recent Activity

joparga3

Commented on kernel In depth skewed data classif. (93% recall acc now)

a day ago

Vlad Balanda

Ran version 2 of kernel Notebook9142bc25ed

a day ago

myst812

Ran version 10 of kernel Sklearn try

2 days ago

Sivaji

Ran version 2 of kernel Notebook6c7d442cd3

2 days ago

Sivaji

Created kernel FraudDetectionAnalysis

2 days ago

Description

Help us describe this dataset

Edit

https://www.kaggle.com/dalpozz/creditcardfraud

1/3

The dataset contains transactions made by credit cards in September 2013 by European cardholders. This dataset presents transactions that occurred in two days, where we have 492 frauds out of 284,807 transactions. The dataset is highly unbalanced, the positive class (frauds) accounts for 0.172% of all transactions.

It contains only numerical input variables which are the result of a PCA transformation. Unfortunately, due to confidentiality issues, we cannot provide the original features and more background information about the data. Features V1, V2, ... V28 are the principal components obtained with PCA, the only features which have not been transformed with PCA are 'Time' and 'Amount'. Feature 'Time' contains the seconds elapsed between each transaction and the first transaction in the dataset. The feature 'Amount' is the transaction Amount, this feature can be used for example-dependent cost-sensitive learning. Feature 'Class' is the response variable and it takes value 1 in case of fraud and 0 otherwise.

Given the class imbalance ratio, we recommend measuring the accuracy using the Area Under the Precision-Recall Curve (AUPRC). Confusion matrix accuracy is not meaningful for unbalanced classification.

The dataset has been collected and analysed during a research collaboration of Worldline and the Machine Learning Group (<http://mlg.ulb.ac.be>) of ULB (Université Libre de Bruxelles) on big data mining and fraud detection. More details on current and past projects on related topics are available on <http://mlg.ulb.ac.be/BruFence> and <http://mlg.ulb.ac.be/ARTML>

Please cite: Andrea Dal Pozzolo, Olivier Caelen, Reid A. Johnson and Gianluca Bontempi. Calibrating Probability with Undersampling for Unbalanced Classification. In Symposium on Computational Intelligence and Data Mining (CIDM), IEEE, 2015

Database released under [Open Database License](#), individual contents under [Database Contents License](#)

## Files

1 files

 [creditcard.csv](#)

# creditcard.csv

[Download File](#)

File size: 68.08 MB





## Description:

CSV format



## File Preview:

 [Edit column descriptions](#) ▾

Time 	V1 	V2 	V3 
0	-1.3598071336738	-0.0727811733098497	2.53634673796914
0	1.19185711131486	0.26615071205963	0.16648011335321
1	-1.35835406159823	-1.34016307473609	1.77320934263119
1	-0.966271711572087	-0.185226008082898	1.79299333957872
2	-1.15823309349523	0.877736754848451	1.548717846511
2	-0.425965884412454	0.960523044882985	1.14110934232219
4	1.22965763450793	0.141003507049326	0.0453707735899449
7	-0.644269442348146	1.41796354547385	1.0743803763556
7	-0.89428608220282	0.286157196276544	-0.113192212729871
9	-0.33826175242575	1.11959337641566	1.04436655157316

[+ Load 90 more rows](#)

Versions

- [Version 2](#)2 months agoCSV format
- [Version 1](#)2 months agoRdata format

20,908 views · 3,201 downloads · 97 kernels · 10 topics

Explore More Datasets