

```
#####
```

```
Kubernetes web dashboard
```

```
#####
```

```
$ kubectl apply -f
```

```
https://raw.githubusercontent.com/kubernetes/dashboard/v2.5.0/aio/deploy/recommended.yaml
```

```
$ kubectl -n kubernetes-dashboard get pods -o wide
```

```
$ kubectl -n kubernetes-dashboard get svc
```

```
# Edit k8s dashboard service and change it to NodePort
```

```
$ kubectl -n kubernetes-dashboard edit svc kubernetes-dashboard
```

```
$ kubectl get pods -o wide -n kubernetes-dashboard
```

```
# access k8s web ui dashboard
```

```
URL : https://node-ip:node-port/
```

```
#create admin user with below yml
```

```
$ vi create-user.yml
```

```
---
```

```
apiVersion: v1
```

```
kind: ServiceAccount
```

```
metadata:
```

```
  name: admin-user
```

```
  namespace: kubernetes-dashboard
```

```
...
```

```
$ kubectl apply -f create-user.yml
```

```
#create cluster role binding
```

```
$ vi cluster-role-binding.yml
```

```
---
```

```
apiVersion: rbac.authorization.k8s.io/v1
```

```
kind: ClusterRoleBinding
```

```
metadata:
```

```
  name: admin-user
```

```
roleRef:
```

```
  apiGroup: rbac.authorization.k8s.io
```

```
  kind: ClusterRole
```

```
  name: cluster-admin
```

```
subjects:
```

```
- kind: ServiceAccount
```

```
  name: admin-user
```

```
  namespace: kubernetes-dashboard
```

```
...
```

```
$ kubectl apply -f cluster-role-binding.yml
```

```
# Get the bearer token
```

```
$ kubectl -n kubernetes-dashboard create token admin-user
```